

# Electric & Petrol Pressure Washers



## Electric Hotwash

### Electric Hot Pressure Washer – ‘Hot Wash’

Heavy duty steam cleaner for stubborn and difficult applications. Easily removes oil and grease. Available in 110 Volt or 240 Volt options.

#### Features:

- Operating Temp – 0 to 150 degrees (steam stage)
- Complete with 12m high pressure hose, lance and gun.
- Four wheel robust chassis provides stability.
- Close coupled pump and motor – no drive belts to replace.
- Fibreglass canopy incorporating lance holder.
- Fault diagnostic PCB fitted – easy fault finding.

MODEL	240 VOLT	110 VOLT
HILTA REF	TW100	TW101
POWER	240 Volt electric motor	110 Volt electric motor
AVERAGE SOUND PRESSURE LEVEL @ 7m	64dB(A)	64dB(A)
MAXIMUM PRESSURE	1500 psi / 100 bar	1500 psi / 100 bar
MAXIMUM FLOW	12 litres / min	9.5 litres / min
DIMENSIONS (LxWxH) mm	1130 x 720 x 965	1130 x 720 x 965
WET WEIGHT	200kg	200kg

## Electric Coldwash

**Electric Cold Pressure Washer** - ideal for light industrial or domestic use.

#### Features:

- Complete with 7.5m high pressure hose, lance and gun
- Close coupled pump and motor – no drive belts to replace
- Stainless steel canopy – longer lasting due to no rust
- Two wheeled chassis for easy mobility



Specifications are subject to change without prior notice.



MODEL	240 VOLT	110 VOLT
HILTA REF	TW1500	TW1501
POWER	240 Volt electric motor	110 Volt electric motor
AVERAGE SOUND PRESSURE LEVEL @ 7m	64dB(A)	64dB(A)
MAXIMUM PRESSURE	1500 psi / 100 bar	1500 psi / 100 bar
MAXIMUM FLOW	12 litres / min	9.5 litres / min
DIMENSIONS (LxWxH) mm	885 x 540 x 930	885 x 540 x 930
WET WEIGHT	58kg	58kg

## Petrol Pressure Washers

**Petrol Pressure Washers** - Hilti's heavy duty petrol driven pressure washers are ideal for construction site use and general cleaning.

### Features:

- Close coupled pump and motor – no drive belts to replace.
- Hose reel option – eliminates trailing hose and subsequent damage to hose.
- 2000/3000psi models: 2:1 reduction gear box fitted to pump – machine longevity.
- Two wheeled chassis – easy mobility.
- Complete with 7.5m high pressure hose, lance and gun – 1500/2000psi models.
- Complete with 12m high pressure hose, lance and gun 3000psi model.



MODEL	1500psi	2000psi	3000psi	1500psi ECONOMY
HILTA REF	TWPT1500	TWPT2000	TWPT3000	TWPFET1500
ENGINE TYPE	Honda GX160 4.8bhp 3.6kW 3000rpm	Honda GX200 5.5bhp 3.6kW 3000rpm	Honda GX340 11bhp 8kW 3000rpm	Honda GX120 4bhp 3kW 3600rpm
AVERAGE SOUND PRESSURE LEVEL @ 7m	77dB(A)	82dB(A)	86dB(A)	77dB(A)
MAXIMUM PRESSURE	1500 psi / 100 bar	2000 psi / 100 bar	3000 psi / 100 bar	1500 psi / 100 bar
MAXIMUM FLOW	11 litres / min	14 litres / min	15 litres / min	11 litres / min
FUEL TANK CAPACITY (LITRES)	3.1	3.1	6.1	2.0
DIMENSIONS (LxWxH) mm	925 x 540 x 930	925 x 540 x 930	1215 x 530 x 905	470 x 365 x 440
WET WEIGHT	45kg	50kg	100kg	32kg

All hoses and fittings available for all pumps. Specifications are subject to change without prior notice.

