



# Gno vs Solidity

---

## Smart Contract Patterns for Solidity Developers

---

Bridging the gap between Ethereum and Gno.land

# Who is this for?

## Target Audience:

- **Experienced Solidity Developers**
- Ethereum smart contract developers
- Web3 developers looking to expand to Gno.land
- Anyone familiar with EVM-based development

## What you'll learn:

- How Gno compares to Solidity
- Common patterns translated from Solidity to Gno
- Best practices for Gno development



# What is Gno?

**Gno** is a blockchain platform using **Go-based smart contracts**

## Key Features:

- **Language:** Based on Go (Golang)
- **Paradigm:** Interpreted, not compiled to bytecode
- **Type System:** Strong static typing
- **Concurrency:** Deterministic (no goroutines in contracts)
- **Storage:** Persistent state with realms

## Philosophy:

Write smart contracts in a **familiar, readable language** (Go) instead of learning Solidity from scratch



# Gno vs Solidity: Language

Feature	Solidity	Gno
<b>Base Language</b>	Custom	Go (Golang)
<b>Execution</b>	Compiled to bytecode	Interpreted
<b>Type System</b>	Static	Static (Go-based)
<b>Inheritance</b>	Yes (OOP)	No (composition)
<b>Interfaces</b>	Yes	Yes (Go interfaces)
<b>Error Handling</b>	<code>require</code> , <code>revert</code>	<code>panic</code> , <code>error</code> returns
<b>Gas Model</b>	EVM gas	Gno gas



# Pattern 1: Basic Counter

## Solidity

```
contract Counter {  
    uint256 private count;  
  
    function increment() public {  
        count += 1;  
    }  
  
    function getCount() public view returns (uint256) {  
        return count;  
    }  
}
```

## Gno

```
package counter  
  
var count int  
  
func Increment() {  
    count++  
}  
  
func GetCount() int {  
    return count  
}
```



## Pattern 2: Ownable / Access Control

### Solidity

```
contract Ownable {
    address private owner;

    constructor() {
        owner = msg.sender;
    }

    modifier onlyOwner() {
        require(msg.sender == owner, "Not owner");
        _;
    }

    function restrictedAction() public onlyOwner {
        // Only owner can call
    }
}
```

### Gno

```
package ownable

import "chain/runtime"

var owner address

func init() {
    owner = runtime.PreviousRealm().Addr()
}

func AssertIsOwner() {
    if runtime.PreviousRealm().Addr() != owner {
        panic("not owner")
    }
}

func RestrictedAction() error {
    AssertIsOwner()
    // Only owner can call
    return nil
}
```



# Pattern 3: State Lock

## Solidity

```
contract StateLock {
    enum State { Open, Closed, Paused }
    State public state;

    modifier inState(State _state) {
        require(state == _state, "Invalid state");
        _;
    }

    function doSomething() public inState(State.Open) {
        // Only callable when Open
    }
}
```

## Gno

```
package statelock

type State int

const (
    Open State = iota
    Closed
    Paused
)

var state State = Open

func AssertState(expected State) {
    if state != expected {
        panic("invalid state")
    }
}

func DoSomething() {
    AssertState(Open)
    // Only callable when Open
}
```



# Pattern 4: Emit Events

## Solidity

```
contract EventEmitter {
    event Transfer(address indexed from, address indexed to,

    function transfer(address to, uint256 amount) public {
        // Transfer logic
        emit Transfer(msg.sender, to, amount);
    }
}
```

## Gno

```
package events

import (
    "chain/runtime"
    "gno.land/p/demo/emit"
)

func Transfer(to address, amount uint64) {
    // Transfer logic
    emit.Emit("Transfer",
        "from", runtime.PreviousRealm().Addr().String(),
        "to", to.String(),
        "amount", amount,
    )
}
```





# Pattern 5: Factory Pattern

## Solidity

```
contract Factory {
    address[] public contracts;

    function createContract() public returns (address) {
        MyContract newContract = new MyContract();
        contracts.push(address(newContract));
        return address(newContract);
    }
}
```

## Gno

```
package factory

import "gno.land/p/demo/avl"

var contracts avl.Tree // realm_path -> instance

func CreateContract(name string) string {
    // Create new realm dynamically
    path := "gno.land/r/demo/" + name
    // Note: Dynamic realm creation not yet supported
    // Use sub-packages or registry pattern instead
    contracts.Set(path, &Contract{})
    return path
}
```



# Pattern 6: Token (ERC20 → GRC20)

## Solidity (ERC20)

```
contract ERC20 {  
    mapping(address ⇒ uint256) public balanceOf;  
  
    function transfer(address to, uint256 amount) public {  
        require(balanceOf[msg.sender] ≥ amount);  
        balanceOf[msg.sender] -= amount;  
        balanceOf[to] += amount;  
    }  
}
```

## Gno (GRC20)

```
package grc20  
  
import (  
    "chain/runtime"  
    "gno.land/p/demo/grc/grc20"  
)  
  
var banker *grc20.Banker  
  
func Transfer(to address, amount uint64) error {  
    caller := runtime.PreviousRealm().Addr()  
    return banker.Transfer(caller, to, amount)  
}
```



# Pattern 7: Reentrancy Guard

## Solidity

```
contract ReentrancyGuard {
    bool private locked;

    modifier noReentrant() {
        require(!locked, "Reentrant call");
        locked = true;
        _;
        locked = false;
    }

    function withdraw() public noReentrant {
        // Safe withdrawal
    }
}
```

## Gno

```
package reentrancy

var locked bool

func AssertNotLocked() {
    if locked {
        panic("reentrant call")
    }
    locked = true
}

func Unlock() {
    locked = false
}

func Withdraw() {
    AssertNotLocked()
    defer Unlock()
    // Safe withdrawal
}
```



# Pattern 8: Wallet - Withdraw

## Solidity

```
contract Wallet {  
    mapping(address ⇒ uint256) public balances;  
  
    function withdraw(uint256 amount) public {  
        require(balances[msg.sender] ≥ amount);  
        balances[msg.sender] -= amount;  
        payable(msg.sender).transfer(amount);  
    }  
}
```

## Gno

```
package wallet  
  
import (  
    "chain"  
    "chain/runtime"  
  
    "gno.land/p/demo/avl"  
)  
  
var balances avl.Tree // Address -> uint64  
  
func Withdraw(amount uint64) {  
    caller := runtime.PreviousRealm().Addr()  
    balance := getBalance(caller)  
    if balance < amount {  
        panic("insufficient balance")  
    }  
    setBalance(caller, balance-amount)  
    banker.SendCoins(caller, chain.Coins{{amount, "ugnot"}})  
}
```



# Pattern 9: Wallet - Deposit

## Solidity

```
contract Wallet {  
    mapping(address ⇒ uint256) public balances;  
  
    receive() external payable {  
        balances[msg.sender] += msg.value;  
    }  
  
    function deposit() public payable {  
        balances[msg.sender] += msg.value;  
    }  
}
```

## Gno

```
package wallet  
  
import (  
    "chain/banker"  
    "chain/runtime"  
)  
  
func Deposit() {  
    caller := runtime.PreviousRealm().Addr()  
    sent := banker.OriginSend()  
  
    if len(sent) == 0 {  
        panic("no coins sent")  
    }  
  
    amount := sent[0].Amount  
    balance := getBalance(caller)  
    setBalance(caller, balance+amount)  
}
```



# Pattern 10: Mapping (AVL Tree)

## Solidity

```
contract Mapping {
    mapping(address ⇒ uint256) public balances;
    mapping(string ⇒ address) public registry;

    function set(string memory key, address value) public {
        registry[key] = value;
    }
}
```

## Gno

```
package mapping

import "gno.land/p/demo/avl"

var balances avl.Tree // Address -> uint64
var registry avl.Tree // string -> Address

func Set(key string, value address) {
    registry.Set(key, value)
}

func Get(key string) address {
    val, _ := registry.Get(key)
    return val.(address)
}
```



# Pattern 11: Guard Check

## Solidity

```
contract GuardCheck {  
    modifier validAmount(uint256 amount) {  
        require(amount > 0, "Amount must be positive");  
        require(amount ≤ 1000, "Amount too large");  
        _;  
    }  
  
    function transfer(uint256 amount) public validAmount(amount)  
        // Transfer logic  
    }  
}
```

## Gno

```
package guardcheck  
  
func AssertValidAmount(amount uint64) {  
    if amount == 0 {  
        panic("amount must be positive")  
    }  
    if amount > 1000 {  
        panic("amount too large")  
    }  
}  
  
func Transfer(amount uint64) {  
    AssertValidAmount(amount)  
    // Transfer logic  
}
```



# Pattern 12: Proxy Pattern

## Solidity

```
contract Proxy {
    address public implementation;

    function upgrade(address newImpl) public onlyOwner {
        implementation = newImpl;
    }

    fallback() external payable {
        address impl = implementation;
        assembly {
            calldatacopy(0, 0, calldatasize())
            let result := delegatecall(gas(), impl, 0, 0, calldatasize())
            returndatacopy(0, 0, returndatasize())
            switch result
            case 0 { revert(0, returndatasize()) }
            default { return(0, returndatasize()) }
        }
    }
}
```

## Gno

```
package proxy

import "gno.land/p/demo/ownable"

var implementation string // realm path

func Upgrade(newImpl string) {
    ownable.AssertCallerIsOwner()
    implementation = newImpl
}

func Call(method string, args ...interface{}) interface{} {
    // Delegate to implementation realm
    // Note: Direct delegation not yet supported
    // Use interface-based composition instead
    return callRealm(implementation, method, args...)
}

// Alternative: Use DAO pattern like GovDAO
// with UpdateImpl() to switch implementations
```





# Pattern 13: Emergency Stop

## Solidity

```
contract EmergencyStop {
    bool public stopped = false;

    modifier stopInEmergency() {
        require(!stopped, "Contract stopped");
        _;
    }

    function emergencyStop() public onlyOwner {
        stopped = true;
    }

    function resume() public onlyOwner {
        stopped = false;
    }
}
```

## Gno

```
package emergency

import "gno.land/p/demo/ownable"

var stopped bool = false

func AssertNotStopped() {
    if stopped {
        panic("contract stopped")
    }
}

func EmergencyStop() {
    ownable.AssertCallerIsOwner()
    stopped = true
}

func Resume() {
    ownable.AssertCallerIsOwner()
    stopped = false
}

func DoSomething() {
    AssertNotStopped()
    // Normal logic
}
```



# Pattern 14: Speed Bump

## Solidity

```
contract SpeedBump {
    mapping(address ⇒ uint256) public lastActionTime;
    uint256 public constant DELAY = 1 days;

    modifier rateLimit() {
        require(block.timestamp ≥ lastActionTime[msg.sender]
            _;
        lastActionTime[msg.sender] = block.timestamp;
    }

    function withdraw() public rateLimit {
        // Withdrawal logic
    }
}
```

## Gno

```
package speedbump

import (
    "chain/runtime"
    "time"

    "gno.land/p/demo/avl"
)

var lastActionTime avl.Tree // Address -> time.Time
const DELAY = 24 * time.Hour

func AssertRateLimit() {
    caller := runtime.PreviousRealm().Addr()
    lastTime, exists := lastActionTime.Get(caller.String())

    now := time.Now()
    if exists && now.Sub(lastTime.(time.Time)) < DELAY {
        panic("rate limit: please wait")
    }
    lastActionTime.Set(caller.String(), now)
}

func Withdraw() {
    AssertRateLimit()
    // Withdrawal logic
}
```



# Key Differences Summary

Solidity

Gno

`msg.sender`

`std.PrevRealm().Addr()`

`require()`

`if !condition { panic() }`

`modifier`

Function calls with `Assert*()`

`mapping`

`avl.Tree`

`emit Event`

`emit.Emit()`

`contract`

`package + realm`

`constructor`

`init()` function

`payable`

`std.GetOrigSend()`

# Best Practices for Gno

## Coming from Solidity:

1. **Think packages, not contracts** - Gno uses Go packages
2. **Use composition over inheritance** - No OOP inheritance
3. **Leverage Go's standard library** - Familiar Go patterns work
4. **AVL trees for mappings** - Efficient key-value storage
5. **Panic for errors** - Or return `error` types
6. **Realms are stateful** - Persistent state across calls
7. **No dynamic dispatch** - Static linking at deploy time



# Resources

## Learning More:

- **Gno Documentation:** [docs.gno.land](https://docs.gno.land)
- **Gno by Example:** [gno.land/r/demo](https://gno.land/r/demo)
- **Standard Library:** `gno.land/p/demo/*`
- **Example Realms:** `gno.land/r/demo/*`

## Key Packages:

- `gno.land/p/demo/avl` - AVL tree (like mapping)
- `gno.land/p/demo/ownable` - Ownership pattern
- `gno.land/p/demo/grc/grc20` - Token standard



# Getting Started

## Next Steps:

1. **Set up Gno development environment**
2. **Clone and explore example realms**
3. **Start with simple counter or blog**
4. **Gradually implement familiar patterns**
5. **Join the Gno community**

## Remember:

- Gno is **Go** - if you know Go, you're 80% there
- Patterns are **similar** - just different syntax
- Community is **helpful** - ask questions!