

# Development:

## Javac:

We can use this command to compile a single or group of java files.

## Syn:

Javac [options]A.java/A.java B.java

java:

we can use java Command to a run a .class file.

## Syn

java[option] A

Note:- we can compile a group of .java files at a time where as we can run only on .class file at a time.

Classpath:

- classpath describes the location where required .class files are available.
- JVM will always locate the required .class file.
- The following are various possible ways to set the classpath.

## 1)Permenently by using environment variable classpath

- This class path will be preserved after system restart also.

## 2)At command prompt level by using set Command.

Set classpath=%classpath %;D:\path>

- This class path will be only for that particular command prompt once command execution completes automatically classpath will be lost.

## 3)At command level by using cp option

java-cpD:\path>Test

- This classpath is applicable only for this particular command. Once command execution completes automatically classpath will be lost.
- Among the above 3 ways the most commonly used approach is setting classpath or command level.

**Example:**

Class Test

```
{  
    public static void main(String args[])  
    {  
        System.out.println("Classpath Demo");  
    }  
}
```

D:\Durgaclass\&gt;javac Test.java

```
>Java Test //valid  
O/p= Classpath Demo
```

D:\&gt;.java Test //R.E.NoClassDefoundError //invalid

D:\&gt;java-cp D:\Durgaclasses Test //valid

O/p= ClasspathDemo

**Note:**

If we set classpath explicitly then we can run java program from any location but if we are not setting the classpath then we have to run java program only from current working directory.

**Example 2)**

C:	D:
public class fresher {	class Company {

<pre>public void m1() {     System.out.println("I Wan't Job"); } }</pre>	<pre>Public static void main(string args[]) {     fresher f=new fresher();     f.m1();     System.out.println("Getting a job is very easy not required to warry"); } }</pre>
--	--

C:\> javac Fresher.java //valid

D:\> javac Company.java // cannot find symbol

Symbol:Class Fresher

Location: class Company

D:\> javac -cp c:Company.java //valid

D:\javac Company //R.E. NoClassDefoundError:Fresher

D:\ java-cp c:Company //R.E. NoClassDefoundError:Company

D:\java-cp D:;C: Company D:\java-cp;C:Company

o/p= I wan't Job

Getting Job is very eassy not required to worry

E:\java-cp D:;C: Company

### Example 3)

C:	D:	E:
<pre>Package pack1.pack2; Public class Ram {     public void m1()     {         System.out.println("Hello");     } }</pre>	<pre>Package pack3.pack4; Import pack1.pack2. Ram Public class Sham {     Public void m1()     {         Ram r=new Ram();         r.m1();         System.out.println("Hi");     } }</pre>	<pre>Package pack3.pack.Sham; Public class Desha {     Public static void main(-)     {         Sham s=new Sham();         s.m1();         System.out.println("Welcome");     } }</pre>

C:\> java -d.Ram //valid

D:\> java-d.Sham.java //C.E.=cannot find symbol

Symbol:class Ram

Location:class Sham

D:\>java-cp c: -d.Sham.java //valid

E:\>javac Desha.java // C.E.= cannot find symbol

Symbol:class Sham

Location:class Desha

E:\>javac-cp D:Desha.java

E:\>java Desha //R.E.=NoClassDefoundError:Sham

E:\>java-cp D:Desha //R.E.=NoClassDefoundError:Desha

E:\>java-cp ;D:Desha //R.E.=NoClassDefoundError:Ram

E:\>java-cp E: ;D:;C:;Desha


**Notes :-**

1) Compiler will check only one level dependency where as JVM will check all Levels of dependency

2) If any folder structure created because Of package statement it should be resolved Through import statement only & Base package Location we have to update in classpath

3) Within the classpath the order of location is very importance for the required .class file ,JVM will always search the location.

Left → Right in classpath. Once JVM finds the required file then the rest of the classpath won't to be searched.



<pre>class Priya {     Public static void main(- )     { System.out.println("C:Pri ya"); } }</pre>	<pre>class Priya {     Public static void main(- )     { System.out.println("D:Pri ya"); } }</pre>	<pre>class Priya {     Public static void main(-)     { System.out.println("E:Pri ya"); } }</pre>
--	--	---

```
C:\> javac Priya.java //valid
```

```
D:\> javac Priya.java //valid
```

```
E:\> javac Priya.java //valid
```

```
C:\> java Priya //valid
```

**Output:** c: Priya

```
D:\> java-cp C:;D:;E: Priya
```

o/p= C: Priya

```
D:\> java-cp E:;D:;C: Priya
```

o/p= E: Priya

```
D:\> java-cp D:;E:;C: Priya
```

o/p= D: Priya

## JAR File

- If several dependent files are available then it is never recommended to set each class file individually in the classpath we have to group all those. Class file into a single I/P file and we have to make that Zip file available in the class path. This zip file is nothing but JAR file.

### Example:

To develop a servlet all required .class files are available in Servlet-api.jar. We have to make this Jar file available in the classpath then only servlet will be compiled.

### ➤ jar vs war vs ear

#### 1) jar : (java archive file)

It contains a group of .class files

#### 2) war : (web archive file)

it represent a web application which may contain  
servlets,JSPS,HTML,CSS.JavaScript,etc.....

### 3) ear : (enterprise archive file)

It represent an enterprise application which may conatins  
Servlets,JSPS,EJBS,JNS Components etc.

#### ➤ Various commands

##### 1) To create a jar file:

```
jar - cvf durga.jar A.class B.class c.class *.class
```

##### 2) To extract a jar File:

```
jar- xvf durga.jar
```

##### 3) To display of contains of a jar file:

```
Jar-tvf durga.jar
```

#### Example:

```
public class Durga
{
    public static int add(int x,int y)
    {
        return x*y;
    }
    public static int add(int x,int y)
    {
        return 2* x*y;
    }
}
```

```
c:\>javac Durga.java
```

```
c:\>jar - cvf Durga.jar durga.class
```

```
class Desha
{
```

```
public static void main(String args[])
{
    System.out.println("durga.add(10,20)");
    System.out.println("durga.multiply(10,20)");
}
a}
D:\> javac Desha.java //invalid
D:\> javac -cp c:Desha.java //invalid
D:\> javac -cp c:\Desha.java //valid
D:\> javac -cp;c:\ Desha.java
```


O/P: 2000 &400

**Note:**

Whenever we are placing a jar file in the classpath compulsory name of the jar file we should include, just Location is not enough.

**➤ Short Cut way to place jar file:-**

- If we are placing the jar file in the following location then it is not required to set classpath explicitly by default it is available to JVM & Java compiler.





## System Properties

- For every system persistence information will be maintain in the form of system properties .These may include os name varchual machine version,user country..etc
- We can get System properties by using getProperties () method of System class

### Example:

#### Demo program to print an System Properties

```
import java.util.*;
class Test
{
    public static void main(String args[])
    {
        Properties p=System.getProperties();
        p.list(System.out);
    }
}
```

- We can set System Property from the command prompt by using option

### Que) JDK vs JRE vs JVM

#### ➤ **JDK(Java Development Kit):-**

To develop & run java application the required environment provided by JDK.

#### ➤ **JRE(Java Runtime Environment):-**

To run java application the required environment provided by JRE.

#### ➤ **JDK(Java Virtual Machine):-**

The machine is responsible to execute java program.

JDK=JRE+TOOLS  
JRE=JVM+Libraries

**Note:**

On client machine we have to install JRE, where as on the developess machine to install JDK.

**Difference Between Path And Classpath****➤ Classpath**

- We can use classpath to describe the location where required.class files are available.
- If we are not setting the classpath then our program wan't be run.

**➤ Path**

- we can use path variable to describe the location where required binary executable are available .
- if we are not setting path variable then java & javac commands wan't work.
- If m1() return type is void, then we will get compiletimeError saying "void type not allowed here"

**4) Various Runtime Flags**

- 1) -ea: To enable assertions in every non-System class.
- 2) -enableassertions:- It is Exactly same as -ea
- 3) -da :- To disable assertion in every non-system class.
- 4) -disableassertions:- same as -da.
- 5) -esa:- To enabled assertions in every system class.
- 6) -enabledSystemassertions:- it is exactly same as -esa.
- 7) -dsa:- To disable assertions in nevery System class.
- 8) -disableSystemassertions:- it is same as -dsa.

**Example:-1)**


java -ea -esa -da -esa -ea -dsa

we can use these flag in together & all these flags executed from Left To Right

### Example:-2)

- 1) java -ea:pack1.A
- 2) java -ea:pack1.B -ea:pack1 pack2.D
- 3) java -ea -da packB

### Example:-3)



- TO enable assertion in only A class
  - 1) Java -ea:pack1.A
- TO enable assertion in both B & D class
  - 2) Java -ea:pack1.B -ea:pack1:pack2.D
- TO enable assertion in every non-System class except B
  - 3) Java -ea:pack1. -da:pack1.B
- TO enable assertion in every class of pack1 & its sub except sub packages
  - 4) Java -ea:pack1.
- TO enable assertion in every where within pack1 except pack2
  - 5) Java -ea:pack1. -da:pack1,pack2

### 6) Appropriate & Inappropriate use of asserting

- 1) It is always Inappropriate to mix programming logic with assert statement because there is no execution of assert statement at runtime.

Example:

<pre>Withdraw(int x) {     If(x&lt;100)     {         Throw new IAE();     } } //proper way</pre>	<pre>Withdraw(int x) {     assert(x&lt;100) } //unproperway</pre>
---	---