

AngularJS Events

1. Fetch the data from mysql database table to AngularJS program.

Answer:

Step 1: MySQL Table

```
CREATE TABLE students (  
    id INT PRIMARY KEY,  
    name VARCHAR(50),  
    course VARCHAR(50)  
);  
  
INSERT INTO students VALUES  
(101, 'Suman', 'BCA'),  
(102, 'Rahul', 'B.Sc'),  
(103, 'Priya', 'B.Com');
```

Step 2: PHP File (students.php)

```
<?php  
  
$conn = new mysqli("localhost","root","","college");  
  
$result = $conn->query("SELECT * FROM students");  
  
$data = array();  
  
while($row = $result->fetch_assoc()){  
    $data[] = $row;  
}  
  
echo json_encode($data);  
  
?>
```

Step 3: AngularJS Program (index.html)

```
<!DOCTYPE html>  
<html ng-app="myApp">  
<head>  
    <title>AngularJS MySQL</title>  
</head>  
  
<body ng-controller="myCtrl">  
  
<h2>Student Details</h2>  
  
<table border="1">  
  
    <tr>  
        <th>ID</th>  
        <th>Name</th>  
        <th>Course</th>  
    </tr>  
  
    <tr ng-repeat="student in students">
```

```

<td>{{student.id}}</td>
<td>{{student.name}}</td>
<td>{{student.course}}</td>

</tr>

</table>

<script
src="https://ajax.googleapis.com/ajax/libs/angularjs/1.8.2/angular.min.js"><
/script>

<script>

var app = angular.module("myApp", []);

app.controller("myCtrl", function($scope, $http){

$http.get("students.php")

.then(function(response){

$scope.students = response.data;

});

});

</script>

</body>
</html>

```

2. What is DOM(Document Object Model). Use ng-show, ng-hide and ng-disabled into your program.

Answer:

The **Document Object Model (DOM)** is a tree-like representation of an HTML document. It allows JavaScript and AngularJS to access, modify, add, or remove HTML elements dynamically.

Program:

```

<!DOCTYPE html>
<html ng-app="myApp">

<head>
<title>DOM Example</title>
</head>

<body ng-controller="myCtrl">

<input type="checkbox" ng-model="showText">

<p ng-show="showText">
This text is displayed using ng-show.
</p>

```

```

<p ng-hide="showText">
This text is hidden when the checkbox is selected.
</p>

<br>

<input type="checkbox" ng-model="disableButton">

<button ng-disabled="disableButton">
Submit
</button>

<script
src="https://ajax.googleapis.com/ajax/libs/angularjs/1.8.2/angular.min.js"><
/script>

<script>

angular.module("myApp", [])

.controller("myCtrl", function($scope){

});

</script>

</body>
</html>

```

3. Program that performs various events using ng-click, ng-mousemove and \$event.

Answer:

```

<!DOCTYPE html>
<html ng-app="myApp">

<head>
<title>AngularJS Events</title>
</head>

<body ng-controller="myCtrl">

<button ng-click="count=count+1">

Click Me

</button>

<p>Button Clicked : {{count}} times</p>

<hr>

<div

```

```
style="width:300px;height:150px;background-color:lightblue;"

ng-mousemove="showCoordinates($event) ">

Move the mouse here.

</div>

<p>

X Position : {{x}}

<br>

Y Position : {{y}}

</p>

<script
src="https://ajax.googleapis.com/ajax/libs/angularjs/1.8.2/angular.min.js"><
/script>

<script>

var app = angular.module("myApp", []);

app.controller("myCtrl", function($scope) {

$scope.count = 0;

$scope.showCoordinates = function(event) {

$scope.x = event.clientX;

$scope.y = event.clientY;

};

});

</script>

</body>
</html>
```

Things to know:

1. What is mysql?

Answer:

MySQL is an open-source **Relational Database Management System (RDBMS)** that stores data in tables using SQL (Structured Query Language).

Features:

- Open-source and free to use.

- Stores data in rows and columns.
- Supports SQL queries.
- Fast and reliable.
- Widely used with PHP, Java, Python, and web applications.

Example SQL Query:

```
SELECT * FROM students;
```

2. What is an event?

Answer:

An **event** is an action or occurrence that happens in a web page. JavaScript and AngularJS can respond to these events by executing code.

Common AngularJS Events:

Event	Description
ng-click	Triggered when an element is clicked.
ng-mousemove	Triggered when the mouse moves over an element.
ng-mouseover	Triggered when the mouse pointer enters an element.
ng-mouseleave	Triggered when the mouse pointer leaves an element.
ng-change	Triggered when the value of an input change.
ng-submit	Triggered when a form is submitted.

Example:

```
<button ng-click="message='Button Clicked'">
```

```
Click Me
```

```
</button>
```

```
<p>{{message}}</p>
```