MCP Envelope Validation Agreement

Page 1 - Sender prefill section (document-level prefill tabs)

This page holds fields the SENDER fills before sending. In the template, place PREFILL (document-level) fields on each anchor below, not recipient fields. Used to validate listEnvelopeDocuments(include_tabs) discovery and updateEnvelopeTabs(documentId, prefillTabs) for text, date, number, checkbox and radio prefill types.

1. Deal details (sender)

Customer legal name
prefill textTab - expected value set by agent

Effective date
prefill dateTab (MM/DD/YYYY)

Contract value (USD)
prefill numberTab

Sender contact email
prefill emailTab

2. Options (sender)

- [ ] Auto-renewal applies
- [ ] Includes data processing addendum

Billing frequency:

- ( ) Monthly
- ( ) Quarterly
- ( ) Annually

3. Sender-name stamps (auto-filled by Docusign)

Sent by
senderNameTab

Sending company
senderCompanyTab

MCP Envelope Validation Agreement

Page 2 - Signer 1 data-entry fields (recipient tabs)

4. Signer 1 information

Purchase order number
textTab with validationPattern ^PO-[0-9]{4}$

Free-text comments
textTab, optional (required=false)

Quantity
numberTab - feeds formula below

Total (Quantity x 100)
*formulaTab: [s1_qty] * 100, read-only*

Requested start date
dateTab

Alternate email
emailTab

Postal / ZIP code
zipTab

Tax ID (masked)
ssnTab, concealValueOnDocument=true

Plan tier
listTab: Basic / Pro / Enterprise

5. Choices

- [ ] I need a hardware token (reveals detail field)

Token delivery address
conditional textTab: parent s1_cb_token = on

- [ ] Subscribe to product updates (optional)
- [ ] I accept the terms (required)

Preferred contact channel:

- ( ) Email
- ( ) Phone
- ( ) Chat

6. Supporting material

Upload signed W-9 / ID
signerAttachmentTab (optional)

Message to signer
noteTab (read-only text placed by sender)

7. Signer 1 (Customer)

Signature
signHereTab

Initials
initialHereTab

Full name
fullNameTab (auto)

Title
titleTab

Company
companyTab

Date signed
dateSignedTab (auto)

Approve / decline:

8. Signer 2 (Provider countersignature - routing order 2)

Signature
signHereTab, recipient 2

Initials

Full name

Date signed

9. In-person signer (hosted)

Walk-in signature
inPersonSigner signHereTab

Envelope reference
envelopeIdTab

10. Edge cases

a) Duplicate anchor: the hidden anchor for the Signer 1 signature appears again below. With anchorPopulationScope=envelope one signHereTab definition will create TWO tabs (page 3 and page 4).
b) Case test: anchor below is upper-case (S1_CASE). Test anchorCaseSensitive true/false.
c) Missing anchor test: use anchor 'not_in_doc' - expect silent drop unless anchorIgnoreIfNotPresent=false.

Signer 1 signature (duplicate) _____

Case-sensitivity probe _____

11. Anchor reference (hidden anchors are backslash-wrapped white text; listed here without slashes)

pf_customer	text (prefill)
pf_effective	date (prefill)
pf_amount	number (prefill)
pf_email	email (prefill)
pf_cb_autorenew / pf_cb_dpa	checkbox (prefill)
pf_bill_1..3	radio group (prefill)
snd_name / snd_company	senderName / senderCompany
s1_po	text + regex
s1_text	text optional
s1_qty / s1_total	number / formula
s1_date	date
s1_email	email
s1_zip / s1_ssn	zip / ssn
s1_plan	list
s1_cb_token / s1_token_addr	checkbox / conditional text
s1_cb_news / s1_cb_terms	checkbox optional / required
s1_ch_1..3	radio group
s1_attach / s1_note	signerAttachment / note
s1_sig / s1_init	signHere / initialHere
s1_fullname / s1_title / s1_company	fullName / title / company
s1_datesigned	dateSigned
s1_approve / s1_decline	approve / decline
s2_sig / s2_init / s2_fullname / s2_datesigned	signer 2 block
ip_sig	in-person signHere
env_id	envelopeId
S1_CASE	case probe