

```

entry:
  %retval = alloca i32, align 4
  %argc.addr = alloca i32, align 4
  %argv.addr = alloca i8**, align 8
  %i = alloca i32, align 4
  %j = alloca i32, align 4
  store i32 0, i32* %retval, align 4
  store i32 %argc, i32* %argc.addr, align 4
  store i8** %argv, i8*** %argv.addr, align 8
  call void @_ZL13mcp_roi_beginv()
  store i32 0, i32* %i, align 4
  br label %for.cond

```

```

for.cond:
  %0 = load i32, i32* %i, align 4
  %1 = load i8**, i8*** %argv.addr, align 8
  %arrayidx = getelementptr inbounds i8*, i8** %1, i64 1
  %2 = load i8*, i8** %arrayidx, align 8
  %call = call i32 @atoi(i8* %2) #8
  %cmp = icmp slt i32 %0, %call
  br i1 %cmp, label %for.body, label %for.end

```

T	F
---	---

```

for.body:
  %call1 = call i32 (i8*, ...) @printf(i8* getelementptr inbounds ([8 x i8],
... [8 x i8]* @.str, i64 0, i64 0))
  br label %for.inc

```

```

for.inc:
  %3 = load i32, i32* %i, align 4
  %inc = add nsw i32 %3, 1
  store i32 %inc, i32* %i, align 4
  br label %for.cond

```

```

for.end:
  %4 = load i8**, i8*** %argv.addr, align 8
  %arrayidx2 = getelementptr inbounds i8*, i8** %4, i64 1
  %5 = load i8*, i8** %arrayidx2, align 8
  %call3 = call i32 @atoi(i8* %5) #8
  store i32 %call3, i32* %j, align 4
  br label %for.cond4

```

```

for.cond4:
  %6 = load i32, i32* %j, align 4
  %7 = load i8**, i8*** %argv.addr, align 8
  %arrayidx5 = getelementptr inbounds i8*, i8** %7, i64 2
  %8 = load i8*, i8** %arrayidx5, align 8
  %call6 = call i32 @atoi(i8* %8) #8
  %cmp7 = icmp sle i32 %6, %call6
  br i1 %cmp7, label %for.body8, label %for.end12

```

T	F
---	---

```

for.body8:
  %call9 = call i32 (i8*, ...) @printf(i8* getelementptr inbounds ([8 x i8],
... [8 x i8]* @.str.1, i64 0, i64 0))
  br label %for.inc10

```

```

for.inc10:
  %9 = load i32, i32* %j, align 4
  %inc11 = add nsw i32 %9, 1
  store i32 %inc11, i32* %j, align 4
  br label %for.cond4

```

```

for.end12:
  ret i32 0

```

CFG for 'main' function