



according to OSHA 29 CFR 1910.1200

ISSUE DATE: 02.06.2016
 REVISION DATE: 14.07.2023
 SUPERSEDES: 19.09.2022
VERSION: 4.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : Sika Primer-217 LUM
 Product code : 200118
 SDS Number : 5293

1.2. Recommended use and restrictions on use

Product use : Professional use
 Recommended use : Primers
 Restrictions on use : None known

1.3. Supplier

Supplier

Jaguar Land Rover Limited
 Abbey Road
 CV3 4LF Whitley, Coventry - UK
 T +44 (0) 370 500 0500 (Mo-Fri 08:00-18:00 GMT/Sat 08:00-14:00 GMT)
 E-mail address: sds-info@sds.jlr.com
 E-mail address of competent person responsible for the SDS : HSE@rle.de

1.4. Emergency telephone number

Emergency number : For Chemical Emergency
 Spill, Leak, Fire, Exposure, or Accident:
 Call CHEMTREC Day or Night
 Within USA and Canada: 1-800-424-9300
 Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

according to OSHA 29 CFR 1910.1200, paragraph (d)

Physical hazards	Flammable liquids Category 2	Highly flammable liquid and vapor
Health hazards	Serious eye damage/eye irritation Category 2	Causes serious eye irritation
	Respiratory sensitization, Category 1	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
	Skin sensitization, Category 1	May cause an allergic skin reaction
	Carcinogenicity Category 2	Suspected of causing cancer
	Specific target organ toxicity – Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness

2.2. GHS Label elements, including precautionary statements

GHS US labeling

according to OSHA 29 CFR 1910.1200, paragraph (f)

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Contains

: ethylacetate; butanone; 4,4'-methylenediphenyl diisocyanate; Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylenetriethanol

Hazard statements

Highly flammable liquid and vapor.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause an allergy or asthma symptoms or breathing difficulties if inhaled.
May cause drowsiness or dizziness.
Suspected of causing cancer.

Precautionary statements

Prevention

Obtain special instructions before use.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Avoid breathing mist, vapors.
Wear eye protection, face protection, protective clothing, protective gloves.

Response

In case of fire: Use dry sand, extinguishing powder, alcohol resistant foam to extinguish.
If exposed or concerned: Get medical advice/attention..

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.2. Mixtures

Name	Common Name (Synonyms)	Product identifier	Conc. %	GHS US classification
ethylacetate		CAS- No: 141-78-6	25 - < 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
butanone		CAS- No: 78-93-3	25 - < 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylenetriethanol		CAS- No: 53317-61-6	5 - < 10	Eye Irrit. 2, H319 Skin Sens. 1, H317
Tris(p-isocyanatophenyl) thiophosphate		CAS- No: 4151-51-3	2.5 - < 5	Acute Tox. 4 (Oral), H302
1,3,5-tris[3-(trimethoxysilyl)propyl]-1,3,5-triazine-2,4,6(1H,3H,5H)-trione		CAS- No: 26115-70-8	2.5 - < 5	Acute Tox. 4 (Oral), H302
4,4'-methylenediphenyl diisocyanate		CAS- No: 101-68-8	0.1 - < 1	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
m-tolylidene diisocyanate		CAS- No: 26471-62-5	0.025 - < 0.1	Carc. 2, H351 Acute Tox. 2 (Inhalation), H330 Eye Irrit. 2, H319

				STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317 Aquatic Chronic 3, H412
--	--	--	--	--

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects:	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause an allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Alcohol resistant foam. Dry sand. extinguishing powder.
Unsuitable extinguishing media	: Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor.
Hazardous decomposition products in case of fire	: During fire, gases hazardous to health may be formed.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Cool containers exposed to heat with water spray and remove container, if no risk is involved.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible and place into containers. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small spills: Take up liquid spill into absorbent material. Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Sika Primer-217 LUM

No additional information available

ethylacetate (141-78-6)

USA - ACGIH - Occupational Exposure Limits

Local name	Ethyl acetate
ACGIH OEL TWA [ppm]	400 ppm
Remark (ACGIH)	URT & eye irr
Regulatory reference	ACGIH 2016

USA - OSHA - Occupational Exposure Limits

Local name	Ethyl acetate
OSHA PEL (TWA) [1]	1400 mg/m ³
OSHA PEL (TWA) [2]	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

butanone (78-93-3)

USA - ACGIH - Occupational Exposure Limits

Local name	Methyl ethyl ketone (MEK)
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL [ppm]	300 ppm

butanone (78-93-3)

Remark (ACGIH)	TLV® Basis: URT irr; CNS & PNS impair. Notations: BEI
Regulatory reference	ACGIH 2023

USA - ACGIH - Biological Exposure Indices

Local name	METHYL ETHYL KETONE
BEI (BLV)	2 mg/l Parameter: Methyl ethyl ketone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2023

USA - OSHA - Occupational Exposure Limits

Local name	2-Butanone (Methyl ethyl ketone)
OSHA PEL (TWA) [1]	590 mg/m³
OSHA PEL (TWA) [2]	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

4,4'-methylenediphenyl diisocyanate (101-68-8)**USA - ACGIH - Occupational Exposure Limits**

Local name	Methylene bisphenyl isocyanate (MDI)
ACGIH OEL TWA [ppm]	0.005 ppm
Remark (ACGIH)	TLV® Basis: Resp sens
Regulatory reference	ACGIH 2023

USA - OSHA - Occupational Exposure Limits

Local name	Methylene bisphenyl isocyanate (MDI)
OSHA PEL (Ceiling)	0.2 mg/m³
OSHA PEL (Ceiling)	0.02 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Toluene diisocyanate, oligomeric reaction products with 2,2'-oxydiethanol and propylenetriethanol (53317-61-6)

No additional information available

Tris(p-isocyanatophenyl) thiophosphate (4151-51-3)

No additional information available

1,3,5-tris[3-(trimethoxysilyl)propyl]-1,3,5-triazine-2,4,6(1H,3H,5H)-trione (26115-70-8)

No additional information available

m-tolylidene diisocyanate (26471-62-5)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Environmental exposure controls	: Inform appropriate managerial or supervisory personnel of all environmental releases.

8.3. Individual protection measures/Personal protective equipment**Personal protective equipment:**

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

Materials for protective clothing:

Wear suitable protective clothing.

Hand protection:

Protective gloves.

Type	Material	Permeation	Thickness (mm)	Penetration
	Viton	2 (> 30 minutes)	0.4	
	In case of splash contact: Nitrile rubber (NBR), butyl rubber	2 (> 30 minutes)	0.4	

Eye protection:

EN 166. Safety glasses with side shields

Skin and body protection:

Wear suitable protective clothing. EN 14605

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection. Type A - High-boiling (>65 °C) organic compounds

Thermal hazard protection:

Wear appropriate thermal protective clothing, when necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	: Liquid
Color	: Black
Odor	: solvents -like
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 70 °C
Flash point	: -4 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Not applicable.
Vapor pressure	: 99.9915 hPa
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: $\approx 0.97 \text{ g/cm}^3$ @ 20°C
Solubility	: insoluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: < 20.5 mm ² /s @ 40°C
Viscosity, dynamic	: $\approx 15 \text{ mPa}\cdot\text{s}$ @ 20°C
Explosion limits	: LEL: 1.8 vol % UEL: 11.5 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content : 68.05 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Methanol.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

4,4'-methylenediphenyl diisocyanate (101-68-8)	
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
Tris(p-isocyanatophenyl) thiophosphate (4151-51-3)	
ATE US (oral)	500 mg/kg body weight
1,3,5-tris[3-(trimethoxysilyl)propyl]-1,3,5-triazine-2,4,6(1H,3H,5H)-trione (26115-70-8)	
LD50 oral rat	1713 mg/kg
ATE US (oral)	1713 mg/kg body weight
m-tolyldiene diisocyanate (26471-62-5)	
ATE US (gases)	100 ppmV/4h
ATE US (vapors)	0.5 mg/l/4h
ATE US (dust, mist)	0.05 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

ethylacetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
butanone (78-93-3)	
STOT-single exposure	May cause drowsiness or dizziness.
4,4'-methylenediphenyl diisocyanate (101-68-8)	
STOT-single exposure	May cause respiratory irritation.
m-tolylidene diisocyanate (26471-62-5)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

4,4'-methylenediphenyl diisocyanate (101-68-8)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified
Viscosity, kinematic : < 20.5 mm²/s @ 40°C
Symptoms/effects: : May cause drowsiness or dizziness.
Symptoms/effects after inhalation : May cause an allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact : May cause an allergic skin reaction.
Symptoms/effects after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

ethylacetate (141-78-6)	
Log Pow	0.68 @ 25°C

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations.

Waste treatment methods : Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations	: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Additional information	: Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA No	: UN1866
UN-No.	: 1866
UN-No. (IMDG)	: 1866
UN-No. (IATA)	: 1866

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Resin solution
Proper Shipping Name (TDG)	: RESIN SOLUTION, flammable
Proper Shipping Name (IMDG)	: RESIN SOLUTION
Proper Shipping Name (IATA)	: Resin solution

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT)	: 3
Hazard labels (DOT)	: 3

TDG

Transport hazard class(es) (TDG)	: 3
----------------------------------	-----

IMDG

Transport hazard class(es) (IMDG)	: 3
Hazard labels (IMDG)	: 3

IATA

Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3

14.4. Packing group

Packing group (DOT)	: II
Packing group (TDG)	: II
Packing group (IMDG)	: II
Packing group (IATA)	: II

14.5. Environmental hazards

Other information	: No supplementary information available.
-------------------	---

14.6. Special precautions for user

DOT

UN-No.(DOT)	: UN1866
-------------	----------

DOT Special Provisions (49 CFR 172.102)	: 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons). B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 173
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

TDG

UN-No.	: 1866
Explosive Limit and Limited Quantity Index	: 5 L
Emergency Response Guide (ERG) Number	: 127

IMDG

Packing instructions (IMDG)	: P001
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	: B

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provision (IATA)	: A3
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

Inventories

All components are listed or exempted:

AICS (Australian Inventory of Chemical Substances)

PICCS (Philippines Inventory of Chemicals and Chemical Substances)

NZIoC (New Zealand Inventory of Chemicals)
Canada DSL
Korea Existing Chemicals Inventory (KECI) : All components are listed or exempted
Inventory of Existing Chemical Substances in China (IECSC)
United States TSCA (Toxic Substances Control Act)
TCSI (Taiwan Chemical Substance Inventory)
At least one component is not listed in:
Japanese ENCS (Existing & New Chemical Substances) inventory
Canadian NDSL (Non-Domestic Substances List)

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

Sika Primer-217 LUM

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 07/14/2023

Data sources : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.


Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOEC	No-Observed Effect Concentration

NOAEL	No-Observed Adverse Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
RRN	REACH Registration no.
VOC	Volatile organic compounds

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Indication of changes:

Composition/Information on ingredients. Hazards identification. Regulatory information.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



	Part Number	Container size	Part of Kit	
1	C2D49241 A	30 ml	C2D49241	Windshield Glazing Repair Kit
2	C2D7026 A	30 ml	C2D7026	Adhesive Glass Bonding
3	LR074642 A	30 ml	LR074642	Adhesive Glass Bonding
4	LR078295 A	30 ml	LR078295	Windshield Glazing Repair Kit
5	LR181405	30 ml		