
Constructing Data-Driven Network Models of Cell Dynamics with Perturbation Experiments

Bo Yuan, Ciyue Shen, Chris Sander
cBio Center, Dana-Farber Cancer Institute
Dept of Cell Biology, Harvard Medical School
Broad Institute of MIT and Harvard

{boyuan, c_shen}@g.harvard.edu, sander.research@gmail.com

Abstract

Systematic perturbation of cells followed by comprehensive measurements of molecular and phenotypic responses provides informative data resources for constructing computational models of cell biology. Existing machine learning models of cell dynamics have limited effectiveness to find global optima in a high-dimensional space and/or lack interpretability in terms of cellular mechanisms. Here we introduce a hybrid approach that combines explicit protein-protein and protein-phenotype interaction models of cell dynamics with automatic differentiation. We tested the modeling framework on a perturbation-response dataset of a melanoma cell line with drug treatments. These machine learning models can be efficiently trained to describe cellular behavior with good accuracy but also can provide direct mechanistic interpretation. The predictions and inference of interactions are robust against simulated experimental noise. The approach is readily applicable to a broad range of kinetic models of cell biology and provides encouragement for the collection of large-scale perturbation-response datasets.

1 Introduction

Resistance to single drug treatment emerged as a new bottleneck for therapeutics in cancer [1–4]. However, experimental screening of all possible pairwise or higher-order combinations of anticancer agents is practically unrealistic. The ability to model cell biology at a larger scale and to infer potential effects of unobserved drug combos is critical in facilitating the search for combinatorial, potentially therapeutic candidates.

Perturbation screens In order to address the challenge of understanding cell behavior, a large variety of experimental screening approaches has been used to profile cellular responses under different perturbations. Phenotypic screening collects high-throughput information on whole-cell responses with univariate readouts such as cell viability or growth rate [5–9]. In order to resolve intracellular interactions and provide mechanistic insights, molecular screenings have been developed to profile post-perturbational systematic responses, e.g., changes in transcript [10–12] and protein levels [13, 14]. These rich datasets challenge computational methods to describe mechanisms more comprehensively and to model cell responses to unseen perturbations quantitatively, e.g. in order to propose potential drug combinations.

Computational methods To efficiently narrow down the search space and nominate promising sets of experimentally testable candidates, computational biology models have been used to predict cellular responses based on sets of perturbation experiments, but the majority are limited by scope. A more detailed review of existing computational models can be found in Section 4. Recently, a promising alternative emerges from the field of machine learning, that is to use deep neural networks to train a

black-box predictor of drug effects. Deep learning has been successfully applied to many domains of biomedical research, from pathology image classification [15, 16] to sequence motif detection [17]. While predictive power of deep learning models is often impressive, their interpretation, which is crucial for providing understandable and, therefore, more trustable predictions in biomedical research, remains challenging. One of the main reasons is that the complex multi-layer network architecture of most deep learning models lacks explicit representations and consequent direct interpretation [18].

CellBox: a hybrid approach To address the problem of both accuracy and interpretability, we apply a deep learning optimization approach to learn a data-driven network model, which incorporates a dynamic differential equations system of an explicitly interpretable interaction network of cellular components [19]. We performed proof-of-concept model training with experimental data from a cancer cell line (Section 2), achieved a high level of learning performance (Section 3.1), and demonstrated the robustness of the approach (Section 3.2). We named this scientific machine learning framework CellBox, in contrast to a 'black-box' neural network. We also provided a detailed review of related modeling approaches (Section 4).

2 Proposed models

Model construction A set of ordinary differential equations (ODE) is used to link the measurements of the system upon perturbations:

$$\frac{\partial x_i^\mu(t)}{\partial t} = \epsilon_i \Phi\left(\sum_{j \neq i} w_{ij} x_j^\mu(t) + u_i^\mu(t)\right) - \alpha_i x_i^\mu(t) \quad (1)$$

where each $x_i^\mu(t)$ represents a log-normalized change of a molecular or phenotypic measurement relative to control measurement under a particular perturbation condition μ . $u_i^\mu(t)$ quantifies the strength of the perturbation on its downstream target i . α_i characterizes the effect of natural decay, which is the tendency of an entity to return to its steady state level before perturbation. The interaction parameter w_{ij} quantifies the directional interaction from network node j to network node i . The interaction parameters w_{ij} are constrained such that there are no i) incoming connections for direct downstream nodes of perturbations, ii) out-going connections for phenotypic nodes, or iii) self-interactions. A sigmoid envelope function $\Phi(x) = \tanh(x)$ is used to introduce a saturation effect of the interaction term so that it is bounded by ϵ_i .




Figure 1: The CellBox pipeline.

Inference As described in Figure 1, the ODE system is numerically solved using Heun’s method [20]:

$$x_i(t+h) = x_i(t) + \frac{h}{2} [f(t, x_i(t)) + f(t+h, \hat{x}_i(t+h))] \quad (2)$$

where $\hat{x}_i(t+h) = x_i(t) + hf(t, x_i(t))$, $x_i(t_0) = 0$. The loss function $L(w)$ is defined as a weighted sum of prediction error, represented as mean squared error, and complexity penalty of the network, represented as L1 regularization:

$$L(w) = \sum_{\mu} \sum_i \|\hat{x}_i(w_{ij}, t) - x_i^{\mu*}(t)\|_2 + \lambda_1 \|w_{ij}\|_1 \quad (3)$$

where $\hat{x}_i(w_{ij}, t)$ is calculated as the converged value of the numerical simulation of the ODE with the inferred interaction parameters w_{ij} and defined simulation time t , and $x_i^{\mu*}(t)$ represents the experimental measurement. During model training, the parameters would be optimized iteratively via back propagation and automatic differentiation on the total loss using Adam optimizer [21].

The implementation is under the TensorFlow framework [22] and is publicly available at <https://github.com/dfci/CellBox>.

Bias-variance tradeoff Optimizing parameters to model a biological system is hard in part because of the huge parameter space. We are interested in examining the bias-variance tradeoff of CellBox models. *Bias* error, or approximation error, is the error resulting from the model choice, e.g. oversimplification or wrong assumptions. We denoted the bias error as $\|f^*(\mathbf{w}) - \hat{f}(\mathbf{w})\|$, which is lower bound of the total error. *Variance*, or estimation error, in contrast, indicates the parameter inference errors resulting from numerical optimization, denoted as $\|\hat{f}(\mathbf{w}) - \hat{f}(\hat{\mathbf{w}})\|$. The total model error is therefore upper bounded by,

$$\|f^*(\mathbf{w}) - \hat{f}(\hat{\mathbf{w}})\| \leq \|f^*(\mathbf{w}) - \hat{f}(\mathbf{w})\| + \|\hat{f}(\mathbf{w}) - \hat{f}(\hat{\mathbf{w}})\| \quad (4)$$

The bias-variance tradeoff describes that, in general, the simpler the proposed model, the larger the approximation error and the smaller estimation error. In the CellBox training objective function (4), we included an L1 loss term, which rewards model with sparser interactions by a factor λ_1 , in addition to the reconstruction loss $\sum_{\mu} \sum_i \|\hat{x}_i(\mathbf{w}, t) - x_i^{\mu*}(t)\|_2$. We also adapted the stability selection tests [23] to evaluate the stability of out inferred interactions.

3 Results

3.1 CellBox models accurately predict cell response to unseen perturbations and the inferred networks are stable

Training We first evaluated the efficiency of training CellBox models to predict cell response. As the training progresses, the predicted response converge to measured experimental response in both the training and test set (Figure 2A). At the end of the training, the predicted values highly correlate with the experimental values, independent of how the data was randomly partitioned into the training and test set.




Figure 2: Model performance with different regularization strength

Bias-variance tradeoff We were interested in the effect of different network complexity upon prediction accuracy. By applying different regularization strength λ_1 , the model performance changes as expected (Figure 2B). Using a smaller λ_1 results in increasing freedom for parameter choices, and therefore a higher upper bound of performance, but meanwhile there would be larger variances for parameter inference. To the opposite, when using smaller λ_1 , the parameter estimation is more stable, i.e. smaller variances, but the upper bound of performance is limited. These results indicate the selection of kernel model for CellBox would affect the model training in a way that is consistent with the bias-variance tradeoff. In our proof-of-concept model training, $\lambda_1 = 1e - 4$ appeared to be the sweet spot for regularization strength.

Network stability We also examine the stability of the resulting interactions in the network [23]. We found that the significant interactions inferred by the models are robust (Figure 2C). When the regularization strength λ_1 is strong, CellBox is not able to robustly identify significant interactions across models, because the objective function would be overwhelmed by the regularization term instead of the term of reconstruction accuracy.

3.2 Prediction accuracy and network stability are robust against common forms of experimental noise




Figure 3: Model robustness against experimental noise

Multiple sources can give rise to uncertainty in data collection, and consequently in model optimization, especially in biomedicine. Common forms of experimental noise include inevitable measurement variances and dropout events, e.g., for single cell measurements. To test the robustness of our models against data precision and sparsity, we perform sensitivity analysis on the data with increasing additive noise and dropout rate. We introduced two noise forms, a Gaussian random noise

(5) and a simulated dropout event (6).

$$\tilde{x}_i(t) = x_i^*(t) + \mathcal{N}(0, \sigma) \quad (5)$$

$$\tilde{x}_i(t) = \begin{cases} 0 & (\text{with a probability of } p) \\ x_i^*(t) & (\text{otherwise}) \end{cases} \quad (6)$$

With the best chosen regularization strength, the prediction accuracy of the models remain high for up to additive Gaussian noise of 0.2 standard deviation or 30% data dropout (Figure 3A-B). In addition, the inferred significant interactions are stable within the levels of data noise and dropout that the models can tolerate (Figure 3C-D). Such levels of data precision and sparsity are relevant for most experimental approaches in biological and biomedical studies, suggesting the potential of CellBox to generalize to various data sources.

4 Related work

Static regression models Co-expression models [24–26], maximum entropy networks [27, 28], or mutual information related methods [29, 30] construct network models of molecular interactions [31, 32] or use regression models to directly predict cellular responses based on molecular perturbation-response measurements [10, 12]. Such static regression models usually provide end-to-end predictions, while inevitably neglecting intermediate steps, and therefore leave prediction challenging for untested perturbations.

Dynamic models with prior knowledge Boolean network models [33], fuzzy logic models [34], dynamic Bayesian networks [35] and ordinary differential equation (ODE) network models [36, 37] can provide mechanistic insight in terms of propagation of cellular signals to phenotypic response over time, but typically require prior knowledge of interaction parameters and thus currently only work for small systems [36, 38]. New algorithms to parametrize large-scale mechanistic models, while computationally efficient, require prior knowledge of a set of relevant interactions [39]. Insufficient prior knowledge is one of the major constraints for modeling large systems, e.g., in that prior information is not available for all components or is aggregated from disparate experimental sources and thus lacks uniform context.

Data-driven dynamic models Previous dynamic optimization approaches such as Monte CarloMCMC methods and belief propagation (BP) algorithms have been used to construct data-driven network models [13, 38, 40–42]. Still, these may not efficiently scale to larger systems (e.g., MC) or may require excessive approximations for the chosen mathematical model to facilitate efficient exploration of solution space (e.g., independent row approximation in BP) [13, 40]. Models that integrate physics ODE system and neural networks uses simulated time-series datasets to look for data-driven physical laws using inductive bias methods [43, 44]. The numerical methods of ODE solver and training techniques, such as minibatching, have also been discussed [45, 46]. Recent work has highlighted mathematical analogies between recurrent neural networks (RNN) and ODEs [47], suggesting a potential merge of the two fields for scientific machine learning (SciML) models [48].

Therefore, we argue that the desired modeling methods requires four key features: 1) accuracy in describing both phenotypic and protein level changes; 2) efficiency in simulating dynamic cellular response; 3) interpretability in terms of biological mechanisms; and 4) ability to be constructed without prior knowledge about the system of interest. And we designed CellBox as an attempt to meet such requirements.

5 Conclusion

We introduced a hybrid approach combining optimization of explicit dynamic models with automatic differentiation and named it CellBox, in contrast to black-box neural network models. We demonstrated that CellBox can be trained with experimental data to accurately predict cellular behavior in response to extracellular perturbations. Without compromising accuracy, CellBox models are directly interpretable by design, in terms of protein-protein interactions that can be compared to established

models of molecular biology, such as signaling pathways. Such accuracy and interpretability of Cell-Box models are robust against common forms of noise in experimental data. We therefore envision such scientific machine learning approach to be broadly applicable to other biological questions, such as developmental biology or synthetic biology, provided that suitable perturbation-response data becomes available.

References

- [1] Jonathan B Fitzgerald, Birgit Schoeberl, Ulrik B Nielsen, and Peter K Sorger. Systems biology and combination therapy in the quest for clinical efficacy. *Nat. Chem. Biol.*, 2(9):458–466, sep 2006.
- [2] Levi A Garraway and Pasi A Jänne. Circumventing cancer drug resistance in the era of personalized medicine. *Cancer Discov.*, 2(3):214–226, mar 2012.
- [3] Behzad Mansoori, Ali Mohammadi, Sadaf Davudian, Solmaz Shirjang, and Behzad Baradaran. The Different Mechanisms of Cancer Drug Resistance: A Brief Review. *Adv Pharm Bull*, 7(3): 339–348, sep 2017.
- [4] Reza Bayat Mokhtari, Tina S Homayouni, Narges Baluch, Evgeniya Morgatskaya, Sushil Kumar, Bikul Das, and Herman Yeger. Combination therapy in combating cancer. *Oncotarget*, 8(23), 2017.
- [5] Justin Lamb, Emily D Crawford, David Peck, Joshua W Modell, Irene C Blat, Matthew J Wrobel, Jim Lerner, Jean-Philippe Brunet, Aravind Subramanian, Kenneth N Ross, Michael Reich, Haley Hieronymus, Guo Wei, Scott A Armstrong, Stephen J Haggarty, Paul A Clemons, Ru Wei, Steven A Carr, Eric S Lander, and Todd R Golub. The Connectivity Map: using gene-expression signatures to connect small molecules, genes, and disease. *Science*, 313(5795): 1929–1935, sep 2006.
- [6] Hiu Wing Cheung, Glenn S Cowley, Barbara A Weir, Jesse S Boehm, Scott Rusin, Justine A Scott, Alexandra East, Levi D Ali, Patrick H Lizotte, Terence C Wong, Guozhi Jiang, Jessica Hsiao, Craig H Mermel, Gad Getz, Jordi Barretina, Shuba Gopal, Pablo Tamayo, Joshua Gould, Aviad Tsherniak, Nicolas Stransky, Biao Luo, Yin Ren, Ronny Drapkin, Sangeeta N Bhatia, Jill P Mesirov, Levi A Garraway, Matthew Meyerson, Eric S Lander, David E Root, and William C Hahn. Systematic investigation of genetic vulnerabilities across cancer cell lines reveals lineage-specific dependencies in ovarian cancer. *Proc. Natl. Acad. Sci. U. S. A.*, 108(30): 12372–12377, jul 2011.
- [7] Tim Wang, Jenny J Wei, David M Sabatini, and Eric S Lander. Genetic screens in human cells using the {CRISPR-Cas9} system. *Science*, 343(6166):80–84, jan 2014.
- [8] E Robert McDonald 3rd, Antoine de Weck, Michael R Schlabach, Eric Billy, Konstantinos J Mavrikakis, Gregory R Hoffman, Dhiren Belur, Deborah Castelletti, Elizabeth Frias, Kalyani Gampa, Javad Golji, Iris Kao, Li Li, Philippe Megel, Thomas A Perkins, Nadire Ramadan, David A Ruddy, Serena J Silver, Sosathya Sovath, Mark Stump, Odile Weber, Roland Widmer, Jianjun Yu, Kristine Yu, Yingzi Yue, Dorothee Abramowski, Elizabeth Ackley, Rosemary Barrett, Joel Berger, Julie L Bernard, Rebecca Billig, Saskia M Brachmann, Frank Buxton, Roger Caothien, Justina X Caushi, Franklin S Chung, Marta Cortés-Cros, Rosalie S DeBeaumont, Clara Delaunay, Aurore Desplat, William Duong, Donald A Dwoske, Richard S Eldridge, Ali Farsidjani, Fei Feng, Jiajia Feng, Daisy Flemming, William Forrester, Giorgio G Galli, Zhenhai Gao, François Gauter, Veronica Gibaja, Kristy Haas, Marc Hattenberger, Tami Hood, Kristen E Hurov, Zainab Jagani, Mathias Jenal, Jennifer A Johnson, Michael D Jones, Avnish Kapoor, Joshua Korn, Jilin Liu, Qiumei Liu, Shumei Liu, Yue Liu, Alice T Loo, Kaitlin J Macchi, Typhaine Martin, Gregory McAllister, Amandine Meyer, Sandra Mollé, Raymond A Pagliarini, Tanushree Phadke, Brian Repko, Tanja Schouwey, Frances Shanahan, Qiong Shen, Christelle Stamm, Christine Stephan, Volker M Stucke, Ralph Tiedt, Malini Varadarajan, Kavitha Venkatesan, Alberto C Vitari, Marco Wallroth, Jan Weiler, Jing Zhang, Craig Mikanin, Vic E Myer, Jeffery A Porter, Albert Lai, Hans Bitter, Emma Lees, Nicholas Keen, Audrey Kauffmann, Frank Stegmeier, Francesco Hofmann, Tobias Schmelzle, and William R Sellers. Project {DRIVE}: A Compendium of Cancer Dependencies and Synthetic Lethal Relationships Uncovered by {Large-Scale}, Deep {RNAi} Screening. *Cell*, 170(3):577—592.e10, jul 2017.
- [9] Aviad Tsherniak, Francisca Vazquez, Phil G Montgomery, Barbara A Weir, Gregory Kryukov, Glenn S Cowley, Stanley Gill, William F Harrington, Sasha Pantel, John M Krill-Burger, Robin M Meyers, Levi Ali, Amy Goodale, Yenarae Lee, Guozhi Jiang, Jessica Hsiao, William F J Gerath, Sara Howell, Erin Merkel, Mahmoud Ghandi, Levi A Garraway, David E Root, Todd R Golub, Jesse S Boehm, and William C Hahn. Defining a Cancer Dependency Map. *Cell*, 170(3):564—576.e16, jul 2017.

- [10] Atray Dixit, Oren Parnas, Biyu Li, Jenny Chen, Charles P Fulco, Livnat Jerby-Arnon, Nemanja D Marjanovic, Danielle Dionne, Tyler Burks, Raktima Raychowdhury, Britt Adamson, Thomas M Norman, Eric S Lander, Jonathan S Weissman, Nir Friedman, and Aviv Regev. {Perturb-Seq}: Dissecting Molecular Circuits with Scalable {Single-Cell} {RNA} Profiling of Pooled Genetic Screens. *Cell*, 167(7):1853—1866.e17, dec 2016.
- [11] Mario Niepel, Marc Hafner, Qiaonan Duan, Zichen Wang, Evan O Paull, Mirra Chung, Xiaodong Lu, Joshua M Stuart, Todd R Golub, Aravind Subramanian, Avi Ma’ayan, and Peter K Sorger. Common and cell-type specific responses to anti-cancer drugs revealed by high throughput transcript profiling. *Nat. Commun.*, 8(1):1186, oct 2017.
- [12] Thomas M Norman, Max A Horlbeck, Joseph M Replogle, Alex Y Ge, Albert Xu, Marco Jost, Luke A Gilbert, and Jonathan S Weissman. Exploring genetic interaction manifolds constructed from rich phenotypes. apr 2019.
- [13] Anil Korkut, Weiqing Wang, Emek Demir, Bülent Arman Aksoy, Xiaohong Jing, Evan J Molinelli, Özgün Babur, Debra L Bemis, Selcuk Onur Sumer, David B Solit, Christine A Pratilas, and Chris Sander. Perturbation biology nominates upstream-downstream drug combinations in {RAF} inhibitor resistant melanoma cells. *Elife*, 4, aug 2015.
- [14] Steven M Hill, Nicole K Nesser, Katie Johnson-Camacho, Mara Jeffress, Aimee Johnson, Chris Boniface, Simon E F Spencer, Yiling Lu, Laura M Heiser, Yancey Lawrence, Nupur T Pande, James E Korkola, Joe W Gray, Gordon B Mills, Sach Mukherjee, and Paul T Spellman. Context Specificity in Causal Signaling Networks Revealed by Phosphoprotein Profiling. *Cell Syst*, 4(1): 73—83.e10, jan 2017.
- [15] Le Hou, Dimitris Samaras, Tahsin M Kurc, Yi Gao, James E Davis, and Joel H Saltz. Patch-based Convolutional Neural Network for Whole Slide Tissue Image Classification. *Proc. IEEE Comput. Soc. Conf. Comput. Vis. Pattern Recognit.*, 2016:2424—2433, jun 2016.
- [16] Andre Esteva, Brett Kuprel, Roberto A Novoa, Justin Ko, Susan M Swetter, Helen M Blau, and Sebastian Thrun. Dermatologist-level classification of skin cancer with deep neural networks. *Nature*, 542(7639):115—118, feb 2017.
- [17] Jian Zhou and Olga G Troyanskaya. Predicting effects of noncoding variants with deep learning-based sequence model. *Nat. Methods*, 12(10):931—934, oct 2015.
- [18] Grégoire Montavon, Wojciech Samek, and Klaus-Robert Müller. Methods for interpreting and understanding deep neural networks. 73:1—15, 2018.
- [19] Bo Yuan, Ciyue Shen, Augustin Luna, Anil Korkut, Debora S. Marks, John Ingraham, and Chris Sander. Interpretable Machine Learning for Perturbation Biology. *bioRxiv*, page 746842, aug 2019. doi: 10.1101/746842. URL <https://www.biorxiv.org/content/10.1101/746842v3>.
- [20] Endre Süli and David F Mayers. *An Introduction to Numerical Analysis*. Cambridge University Press, aug 2003.
- [21] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. 2017.
- [22] Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dandelion Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. URL <https://www.tensorflow.org/>. Software available from tensorflow.org.
- [23] Nicolai Meinshausen and Peter Bühlmann. Stability selection. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 72(4):417—473, jul 2010. ISSN 13697412. doi: 10.1111/j.1467-9868.2010.00740.x. URL <http://doi.wiley.com/10.1111/j.1467-9868.2010.00740.x>.

- [24] S. L. Carter, C. M. Brechbuhler, M. Griffin, and A. T. Bond. Gene co-expression network topology provides a framework for molecular characterization of cellular state. *Bioinformatics*, 20(14):2242–2250, sep 2004. ISSN 1367-4803. doi: 10.1093/bioinformatics/bth234. URL <https://academic.oup.com/bioinformatics/article-lookup/doi/10.1093/bioinformatics/bth234>.
- [25] Kai Wang, Masumichi Saito, Brygida C Bisikirska, Mariano J Alvarez, Wei Keat Lim, Presha Rajbhandari, Qiong Shen, Ilya Nemenman, Katia Basso, Adam A Margolin, Ulf Klein, Riccardo Dalla-Favera, and Andrea Califano. Genome-wide identification of post-translational modulators of transcription factor activity in human B cells. *Nature Biotechnology*, 27(9):829–837, sep 2009. ISSN 1087-0156. doi: 10.1038/nbt.1563. URL <http://www.ncbi.nlm.nih.gov/pubmed/19741643><http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=PMC2753889><http://www.nature.com/articles/nbt.1563>.
- [26] Özgün Babur, Emek Demir, Mithat Gönen, Chris Sander, and Ugur Dogrusoz. Discovering modulators of gene expression. *Nucleic Acids Research*, 38(17):5648–5656, sep 2010. ISSN 1362-4962. doi: 10.1093/nar/gkq287. URL <https://academic.oup.com/nar/article-lookup/doi/10.1093/nar/gkq287>.
- [27] T. R. Lezon, J. R. Banavar, M. Cieplak, A. Maritan, and N. V. Fedoroff. Using the principle of entropy maximization to infer genetic interaction networks from gene expression patterns. *Proceedings of the National Academy of Sciences*, 103(50):19033–19038, dec 2006. ISSN 0027-8424. doi: 10.1073/pnas.0609152103. URL <http://www.ncbi.nlm.nih.gov/pubmed/17138668><http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=PMC1748172><http://www.pnas.org/cgi/doi/10.1073/pnas.0609152103>.
- [28] Jason W. Locasale and Alejandro Wolf-Yadlin. Maximum Entropy Reconstructions of Dynamic Signaling Networks from Quantitative Proteomics Data. *PLoS ONE*, 4(8):e6522, aug 2009. ISSN 1932-6203. doi: 10.1371/journal.pone.0006522. URL <https://dx.plos.org/10.1371/journal.pone.0006522>.
- [29] Patrick E Meyer, Frédéric Lafitte, and Gianluca Bontempi. minet: A R/Bioconductor Package for Inferring Large Transcriptional Networks Using Mutual Information. *BMC Bioinformatics*, 9(1):461, dec 2008. ISSN 1471-2105. doi: 10.1186/1471-2105-9-461. URL <https://bmcbioinformatics.biomedcentral.com/articles/10.1186/1471-2105-9-461>.
- [30] Thalia E. Chan, Michael P.H. Stumpf, and Ann C. Babbie. Gene regulatory network inference from single-cell data using multivariate information measures. *Cell Systems*, 5(3):251–267.e3, September 2017. doi: 10.1016/j.cels.2017.08.014. URL <https://doi.org/10.1016/j.cels.2017.08.014>.
- [31] Yasin Senbabaoglu, Selçuk Onur Sümer, Francisco Sánchez-Vega, Debra Bemis, Giovanni Ciriello, Nikolaus Schultz, and Chris Sander. A {Multi-Method} Approach for Proteomic Network Inference in 11 Human Cancers. *PLoS Comput. Biol.*, 12(2):e1004765, feb 2016.
- [32] Song Yi, Shengda Lin, Yongsheng Li, Wei Zhao, Gordon B Mills, and Nidhi Sahni. Functional variomics and network perturbation: connecting genotype to phenotype in cancer. *Nat. Rev. Genet.*, 18(7):395–410, jul 2017.
- [33] P. D’haeseleer, S. Liang, and R. Somogyi. Genetic network inference: from co-expression clustering to reverse engineering. *Bioinformatics*, 16(8):707–726, aug 2000. ISSN 1367-4803. doi: 10.1093/bioinformatics/16.8.707. URL <https://academic.oup.com/bioinformatics/article-lookup/doi/10.1093/bioinformatics/16.8.707>.
- [34] Bree B. Aldridge, Julio Saez-Rodriguez, Jeremy L. Muhlich, Peter K. Sorger, and Douglas A. Lauffenburger. Fuzzy Logic Analysis of Kinase Pathway Crosstalk in TNF/EGF/Insulin-Induced Signaling. *PLoS Computational Biology*, 5(4):e1000340, apr 2009. ISSN 1553-7358. doi: 10.1371/journal.pcbi.1000340. URL <https://dx.plos.org/10.1371/journal.pcbi.1000340>.

- [35] Zou M and Conzen SD. A New Dynamic Bayesian Network (DBN) Approach for Identifying Gene Regulatory Networks From Time Course Microarray Data. *Bioinformatics (Oxford, England)*, 21(1), 2005. ISSN 1367-4803. doi: 10.1093/BIOINFORMATICS/BTH463. URL <https://pubmed.ncbi.nlm.nih.gov/15308537/>.
- [36] Timothy S Gardner, Diego di Bernardo, David Lorenz, and James J Collins. Inferring genetic networks and identifying compound mode of action via expression profiling. *Science*, 301(5629):102–105, jul 2003.
- [37] Elin Nyman, Richard R. Stein, Xiaohong Jing, Weiqing Wang, Benjamin Marks, Ioannis K. Zervantonakis, Anil Korkut, Nicholas P. Gauthier, and Chris Sander. Perturbation biology links temporal protein changes to drug responses in a melanoma cell line. *PLOS Computational Biology*, 16(7):e1007909, July 2020. doi: 10.1371/journal.pcbi.1007909. URL <https://doi.org/10.1371/journal.pcbi.1007909>.
- [38] Bertram Klinger, Anja Sieber, Raphaela Fritsche-Guenther, Franziska Witzel, Leanne Berry, Dirk Schumacher, Yibing Yan, Pawel Durek, Mark Merchant, Reinhold Schäfer, Christine Sers, and Nils Blüthgen. Network quantification of EGFR signaling unveils potential for targeted combination therapy. *Molecular systems biology*, 9(1):673, apr 2013. ISSN 1744-4292. doi: 10.1038/msb.2013.29. URL <http://msb.embopress.org/cgi/doi/10.1038/msb.2013.29><http://www.ncbi.nlm.nih.gov/pubmed/23752269><http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=PMC3964313>.
- [39] Fabian Fröhlich, Thomas Kessler, Daniel Weindl, Alexey Shadrin, Leonard Schmiester, Hendrik Hache, Artur Muradyan, Moritz Schütte, Ji Hyun Lim, Matthias Heinig, Fabian J. Theis, Hans Lehrach, Christoph Wierling, Bodo Lange, and Jan Hasenauer. Efficient Parameter Estimation Enables the Prediction of Drug Response Using a Mechanistic Pan-Cancer Pathway Model. *Cell Systems*, 7(6):567–579.e6, 2018. ISSN 24054720. doi: 10.1016/j.cels.2018.10.013.
- [40] Frank J. Bruggeman, Hans V. Westerhoff, Jan B. Hoek, and Bori N. Kholodenko. Modular Response Analysis of Cellular Regulatory Networks. *Journal of Theoretical Biology*, 218(4): 507–520, oct 2002. ISSN 0022-5193. doi: 10.1006/JTBI.2002.3096. URL <https://www.sciencedirect.com/science/article/abs/pii/S0022519302930961>.
- [41] Sven Nelander, Weiqing Wang, Björn Nilsson, Qing-Bai She, Christine Pratilas, Neal Rosen, Peter Gennemark, and Chris Sander. Models from experiments: combinatorial drug perturbations of cancer cells. *Mol. Syst. Biol.*, 4:216, sep 2008.
- [42] S Hug, A Raue, J Hasenauer, J Bachmann, U Klingmüller, J Timmer, and F J Theis. High-dimensional Bayesian parameter estimation: case study for a model of {JAK2/STAT5} signaling. *Math. Biosci.*, 246(2):293–304, dec 2013.
- [43] Miles Cranmer, Alvaro Sanchez-Gonzalez, Peter Battaglia, Rui Xu, Kyle Cranmer, David Spergel, and Shirley Ho. Discovering Symbolic Models from Deep Learning with Inductive Biases. jun 2020. URL <http://arxiv.org/abs/2006.11287>.
- [44] Samuel H. Rudy, Steven L. Brunton, Joshua L. Proctor, and J. Nathan Kutz. Data-driven discovery of partial differential equations. *Science Advances*, 3(4):e1602614, apr 2017. ISSN 2375-2548. doi: 10.1126/sciadv.1602614. URL <https://advances.sciencemag.org/lookup/doi/10.1126/sciadv.1602614>.
- [45] Philipp Städter, Yannik Schälte, Leonard Schmiester, Jan Hasenauer, and Paul L. Stapor. Benchmarking of numerical integration methods for ode models of biological systems. *bioRxiv*, 2020. doi: 10.1101/2020.09.03.268276. URL <https://www.biorxiv.org/content/early/2020/09/04/2020.09.03.268276>.
- [46] Paul Stapor, Leonard Schmiester, Christoph Wierling, Bodo M.H. Lange, Daniel Weindl, and Jan Hasenauer. Mini-batch optimization enables training of ODE models on large-scale datasets. *bioRxiv*, (42):859884, 2019. doi: 10.1101/859884.
- [47] Ricky T Q Chen, Yulia Rubanova, Jesse Bettencourt, and David Duvenaud. Neural Ordinary Differential Equations. *NeurIPS*, 2018. URL <https://arxiv.org/pdf/1806.07366.pdf>.

- [48] Christopher Rackauckas, Yingbo Ma, Julius Martensen, Collin Warner, Kirill Zubov, Rohit Supekar, Dominic Skinner, Ali Ramadhan, and Alan Edelman. Universal differential equations for scientific machine learning. 2020.