

ATTORNEY SHIELD

ASI 2.0 - Native Android & iOS

Attorney Shield 2.0 - Backend asks from

Backend asks — updated 2026-08-13

Colour system: Attorney-Shield Color Scheme Review

Repository: samson-phillip/asi-claude

DRAFT FOR APPROVAL

Contents

Where things stand	3
You shipped four operations this afternoon - thank you	3
Earlier the same day	3
At a glance	4
Already working - please don't re-do these	5
Yes A1, A2 and A3 are fixed - verified 2026-08-13	6
~~A1 - countries returns empty while the same rows resolve by id~~ · FIXED	7
~~A2 - Incident types are not seeded~~ · FIXED	7
~~A3 - Document types and fields are not seeded~~ · FIXED	8
A4 - Still no real case for the test member · MEDIUM	8
A7 - addSubaccount accepts a seatPriceID that does not exist · DATA	8
A8 - the attorney behind a call cannot be read without a timeout · MEDIUM	9
A5 - a member cannot delete their own document · HIGH	9
A6 - what does the document-field type vocabulary mean? · MEDIUM	10
B1 - Phone verification · HIGH · blocks screens 08, 09	10
B2 - Pronouns · LOW · blocks one field of screen 10	10
B3 - Situation preferences · HIGH · blocks screens 13B, 13C, 27B	11
B4 - Emergency-contact notify-by · MEDIUM · blocks two controls on screen 16	11
B5 - The trial conversion, in detail · HIGH · blocks 5 native screens	11
B5a - Guest mode · HIGH · blocks G1-G3	12
B6 - No member-readable transcript · LOW · one link on screen 32	12
B8 - Notification categories, a frequency dial, and what kind means · MEDIUM	12
B7 - A member cannot change their card in the app · MEDIUM · blocks 33D	13
D1 - POST /api/vonage/video/member-call takes no authentication	14
E1 - Deep-link contract for the web->app handoff · HIGH	14
E2 - Domain verification files · HIGH · web hosting	15
What we ship as each lands	15
Where we are	16

From: mobile (Android + iOS) **Date:** 2026-08-13 - **re-verified twice; second pass caught four operations you shipped mid-afternoon** **Environment:** <https://gateway-dev.attorneyshield.io/query> · <https://comms-dev.attorneyshield.io>

Every item below is something **you can act on**. Our own to-dos, design questions and the things we are arranging ourselves are deliberately not here.

Everything was verified by introspecting the schema and calling the operations as the test member - not inferred from the web client. Where we were wrong earlier, it is corrected and marked.

Where things stand

You shipped four operations this afternoon - thank you

We went looking for trial operations and found these instead. **They close B1, B3 and C8 outright**, and we had not been told, so flagging in case anything else landed with them:

New	Closes	Unblocks
<code>requestPhoneVerification(phoneE164) -> { sent, maskedPhone, expiresInSeconds }</code>	B1	Registration screens 08 and 09
<code>verifyPhone(phoneE164, code) -> Boolean</code>	B1	"
<code>myCommonSituations / setMyCommonSituations(incidentTypeIds)</code>	B3	Screens 13B, 13C, 27B
<code>completeMyOnboarding() -> UserProfile, plus UserProfile.onboardingCompletedAt</code>	C8	We can stop inferring completeness from five other fields

`myCommonSituations` returns `[]` for our test member and `onboardingCompletedAt` is null, both as expected. **We have not called** `requestPhoneVerification` - it sends a real SMS, and we would rather do that deliberately when we build the screen than as a probe.

One question on B1: **how many digits is the phone code?** Sign-in codes are 4; the design draws 6 cells for phone verification.

Earlier the same day

Re-tested	Result
<code>countries { iso2 name }</code>	United States Yes - was <code>[]</code>
A5 <code>deleteUserDocument</code> on the member's own file	still forbidden
A6 field type vocabulary and the dev test rows	unchanged

Re-tested	Result
D1 POST <code>/api/vonage/video/member-call</code> unauthenticated	still accepted (reaches body validation with no token)
A4 casesByUser	not empty any more - but only because our own test calls created six cases. partnerID is null on all of them and the jurisdiction is still the hard-coded dev seed, so attorney pre-selection is as untestable as before

We are not blocked on any of it right now - this week's screens are all built on operations that already work. Please treat the below as a queue, not an emergency.

At a glance

#	Ask	Severity	Unblocks
A1	<code>countries</code> returns []	~~HIGH~~	Yes FIXED - verified today
A2	Incident types + an English default language	~~BLOCKING~~	Yes FIXED - Home renders real tiles
A3	Document types + fields	~~HIGH~~	Yes FIXED - the Glovebox is built
A4	Still no <i>real</i> case for the test member	MEDIUM	Attorney pre-selection, real jurisdiction
A5	<code>deleteUserDocument</code> is forbidden for a member's own file	HIGH	Removing a document from the Glovebox
A6	What the document-field type vocabulary means	MEDIUM	Rendering the right control per field
A7	<code>addSubaccount</code> accepts a <code>seatPriceID</code> that does not exist	DATA	Correct billing on family seats
A8	<code>attorneyAssignments { attorney { ... } }</code> times out	MEDIUM	Attorney name on the Activity timeline
B1	No phone send/verify operations	~~HIGH~~	Yes SHIPPED - <code>requestPhoneVerification / verifyPhone</code>
B2	No pronouns field	LOW	The last field of screen 10
B3	No situation-preference operations	~~HIGH~~	Yes SHIPPED - <code>myCommonSituations / setMyCommonSituations</code>
B4	No notify-by field on emergency contacts	MEDIUM	Two controls on screen 16
B5	No way to convert a trial and charge	HIGH	5 native screens (V2, T5-T8) - spec below

#	Ask	Severity	Unblocks
B5a	No guest model	HIGH	3 screens (G1-G3)
B6	No member-readable transcript	LOW	"View transcript" on Test Call entries (screen 32)
B7	No way to change a card in-app	MEDIUM	Screen 33D, and the Update row on 33A
B8	Notification categories, frequency and kind	MEDIUM	Most of screen 26
C1-C7	Seven answers we are currently guessing	MEDIUM	Token refresh, PIN gate, guest design
C8	An onboarding-complete flag	~~MEDIUM~~	Yes SHIPPED - completeMyOnboarding, onboardingCompletedAt
D1	member - call takes no authentication	SECURITY	-
E1-E2	Deep-link contract + domain files (not the gateway)	HIGH	Silent web->app handoff

Already working - please don't re-do these

Area	Operations
Sign in, password	login
Sign in, one-time code	requestLoginOtp / verifyLoginOtp
Date of birth, gender	updateMyProfile
Home + mailing address	updateMyProfile, createUserAddress
Security PIN	setMemberPin, memberPinStatus
Set a password	setPassword, User.hasPassword
Emergency contacts	createEmergencyContact + CRUD
States/provinces	subdivisionsByCountry - all 50 US states resolve
Video call credentials	POST /api/vonage/video/member-call
Membership + entitlement	myMembership, membershipEntitlement
Plan name and price	Membership.items -> price -> product
Card on file (read)	myPaymentMethods

Area	Operations
Family sub-accounts	mySubaccounts, addSubaccount, removeSubaccount, sendUserInvite
Receipts	invoicesBySubscriber
Call history	commsCallsByMember
Change password	changePassword
Language + notification prefs	updateMyProfile (primaryLanguageTag, notificationsEnabled, marketingOptIn)
Terms and privacy text	adminTermsOfServiceList - four live documents
Notifications	notificationList, unreadNotificationCount, markNotificationRead, markAllNotificationsRead, clearNotifications
Close account	deleteMyAccount

All of the above are **built and writing to dev**. The Vonage SDK is also proven on a real Android device: the native library loads, reports 2.32.1, and completes a round trip to Vonage.

The second half of that table is new since the last version of this document. We had not looked past registration; when we did, most of the account section turned out to already exist. **We are telling you so you don't build it twice** - the member-facing Profile, Payment & plan, Family members, Settings and Activity screens are all built on operations that were already there.

A. Environment and seeding

Yes A1, A2 and A3 are fixed - verified 2026-08-13

Confirmed against dev as the test member, and the apps now render it:

Check	Result
countries	United States Yes
adminIncidentTypeList(activeOnly: true, countryISO2: "US")	6 types - Test Call, Traffic Stop, Domestic, Auto Accident, Pedestrian Stop, Other Yes
adminLanguageList	en-US with isDefault: true, plus es-ES and ar-SA Yes
Translations	English and Spanish on every type Yes
iconFilePath	Real CloudFront URLs on all six Yes
adminDocumentTypeList	Driver's Information, Health Information, Gun Information, Citizenship Info - all four Glovebox sections Yes
adminDocumentFieldList	20 fields Yes

Home now shows six real incident tiles with their English names for the first time. That was the blocking item; it is gone.

Two small notes, neither urgent:

- 1 The code values are human strings** - "Traffic Stop", not `traffic_stop`. We had assumed `snake_case`, so our icon lookup matched nothing and every tile fell back to a generic shield until we normalised it. Only flagging in case another client made the same assumption.
- 2 adminDocumentTypeList also contains what look like test rows** - "contract 2" and "Extra books", alongside the generic Contract / Form / Guide / Policy / Incident Report. We will render only the four Glovebox sections, but you may want to tidy those out of dev.

The rest of this section - A4 - is still open.

~~A1 - countries returns empty while the same rows resolve by id~~ · FIXED

Correction to what we told you earlier. We previously said no countries were configured. That was wrong:

Query	Result
<code>countries { iso2 }</code>	<code>[]</code>
<code>country(id: "f989d06a-8813-11f1-a446-06cf81ac74a7")</code>	United States , US Yes
<code>subdivisionsByCountry(<that id>)</code>	all 50 states + DC Yes

The data exists. The **list query** is what comes back empty, and our test member's own profile points at that same US id.

We work around it by reading the country from the member's profile instead of offering a picker - so it is not blocking us - but the list query looks broken or scoped in a way nobody intended, and we would rather tell you than quietly route around it.

~~A2 - Incident types are not seeded~~ · FIXED

```
adminIncidentTypeList(activeOnly: false) -> []
adminIncidentTypeList(activeOnly: true, countryISO2: "US") -> []
adminLanguageList -> 1 entry: ar-SA, isDefault: false
```

Retested **while authenticated**, with and without a country filter, so this is not a side-effect of A1.

This is the one that hurts most. The home screen shows "No incident types are configured yet.", so we cannot exercise the incident tiles, the attorney chip row, or place a call with a real incident type. Finishing onboarding currently lands the member on an empty screen.

Need: incident types seeded with translations - the design uses Traffic Stop, Auto Accident, Pedestrian Stop, Domestic, Test Call, Other - plus **an English language entry marked** `isDefault: true`. Without the language, our label resolution (English -> org default -> first available -> humanized code) falls through to Arabic.

~~A3 - Document types and fields are not seeded~~ · FIXED

```
adminDocumentTypeList -> []
```

The operations all exist - adminDocumentFieldList, requestUserDocumentUpload, createUserDocument, userDocumentList, userDocumentDownloadUrl, and saveUserDocumentValue for plain text fields. So this is a **seeding** ask, not a build ask.

Every upload and every saved value is keyed by adminDocumentFieldsId. With no types there are no fields, so there is nothing to attach a document or a value to, and none of the Glovebox can be built.

Need: the four sections seeded with their fields, per the design:

Section	Fields the design shows
Driver's Information	licence document upload
Health Information	three plain text fields + document upload
Gun Information	two yes/no questions, permit number, issue state
Citizenship Info	plain fields + document upload

Also please tell us **what fieldType values exist**, so we render the right control for each field rather than guessing.

A4 - Still no *real* case for the test member · MEDIUM

casesByUser is no longer empty, but nothing was seeded - **the six cases there are ones our own test calls created**. All six look like this:

```
jurisdictionID: de400000-0000-4000-8000-000000000001 <- the hard-coded dev seed
partnerID: null
```

partnerAttorneys returns [] for both the dev partner id and the org id, so attorney pre-selection still cannot be exercised at all - which was the point of the ask.

Need: one case on the test member with a real jurisdiction and a real partner, and at least one attorney under that partner.

If it is easier to point us at an environment that already has this, that works just as well. We only need somewhere to develop against.

A7 - addSubaccount **accepts a seatPriceID that does not exist** · DATA

Found by accident while probing permissions. We sent an all-zeros UUID expecting a validation error:

```
addSubaccount(input: {
  organizationID: "<org>", firstName: "Probe", lastName: "Only",
  email: "probe-only@example.invalid",
  seatPriceID: "00000000-0000-0000-0000-000000000000" # does not exist
```



```

})
-> { "id": "33d1fdb4-..." } # created anyway

```

The sub-account was created with kind: "included", status: "invited". We removed it immediately with removeSubaccount and confirmed mySubaccounts is empty and the seat counts are back to seatsUsed: 1.

Blank names or a blank email are rejected (billing: first name, last name and email are required), so validation exists - the price id simply is not checked. A client that passes the wrong id gets a seat that bills against nothing.

Need: reject an unknown seatPriceID. (We pass the real one from myMembership.items[].price.id, so this is not blocking us.)

A8 - the attorney behind a call cannot be read without a timeout · MEDIUM

For the Activity timeline we want the attorney's name on each session, as the design shows. The nested field hangs:

Selection	Result
attorneyAssignments { id status }	1.7 s Yes
attorneyAssignments { id status attorneyId }	1.1 s Yes
attorneyAssignments { id attorney { displayName } }	504 after 60 s

attorneyId resolves (de300000-0000-4000-8000-000000020006) but there is no member-callable query that turns an attorney id into a name - partnerAttorneys is empty for us (A4).

We ship the timeline without attorney names rather than showing an id or leaving a blank where a name belongs.

Need: either the nested resolver fixed, or a name on the assignment itself.

A5 - a member cannot delete their own document · HIGH

The Glovebox is built and uploading against dev. One thing does not work:

```

mutation { deleteUserDocument(id: "<the member's own document>") }
-> {"errors":[{"message":"forbidden"}]}

```

Called as the signed-in member, on a document that member uploaded a moment earlier. Everything else in the chain works - requestUserDocumentUpload -> PUT to S3 -> createUserDocument -> userDocumentList -> userDocumentDownloadUrl all round-trip, and we fetched the exact bytes back.

The design puts a `` on every uploaded document tile (screens 14A, 14C: "Deleting the last file restores the dropzone"). **We have shipped no delete control**, because one that always fails is worse than none.

What we need: either member scope on deleteUserDocument for their own rows, or a deleteMyUserDocument-style operation.

Meanwhile: two test files of ours are stuck on the test member's Driver's Information section (probe.txt, ui.xml) and we cannot remove them.

A6 - what does the document-field type vocabulary mean? · MEDIUM

AdminDocumentField.type is a free-form string. Across dev we see:

```
text dropdown file image agreement policy guide form
example "example 3" "example 4" "example 5"
```

We render text, dropdown and file, and treat everything else as not-member- input. That rule is what keeps the organisation's templates (Contract, Form, Guide, Policy, Incident Report) out of a member's personal Glovebox.

image **is the one that bit us**. We first mapped it to a file upload - it looks like one - and "Policy" duly appeared in the member's Glovebox, because Policy has an image field called "Example". We now treat image as unknown.

What we need: the intended list of type values and what each should render as. If image really is an upload, we will map it - we just will not guess.

Also, adminDocumentTypeList still holds dev test rows (contract 2, Extra books) and several example* fields. Harmless to us now, but worth tidying.

B. Operations that do not exist

We searched all **238 queries and 297 mutations** for each of these. Where a backend piece is missing, we have **left the screen unbuilt and listed it here** rather than shipping a placeholder that looks finished.

B1 - Phone verification · HIGH · blocks screens 08, 09

- updateMyContactInfo(input: { phoneE164 }) **stores** a number. That works.
- **Nothing sends or checks a phone code.** No requestPhoneOtp, no verifyPhone, nothing equivalent.
- requestLoginOtp(channel: SMS) is a **sign-in** code sent to an *already-verified* phone, so it cannot verify a new number - it is circular.
- phoneVerifiedAt is writable only via CreateUserInput / UpdateUserInput, which are admin operations, not member self-service.

Need: two operations a signed-in member can call - send a code to a supplied number, and verify that code, setting phoneVerifiedAt on success.

Also confirm the code length. Sign-in codes are 4 digits; the design specifies 6 for phone verification.

We deliberately did not ship screen 08 alone. Its own sub-line promises "We'll text a code to verify it", and rewording that to hide the missing half would leave a feature that looks finished and never gets revisited.

B2 - Pronouns · LOW · blocks one field of screen 10

Date of birth and gender are both on `UpdateMyProfileInput`. Pronouns are not, and no input type in the schema has a field matching pronoun.

Need: one nullable string on `UpdateMyProfileInput` (and on `UserProfile` if you want it readable).

B3 - Situation preferences · HIGH · blocks screens 13B, 13C, 27B

The member's saved "three most common situations". Nothing matching situation, preference or favourite anywhere.

Need: a read and a write, capped at three incident-type IDs per member. Roughly:

```
myCommonSituations: [ID!]!
setMyCommonSituations(incidentTypeIds: [ID!]!): Boolean
```

Home currently shows the full incident list because there is nowhere to store a choice of three.

B4 - Emergency-contact notify-by · MEDIUM · blocks two controls on screen 16

The design collects *how* each contact is alerted: "Notify them by - Text message / Email / Choose one or both".

`CreateEmergencyContactInput` has `userId`, `name`, `relationship`, `phoneE164`, `email`, `isPrimary`, `notes`. There is **no notify-by field**, and nothing matching `notify` on any input type.

We could have written it into `notes`, but that is free text being used as a settings column - it works until something reads `notes` expecting notes.

Need: two booleans (`notifyBySms`, `notifyByEmail`) or a small enum on the contact.

B5 - The trial conversion, in detail · HIGH · blocks 5 native screens

This is the one that is now precisely specifiable, so here it is in full.

Of the ten trial screens, five are yours on the web (V1, T1, T2, T3, T4 - the plan card, the conversion-plan chooser, trial checkout, trial confirmation, and the return-to-app handoff). We do not build those. Five are native: **V2** the gate, **T5/T6** the charge notice, **T7** processing, **T8** confirmed.

What already works. A member can see they are on a trial: `myMembership.trialEnd` is readable, and so are the plan, the price and the card on file. So V2's status line and T5/T6's summary all have real data behind them.

What is missing is the single action they exist for. Nothing converts a trial to a paid membership and charges the card on file:

Candidate	Why it is not this
<code>createPayment</code>	Takes <code>invoiceID</code> + <code>providerPaymentID</code> - it records a payment a provider already took, it does not take one
<code>changeMembershipPlan</code>	Changes which plan, not trial -> paid
<code>resumeMembership</code>	For a paused membership
<code>PublicCheckoutInput.trialDays</code>	Web checkout, unauthenticated, starts a trial rather than ending one

Need: one member-callable mutation. Roughly:

```
convertMyTrial(organizationID: ID!): Membership!
```

charging the card already on file, ending the trial immediately, and returning the membership so we can show T8. Errors we would need to tell apart: no card on file, card declined, and not-on-a-trial.

We have built none of the five. Showing the gate without its action would be worse than not showing it: a member on a trial would be told "live attorney access starts your paid membership", tap the only button offered, and nothing would happen. Worse, if we shipped the *status* alone, the app would advertise a trial while still behaving like a paid membership, because there is nothing to gate on.

Also needed to test any of it: a way to put the test member on a trial. `trialEnd` is null on our account and nothing member-callable can set it.

B5a - Guest mode · HIGH · blocks G1-G3

Still nothing matching guest.

The question that decides the whole design: is a guest a real account with a role, or purely local state?

Note also that `requestLoginOtp` **deliberately does not enumerate accounts** - an address with no account still returns `sent: true` with the submitted address masked back. That is good security, and it means **the app cannot detect an unrecognised email at sign-in**, so guest mode cannot be entered the way the design describes. Whatever the model turns out to be, that branch needs rethinking with you.

B6 - No member-readable transcript · LOW · one link on screen 32

The Activity design deliberately drops recording replay, but keeps *"Test Call entries keep View transcript, the intended way to review demo sessions."*

`CommsCallRecording` exists with `playbackUrl` and `vonageRecordingUrl`, but those are recordings, not transcripts, and `biCallRecordingUrl` is a BI operation a member cannot call. Nothing matching transcript exists.

We ship the timeline without the link. Not urgent - but if transcripts are coming, we would rather wire the real thing than add a link now.

B8 - Notification categories, a frequency dial, and what `kind` means · MEDIUM

The notification chain itself works, and is correctly scoped - we verified create, list, `unreadOnly`, mark one, mark all and clear, and confirmed that reading or writing another member's inbox returns `forbidden`. Screens 22, 23, 24 and 25 are built on it. Thank you; nothing here is blocking.

Screen 26 is the exception. The design has **four category toggles and a frequency dial**:

Design control	Field we could store it in
Setup reminders	-
Tips & know-your-rights	-

Design control	Field we could store it in
Account & billing	-
Safety-critical (always on)	n/a - nothing to store
How often: Occasionally / Rarely / Off	-

UserProfile has exactly two booleans: notificationsEnabled and marketingOptIn. **We did not map "Tips & know-your-rights" onto marketingOptIn.** That flag is a marketing-consent record with legal weight, and quietly relabelling a consent as a content preference is the kind of thing that is discovered during an audit. It is shown as "Marketing emails", which is what it is.

Need: either per-category booleans and a frequency enum on the profile, or a decision that one master switch is the product.

Also: what is kind supposed to be? createNotification accepted a kind of "totally-made-up-kind" without complaint. We carry it through and group loosely rather than switching on it - the document-field type already taught us what guessing costs (A6) - but we would rather render the right icon and grouping than a generic one.

One more, small: createNotification is callable by a member for their own inbox. Correctly scoped (other users are refused), so it is not a hole - just odd, and worth a look in case it was meant to be admin-only.

And a related gap, lowest priority of anything in this document: there is nowhere to store **per-member app state that is not a preference** - whether the guided tour has been seen, and whether a member said "don't remind me" to a particular nudge. Both live in device storage today, so they do not follow a member to a second phone. A single free-form JSON column on the profile would cover both and anything like them. Genuinely not urgent.

B7 - A member cannot change their card in the app · MEDIUM · blocks 33D

Screen 33D lets a member edit the expiry and billing ZIP inline and replace the card. Today:

- **No** updatePaymentMethod. The mutations are createPaymentMethod, attachPaymentMethod, setDefaultPaymentMethod, detachPaymentMethod.
- **No billing ZIP** on PaymentMethod at all - the fields are brand, last4, expMonth, expYear, billingName, billingEmail, billingCountryID.
- attachPaymentMethod **takes a** providerRef - a token from the payment provider. Minting one needs the provider's SDK and publishable key in the app, which is a decision for you, not something we should choose unilaterally.

We show the card read-only on Payment & plan - brand, last four, expiry - with no Update control, because every write path available to us either does not exist or would need a credential we have not been given.

Need, in order of preference: (a) a hosted card-update link we can open, the same way checkout already works on the web; or (b) updatePaymentMethod for expiry, plus a ZIP field; or (c) the provider's publishable key and a decision to embed their SDK.

C. Answers we need - each of these is a guess today

- 1 **countryISO2 on verifyLoginOtp** - we send null, because it is optional and that is what the web client sends. But what is it *for*? If it affects routing or jurisdiction we would rather send something real.
- 2 **refreshToken - access-token lifetime, and does refreshing rotate the refresh token?** This matters more for us than for web: a browser tab is short-lived, but a native app sits backgrounded for days, and this is an app people open during a police encounter. **We have not wired refresh yet because of this.**
- 3 **Is verifyMemberPin the intended server-side gate for ending a call?** The design says the PIN's only job is ending a live session securely - it does not unlock the app or protect recordings.
- 4 **Who sends the emergency-contact alert?** The design says contacts are "alerted with your location the moment you connect to an attorney". We only ever call `member-call`, so it must be server-side - but if the app is meant to trigger it, we need an operation.
- 5 **Is one-device-at-a-time deliberate and permanent?** `LoginPayload` returns `otherSessionsRevoked` and `mySessionStatus` reports `another_device`, so signing in on the web ends the app's session and vice versa. We can live with it; it is worth confirming for a phone people open during an encounter, since signing in on a laptop signs out the phone in their pocket.
- 6 **Casing is inconsistent and we follow whatever each operation asks for** - the gateway mixes `userId` (`login`, `casesByUser`) with `userId` (`setMemberPin`, `updateMyProfile`'s `countryId`), and comms REST uses `memberUserId`. Worth settling before anyone adds a field.
- 7 **Sign-in codes are 4 digits** - confirmed live, and we have built for 4. Flagging only because the design specifies six-cell entry; we assume that describes phone verification (B1), which is a different code.
- 8 **Is there, or could there be, an "onboarding complete" flag?** We currently infer completeness from date of birth + address + PIN + password + contacts. A real flag would be more honest than our inference.

D. Security

D1 - POST `/api/vonage/video/member-call` takes no authentication

Anyone can place a call against any `organizationId` / `memberUserId` they can guess, and that call routes to a **real attorney**.

Nothing we have built depends on it staying open, and we are not designing around it. Flagging rather than assuming it is known.

E. Not the gateway - please forward these

Both are blocking us, but neither is a backend/GraphQL task. Included so they do not fall between teams.

E1 - Deep-link contract for the web->app handoff · HIGH

Screens 07 and T4 hand the member back to the app "with email pre-filled", but nothing records the actual path or parameter names.

Currently implemented: we accept `/app/return`, `/return-to-app` and `/app` on `attorney-shield.com` and `www.attorney-shield.com`, reading an `email` query parameter. It is confined to one file, so a confirmed contract is a one-line change.

Please do not design the link to carry a credential. We treat it as untrusted input - anyone can send a link. The email is a text-field prefill only, and we have a test asserting that a link carrying `accessToken`, `userID` or `roles` yields nothing but the email.

E2 - Domain verification files · HIGH · web hosting

For a link to open the app *silently*, both hosts need:

- **Android:** `/.well-known/assetlinks.json` with our signing-certificate SHA-256 fingerprint for `com.app.attorney.shield`
- **iOS:** `/.well-known/apple-app-site-association` for our Team ID + `com.app.attorney.shield`

Until these exist, Android shows a "which app?" chooser and iOS universal links do not fire at all. **We owe you the fingerprint and Team ID** once our release keystore exists - that part is on us.

What we ship as each lands

You give us	We ship
~~B1 - phone send/verify~~	Yes shipped - screens 08 and 09 are unblocked
~~B3 - situation preferences~~	Yes shipped - screens 13B, 13C, 27B are unblocked
~~C8 - an onboarding flag~~	Yes shipped - we can stop inferring completeness
~~A2 - incident types + an English language~~	Yes done - Home renders real tiles
~~A3 - document types + fields~~	Yes done - the Glovebox is built and uploading
A5 - member scope on delete	The `` on each document tile
A6 - the type vocabulary	Confidence that every field renders as intended
A4 - a case for the test member	Real jurisdiction and attorney pre-selection
A8 - the attorney behind a call	Attorney names on the Activity timeline
B6 - a transcript	"View transcript" on Test Call entries
B8 - categories + frequency	The rest of screen 26's controls
B7 - a card-update path	Screen 33D and the Update row on Payment & plan
B1 - phone send/verify	Registration screens 08 and 09
B2 - a pronouns field	The last field of screen 10

You give us	We ship
B3 - situation preferences	Screens 13B, 13C and the saved-three row on Home
B4 - notify-by	The last two controls of screen 16
B5 - a decision on the guest model	Trial and guest scoped, 13 screens
C2 - token lifetime and rotation	Token refresh, so sessions survive being backgrounded
C1, C3-C8 - the remaining answers	Guesses removed from code we have already shipped
E1 - the deep-link contract	A one-line change, then verified end to end

Where we are

Built and verified against dev: the welcome carousel, sign-in by password **and one-time code**, the profile checklist and its readiness card on Home, personal details, address, security PIN, set-a-password, emergency contacts, **a home screen with six real incident tiles**, the call flow up to "connecting", and the deep-link handler.

The Glovebox is built and verified on a device against dev - sections and fields render from your configuration rather than being hardcoded, text and dropdown answers save, and a file goes picker -> presigned S3 -> createUserDocument with the tile appearing straight afterwards.

One thing we have never been able to prove: a video call actually going live. `member-call` returns 409 no attorney is available on dev. We are arranging an attorney ourselves by running the desktop app - not an ask - but until that happens, the step from "connecting" to a live picture is the one part of the product still taken on faith.