

ATTORNEY SHIELD

ASI 2.0 - Native Android & iOS

Attorney Shield 2.0 - Backend asks for

Colour system: Attorney-Shield Color Scheme Review

Repository: samson-phillip/asi-claude

DRAFT FOR APPROVAL

Contents

At a glance	3
Already working - please don't re-do these	3
Yes A1, A2 and A3 are fixed - verified 2026-08-13	4
~~A1 - countries returns empty while the same rows resolve by id~~ · FIXED	5
~~A2 - Incident types are not seeded~~ · FIXED	5
~~A3 - Document types and fields are not seeded~~ · FIXED	5
A4 - No case for the test member · MEDIUM	6
A5 - a member cannot delete their own document · HIGH	6
A6 - what does the document-field type vocabulary mean? · MEDIUM	7
B1 - Phone verification · HIGH · blocks screens 08, 09	7
B2 - Pronouns · LOW · blocks one field of screen 10	7
B3 - Situation preferences · HIGH · blocks screens 13B, 13C, 27B	8
B4 - Emergency-contact notify-by · MEDIUM · blocks two controls on screen 16	8
B5 - Trial and guest · HIGH · blocks 13 screens	8
D1 - POST /api/vonage/video/member-call takes no authentication	9
E1 - Deep-link contract for the web->app handoff · HIGH	9
E2 - Domain verification files · HIGH · web hosting	9
What we ship as each lands	10
Where we are	10

From: mobile (Android + iOS) **Date:** 2026-08-13 (updated after the seeding landed) **Environment:**
<https://gateway-dev.attorneyshield.io/query> · <https://comms-dev.attorneyshield.io>

Every item below is something **you can act on**. Our own to-dos, design questions and the things we are arranging ourselves are deliberately not here.

Everything was verified by introspecting the schema and calling the operations as the test member - not inferred from the web client. Where we were wrong earlier, it is corrected and marked.

At a glance

#	Ask	Severity	Unblocks
A1	countries returns []	~~HIGH~~	Yes FIXED - thank you
A2	Incident types + an English default language	~~BLOCKING~~	Yes FIXED - Home now renders real tiles
A3	Document types + fields	~~HIGH~~	Yes FIXED - the Glovebox is unblocked
A4	No case for the test member	MEDIUM	Attorney pre-selection, real jurisdiction
B1	No phone send/verify operations	HIGH	Registration screens 08, 09
B2	No pronouns field	LOW	The last field of screen 10
B3	No situation-preference operations	HIGH	Screens 13B, 13C + the saved-three row on Home
B4	No notify-by field on emergency contacts	MEDIUM	Two controls on screen 16
B5	No trial or guest operations	HIGH	13 screens (V1-V2, T1-T8, G1-G3)
C1-C8	Eight answers we are currently guessing	MEDIUM	Token refresh, PIN gate, guest design
A5	deleteUserDocument is forbidden for a member's own file	HIGH	Removing a document from the Glovebox
A6	What the document-field type vocabulary means	MEDIUM	Rendering the right control per field
D1	member - call takes no authentication	SECURITY	-
E1-E2	Deep-link contract + domain files (not the gateway)	HIGH	Silent web->app handoff

Already working - please don't re-do these

Area	Operations
Sign in, password	login
Sign in, one-time code	requestLoginOtp / verifyLoginOtp
Date of birth, gender	updateMyProfile
Home + mailing address	updateMyProfile, createUserAddress
Security PIN	setMemberPin, memberPinStatus
Set a password	setPassword, User.hasPassword
Emergency contacts	createEmergencyContact + CRUD
States/provinces	subdivisionsByCountry - all 50 US states resolve
Video call credentials	POST /api/vonage/video/member-call

All of the above are **built and writing to dev**. The Vonage SDK is also proven on a real Android device: the native library loads, reports 2.32.1, and completes a round trip to Vonage.

A. Environment and seeding

Yes A1, A2 and A3 are fixed - verified 2026-08-13

Confirmed against dev as the test member, and the apps now render it:

Check	Result
countries	United States Yes
adminIncidentTypeList(activeOnly: true, countryISO2: "US")	6 types - Test Call, Traffic Stop, Domestic, Auto Accident, Pedestrian Stop, Other Yes
adminLanguageList	en-US with isDefault: true, plus es-ES and ar-SA Yes
Translations	English and Spanish on every type Yes
iconFilePath	Real CloudFront URLs on all six Yes
adminDocumentTypeList	Driver's Information, Health Information, Gun Information, Citizenship Info - all four Glovebox sections Yes
adminDocumentFieldList	20 fields Yes

Home now shows six real incident tiles with their English names for the first time. That was the blocking item; it is gone.

Two small notes, neither urgent:

- 1 **The code values are human strings** - "Traffic Stop", not `traffic_stop`. We had assumed `snake_case`, so our icon lookup matched nothing and every tile fell back to a generic shield until we normalised it. Only flagging in case another client made the same assumption.
- 2 `adminDocumentTypeList` **also contains what look like test rows** - "contract 2" and "Extra books", alongside the generic Contract / Form / Guide / Policy / Incident Report. We will render only the four Glovebox sections, but you may want to tidy those out of dev.

The rest of this section - A4 - is still open.

~~A1 - countries returns empty while the same rows resolve by id~~ · FIXED

Correction to what we told you earlier. We previously said no countries were configured. That was wrong:

Query	Result
<code>countries { iso2 }</code>	<code>[]</code>
<code>country(id: "f989d06a-8813-11f1-a446-06cf81ac74a7")</code>	United States , US Yes
<code>subdivisionsByCountry(<that id>)</code>	all 50 states + DC Yes

The data exists. The **list query** is what comes back empty, and our test member's own profile points at that same US id.

We work around it by reading the country from the member's profile instead of offering a picker - so it is not blocking us - but the list query looks broken or scoped in a way nobody intended, and we would rather tell you than quietly route around it.

~~A2 - Incident types are not seeded~~ · FIXED

```
adminIncidentTypeList(activeOnly: false) -> []
adminIncidentTypeList(activeOnly: true, countryISO2: "US") -> []
adminLanguageList -> 1 entry: ar-SA, isDefault: false
```

Retested **while authenticated**, with and without a country filter, so this is not a side-effect of A1.

This is the one that hurts most. The home screen shows "No incident types are configured yet.", so we cannot exercise the incident tiles, the attorney chip row, or place a call with a real incident type. Finishing onboarding currently lands the member on an empty screen.

Need: incident types seeded with translations - the design uses Traffic Stop, Auto Accident, Pedestrian Stop, Domestic, Test Call, Other - plus **an English language entry marked** `isDefault: true`. Without the language, our label resolution (English -> org default -> first available -> humanized code) falls through to Arabic.

~~A3 - Document types and fields are not seeded~~ · FIXED

```
adminDocumentTypeList -> []
```

The operations all exist - `adminDocumentFieldList`, `requestUserDocumentUpload`, `createUserDocument`, `userDocumentList`, `userDocumentDownloadUrl`, and `saveUserDocumentValue` for plain text fields. So this is a **seeding** ask, not a build ask.

Every upload and every saved value is keyed by `adminDocumentFieldsId`. With no types there are no fields, so there is nothing to attach a document or a value to, and none of the Glovebox can be built.

Need: the four sections seeded with their fields, per the design:

Section	Fields the design shows
Driver's Information	licence document upload
Health Information	three plain text fields + document upload
Gun Information	two yes/no questions, permit number, issue state
Citizenship Info	plain fields + document upload

Also please tell us **what** `fieldType` **values exist**, so we render the right control for each field rather than guessing.

A4 - No case for the test member · MEDIUM

```
casesByUser(userID: <test member>) -> [].
```

The member's organization resolves correctly (6c53e00d-8682-11f1-a446-06cf81ac74a7), but with no case, jurisdiction and partner fall back to the hard-coded dev seed ids and we cannot exercise attorney pre-selection at all.

If it is easier to point us at an environment that already has A1-A4, that works just as well. We only need somewhere to develop against.

A5 - a member cannot delete their own document · HIGH

The Glovebox is built and uploading against dev. One thing does not work:

```
mutation { deleteUserDocument(id: "<the member's own document>") }
-> {"errors":[{"message":"forbidden"]}}
```

Called as the signed-in member, on a document that member uploaded a moment earlier. Everything else in the chain works - `requestUserDocumentUpload` -> PUT to S3 -> `createUserDocument` -> `userDocumentList` -> `userDocumentDownloadUrl` all round-trip, and we fetched the exact bytes back.

The design puts a `` on every uploaded document tile (screens 14A, 14C: *"Deleting the last file restores the dropzone"*). **We have shipped no delete control**, because one that always fails is worse than none.

What we need: either member scope on `deleteUserDocument` for their own rows, or a `deleteMyUserDocument`-style operation.

Meanwhile: two test files of ours are stuck on the test member's Driver's Information section (`probe.txt`, `ui.xml`) and we cannot remove them.

A6 - what does the document-field type vocabulary mean? · MEDIUM

`AdminDocumentField.type` is a free-form string. Across dev we see:

```
text dropdown file image agreement policy guide form
example "example 3" "example 4" "example 5"
```

We render text, dropdown and file, and treat everything else as not-member- input. That rule is what keeps the organisation's templates (Contract, Form, Guide, Policy, Incident Report) out of a member's personal Glovebox.

image **is the one that bit us**. We first mapped it to a file upload - it looks like one - and "Policy" duly appeared in the member's Glovebox, because Policy has an image field called "Example". We now treat image as unknown.

What we need: the intended list of type values and what each should render as. If image really is an upload, we will map it - we just will not guess.

Also, `adminDocumentTypeList` still holds dev test rows (contract 2, Extra books) and several example* fields. Harmless to us now, but worth tidying.

B. Operations that do not exist

We searched all **238 queries and 297 mutations** for each of these. Where a backend piece is missing, we have **left the screen unbuilt and listed it here** rather than shipping a placeholder that looks finished.

B1 - Phone verification · HIGH · blocks screens 08, 09

- `updateMyContactInfo(input: { phoneE164 })` **stores** a number. That works.
- **Nothing sends or checks a phone code.** No `requestPhoneOtp`, no `verifyPhone`, nothing equivalent.
- `requestLoginOtp(channel: SMS)` is a **sign-in** code sent to an *already-verified* phone, so it cannot verify a new number - it is circular.
- `phoneVerifiedAt` is writable only via `CreateUserInput` / `UpdateUserInput`, which are admin operations, not member self-service.

Need: two operations a signed-in member can call - send a code to a supplied number, and verify that code, setting `phoneVerifiedAt` on success.

Also confirm the code length. Sign-in codes are 4 digits; the design specifies 6 for phone verification.

We deliberately did not ship screen 08 alone. Its own sub-line promises "We'll text a code to verify it", and rewording that to hide the missing half would leave a feature that looks finished and never gets revisited.

B2 - Pronouns · LOW · blocks one field of screen 10

Date of birth and gender are both on `UpdateMyProfileInput`. Pronouns are not, and no input type in the schema has a field matching pronoun.

Need: one nullable string on `UpdateMyProfileInput` (and on `UserProfile` if you want it readable).

B3 - Situation preferences · HIGH · blocks screens 13B, 13C, 27B

The member's saved "three most common situations". Nothing matching situation, preference or favourite anywhere.

Need: a read and a write, capped at three incident-type IDs per member. Roughly:

```
myCommonSituations: [ID!]!
setMyCommonSituations(incidentTypeIds: [ID!]!): Boolean
```

Home currently shows the full incident list because there is nowhere to store a choice of three.

B4 - Emergency-contact notify-by · MEDIUM · blocks two controls on screen 16

The design collects *how* each contact is alerted: "Notify them by - Text message / Email / Choose one or both".

CreateEmergencyContactInput has userId, name, relationship, phoneE164, email, isPrimary, notes. There is **no notify-by field**, and nothing matching notify on any input type.

We could have written it into notes, but that is free text being used as a settings column - it works until something reads notes expecting notes.

Need: two booleans (notifyBySms, notifyByEmail) or a small enum on the contact.

B5 - Trial and guest · HIGH · blocks 13 screens

Nothing matching trial or guest.

The design has a 7-day limited trial with an in-app conversion gate (V1-V2, T1-T8) and a guest mode entered from an unrecognised email at sign-in (G1-G3).

The question that decides the whole design: is a guest a real account with a role, or purely local state?

Note also that requestLoginOtp **deliberately does not enumerate accounts** - an address with no account still returns sent: true with the submitted address masked back. That is good security, and it means **the app cannot detect an unrecognised email at sign-in**, so guest mode cannot be entered the way the design describes. Whatever the model turns out to be, that branch needs rethinking with you.

C. Answers we need - each of these is a guess today

- 1 countryISO2 **on** verifyLoginOtp - we send null, because it is optional and that is what the web client sends. But what is it *for*? If it affects routing or jurisdiction we would rather send something real.
- 2 refreshToken - **access-token lifetime, and does refreshing rotate the refresh token?** This matters more for us than for web: a browser tab is short-lived, but a native app sits backgrounded for days, and this is an app people open during a police encounter. **We have not wired refresh yet because of this.**
- 3 Is verifyMemberPin **the intended server-side gate for ending a call?** The design says the PIN's only job is ending a live session securely - it does not unlock the app or protect recordings.

- 4 **Who sends the emergency-contact alert?** The design says contacts are "alerted with your location the moment you connect to an attorney". We only ever call `member-call`, so it must be server-side - but if the app is meant to trigger it, we need an operation.
 - 5 **Is one-device-at-a-time deliberate and permanent?** `LoginPayload` returns `otherSessionsRevoked` and `mySessionStatus` reports `another_device`, so signing in on the web ends the app's session and vice versa. We can live with it; it is worth confirming for a phone people open during an encounter, since signing in on a laptop signs out the phone in their pocket.
 - 6 **Casing is inconsistent and we follow whatever each operation asks for** - the gateway mixes `userID` (`login`, `casesByUser`) with `userId` (`setMemberPin`, `updateMyProfile`'s `countryId`), and comms REST uses `memberUserId`. Worth settling before anyone adds a field.
 - 7 **Sign-in codes are 4 digits** - confirmed live, and we have built for 4. Flagging only because the design specifies six-cell entry; we assume that describes phone verification (B1), which is a different code.
 - 8 **Is there, or could there be, an "onboarding complete" flag?** We currently infer completeness from date of birth + address + PIN + password + contacts. A real flag would be more honest than our inference.
-

D. Security

D1 - POST `/api/vonage/video/member-call` takes no authentication

Anyone can place a call against any `organizationId` / `memberUserId` they can guess, and that call routes to a **real attorney**.

Nothing we have built depends on it staying open, and we are not designing around it. Flagging rather than assuming it is known.

E. Not the gateway - please forward these

Both are blocking us, but neither is a backend/GraphQL task. Included so they do not fall between teams.

E1 - Deep-link contract for the web->app handoff · HIGH

Screens 07 and T4 hand the member back to the app "with email pre-filled", but nothing records the actual path or parameter names.

Currently implemented: we accept `/app/return`, `/return-to-app` and `/app` on `attorney-shield.com` and `www.attorney-shield.com`, reading an `email` query parameter. It is confined to one file, so a confirmed contract is a one-line change.

Please do not design the link to carry a credential. We treat it as untrusted input - anyone can send a link. The email is a text-field prefill only, and we have a test asserting that a link carrying `accessToken`, `userId` or `roles` yields nothing but the email.

E2 - Domain verification files · HIGH · web hosting

For a link to open the app *silently*, both hosts need:

- **Android:** /.well-known/assetlinks.json with our signing-certificate SHA-256 fingerprint for com.app.attorney.shield
- **iOS:** /.well-known/apple-app-site-association for our Team ID + com.app.attorney.shield

Until these exist, Android shows a "which app?" chooser and iOS universal links do not fire at all. **We owe you the fingerprint and Team ID** once our release keystore exists - that part is on us.

What we ship as each lands

You give us	We ship
~~A2 - incident types + an English language~~	Yes done - Home renders real tiles
~~A3 - document types + fields~~	Yes done - the Glovebox is built and uploading
A5 - member scope on delete	The `` on each document tile
A6 - the type vocabulary	Confidence that every field renders as intended
A4 - a case for the test member	Real jurisdiction and attorney pre-selection
B1 - phone send/verify	Registration screens 08 and 09
B2 - a pronouns field	The last field of screen 10
B3 - situation preferences	Screens 13B, 13C and the saved-three row on Home
B4 - notify-by	The last two controls of screen 16
B5 - a decision on the guest model	Trial and guest scoped, 13 screens
C2 - token lifetime and rotation	Token refresh, so sessions survive being backgrounded
C1, C3-C8 - the remaining answers	Guesses removed from code we have already shipped
E1 - the deep-link contract	A one-line change, then verified end to end

Where we are

Built and verified against dev: the welcome carousel, sign-in by password **and one-time code**, the profile checklist and its readiness card on Home, personal details, address, security PIN, set-a-password, emergency contacts, **a home screen with six real incident tiles**, the call flow up to "connecting", and the deep-link handler.

The Glovebox is built and verified on a device against dev - sections and fields render from your configuration rather than being hardcoded, text and dropdown answers save, and a file goes picker -> presigned S3 -> createUserDocument with the tile appearing straight afterwards.

One thing we have never been able to prove: a video call actually going live. `member-call` returns 409 no attorney is available on dev. We are arranging an attorney ourselves by running the desktop app - not an ask - but until that happens, the step from "connecting" to a live picture is the one part of the product still taken on faith.