

Class 6: R functions

Samson A16867000

Today we are going to explore R functions and begin to think about writing our own functions

Let's start simple and write out first function to add some numbers.

Every function in R has at least 3 things:

- a **name**, we pick this
- one or more input **arguments**
- the **body**, where the work gets done.

```
add <- function(x,y=1, z=0){  
  x+y+z  
}
```

Now lets try it out

```
add(1,1)
```

```
[1] 2
```

```
add(10,1)
```

```
[1] 11
```

```
add(10,10)
```

```
[1] 20
```

```
add(10,10,20)
```

```
[1] 40
```

```
mean(c(10,10,NA),na.rm=T)
```

```
[1] 10
```

Lab sheet work

. Q1. Q1. Write a function grade() to determine an overall grade from a vector of student homework assignment scores dropping the lowest single score. If a student misses a homework (i.e. has an NA value) this can be used as a score to be potentially dropped. Your final function should be adequately explained with code comments and be able to work on an example class gradebook such as this one in CSV format: “<https://tinyurl.com/gradeinput>” [3pts]

```
student1 <- c(100, 100, 100, 100, 100, 100, 100, 90)
student2 <- c(100, NA, 90, 90, 90, 90, 97, 80)
student3 <- c(90, NA, NA, NA, NA, NA, NA, NA)
```

Begin by calculating the average for student 1

```
mean(student1)
```

```
[1] 98.75
```

```
student2
```

```
[1] 100 NA 90 90 90 90 97 80
```

```
mean(student2,na.rm=T)
```

```
[1] 91
```

and student3

```
student3
```

```
[1] 90 NA NA NA NA NA NA NA
```

```
mean(student3,na.rm=T)
```

```
[1] 90
```

Hmm.... this sucks! I need to try something else and come back to this issue of missing values (Nas).

We also want to drop the lowest score from a given student's set of scores.

```
student1[-8]
```

```
[1] 100 100 100 100 100 100 100
```

We can try the `min()` function to find the lowest score

```
min(student1)
```

```
[1] 90
```

I want to find location of the min value not the value itself. For this I can use `which.min()`

```
student1
```

```
[1] 100 100 100 100 100 100 100 90
```

```
which.min(student1)
```

```
[1] 8
```

Let's put these two things together

```
mean(student1[-which.min(student1)])
```

```
[1] 100
```

```
x <- student2  
x
```

```
[1] 100 NA 90 90 90 90 97 80
```

```
x[is.na(x)]=0  
x
```

```
[1] 100  0  90  90  90  90  97  80
```

So far we have a working snippet.

```
x <- student1  
## Finds NAs in `x` and make them 0  
x[is.na(x)] <- 0  
  
# finds the minimum and rm's it before getting mean  
mean(x[-which.min(x)])
```

```
[1] 100
```

Now turn it into a function

```
grade <- function(x) {  
  ## Finds NAs in `x` and make them 0  
  x[is.na(x)] <- 0  
  
  # finds the minimum and rm's it before getting mean  
  mean(x[-which.min(x)])  
}
```

```
grade(student1)
```

```
[1] 100
```

```
grade(student2)
```

```
[1] 91
```

```
grade(student3)
```

```
[1] 12.85714
```

Now `apply()` to our class gradebook

```
gradebook <-read.csv("https://tinyurl.com/gradeinput",
                     row.names =1)
head(gradebook)
```

	hw1	hw2	hw3	hw4	hw5
student-1	100	73	100	88	79
student-2	85	64	78	89	78
student-3	83	69	77	100	77
student-4	88	NA	73	100	76
student-5	88	100	75	86	79
student-6	89	78	100	89	77

To use the `apply()` function on this `gradebook` dataset I need to decide whether I want to “apply” the `grade()` function over the rows (1)or columns (2)of the `gradebook`.

```
ans <-apply(gradebook,1,grade)
ans
```

student-1	student-2	student-3	student-4	student-5	student-6	student-7
91.75	82.50	84.25	84.25	88.25	89.00	94.00
student-8	student-9	student-10	student-11	student-12	student-13	student-14
93.75	87.75	79.00	86.00	91.75	92.25	87.75
student-15	student-16	student-17	student-18	student-19	student-20	
78.75	89.50	88.00	94.50	82.75	82.75	

. Q2. Using your `grade()` function and the supplied `gradebook`, Who is the top scoring student overall in the `gradebook`? [3pts]

```
which.max(ans)
```

```
student-18
18
```

```
ans[which.max(ans)]
```

```
student-18
94.5
```

. Q3. From your analysis of the `gradebook`, which homework was toughest on students (i.e. obtained the lowest scores overall)? [2pts]

```
masked_gradebook <- gradebook
masked_gradebook[is.na(masked_gradebook)] = 0
apply(masked_gradebook, 2, mean)
```

```
hw1 hw2 hw3 hw4 hw5
89.00 72.80 80.80 85.15 79.25
```

I could modify the `grade()` function to do this too - i.e not drop the lowest option

```
grade2 <- function(x, drop.low = TRUE) {
  # Finds NAs in `x` and make them 0
  x[is.na(x)] <- 0

  if (drop.low) {
    cat("Hello low")
    # Drop lowest values and find mean
    out <- mean(x[-which.min(x)])
  } else {
    out <- mean(x)
    cat("No low")
  }
  return(out)
}
```

```
grade2(student1, TRUE)
```

```
Hello low
```

```
[1] 100
```

.Q4. Optional Extension: From your analysis of the gradebook, which homework was most predictive of overall score (i.e. highest correlation with average grade score)? [1pt]

The function to calculate correlations in R is called `cor()`

```
x <- c(100,90,80,100)
y <- c(100,90,80,100)
z <- c(80,90,100,10)

cor(x,y)
```

```
[1] 1
```

```
cor(x,z)
```

```
[1] -0.6822423
```

```
cor(ans, masked_gradebook$hw5)
```

```
[1] 0.6325982
```

I want to `apply()` the `cor()` function over the `masked_gradebook` and use the `ans` scores for the class

```
apply(masked_gradebook, 2, cor, ans)
```

hw1	hw2	hw3	hw4	hw5
0.4250204	0.1767780	0.3042561	0.3810884	0.6325982