

```

<?xml version="1.0" encoding="ISO-8859-1" ?>
- <XMI xmi.version="1.0">
- <XMI.header>
- <XMI.documentation>
  <XMI.exporter>Together</XMI.exporter>
  <XMI.exporterVersion>4.0</XMI.exporterVersion>
</XMI.documentation>
  <XMI.metamodel xmi.name="UML" xmi.version="1.1" />
</XMI.header>
- <XMI.content>
- <Model_Management.Model xmi.id="txmiid1">

  <Foundation.Core.ModelElement.name>GEE</Foundation.Core.ModelEI
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.ModelElement.taggedValue>
- <Foundation.Extension_Mechanisms.TaggedValue>

  <Foundation.Extension_Mechanisms.TaggedValue.tag>documenta
    <Foundation.Extension_Mechanisms.TaggedValue.value />
  </Foundation.Extension_Mechanisms.TaggedValue>
</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Namespace.ownedElement>
- <Foundation.Core.Dependency xmi.id="txmiid2.D">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Dependency.description />
- <Foundation.Core.Dependency.client>
  <Model_Management.Package
    xmi.idref="txmiid3" />
  </Foundation.Core.Dependency.client>
- <Foundation.Core.Dependency.supplier>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.Dependency.supplier>

```

```

</Foundation.Core.Dependency>
- <Foundation.Core.Dependency xmi.id="txmiid5.D">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Dependency.description />
- <Foundation.Core.Dependency.client>
  <Model_Management.Package
    xmi.idref="txmiid3" />
  </Foundation.Core.Dependency.client>
- <Foundation.Core.Dependency.supplier>
  <Model_Management.Package
    xmi.idref="txmiid6" />
  </Foundation.Core.Dependency.supplier>
</Foundation.Core.Dependency>
- <Foundation.Core.Dependency xmi.id="txmiid7.D">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Dependency.description />
- <Foundation.Core.Dependency.client>
  <Model_Management.Package
    xmi.idref="txmiid8" />
  </Foundation.Core.Dependency.client>
- <Foundation.Core.Dependency.supplier>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.Dependency.supplier>
</Foundation.Core.Dependency>
- <Foundation.Core.Dependency xmi.id="txmiid9.D">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Dependency.description />
- <Foundation.Core.Dependency.client>
  <Model_Management.Package
    xmi.idref="txmiida" />
  </Foundation.Core.Dependency.client>
- <Foundation.Core.Dependency.supplier>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.Dependency.supplier>
</Foundation.Core.Dependency>
- <Foundation.Core.Dependency xmi.id="txmiidb.D">

```

```

<Foundation.Core.ModelElement.name />
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.Dependency.description />
- <Foundation.Core.Dependency.client>
  <Model_Management.Package
    xmi.idref="txmiida" />
  </Foundation.Core.Dependency.client>
- <Foundation.Core.Dependency.supplier>
  <Model_Management.Package
    xmi.idref="txmiid8" />
  </Foundation.Core.Dependency.supplier>
</Foundation.Core.Dependency>
- <Behavioral_Elements.Collaborations.Collaboration
  xmi.id="txmiidc">

  <Foundation.Core.ModelElement.name>GEESequence</Foundation
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>Diagram

      <Foundation.Extension_Mechanisms.TaggedValue.value>Seque

    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Namespace.ownedElement>
  - <Behavioral_Elements.Collaborations.ClassifierRole
    xmi.id="txmiidd">

      <Foundation.Core.ModelElement.name>GEEServer
      Administrator</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />

```

```

        <Behavioral_Elements.Collaborations.ClassifierRole.multiplicity>
- <Foundation.Core.ModelElement.stereotype>

        <Foundation.Extension_Mechanisms.Stereotype
          xmi.idref="txmiide.S" />
        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.ClassifierRole.message>

        <Behavioral_Elements.Collaborations.Message
          xmi.idref="txmiidf.M" />

        <Behavioral_Elements.Collaborations.Message
          xmi.idref="txmiid10.M" />

        </Behavioral_Elements.Collaborations.ClassifierRole.message>
-
        <Behavioral_Elements.Collaborations.ClassifierRole.base>
        <Foundation.Core.Class
          xmi.idref="DummyClass" />

        </Behavioral_Elements.Collaborations.ClassifierRole.base>

        </Behavioral_Elements.Collaborations.ClassifierRole>
- <Behavioral_Elements.Collaborations.ClassifierRole
  xmi.id="txmiid11">

        <Foundation.Core.ModelElement.name>GEEServer</Foundatio
        <Foundation.Core.ModelElement.visibility
          xmi.value="private" />
        <Foundation.Core.GeneralizableElement.isRoot
          xmi.value="false" />
        <Foundation.Core.GeneralizableElement.isLeaf
          xmi.value="false" />

        <Foundation.Core.GeneralizableElement.isAbstract
          xmi.value="false" />

        <Behavioral_Elements.Collaborations.ClassifierRole.multiplicity>
-
        <Behavioral_Elements.Collaborations.ClassifierRole.message>

        <Behavioral_Elements.Collaborations.Message
          xmi.idref="txmiid12.M" />

```

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid13.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid14.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid15.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid16.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid17.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid18.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid19.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1a.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1b.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1c.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1d.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1e.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1f.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid20.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid21.M" />

```

    <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid22.M" />

    <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid23.M" />

</Behavioral_Elements.Collaborations.ClassifierRole.message>
-
    <Behavioral_Elements.Collaborations.ClassifierRole.base>
    <Foundation.Core.Class
    xmi.idref="txmiid24" />

</Behavioral_Elements.Collaborations.ClassifierRole.base>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>crea

        <Foundation.Extension_Mechanisms.TaggedValue.value>tru

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>dest

        <Foundation.Extension_Mechanisms.TaggedValue.value>tru

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>

</Behavioral_Elements.Collaborations.ClassifierRole>
- <Behavioral_Elements.Collaborations.ClassifierRole
    xmi.id="txmiid25">

    <Foundation.Core.ModelElement.name>GEEClientHandle</Foi
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />

```

```

<Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

<Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />

<Behavioral_Elements.Collaborations.ClassifierRole.multiplicity>
-
<Behavioral_Elements.Collaborations.ClassifierRole.message>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid26.M" />

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid27.M" />

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid28.M" />

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid29.M" />

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2a.M" />

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2b.M" />

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2c.M" />

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2d.M" />

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2e.M" />

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2f.M" />

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid30.M" />

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid31.M" />

```

```

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid32.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid33.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid34.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid35.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid36.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid37.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid38.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid39.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid3a.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid3b.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid3c.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid3d.M" />

</Behavioral_Elements.Collaborations.ClassifierRole.message>
-
  <Behavioral_Elements.Collaborations.ClassifierRole.base>
  <Foundation.Core.Class
    xmi.idref="txmiid3e" />

  </Behavioral_Elements.Collaborations.ClassifierRole.base>
- <Foundation.Core.ModelElement.taggedValue>

```



```

-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>crea

    <Foundation.Extension_Mechanisms.TaggedValue.value>tru

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>dest

    <Foundation.Extension_Mechanisms.TaggedValue.value>tru

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>

</Behavioral_Elements.Collaborations.ClassifierRole>
- <Behavioral_Elements.Collaborations.ClassifierRole
  xmi.id="txmiid3f">

  <Foundation.Core.ModelElement.name>GEEClient</Foundator
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />

  <Behavioral_Elements.Collaborations.ClassifierRole.multiplicity>
-
  <Behavioral_Elements.Collaborations.ClassifierRole.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid40.M" />

    <Behavioral_Elements.Collaborations.Message

```

```

xmi.idref="txmiid41.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid42.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid43.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid44.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid45.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid46.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid47.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid48.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid49.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid4a.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid4b.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid4c.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid4d.M" />

</Behavioral_Elements.Collaborations.ClassifierRole.message>
-
  <Behavioral_Elements.Collaborations.ClassifierRole.base>
  <Foundation.Core.Class
    xmi.idref="txmiid4e" />

  </Behavioral_Elements.Collaborations.ClassifierRole.base>

```

```

- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>crea

      <Foundation.Extension_Mechanisms.TaggedValue.value>tru

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>dest

      <Foundation.Extension_Mechanisms.TaggedValue.value>tru

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>

</Behavioral_Elements.Collaborations.ClassifierRole>
- <Behavioral_Elements.Collaborations.ClassifierRole
  xmi.id="txmiid4f">

  <Foundation.Core.ModelElement.name>GEEClient
  User</Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />

  <Behavioral_Elements.Collaborations.ClassifierRole.multiplicity>
- <Foundation.Core.ModelElement.stereotype>

  <Foundation.Extension_Mechanisms.Stereotype
    xmi.idref="txmiide.S" />
  </Foundation.Core.ModelElement.stereotype>

```

-

<Behavioral_Elements.Collaborations.ClassifierRole.message>

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid50.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid51.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid52.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid53.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid54.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid55.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid56.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid57.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid58.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid59.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid5a.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid5b.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid5c.M" />

<Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid5d.M" />

```

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid5e.M" />

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid5f.M" />

    </Behavioral_Elements.Collaborations.ClassifierRole.message>
-
        <Behavioral_Elements.Collaborations.ClassifierRole.base>
        <Foundation.Core.Class
            xmi.idref="DummyClass" />

        </Behavioral_Elements.Collaborations.ClassifierRole.base>

    </Behavioral_Elements.Collaborations.ClassifierRole>
- <Behavioral_Elements.Collaborations.ClassifierRole
    xmi.id="txmiid60">

        <Foundation.Core.ModelElement.name>Patient</Foundation.C
        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
        <Foundation.Core.GeneralizableElement.isRoot
            xmi.value="false" />
        <Foundation.Core.GeneralizableElement.isLeaf
            xmi.value="false" />

        <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />

        <Behavioral_Elements.Collaborations.ClassifierRole.multiplicity>
-
        <Behavioral_Elements.Collaborations.ClassifierRole.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid61.M" />

        </Behavioral_Elements.Collaborations.ClassifierRole.message>
-
        <Behavioral_Elements.Collaborations.ClassifierRole.base>
        <Foundation.Core.Class
            xmi.idref="txmiid62" />

        </Behavioral_Elements.Collaborations.ClassifierRole.base>
- <Foundation.Core.ModelElement.taggedValue>
-

```

```

    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>crea

        <Foundation.Extension_Mechanisms.TaggedValue.value>tru

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>dest

        <Foundation.Extension_Mechanisms.TaggedValue.value>tru

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>

</Behavioral_Elements.Collaborations.ClassifierRole>
- <Behavioral_Elements.Collaborations.ClassifierRole
  xmi.id="txmiid63">

    <Foundation.Core.ModelElement.name>Guideline</Foundation
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />

    <Behavioral_Elements.Collaborations.ClassifierRole.multiplicity>

-
    <Behavioral_Elements.Collaborations.ClassifierRole.message>

        <Behavioral_Elements.Collaborations.Message
          xmi.idref="txmiid64.M" />

        <Behavioral_Elements.Collaborations.Message
          xmi.idref="txmiid65.M" />

```

```

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid66.M" />

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid67.M" />

    </Behavioral_Elements.Collaborations.ClassifierRole.message>
-
        <Behavioral_Elements.Collaborations.ClassifierRole.base>
        <Foundation.Core.Class
xmi.idref="txmiid68" />

    </Behavioral_Elements.Collaborations.ClassifierRole.base>
- <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>crea

            <Foundation.Extension_Mechanisms.TaggedValue.value>tru

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>dest

            <Foundation.Extension_Mechanisms.TaggedValue.value>tru

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>

    </Behavioral_Elements.Collaborations.ClassifierRole>
</Foundation.Core.Namespace.ownedElement>
-
    <Behavioral_Elements.Collaborations.Collaboration.interaction>
- <Behavioral_Elements.Collaborations.Interaction
xmi.id="txmiidc.I">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility

```

```

xmi.value="private" />
-
<Behavioral_Elements.Collaborations.Interaction.message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiidf.M">

    <Foundation.Core.ModelElement.name>GEEServer
    O
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiidf.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.message>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiidf5a.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

      <Behavioral_Elements.Common_Behavior.CallAction
        xmi.idref="txmiidf.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

      <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiidf11" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

      <Behavioral_Elements.Collaborations.ClassifierRole

```



```

        xmi.idref="txmiidd" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid5a.M">

        <Foundation.Core.ModelElement.name>refuseDecision
(int,int,int,GLIF3.Case_Step)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid5a.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiidf.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid48.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-
        <Behavioral_Elements.Collaborations.Message.action>

            <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid5a.A" />

        </Behavioral_Elements.Collaborations.Message.action>
-
        <Behavioral_Elements.Collaborations.Message.receiver>

```

```

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid4f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid48.M">

        <Foundation.Core.ModelElement.name>refuseDecision</F

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid48.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid5a.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1e.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-
        <Behavioral_Elements.Collaborations.Message.action>

```

```

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid48.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid1e.M">

        <Foundation.Core.ModelElement.name>refuseDecision
(int,int,int,GLIF3.Case_Step)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid1e.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid48.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>

```

```

-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid2e.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
      xmi.idref="txmiid1e.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid11" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid2e.M">

    <Foundation.Core.ModelElement.name>setTrace
      (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
      xmi.idref="txmiid2e.MessageStereotype" />

```

```

</Foundation.Core.ModelElement.stereotype>
-
  <Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid1e.M" />

  </Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid5b.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
      xmi.idref="txmiid2e.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid5b.M">

    <Foundation.Core.ModelElement.name>getOptions
      (int,int,int,GLIF3.Decision_Step)

```

```

</Foundation.Core.ModelElement.name>

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid5b.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2e.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid49.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid5b.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid4f" />

```

```

</Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
<Behavioral_Elements.Collaborations.Message
xmi.id="txmiid49.M">

    <Foundation.Core.ModelElement.name>getOptions</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

        <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid49.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid5b.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1f.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid49.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

```

```

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
    xmi.idref="txmiid3f" />

</Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
<Behavioral_Elements.Collaborations.Message
xmi.id="txmiid1f.M">

    <Foundation.Core.ModelElement.name>getOptions
    (int,int,int,GLIF3.Decision_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

        <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid1f.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid49.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid2f.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction

```



```

        xmi.idref="txmiid1f.A" />
    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
        xmi.id="txmiid2f.M">

        <Foundation.Core.ModelElement.name>getOptions</Foun

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
                xmi.idref="txmiid2f.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
                xmi.idref="txmiid1f.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message

```

```

        xmi.idref="txmiid5c.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
        xmi.idref="txmiid2f.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiid63" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid5c.M">

        <Foundation.Core.ModelElement.name>selectOption
        (int,int,int,GLIF3.Decision_Step,GLIF3.Decision_Optio
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
            xmi.idref="txmiid5c.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

```

```

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2f.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid4a.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid5c.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid4f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid4a.M">

        <Foundation.Core.ModelElement.name>selectOption</Fou

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

```

```

        <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid4a.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid5c.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid20.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
        xmi.idref="txmiid4a.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid20.M">

```

```

<Foundation.Core.ModelElement.name>selectOption
(int,int,int,GLIF3.Decision_Step,GLIF3.Decision_Optio
</Foundation.Core.ModelElement.name>

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid20.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
<Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid4a.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
<Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid30.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
<Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid20.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
<Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

```

```

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid30.M">

        <Foundation.Core.ModelElement.name>getCurrentStep
(int,int,int)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid30.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid20.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid31.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-
        <Behavioral_Elements.Collaborations.Message.action>

            <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid30.A" />

        </Behavioral_Elements.Collaborations.Message.action>
-

```

```

    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
        xmi.id="txmiid31.M">

        <Foundation.Core.ModelElement.name>getCurrentStep</

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />

-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
                xmi.idref="txmiid31.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
                xmi.idref="txmiid30.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
                xmi.idref="txmiid39.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-

```

```

    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid31.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid63" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid39.M">

        <Foundation.Core.ModelElement.name>setTrace
(int,int,int,GLIF3.Guideline_Step)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid39.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid31.M" />

```



```

</Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid5d.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
      xmi.idref="txmiid39.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid5d.M">

    <Foundation.Core.ModelElement.name>getBranches
      (int,int,int,GLIF3.Branch_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype

```

```

xmi.idref="txmiid5d.MessageStereotype" />
</Foundation.Core.ModelElement.stereotype>
-
<Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid39.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
<Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid4b.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
<Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
      xmi.idref="txmiid5d.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
<Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid3f" />

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid4f" />

</Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
<Behavioral_Elements.Collaborations.Message
  xmi.id="txmiid4b.M">

    <Foundation.Core.ModelElement.name>getBranches</Fou

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

        <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid4b.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid5d.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid21.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid4b.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.sender>

```

```

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid21.M">

    <Foundation.Core.ModelElement.name>getBranches
      (int,int,int,GLIF3.Branch_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  -
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid21.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
  -
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid4b.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
  -
    <Behavioral_Elements.Collaborations.Message.message>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid32.M" />

    </Behavioral_Elements.Collaborations.Message.message>
  -
    <Behavioral_Elements.Collaborations.Message.action>

      <Behavioral_Elements.Common_Behavior.CallAction
        xmi.idref="txmiid21.A" />

    </Behavioral_Elements.Collaborations.Message.action>
  -
    <Behavioral_Elements.Collaborations.Message.receiver>

      <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiid25" />

```

```

</Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid11" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid32.M">

    <Foundation.Core.ModelElement.name>getBranches</Fou

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

  -
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid32.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
  -
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid21.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
  -
    <Behavioral_Elements.Collaborations.Message.message>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid5e.M" />

    </Behavioral_Elements.Collaborations.Message.message>
  -
    <Behavioral_Elements.Collaborations.Message.action>

      <Behavioral_Elements.Common_Behavior.UninterpretedA
        xmi.idref="txmiid32.A" />

```

```

</Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid63" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid5e.M">

    <Foundation.Core.ModelElement.name>selectBranch
      (int,int,int,GLIF3.Branch_Step,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid5e.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid32.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

```

```

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid4c.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid5e.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid4f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid4c.M">

        <Foundation.Core.ModelElement.name>selectBranch</Fo

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid4c.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

```

```

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid5e.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid22.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid4c.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid22.M">

        <Foundation.Core.ModelElement.name>selectBranch
(int,int,int,GLIF3.Branch_Step,GLIF3.Guideline_Step)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-

```



```

<Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
      xmi.idref="txmiid22.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
          xmi.idref="txmiid4c.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
          xmi.idref="txmiid33.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
          xmi.idref="txmiid22.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
          xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
          xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message

```

```

xmi.id="txmiid33.M">

  <Foundation.Core.ModelElement.name>getCurrentStep
  (int,int,int)
</Foundation.Core.ModelElement.name>

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
    xmi.idref="txmiid33.MessageStereotype" />

  </Foundation.Core.ModelElement.stereotype>
-
  <Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid22.M" />

  </Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid34.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
    xmi.idref="txmiid33.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
    xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

```

```

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid34.M">

        <Foundation.Core.ModelElement.name>getCurrentStep</

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid34.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid33.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid3a.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-
        <Behavioral_Elements.Collaborations.Message.action>

            <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid34.A" />

        </Behavioral_Elements.Collaborations.Message.action>
-
        <Behavioral_Elements.Collaborations.Message.receiver>

```

```

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid63" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid3a.M">

        <Foundation.Core.ModelElement.name>setTrace
(int,int,int,GLIF3.Guideline_Step)
</Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid3a.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid34.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid5f.M" />

        </Behavioral_Elements.Collaborations.Message.message>

```

```

-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
      xmi.idref="txmiid3a.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid5f.M">

    <Foundation.Core.ModelElement.name>continueSynchror
      (int,int,int,GLIF3.Synchronization_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid5f.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid3a.M" />

```

```

</Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid4d.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
      xmi.idref="txmiid5f.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid3f" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid4f" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid4d.M">

    <Foundation.Core.ModelElement.name>continueSynchr
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
      xmi.idref="txmiid4d.MessageStereotype" />

```

```

</Foundation.Core.ModelElement.stereotype>
-
  <Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid5f.M" />

  </Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid23.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.UninterpretedA
      xmi.idref="txmiid4d.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid11" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid3f" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid23.M">

    <Foundation.Core.ModelElement.name>continueSynchronor
      (int,int,int,GLIF3.Synchronization_Step)

```

```

</Foundation.Core.ModelElement.name>

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid23.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid4d.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid35.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid23.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

```



```

</Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
<Behavioral_Elements.Collaborations.Message
xmi.id="txmiid35.M">

    <Foundation.Core.ModelElement.name>evaluateContinua

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

        <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid35.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid23.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid36.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid35.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

```

```

</Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.sender>
</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid36.M">

    <Foundation.Core.ModelElement.name>evaluationContinu

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid36.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid35.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid3b.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

      <Behavioral_Elements.Common_Behavior.UninterpretedA
        xmi.idref="txmiid36.A" />

```

```

</Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid63" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid3b.M">

    <Foundation.Core.ModelElement.name>getCurrentStep
(int,int,int)
  </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid3b.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid36.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

      <Behavioral_Elements.Collaborations.Message

```

```

        xmi.idref="txmiid3c.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
        xmi.idref="txmiid3b.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid3c.M">

        <Foundation.Core.ModelElement.name>getCurrentStep</

        <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
            xmi.idref="txmiid3c.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message

```

```

        xmi.idref="txmiid3b.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
<Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid3d.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
<Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.UninterpretedA
      xmi.idref="txmiid3c.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
<Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid63" />

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

</Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
<Behavioral_Elements.Collaborations.Message
  xmi.id="txmiid3d.M">

    <Foundation.Core.ModelElement.name>setTrace
      (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

```

```

        <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid3d.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid3c.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid53.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
        xmi.idref="txmiid3d.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid53.M">

```

```

<Foundation.Core.ModelElement.name>deleteGEEClientH
O
</Foundation.Core.ModelElement.name>

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid53.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
<Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid3d.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
<Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid42.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
<Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid53.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
<Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

```

```

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid4f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid42.M">

        <Foundation.Core.ModelElement.name>deleteGEEClientH:
(int,int,int)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid42.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid53.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid14.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-
        <Behavioral_Elements.Collaborations.Message.action>

            <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid42.A" />

        </Behavioral_Elements.Collaborations.Message.action>
-

```



```

    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
        xmi.id="txmiid14.M">

        <Foundation.Core.ModelElement.name>check
            if primaryClient, if so assign
            another primaryClient and
            notify</Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
                xmi.idref="txmiid14.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
                xmi.idref="txmiid42.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
                xmi.idref="txmiid54.M" />

```

```

</Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.UninterpretedA
      xmi.idref="txmiid14.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid11" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid54.M">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid54.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid14.M" />

```

```

</Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid10.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.UninterpretedA
      xmi.idref="txmiid54.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid3f" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid4f" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid10.M">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
      xmi.idref="txmiid10.MessageStereotype" />

```

```

</Foundation.Core.ModelElement.stereotype>
-
  <Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid54.M" />

  </Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid17.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.UninterpretedA
      xmi.idref="txmiid10.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid11" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiidd" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid17.M">

    <Foundation.Core.ModelElement.name />

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

        <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid17.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid10.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid18.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid17.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid60" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.sender>

```

```

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid18.M">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  -
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid18.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
  -
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid17.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
  -
    <Behavioral_Elements.Collaborations.Message.message>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid50.M" />

    </Behavioral_Elements.Collaborations.Message.message>
  -
    <Behavioral_Elements.Collaborations.Message.action>

      <Behavioral_Elements.Common_Behavior.UninterpretedA
        xmi.idref="txmiid18.A" />

    </Behavioral_Elements.Collaborations.Message.action>
  -
    <Behavioral_Elements.Collaborations.Message.receiver>

      <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiid63" />

    </Behavioral_Elements.Collaborations.Message.receiver>
  -

```

```

    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid50.M">

        <Foundation.Core.ModelElement.name>GEEClient
O
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid50.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid18.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid52.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-
        <Behavioral_Elements.Collaborations.Message.action>

            <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid50.A" />

```

```

</Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid3f" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid4f" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid52.M">

    <Foundation.Core.ModelElement.name>createGEEClientH:
    O
  </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid52.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid50.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

      <Behavioral_Elements.Collaborations.Message

```



```

        xmi.idref="txmiid41.M" />
    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
            xmi.idref="txmiid52.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid4f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
        xmi.id="txmiid41.M">

        <Foundation.Core.ModelElement.name>createGEEClientH:
            (java.lang.String,int)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
                xmi.idref="txmiid41.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

```

```

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid52.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid12.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid41.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid12.M">

        <Foundation.Core.ModelElement.name>GEEClientHandle
(int,java.lang.String,int)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />

```

```

-
  <Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
      xmi.idref="txmiid12.MessageStereotype" />

  </Foundation.Core.ModelElement.stereotype>
-
  <Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid41.M" />

  </Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid51.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
      xmi.idref="txmiid12.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid11" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-

```

```

<Behavioral_Elements.Collaborations.Message
xmi.id="txmiid51.M">

  <Foundation.Core.ModelElement.name>selectGuidelinePa
(int,int)
</Foundation.Core.ModelElement.name>

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid51.MessageStereotype" />

  </Foundation.Core.ModelElement.stereotype>
-
  <Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid12.M" />

  </Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid40.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid51.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-

```

```

    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid4f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
        xmi.id="txmiid40.M">

        <Foundation.Core.ModelElement.name>selectGuidelinePa
            (int,int,int)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
                xmi.idref="txmiid40.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
                xmi.idref="txmiid51.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
                xmi.idref="txmiid13.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-
        <Behavioral_Elements.Collaborations.Message.action>

            <Behavioral_Elements.Common_Behavior.CallAction
                xmi.idref="txmiid40.A" />

```

```

</Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid11" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid3f" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid13.M">

    <Foundation.Core.ModelElement.name>set
      PatientID and GuidelineID,
      decide if
      primaryClient</Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid13.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid40.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

```

```

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid15.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid13.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid15.M">

        <Foundation.Core.ModelElement.name>if
new patient,
construct</Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid15.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-

```

```

    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
            xmi.idref="txmiid13.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
            xmi.idref="txmiid61.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
            xmi.idref="txmiid15.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid60" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
        xmi.id="txmiid61.M">

        <Foundation.Core.ModelElement.name>loadPatient
        O
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility

```



```

xmi.value="private" />
-
<Foundation.Core.ModelElement.stereotype>

  <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid61.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
<Behavioral_Elements.Collaborations.Message.predecessor>

  <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid15.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
<Behavioral_Elements.Collaborations.Message.message>

  <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid16.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
<Behavioral_Elements.Collaborations.Message.action>

  <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid61.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
<Behavioral_Elements.Collaborations.Message.receiver>

  <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid60" />

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

  <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid60" />

</Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>

```

```

-
<Behavioral_Elements.Collaborations.Message
xmi.id="txmiid16.M">

  <Foundation.Core.ModelElement.name>if
  new guideline,
  construct</Foundation.Core.ModelElement.name>

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid16.MessageStereotype" />

  </Foundation.Core.ModelElement.stereotype>
-
  <Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid61.M" />

  </Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid64.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid16.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid63" />

  </Behavioral_Elements.Collaborations.Message.receiver>

```

```

-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid11" />

  </Behavioral_Elements.Collaborations.Message.sender>
</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid64.M">

    <Foundation.Core.ModelElement.name>loadGuidelines
    O
  </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid64.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid16.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid65.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

      <Behavioral_Elements.Common_Behavior.CallAction
        xmi.idref="txmiid64.A" />

```

```

</Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid63" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid63" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid65.M">

    <Foundation.Core.ModelElement.name>parseGuideline
    O
  </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid65.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid64.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

```

```

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid66.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid65.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid63" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid63" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid66.M">

        <Foundation.Core.ModelElement.name>mapGuidelineData
0
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid66.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-

```

```

    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
            xmi.idref="txmiid65.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
            xmi.idref="txmiid67.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
            xmi.idref="txmiid66.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid63" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid63" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
        xmi.id="txmiid67.M">

        <Foundation.Core.ModelElement.name>browseGuideline
        O
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility

```

```

xmi.value="private" />
-
<Foundation.Core.ModelElement.stereotype>

  <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid67.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
<Behavioral_Elements.Collaborations.Message.predecessor>

  <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid66.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
<Behavioral_Elements.Collaborations.Message.message>

  <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid55.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
<Behavioral_Elements.Collaborations.Message.action>

  <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid67.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
<Behavioral_Elements.Collaborations.Message.receiver>

  <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid63" />

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

  <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid63" />

</Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>

```

```

-
<Behavioral_Elements.Collaborations.Message
xmi.id="txmiid55.M">

    <Foundation.Core.ModelElement.name>setCurrentStep
    (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

        <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid55.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid67.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid43.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
        xmi.idref="txmiid55.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
        xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.receiver>

```



```

-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid4f" />

  </Behavioral_Elements.Collaborations.Message.sender>
</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid43.M">

    <Foundation.Core.ModelElement.name>setCurrentStep</I

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid43.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid55.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid19.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

      <Behavioral_Elements.Common_Behavior.UninterpretedA
        xmi.idref="txmiid43.A" />

    </Behavioral_Elements.Collaborations.Message.action>

```

```

-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid11" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid3f" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid19.M">

    <Foundation.Core.ModelElement.name>setCurrentStep
      (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid19.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid43.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

      <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid56.M" />

```

```

</Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
      xmi.idref="txmiid19.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid11" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid56.M">

    <Foundation.Core.ModelElement.name>acceptActionReco
(int,int,int,GLIF3.Action_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid56.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

```

```

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid19.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid44.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid56.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid4f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid44.M">

        <Foundation.Core.ModelElement.name>acceptActionReco

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

```

```

        <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid44.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid56.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1a.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid44.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid1a.M">

```

```

<Foundation.Core.ModelElement.name>acceptActionReco
(int,int,int,GLIF3.Action_Step)
</Foundation.Core.ModelElement.name>

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
    xmi.idref="txmiid1a.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
<Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid44.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
<Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid26.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
<Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
    xmi.idref="txmiid1a.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
<Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
    xmi.idref="txmiid25" />

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole

```

```

        xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid26.M">

        <Foundation.Core.ModelElement.name>getCurrentStep
(int,int,int)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid26.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1a.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid29.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-
        <Behavioral_Elements.Collaborations.Message.action>

            <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid26.A" />

        </Behavioral_Elements.Collaborations.Message.action>
-
        <Behavioral_Elements.Collaborations.Message.receiver>

```

```

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid29.M">

        <Foundation.Core.ModelElement.name>getCurrentStep</

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid29.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid26.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid27.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-
        <Behavioral_Elements.Collaborations.Message.action>

```



```

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid29.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid63" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid27.M">

        <Foundation.Core.ModelElement.name>setTrace
(int,int,int,GLIF3.Guideline_Step)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid27.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid29.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>

```

```

-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid57.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
      xmi.idref="txmiid27.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid57.M">

    <Foundation.Core.ModelElement.name>refuseActionReco
      (int,int,int,GLIF3.Action_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
      xmi.idref="txmiid57.MessageStereotype" />

```

```

</Foundation.Core.ModelElement.stereotype>
-
  <Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid27.M" />

  </Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid45.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
      xmi.idref="txmiid57.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid3f" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid4f" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid45.M">

    <Foundation.Core.ModelElement.name>refuseActionReco

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

        <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid45.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid57.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1b.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid45.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.sender>

```

```
</Behavioral_Elements.Collaborations.Message>
```

```
-
```

```
<Behavioral_Elements.Collaborations.Message  
xmi.id="txmiid1b.M">
```

```
<Foundation.Core.ModelElement.name>refuseActionReco  
(int,int,int,GLIF3.Action_Step)  
</Foundation.Core.ModelElement.name>
```

```
<Foundation.Core.ModelElement.visibility  
xmi.value="private" />
```

```
-
```

```
<Foundation.Core.ModelElement.stereotype>
```

```
<Foundation.Extension_Mechanisms.Stereotype  
xmi.idref="txmiid1b.MessageStereotype" />
```

```
</Foundation.Core.ModelElement.stereotype>
```

```
-
```

```
<Behavioral_Elements.Collaborations.Message.predecessor>
```

```
<Behavioral_Elements.Collaborations.Message  
xmi.idref="txmiid45.M" />
```

```
</Behavioral_Elements.Collaborations.Message.predecessor>
```

```
-
```

```
<Behavioral_Elements.Collaborations.Message.message>
```

```
<Behavioral_Elements.Collaborations.Message  
xmi.idref="txmiid28.M" />
```

```
</Behavioral_Elements.Collaborations.Message.message>
```

```
-
```

```
<Behavioral_Elements.Collaborations.Message.action>
```

```
<Behavioral_Elements.Common_Behavior.CallAction  
xmi.idref="txmiid1b.A" />
```

```
</Behavioral_Elements.Collaborations.Message.action>
```

```
-
```

```
<Behavioral_Elements.Collaborations.Message.receiver>
```

```
<Behavioral_Elements.Collaborations.ClassifierRole  
xmi.idref="txmiid25" />
```

```

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
    xmi.idref="txmiid11" />

</Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
<Behavioral_Elements.Collaborations.Message
xmi.id="txmiid28.M">

    <Foundation.Core.ModelElement.name>setTrace
    (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

        <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid28.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid1b.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid58.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction

```

```

        xmi.idref="txmiid28.A" />
    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
        xmi.id="txmiid58.M">

        <Foundation.Core.ModelElement.name>completeAction
            (int,int,int,GLIF3.Action_Step)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
                xmi.idref="txmiid58.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
                xmi.idref="txmiid28.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

```

```

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid46.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid58.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid4f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid46.M">

        <Foundation.Core.ModelElement.name>completeAction</

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid46.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

```



```

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid58.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1c.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid46.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid1c.M">

        <Foundation.Core.ModelElement.name>completeAction
(int,int,int,GLIF3.Action_Step)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />

```

```

-
<Foundation.Core.ModelElement.stereotype>

  <Foundation.Extension_Mechanisms.Stereotype
    xmi.idref="txmiid1c.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
<Behavioral_Elements.Collaborations.Message.predecessor>

  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid46.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
<Behavioral_Elements.Collaborations.Message.message>

  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid2a.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
<Behavioral_Elements.Collaborations.Message.action>

  <Behavioral_Elements.Common_Behavior.CallAction
    xmi.idref="txmiid1c.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
<Behavioral_Elements.Collaborations.Message.receiver>

  <Behavioral_Elements.Collaborations.ClassifierRole
    xmi.idref="txmiid25" />

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

  <Behavioral_Elements.Collaborations.ClassifierRole
    xmi.idref="txmiid11" />

</Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-

```

```

<Behavioral_Elements.Collaborations.Message
xmi.id="txmiid2a.M">

  <Foundation.Core.ModelElement.name>getCurrentStep
(int,int,int)
</Foundation.Core.ModelElement.name>

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid2a.MessageStereotype" />

  </Foundation.Core.ModelElement.stereotype>
-
  <Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1c.M" />

  </Behavioral_Elements.Collaborations.Message.predecessor>
-
  <Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2b.M" />

  </Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid2a.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-

```

```

    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid2b.M">

        <Foundation.Core.ModelElement.name>getCurrentStep</

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid2b.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2a.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid37.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-
        <Behavioral_Elements.Collaborations.Message.action>

            <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid2b.A" />

        </Behavioral_Elements.Collaborations.Message.action>
-

```

```

    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid63" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
        xmi.id="txmiid37.M">

        <Foundation.Core.ModelElement.name>setTrace
            (int,int,int,GLIF3.Guideline_Step)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
                xmi.idref="txmiid37.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
                xmi.idref="txmiid2b.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
                xmi.idref="txmiid59.M" />

```

```

</Behavioral_Elements.Collaborations.Message.message>
-
  <Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
      xmi.idref="txmiid37.A" />

  </Behavioral_Elements.Collaborations.Message.action>
-
  <Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.receiver>
-
  <Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid25" />

  </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
  <Behavioral_Elements.Collaborations.Message
    xmi.id="txmiid59.M">

    <Foundation.Core.ModelElement.name>acceptDecision
(int,int,int,GLIF3.Case_Step)
  </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

      <Foundation.Extension_Mechanisms.Stereotype
        xmi.idref="txmiid59.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message

```

```

        xmi.idref="txmiid37.M" />
    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
            xmi.idref="txmiid47.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
            xmi.idref="txmiid59.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid3f" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid4f" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
        xmi.id="txmiid47.M">

        <Foundation.Core.ModelElement.name>acceptDecision</f

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

        <Foundation.Extension_Mechanisms.Stereotype

```

```

xmi.idref="txmiid47.MessageStereotype" />
</Foundation.Core.ModelElement.stereotype>
-
<Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid59.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
<Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid1d.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
<Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.UninterpretedA
      xmi.idref="txmiid47.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
<Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid11" />

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
      xmi.idref="txmiid3f" />

</Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
<Behavioral_Elements.Collaborations.Message
  xmi.id="txmiid1d.M">

    <Foundation.Core.ModelElement.name>acceptDecision

```



```

(int,int,int,GLIF3.Case_Step)
</Foundation.Core.ModelElement.name>

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.ModelElement.stereotype>

    <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid1d.MessageStereotype" />

</Foundation.Core.ModelElement.stereotype>
-
<Behavioral_Elements.Collaborations.Message.predecessor>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid47.M" />

</Behavioral_Elements.Collaborations.Message.predecessor>
-
<Behavioral_Elements.Collaborations.Message.message>

    <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2c.M" />

</Behavioral_Elements.Collaborations.Message.message>
-
<Behavioral_Elements.Collaborations.Message.action>

    <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid1d.A" />

</Behavioral_Elements.Collaborations.Message.action>
-
<Behavioral_Elements.Collaborations.Message.receiver>

    <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

</Behavioral_Elements.Collaborations.Message.receiver>
-
<Behavioral_Elements.Collaborations.Message.sender>

    <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid11" />

```

```

</Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
<Behavioral_Elements.Collaborations.Message
xmi.id="txmiid2c.M">

    <Foundation.Core.ModelElement.name>getCurrentStep
    (int,int,int)
    </Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.ModelElement.stereotype>

        <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid2c.MessageStereotype" />

    </Foundation.Core.ModelElement.stereotype>
-
    <Behavioral_Elements.Collaborations.Message.predecessor>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid1d.M" />

    </Behavioral_Elements.Collaborations.Message.predecessor>
-
    <Behavioral_Elements.Collaborations.Message.message>

        <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2d.M" />

    </Behavioral_Elements.Collaborations.Message.message>
-
    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
xmi.idref="txmiid2c.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

```

```

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid2d.M">

        <Foundation.Core.ModelElement.name>getCurrentStep</

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid2d.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2c.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-
        <Behavioral_Elements.Collaborations.Message.message>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid38.M" />

        </Behavioral_Elements.Collaborations.Message.message>
-
        <Behavioral_Elements.Collaborations.Message.action>

```

```

        <Behavioral_Elements.Common_Behavior.UninterpretedA
xmi.idref="txmiid2d.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid63" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>
-
    <Behavioral_Elements.Collaborations.Message
xmi.id="txmiid38.M">

        <Foundation.Core.ModelElement.name>setTrace
(int,int,int,GLIF3.Guideline_Step)
        </Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.ModelElement.stereotype>

            <Foundation.Extension_Mechanisms.Stereotype
xmi.idref="txmiid38.MessageStereotype" />

        </Foundation.Core.ModelElement.stereotype>
-
        <Behavioral_Elements.Collaborations.Message.predecessor>

            <Behavioral_Elements.Collaborations.Message
xmi.idref="txmiid2d.M" />

        </Behavioral_Elements.Collaborations.Message.predecessor>
-

```

```

    <Behavioral_Elements.Collaborations.Message.action>

        <Behavioral_Elements.Common_Behavior.CallAction
            xmi.idref="txmiid38.A" />

    </Behavioral_Elements.Collaborations.Message.action>
-
    <Behavioral_Elements.Collaborations.Message.receiver>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.receiver>
-
    <Behavioral_Elements.Collaborations.Message.sender>

        <Behavioral_Elements.Collaborations.ClassifierRole
            xmi.idref="txmiid25" />

    </Behavioral_Elements.Collaborations.Message.sender>

</Behavioral_Elements.Collaborations.Message>

</Behavioral_Elements.Collaborations.Interaction.message>

</Behavioral_Elements.Collaborations.Interaction>

    </Behavioral_Elements.Collaborations.Collaboration.interaction>
</Behavioral_Elements.Collaborations.Collaboration>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiidf.A">
    <Foundation.Core.ModelElement.name>GEEServer()
        </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-

```

```

    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid69.O" />

</Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid10.A">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

```

```

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid1e.A">

    <Foundation.Core.ModelElement.name>refuseDecision
(int,int,int,GLIF3.Case_Step)
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />

```

```

-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid6a.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid1f.A">
  <Foundation.Core.ModelElement.name>getOptions
    (int,int,int,GLIF3.Decision_Step)
  </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

  <Foundation.Data_Types.Expression.language />
  <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

  <Foundation.Data_Types.Expression.language />
  <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid6b.O" />

```



```

    </Behavioral_Elements.Common_Behavior.Action.request>
  </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid20.A">
  <Foundation.Core.ModelElement.name>selectOption
    (int,int,int,GLIF3.Decision_Step,GLIF3.Decision_Option)
  </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

  <Foundation.Data_Types.Expression.language />
  <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

  <Foundation.Data_Types.Expression.language />
  <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid6c.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
  </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid21.A">
  <Foundation.Core.ModelElement.name>getBranches

```

```

    (int,int,int,GLIF3.Branch_Step)
    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
  - <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
  - <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

  </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
      xmi.idref="txmiid6d.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
  </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid22.A">
  <Foundation.Core.ModelElement.name>selectBranch
    (int,int,int,GLIF3.Branch_Step,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-

```

```

    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid6e.0" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-   <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid23.A">

        <Foundation.Core.ModelElement.name>continueSynchronization
(int,int,int,GLIF3.Synchronization_Step)
        </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid6f.O" />

</Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid14.A">
    <Foundation.Core.ModelElement.name>check if
    primaryClient, if so assign another
    primaryClient and
    notify</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

```

```

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
  <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid17.A">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous

```

```

xmi.value="false" />

<Behavioral_Elements.Common_Behavior.Action.script />

<Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
  <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid18.A">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
xmi.id="txmiid12.A">

  <Foundation.Core.ModelElement.name>GEEClientHandle
(int,java.lang.String,int)

```

```

    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
  - <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
  - <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

  </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
      xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
      xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
      xmi.idref="txmiid70.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
      xmi.id="txmiid13.A">
    <Foundation.Core.ModelElement.name>set PatientID
      and GuidelineID, decide if
      primaryClient</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-

```

```

    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid15.A">
    <Foundation.Core.ModelElement.name>if new
    patient,
    construct</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>

```



```

- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

<Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

<Behavioral_Elements.Common_Behavior.Action.script />

<Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid16.A">
    <Foundation.Core.ModelElement.name>if new
guideline,
construct</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

<Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

```

```

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid19.A">

    <Foundation.Core.ModelElement.name>setCurrentStep
    (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
    xmi.idref="txmiid71.O" />

```

```

    </Behavioral_Elements.Common_Behavior.Action.request>
  </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid1a.A">

    <Foundation.Core.ModelElement.name>acceptActionRecommenc
    (int,int,int,GLIF3.Action_Step)
    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
  - <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />
      <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
  - <Foundation.Data_Types.ObjectSetExpression>

      <Foundation.Data_Types.Expression.language />
      <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

  </Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
      xmi.idref="txmiid72.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
  </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid1b.A">

```

```

    <Foundation.Core.ModelElement.name>refuseActionRecommend
    (int,int,int,GLIF3.Action_Step)
  </Foundation.Core.ModelElement.name>
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
  xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
  xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid73.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid1c.A">

  <Foundation.Core.ModelElement.name>completeAction
  (int,int,int,GLIF3.Action_Step)
  </Foundation.Core.ModelElement.name>

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid74.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid1d.A">

  <Foundation.Core.ModelElement.name>acceptDecision
    (int,int,int,GLIF3.Case_Step)
  </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>

```

```

- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid75.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid2e.A">
    <Foundation.Core.ModelElement.name>setTrace
        (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>

```

```

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid76.O" />
  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
  <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid2f.A">

    <Foundation.Core.ModelElement.name>getOptions</Foundation.C
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

```

```

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid30.A">

        <Foundation.Core.ModelElement.name>getCurrentStep
(int,int,int)
        </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

```



```

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid77.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid31.A">

        <Foundation.Core.ModelElement.name>getCurrentStep</Foundat
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
        <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>

```

```

- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid39.A">
  <Foundation.Core.ModelElement.name>setTrace
    (int,int,int,GLIF3.Guideline_Step)
  </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

  <Foundation.Data_Types.Expression.language />
  <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

  <Foundation.Data_Types.Expression.language />
  <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid76.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
  <Behavioral_Elements.Common_Behavior.UninterpretedAction
    xmi.id="txmiid32.A">

  <Foundation.Core.ModelElement.name>getBranches</Foundation

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />
      <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

      <Foundation.Data_Types.Expression.language />
      <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

  </Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="false" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid33.A">

    <Foundation.Core.ModelElement.name>getCurrentStep
      (int,int,int)
    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
      </Foundation.Data_Types.Expression>

```

```

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid77.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
  <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid34.A">

    <Foundation.Core.ModelElement.name>getCurrentStep</Foundat
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

```

```

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid3a.A">
    <Foundation.Core.ModelElement.name>setTrace
        (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

```

```

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid76.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid35.A">

        <Foundation.Core.ModelElement.name>evaluateContinuation</F
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
        <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

        <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

        <Behavioral_Elements.Common_Behavior.Action.script />

        <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

    </Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
        <Behavioral_Elements.Common_Behavior.UninterpretedAction

```

```

xmi.id="txmiid36.A">
  <Foundation.Core.ModelElement.name>evaluationContinuation<
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid3b.A">

    <Foundation.Core.ModelElement.name>getCurrentStep
    (int,int,int)
    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid77.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid3c.A">

        <Foundation.Core.ModelElement.name>getCurrentStep</Foundat
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-

```



```

    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-   <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid3d.A">
    <Foundation.Core.ModelElement.name>setTrace
    (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

```

```

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid76.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
    </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid26.A">

        <Foundation.Core.ModelElement.name>getCurrentStep
(int,int,int)
        </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
        <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode

```

```

xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid77.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
  <Behavioral_Elements.Common_Behavior.UninterpretedAction
    xmi.id="txmiid29.A">

    <Foundation.Core.ModelElement.name>getCurrentStep</Foundat
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
  - <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
  - <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

  </Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="false" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

  </Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid27.A">
  <Foundation.Core.ModelElement.name>setTrace

```

```

    (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
  - <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
  - <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

  </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
      xmi.idref="txmiid76.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
  </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid28.A">
  <Foundation.Core.ModelElement.name>setTrace
    (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-

```

```

    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid76.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid2a.A">

        <Foundation.Core.ModelElement.name>getCurrentStep
(int,int,int)
        </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid77.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid2b.A">

        <Foundation.Core.ModelElement.name>getCurrentStep</Foundat
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-

```

```

    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-   <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid37.A">
    <Foundation.Core.ModelElement.name>setTrace
    (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

```

```

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid76.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
    </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid2c.A">

        <Foundation.Core.ModelElement.name>getCurrentStep
(int,int,int)
        </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
        <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode

```



```

xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid77.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
  <Behavioral_Elements.Common_Behavior.UninterpretedAction
    xmi.id="txmiid2d.A">

    <Foundation.Core.ModelElement.name>getCurrentStep</Foundat
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
  - <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
  - <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

  </Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="false" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

  </Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid38.A">
  <Foundation.Core.ModelElement.name>setTrace

```

```

    (int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
  - <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
  - <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

  </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
      xmi.idref="txmiid76.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
  <Behavioral_Elements.Common_Behavior.UninterpretedAction
  xmi.id="txmiid48.A">

    <Foundation.Core.ModelElement.name>refuseDecision</Foundati
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-

```

```

    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid49.A">

        <Foundation.Core.ModelElement.name>getOptions</Foundation.C
<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

```

```

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid4a.A">

        <Foundation.Core.ModelElement.name>selectOption</Foundation
<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
        <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

```

```

        <Behavioral_Elements.Common_Behavior.UninterpretedAction.body
</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid4b.A">

        <Foundation.Core.ModelElement.name>getBranches</Foundation
<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
        <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body
</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid4c.A">

        <Foundation.Core.ModelElement.name>selectBranch</Foundation
<Foundation.Core.ModelElement.visibility
xmi.value="private" />

```

```

-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
  <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid4d.A">

    <Foundation.Core.ModelElement.name>continueSynchronization
  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>

```

```

- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

<Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

<Behavioral_Elements.Common_Behavior.Action.script />

<Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid42.A">

    <Foundation.Core.ModelElement.name>deleteGEEClientHandle
    (int,int,int)
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

<Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

```

```

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid78.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
    </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid41.A">

        <Foundation.Core.ModelElement.name>createGEEClientHandle
        (java.lang.String,int)
        </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Behavioral_Elements.Common_Behavior.Action.recurrence>
        - <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
        <Behavioral_Elements.Common_Behavior.Action.target>
        - <Foundation.Data_Types.ObjectSetExpression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode

```



```

xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid79.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
  </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid40.A">

    <Foundation.Core.ModelElement.name>selectGuidelinePatientPa
      (int,int,int)
    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

  </Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation

```

```

xmi.idref="txmiid7a.O" />

</Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-
<Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid43.A">

    <Foundation.Core.ModelElement.name>setCurrentStep</Foundat
<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid44.A">

    <Foundation.Core.ModelElement.name>acceptActionRecommenc
<Foundation.Core.ModelElement.visibility
xmi.value="private" />

```

```

-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
  <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid45.A">

    <Foundation.Core.ModelElement.name>refuseActionRecommend
  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>

```

```

- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

<Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

<Behavioral_Elements.Common_Behavior.Action.script />

<Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
<Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid46.A">

    <Foundation.Core.ModelElement.name>completeAction</Foundat
<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

<Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

```

```

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
-
    <Behavioral_Elements.Common_Behavior.UninterpretedAction
xmi.id="txmiid47.A">

        <Foundation.Core.ModelElement.name>acceptDecision</Foundati
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
        <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

        <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="false" />

        <Behavioral_Elements.Common_Behavior.Action.script />

        <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

    </Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
xmi.id="txmiid5a.A">

        <Foundation.Core.ModelElement.name>refuseDecision
(int,int,int,GLIF3.Case_Step)
    </Foundation.Core.ModelElement.name>

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid7b.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid5b.A">
  <Foundation.Core.ModelElement.name>getOptions
    (int,int,int,GLIF3.Decision_Step)
  </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid7c.0" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid5c.A">
    <Foundation.Core.ModelElement.name>selectOption
        (int,int,int,GLIF3.Decision_Step,GLIF3.Decision_Option)
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

```

```

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid7d.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid5d.A">
  <Foundation.Core.ModelElement.name>getBranches
    (int,int,int,GLIF3.Branch_Step)
  </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

```



```

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid7e.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid5e.A">
    <Foundation.Core.ModelElement.name>selectBranch
        (int,int,int,GLIF3.Branch_Step,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

```

```

<Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

<Behavioral_Elements.Common_Behavior.Action.script />

<Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
<Behavioral_Elements.Common_Behavior.Action.request>
<Foundation.Core.Operation
  xmi.idref="txmiid7f.O" />

</Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid5f.A">

  <Foundation.Core.ModelElement.name>continueSynchronization
  (int,int,int,GLIF3.Synchronization_Step)
  </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
  - <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
  -
    <Behavioral_Elements.Common_Behavior.Action.target>
    - <Foundation.Data_Types.ObjectSetExpression>

      <Foundation.Data_Types.Expression.language />
      <Foundation.Data_Types.Expression.body />
      </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

```

```

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid80.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
    </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid53.A">

        <Foundation.Core.ModelElement.name>deleteGEEClientHandle
        ()</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
        <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-

```

```

    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
      xmi.idref="txmiid81.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>

-
  <Behavioral_Elements.Common_Behavior.UninterpretedAction
    xmi.id="txmiid54.A">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />
      <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>

-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

      <Foundation.Data_Types.Expression.language />
      <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

  </Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="false" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.UninterpretedAction.body

</Behavioral_Elements.Common_Behavior.UninterpretedAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid50.A">
  <Foundation.Core.ModelElement.name>GEEClient()
    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

```

```

-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid82.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid52.A">

    <Foundation.Core.ModelElement.name>createGEEClientHandle
    O</Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid83.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid51.A">

        <Foundation.Core.ModelElement.name>selectGuidelinePatientPa
(int,int)</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-

```

```

    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid84.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid55.A">

    <Foundation.Core.ModelElement.name>setCurrentStep
(int,int,int,GLIF3.Guideline_Step)
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid85.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid56.A">

    <Foundation.Core.ModelElement.name>acceptActionRecommenc
(int,int,int,GLIF3.Action_Step)
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

```



```

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid86.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
    </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid57.A">

        <Foundation.Core.ModelElement.name>refuseActionRecommend
(int,int,int,GLIF3.Action_Step)
        </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
        <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

```

```

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid87.O" />

    </Behavioral_Elements.Common_Behavior.Action.request>
    </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid58.A">

        <Foundation.Core.ModelElement.name>completeAction
(int,int,int,GLIF3.Action_Step)
        </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>

    </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
        <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

            <Foundation.Data_Types.Expression.language />
            <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.ObjectSetExpression>

    </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />

```

```

-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid88.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid59.A">

  <Foundation.Core.ModelElement.name>acceptDecision
    (int,int,int,GLIF3.Case_Step)
  </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

  <Foundation.Data_Types.Expression.language />
  <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

  <Foundation.Data_Types.Expression.language />
  <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid89.O" />

```

```

    </Behavioral_Elements.Common_Behavior.Action.request>
  </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid61.A">
  <Foundation.Core.ModelElement.name>loadPatient
    </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

  <Foundation.Data_Types.Expression.language />
  <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

  <Foundation.Data_Types.Expression.language />
  <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid8a.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid64.A">

```

```

    <Foundation.Core.ModelElement.name>loadGuidelines
    () </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
  - <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

  </Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
  - <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

  </Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
    xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
    xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
      xmi.idref="txmiid8b.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
  </Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid65.A">

    <Foundation.Core.ModelElement.name>parseGuideline
    () </Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-

```

```

    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
    <Behavioral_Elements.Common_Behavior.Action.target>
-   <Foundation.Data_Types.ObjectSetExpression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

    <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

    <Behavioral_Elements.Common_Behavior.Action.script />

    <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid8c.0" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
-   <Behavioral_Elements.Common_Behavior.CallAction
    xmi.id="txmiid66.A">

        <Foundation.Core.ModelElement.name>mapGuidelineData
    O</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Behavioral_Elements.Common_Behavior.Action.recurrence>
-   <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />

```

```

</Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>
- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

  <Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

  <Behavioral_Elements.Common_Behavior.Action.script />

  <Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
  <Behavioral_Elements.Common_Behavior.Action.request>
  <Foundation.Core.Operation
    xmi.idref="txmiid8d.O" />

  </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Behavioral_Elements.Common_Behavior.CallAction
  xmi.id="txmiid67.A">

  <Foundation.Core.ModelElement.name>browseGuideline
  O</Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Behavioral_Elements.Common_Behavior.Action.recurrence>
- <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>

</Behavioral_Elements.Common_Behavior.Action.recurrence>
-
  <Behavioral_Elements.Common_Behavior.Action.target>

```

```

- <Foundation.Data_Types.ObjectSetExpression>

    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.ObjectSetExpression>

</Behavioral_Elements.Common_Behavior.Action.target>

<Behavioral_Elements.Common_Behavior.Action.isAsynchronous
xmi.value="true" />

<Behavioral_Elements.Common_Behavior.Action.script />

<Behavioral_Elements.Common_Behavior.CallAction.mode
xmi.value="asynchronous" />
-
    <Behavioral_Elements.Common_Behavior.Action.request>
    <Foundation.Core.Operation
        xmi.idref="txmiid8e.0" />

    </Behavioral_Elements.Common_Behavior.Action.request>
</Behavioral_Elements.Common_Behavior.CallAction>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiidf.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
    - <Foundation.Data_Types.Geometry>
        <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiidf.M" />

```



```

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  </Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid10.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid10.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid1e.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>

```

```

</Foundation.Extension_Mechanisms.Stereotype.icon>

<Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
<Foundation.Extension_Mechanisms.Stereotype.extendedElement>
<Behavioral_Elements.Collaborations.Message
  xmi.idref="txmiid1e.M" />

</Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid1f.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
  -
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid1f.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    </Foundation.Extension_Mechanisms.Stereotype>
  - <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid20.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf

```

```

    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid20.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid21.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid21.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid22.MessageStereotype">

```

```

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid22.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid23.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>

```

```

        <Behavioral_Elements.Collaborations.Message
            xmi.idref="txmiid23.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid14.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
</Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid14.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid17.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>

```

```

        <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid17.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid18.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid18.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid12.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot

```

```

    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid12.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid13.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid13.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>

```



```

- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid15.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid15.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid16.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag

```



```

-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid16.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid19.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
    - <Foundation.Data_Types.Geometry>
        <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid19.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid1a.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />

```

```

- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid1a.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid1b.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid1b.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid1c.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid1c.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid1d.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid1d.M" />

```

```

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  </Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid2e.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid2e.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid2f.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>

```

```

</Foundation.Extension_Mechanisms.Stereotype.icon>

<Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
<Foundation.Extension_Mechanisms.Stereotype.extendedElement>
<Behavioral_Elements.Collaborations.Message
  xmi.idref="txmiid2f.M" />

</Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid30.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
  -
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid30.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    </Foundation.Extension_Mechanisms.Stereotype>
  - <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid31.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf

```

```

    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid31.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid39.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid39.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid32.MessageStereotype">

```

```

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid32.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid33.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>

```



```

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid33.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid34.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>
  <Foundation.Data_Types.Geometry.body />
</Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid34.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid3a.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>

```



```

        <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid3a.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid35.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid35.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid36.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot

```

```

    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid36.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid3b.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid3b.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>

```

```

- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid3c.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid3c.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid3d.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag

```

```

-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid3d.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid26.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
    - <Foundation.Data_Types.Geometry>
        <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid26.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid29.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />

```

```

- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid29.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid27.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid27.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid28.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid28.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid2a.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid2a.M" />

```

```

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  </Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid2b.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid2b.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid37.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>

```



```

</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid37.M" />

</Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid2c.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid2c.M" />

</Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid2d.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf

```



```

    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid2d.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid38.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid38.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid48.MessageStereotype">

```

```

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid48.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid49.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>

```

```

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid49.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid4a.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>
  <Foundation.Data_Types.Geometry.body />
</Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid4a.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid4b.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>

```

```

        <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid4b.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid4c.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid4c.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid4d.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot

```

```

    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid4d.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid42.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid42.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>

```

```

- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid41.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid41.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid40.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag

```

```

-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid40.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    </Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid43.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
    - <Foundation.Data_Types.Geometry>
        <Foundation.Data_Types.Geometry.body />
        </Foundation.Data_Types.Geometry>
    </Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid43.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    </Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid44.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />

```



```

- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid44.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid45.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid45.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid46.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M

```



```

<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid46.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid47.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid47.M" />

```

```

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  </Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid5a.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid5a.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid5b.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>

```

```

</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid5b.M" />

</Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid5c.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid5c.M" />

</Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid5d.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf

```

```

    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid5d.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid5e.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid5e.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid5f.MessageStereotype">

```

```

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid5f.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid53.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>

```

```

    <Behavioral_Elements.Collaborations.Message
      xmi.idref="txmiid53.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid54.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>
  <Foundation.Data_Types.Geometry.body />
</Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid54.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid50.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>

```

```

        <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid50.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid52.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid52.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid51.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot

```



```

    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid51.M" />

</Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid55.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid55.M" />

</Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>

```



```

- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid56.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid56.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid57.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag

```

```

-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid57.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    </Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid58.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
    - <Foundation.Data_Types.Geometry>
        <Foundation.Data_Types.Geometry.body />
        </Foundation.Data_Types.Geometry>
    </Foundation.Extension_Mechanisms.Stereotype.icon>

    <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
    <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    <Behavioral_Elements.Collaborations.Message
        xmi.idref="txmiid58.M" />

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
    </Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
    xmi.id="txmiid59.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />

```

```

- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid59.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid61.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid61.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid64.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid64.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid65.MessageStereotype">

  <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid65.M" />

```

```

    </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  </Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid66.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>
</Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass>Messag
-
  <Foundation.Extension_Mechanisms.Stereotype.extendedElement>
  <Behavioral_Elements.Collaborations.Message
    xmi.idref="txmiid66.M" />

  </Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiid67.MessageStereotype">

    <Foundation.Core.ModelElement.name>simple</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
  - <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
  </Foundation.Data_Types.Geometry>

```

```

</Foundation.Extension_Mechanisms.Stereotype.icon>

<Foundation.Extension_Mechanisms.Stereotype.baseClass>Message
-
<Foundation.Extension_Mechanisms.Stereotype.extendedElement>
<Behavioral_Elements.Collaborations.Message
  xmi.idref="txmiid67.M" />

</Foundation.Extension_Mechanisms.Stereotype.extendedElement>
</Foundation.Extension_Mechanisms.Stereotype>
- <Model_Management.Package xmi.id="txmiid8">

  <Foundation.Core.ModelElement.name>GEEClient</Foundation.Co
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Core.ModelElement.requirement>
  <Foundation.Core.Dependency
    xmi.idref="txmiid7.D" />
  </Foundation.Core.ModelElement.requirement>
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Model
    xmi.idref="txmiid1" />
  </Foundation.Core.ModelElement.namespace>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docume

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Namespace.ownedElement>
  - <Foundation.Core.Class xmi.id="txmiid4e">

    <Foundation.Core.ModelElement.name>GEEClient</Foundator
    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

```

```

<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
<Foundation.Core.Class.isActive
  xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid8" />
</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEClient.GEEClientGuidelineExecutorUserFur

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid8f.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid90.a">

    <Foundation.Core.ModelElement.name>servername</Fou

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

```

```

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four
<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid91" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid92.a">

    <Foundation.Core.ModelElement.name>clientID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />

```



```

<Foundation.Core.Feature.ownerScope
  xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four

<Foundation.Core.StructuralFeature.changeable
  xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
  xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid93" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid94.a">

  <Foundation.Core.ModelElement.name>guidelineID</Four

```

```

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid93" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute

```

```

xmi.id="txmiid95.a">

  <Foundation.Core.ModelElement.name>patientID</Found:

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
<Foundation.Core.Feature.ownerScope
xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

```

```

    </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid96.a">

    <Foundation.Core.ModelElement.name>serverport</Found

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid93" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

```

```

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid97.a">

  <Foundation.Core.ModelElement.name>primaryclient</Fo

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid98" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c
        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid99.a">

    <Foundation.Core.ModelElement.name>currentstate</Fou

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid9a" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>

```

```

-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid9b.a">

    <Foundation.Core.ModelElement.name>trace</Foundation.

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid9c" />

```

```

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>
      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid9d.a">

  <Foundation.Core.ModelElement.name>clientdaemon</Fo

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>
      <Foundation.Data_Types.Expression.language />
      <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>
  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>

```



```

    <Foundation.Core.DataType
      xmi.idref="txmiid9e" />
  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid9f.a">

    <Foundation.Core.ModelElement.name>connected</Founc

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body>false</Foun

      </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid98" />

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiida0.a">

    <Foundation.Core.ModelElement.name>serverfile</Founda

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

</Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiida1" />

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiida2.a">

    <Foundation.Core.ModelElement.name>logfile</Foundation

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiida1" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiida3.a">

        <Foundation.Core.ModelElement.name>clientUI Agent</Fc

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>

```

```

-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body>null</Found

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiida4" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Operation
  xmi.id="txmiid82.O">

    <Foundation.Core.ModelElement.name>GEEClient</Found:

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic

```

```

xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.BehavioralFeature.raisedException>

    <Behavioral_Elements.Common_Behavior.Exception
    xmi.idref="txmiid82.Ex_IOException" />

</Foundation.Core.BehavioralFeature.raisedException>
-
<Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c
        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>

    <Foundation.Core.BehavioralFeature.parameter />
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid83.O">

    <Foundation.Core.ModelElement.name>createGEEClientH:

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency

```

```

xmi.value="sequential" />
-
<Foundation.Core.BehavioralFeature.raisedException>

  <Behavioral_Elements.Common_Behavior.Exception
xmi.idref="txmiid83.Ex_IOException" />

</Foundation.Core.BehavioralFeature.raisedException>
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c
    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid83.Return">

    <Foundation.Core.ModelElement.name>createGEEClient
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />
      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-

```

```

        <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid98" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid81.O">

    <Foundation.Core.ModelElement.name>deleteGEEClientH

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.BehavioralFeature.raisedException>

        <Behavioral_Elements.Common_Behavior.Exception
xmi.idref="txmiid81.Ex_IOException" />

    </Foundation.Core.BehavioralFeature.raisedException>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

```



```

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid81.Return">

        <Foundation.Core.ModelElement.name>deleteGEEClie

        <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
        xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
            xmi.idref="txmiid98" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid84.O">

        <Foundation.Core.ModelElement.name>selectGuidelinePa

        <Foundation.Core.ModelElement.visibility

```

```

    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
  xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
  xmi.value="false" />

<Foundation.Core.Operation.concurrency
  xmi.value="sequential" />
-
  <Foundation.Core.BehavioralFeature.raisedException>

    <Behavioral_Elements.Common_Behavior.Exception
      xmi.idref="txmiid84.Ex_IOException" />

  </Foundation.Core.BehavioralFeature.raisedException>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid84.Return">

    <Foundation.Core.ModelElement.name>selectGuidelin

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-

```

```

    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid98" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid84.1">

    <Foundation.Core.ModelElement.name>guidelineID</

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid84.2">

    <Foundation.Core.ModelElement.name>patientID</Fo

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

-
    <Foundation.Core.Parameter.defaultValue>

-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />

-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiida5.O">

    <Foundation.Core.ModelElement.name>browsePatients</

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

```

```

<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
  xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
  xmi.value="false" />

<Foundation.Core.Operation.concurrency
  xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>
      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value
      </Foundation.Extension_Mechanisms.TaggedValue>
    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiida5.Return">

    <Foundation.Core.ModelElement.name>browsePatient
    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>
        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
      </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiida7.O">

    <Foundation.Core.ModelElement.name>browsePatients</

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

```

```

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiida7.Return">

      <Foundation.Core.ModelElement.name>browsePatient

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiida7.1">

      <Foundation.Core.ModelElement.name>GLID</Founda

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiida8.O">

    <Foundation.Core.ModelElement.name>browseGuidelines

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-

```



```

<Foundation.Extension_Mechanisms.TaggedValue>

  <Foundation.Extension_Mechanisms.TaggedValue.tag>c

  <Foundation.Extension_Mechanisms.TaggedValue.value

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiida8.Return">

    <Foundation.Core.ModelElement.name>browseGuideli

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation

```

```

xmi.id="txmiida9.O">

  <Foundation.Core.ModelElement.name>browseGuidelines

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

  <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiida9.Return">

    <Foundation.Core.ModelElement.name>browseGuideli

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiida9.1">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

```

```

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidaa.O">

        <Foundation.Core.ModelElement.name>startGuidelineExe

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />
        <Foundation.Core.Feature.ownerScope
            xmi.value="instance" />

        <Foundation.Core.BehavioralFeature.isQuery
            xmi.value="false" />

        <Foundation.Core.Operation.specification />

        <Foundation.Core.Operation.isPolymorphic
            xmi.value="false" />

        <Foundation.Core.Operation.concurrency
            xmi.value="sequential" />
-
        <Foundation.Core.ModelElement.taggedValue>
-
            <Foundation.Extension_Mechanisms.TaggedValue>

                <Foundation.Extension_Mechanisms.TaggedValue.tag>c

                <Foundation.Extension_Mechanisms.TaggedValue.value

            </Foundation.Extension_Mechanisms.TaggedValue>

        </Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
            xmi.id="txmiidaa.Return">

                <Foundation.Core.ModelElement.name>startGuideline

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidaa.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidaa.2">

        <Foundation.Core.ModelElement.name>GLID</Foundati

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidaa.3">

        <Foundation.Core.ModelElement.name>PID</Foundatic

```

```

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidab.O">

    <Foundation.Core.ModelElement.name>stopGuidelineExe

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

```

```

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidab.Return">

        <Foundation.Core.ModelElement.name>stopGuideline1

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiida6" />

```



```

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidab.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidab.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidab.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

```

```

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidac.O">

        <Foundation.Core.ModelElement.name>notifyPrimaryClien

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />
        <Foundation.Core.Feature.ownerScope
            xmi.value="instance" />

        <Foundation.Core.BehavioralFeature.isQuery
            xmi.value="false" />

        <Foundation.Core.Operation.specification />

        <Foundation.Core.Operation.isPolymorphic
            xmi.value="false" />

        <Foundation.Core.Operation.concurrency
            xmi.value="sequential" />
-
        <Foundation.Core.ModelElement.taggedValue>
-
            <Foundation.Extension_Mechanisms.TaggedValue>

                <Foundation.Extension_Mechanisms.TaggedValue.tag>c

                <Foundation.Extension_Mechanisms.TaggedValue.value

            </Foundation.Extension_Mechanisms.TaggedValue>

        </Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
            xmi.id="txmiidac.Return">

                <Foundation.Core.ModelElement.name>notifyPrimaryClien

                <Foundation.Core.ModelElement.visibility

```

```

        xmi.value="private" />
      -
      <Foundation.Core.Parameter.defaultValue>
      -
      <Foundation.Data_Types.Expression>
        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
      </Foundation.Data_Types.Expression>
    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="return" />
  -
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiidad.O">

    <Foundation.Core.ModelElement.name>getCurrentStep</

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
  xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
  xmi.value="false" />

```

```

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidad.Return">

        <Foundation.Core.ModelElement.name>getCurrentSte

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiidae" />

        </Foundation.Core.Parameter.type>

```

```

</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidad.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidad.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidad.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>

```

```

</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid85.O">

    <Foundation.Core.ModelElement.name>setCurrentStep</I

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Core.BehavioralFeature.parameter>
  - <Foundation.Core.Parameter
      xmi.id="txmiid85.Return">

        <Foundation.Core.ModelElement.name>setCurrentSte|

        <Foundation.Core.ModelElement.visibility
          xmi.value="private" />

```



```

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid85.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />

```

```

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid85.2">

  <Foundation.Core.ModelElement.name>GLID</Foundati

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid85.3">

  <Foundation.Core.ModelElement.name>PID</Foundati

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

```

```

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid85.4">

  <Foundation.Core.ModelElement.name>GS</Foundation

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />

```

```

-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidaf.O">

    <Foundation.Core.ModelElement.name>getTrace</Founda

    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
        xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
        xmi.value="false" />

    <Foundation.Core.Operation.concurrency
        xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>

```

```

- <Foundation.Core.Parameter
  xmi.id="txmiidaf.Return">

  <Foundation.Core.ModelElement.name>getTrace.Retu

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
  <Foundation.Data_Types.Expression>

  <Foundation.Data_Types.Expression.language />

  <Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
  xmi.idref="txmiidb0" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidaf.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
  <Foundation.Data_Types.Expression>

  <Foundation.Data_Types.Expression.language />

  <Foundation.Data_Types.Expression.body />

```

```

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidaf.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

```

```

- <Foundation.Core.Parameter
  xmi.id="txmiidaf.3">

  <Foundation.Core.ModelElement.name>PID</Foundati

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiidb1.0">

  <Foundation.Core.ModelElement.name>setTrace</Foundati

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

```

```

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c
    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidb1.Return">

    <Foundation.Core.ModelElement.name>setTrace.Retui

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-

```



```

    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidb1.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
        xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidb1.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-

```

```

    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidb1.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-

```

```

    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidb1.4">

    <Foundation.Core.ModelElement.name>GS</Foundation

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid86.O">

    <Foundation.Core.ModelElement.name>acceptActionReco

```

```

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid86.Return">

    <Foundation.Core.ModelElement.name>acceptActionR

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

```

```

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="return" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiida6" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid86.1">

<Foundation.Core.ModelElement.name>GEECID</Foun

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>

<Foundation.Data_Types.Expression.language />

<Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter

```

```

xmi.id="txmiid86.2">

  <Foundation.Core.ModelElement.name>GLID</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid86.3">

  <Foundation.Core.ModelElement.name>PID</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid86.4">

    <Foundation.Core.ModelElement.name>AS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb2" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

```

```

    </Foundation.Core.BehavioralFeature.parameter>
  </Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid87.O">

    <Foundation.Core.ModelElement.name>refuseActionReco

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

      </Foundation.Extension_Mechanisms.TaggedValue>
    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid87.Return">

    <Foundation.Core.ModelElement.name>refuseActionR

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>

```



```

-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid87.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid87.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid87.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>

```

```

-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid87.4">

    <Foundation.Core.ModelElement.name>AS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiidb2" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid88.O">

    <Foundation.Core.ModelElement.name>completeAction</

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid88.Return">

```

```

<Foundation.Core.ModelElement.name>completeActio

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid88.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid88.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid88.3">

```

```

    <Foundation.Core.ModelElement.name>PID</Foundati
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid88.4">

    <Foundation.Core.ModelElement.name>AS</Foundati
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiidb2" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid89.O">

<Foundation.Core.ModelElement.name>acceptDecision</f

<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
<Foundation.Extension_Mechanisms.TaggedValue>

<Foundation.Extension_Mechanisms.TaggedValue.tag>c

<Foundation.Extension_Mechanisms.TaggedValue.value

```



```

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid89.Return">

      <Foundation.Core.ModelElement.name>acceptDecision

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid89.1">

      <Foundation.Core.ModelElement.name>GEECID</Foun

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-

```

```

    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid89.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid89.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid89.4">

    <Foundation.Core.ModelElement.name>CS</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-

```

```

        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb3" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid7b.O">

    <Foundation.Core.ModelElement.name>refuseDecision</F

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>

```

```

-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid7b.Return">

    <Foundation.Core.ModelElement.name>refuseDecisior

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid7b.1">

```

```

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7b.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7b.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7b.4">

```

```

    <Foundation.Core.ModelElement.name>CS</Foundator
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb3" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid7c.O">

    <Foundation.Core.ModelElement.name>getOptions</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

```



```

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid7c.Return">

    <Foundation.Core.ModelElement.name>getOptions.Re

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType

```

```

xmi.idref="txmiida6" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid7c.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>

-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid7c.2">

  <Foundation.Core.ModelElement.name>GLID</Founda

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>

-
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7c.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType

```

```

        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid7c.4">

    <Foundation.Core.ModelElement.name>DS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb4" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid7d.0">

    <Foundation.Core.ModelElement.name>selectOption</Fou

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope

```

```

xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid7d.Return">

    <Foundation.Core.ModelElement.name>selectOption.F

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7d.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7d.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7d.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7d.4">

        <Foundation.Core.ModelElement.name>DS</Foundation

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiidb4" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7d.5">

        <Foundation.Core.ModelElement.name>DO</Foundatio

```



```

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiidb5" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid7e.O">

    <Foundation.Core.ModelElement.name>getBranches</Fou

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic

```

```

xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid7e.Return">

    <Foundation.Core.ModelElement.name>getBranches.R

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

      <Foundation.Core.DataType
xmi.idref="txmiidb0" />

```

```

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid7e.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid7e.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7e.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

```

```

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid7e.4">

        <Foundation.Core.ModelElement.name>BS</Foundation

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
            xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
                xmi.idref="txmiidb6" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid7f.0">

        <Foundation.Core.ModelElement.name>selectBranch</Fou

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

```

```

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c
    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>
</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid7f.Return">

    <Foundation.Core.ModelElement.name>selectBranch.f
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7f.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7f.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7f.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```



```

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7f.4">

    <Foundation.Core.ModelElement.name>BS</Foundatio

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7f.5">

    <Foundation.Core.ModelElement.name>GS</Foundatio

```

```

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid80.O">

    <Foundation.Core.ModelElement.name>continueSynchr

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

```

```

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>
    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid80.Return">

        <Foundation.Core.ModelElement.name>continueSynch
        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>
        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid98" />

```

```

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid80.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid80.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid80.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

```

```

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid80.4">

        <Foundation.Core.ModelElement.name>SS</Foundation

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
            xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
                xmi.idref="txmiidb7" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidb8.0">

        <Foundation.Core.ModelElement.name>getClientdaemon<

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

```

```

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidb8.Return">

    <Foundation.Core.ModelElement.name>getClientdaerr

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind

```

```

xmi.value="return" />
-
<Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiid9e" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidb9.O">

    <Foundation.Core.ModelElement.name>setClientdaemon<

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

            </Foundation.Extension_Mechanisms.TaggedValue>

        </Foundation.Core.ModelElement.taggedValue>
-

```



```

    <Foundation.Core.BehavioralFeature.parameter>
-   <Foundation.Core.Parameter
        xmi.id="txmiidb9.Return">

        <Foundation.Core.ModelElement.name>setClientdaem

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
            xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
                xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
-   <Foundation.Core.Parameter
        xmi.id="txmiidb9.1">

        <Foundation.Core.ModelElement.name>clientdaemon<

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid9e" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidba.O">

    <Foundation.Core.ModelElement.name>isConnected</Fou

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidba.Return">

        <Foundation.Core.ModelElement.name>isConnected.R

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid98" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidbb.O">

        <Foundation.Core.ModelElement.name>setConnected</Fc

```

```

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Core.BehavioralFeature.parameter>
  - <Foundation.Core.Parameter
    xmi.id="txmiidbb.Return">

      <Foundation.Core.ModelElement.name>setConnected.

      <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    -
      <Foundation.Core.Parameter.defaultValue>
    -
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

```

```

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="return" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiida6" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidbb.1">

<Foundation.Core.ModelElement.name>connected</Fo

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>

<Foundation.Data_Types.Expression.language />

<Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid98" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

```

```

    </Foundation.Core.BehavioralFeature.parameter>
  </Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiidbc.O">

    <Foundation.Core.ModelElement.name>getservername</I

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
  - <Foundation.Core.Parameter
      xmi.id="txmiidbc.Return">

    <Foundation.Core.ModelElement.name>getservernam

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  -

```

```

    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid91" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidbd.O">

    <Foundation.Core.ModelElement.name>getserverport</Fo

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />

```

```

-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidbd.Return">

      <Foundation.Core.ModelElement.name>getserverport.

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

```



```

    </Foundation.Core.BehavioralFeature.parameter>
  </Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiidbe.O">

    <Foundation.Core.ModelElement.name>getClientID</Foun

    <Foundation.Core.ModelElement.visibility
  xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
  xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
  xmi.value="false" />

    <Foundation.Core.Operation.concurrency
  xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidbe.Return">

    <Foundation.Core.ModelElement.name>getClientID.Re

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>

```

```

-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidbf.O">

    <Foundation.Core.ModelElement.name>getpatientID</Fou

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-

```

```

    <Foundation.Core.ModelElement.taggedValue>
    -
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
    -
        <Foundation.Core.BehavioralFeature.parameter>
    - <Foundation.Core.Parameter
        xmi.id="txmiidbf.Return">

            <Foundation.Core.ModelElement.name>getpatientID.f

            <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
        -
            <Foundation.Core.Parameter.defaultValue>
        -
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
        xmi.value="return" />
    -
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
            xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>

```

```

</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiidc0.O">

    <Foundation.Core.ModelElement.name>getguidelineID</f

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Core.BehavioralFeature.parameter>
  - <Foundation.Core.Parameter
      xmi.id="txmiidc0.Return">

        <Foundation.Core.ModelElement.name>getguidelineI

        <Foundation.Core.ModelElement.visibility
          xmi.value="private" />
      -
        <Foundation.Core.Parameter.defaultValue>
      -

```

```

        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidc1.O">

    <Foundation.Core.ModelElement.name>isprimaryclient</I

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>

```

```

-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidc1.Return">

    <Foundation.Core.ModelElement.name>isprimaryclien

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid98" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>

```

```

- <Foundation.Core.Operation
  xmi.id="txmiidc2.O">

  <Foundation.Core.ModelElement.name>setservername</f

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidc2.Return">

    <Foundation.Core.ModelElement.name>setservername

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidc2.1">

    <Foundation.Core.ModelElement.name>servername</

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType

```



```

        xmi.idref="txmiid91" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidc3.O">

        <Foundation.Core.ModelElement.name>setserverport</Fc

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

        <Foundation.Core.BehavioralFeature.isQuery
            xmi.value="false" />

        <Foundation.Core.Operation.specification />

        <Foundation.Core.Operation.isPolymorphic
            xmi.value="false" />

        <Foundation.Core.Operation.concurrency
            xmi.value="sequential" />
-
        <Foundation.Core.ModelElement.taggedValue>
-
            <Foundation.Extension_Mechanisms.TaggedValue>

                <Foundation.Extension_Mechanisms.TaggedValue.tag>c

                <Foundation.Extension_Mechanisms.TaggedValue.value

            </Foundation.Extension_Mechanisms.TaggedValue>

        </Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
            xmi.id="txmiidc3.Return">

            <Foundation.Core.ModelElement.name>setserverport.

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidc3.1">

    <Foundation.Core.ModelElement.name>serverport</Fo

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidc4.O">

    <Foundation.Core.ModelElement.name>setserverfile</Fou

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

```

```

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidc4.Return">

      <Foundation.Core.ModelElement.name>setserverfile.R

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidc4.1">

      <Foundation.Core.ModelElement.name>serverfile</Foi

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida1" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidc5.O">

    <Foundation.Core.ModelElement.name>setlogfile</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c
        <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>
</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidc5.Return">

        <Foundation.Core.ModelElement.name>setlogfile.Retu

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidc5.1">

        <Foundation.Core.ModelElement.name>logfile</Found.

```

```

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida1" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidc6.O">

    <Foundation.Core.ModelElement.name>getserverfile</Fou

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

```

```

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidc6.Return">

        <Foundation.Core.ModelElement.name>getserverfile.F

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiida1" />

```



```

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidc7.O">

        <Foundation.Core.ModelElement.name>getlogfile</Founda

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />
        <Foundation.Core.Feature.ownerScope
            xmi.value="instance" />

        <Foundation.Core.BehavioralFeature.isQuery
            xmi.value="false" />

        <Foundation.Core.Operation.specification />

        <Foundation.Core.Operation.isPolymorphic
            xmi.value="false" />

        <Foundation.Core.Operation.concurrency
            xmi.value="sequential" />
-
        <Foundation.Core.ModelElement.taggedValue>
-
            <Foundation.Extension_Mechanisms.TaggedValue>

                <Foundation.Extension_Mechanisms.TaggedValue.tag>c

                <Foundation.Extension_Mechanisms.TaggedValue.value

            </Foundation.Extension_Mechanisms.TaggedValue>

        </Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
            xmi.id="txmiidc7.Return">

                <Foundation.Core.ModelElement.name>getlogfile.Retu

                <Foundation.Core.ModelElement.visibility

```

```

xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>

<Foundation.Data_Types.Expression.language />

<Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="return" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiida1" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidc8.O">

<Foundation.Core.ModelElement.name>setClientUIAgent<

<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

```

```

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidc8.Return">

        <Foundation.Core.ModelElement.name>setClientUIAg

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>

```

```

</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidc8.1">

    <Foundation.Core.ModelElement.name>clientUIAgent

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiida4" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
-
  <Behavioral_Elements.Common_Behavior.Exception
  xmi.id="txmiid82.Ex_IOException">

    <Foundation.Core.ModelElement.name>IOException</Founda
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />

```

```

<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
-
  <Behavioral_Elements.Common_Behavior.Exception.context>
  <Foundation.Core.Operation
    xmi.idref="txmiid82.O" />

</Behavioral_Elements.Common_Behavior.Exception.context>

</Behavioral_Elements.Common_Behavior.Exception>
-
  <Behavioral_Elements.Common_Behavior.Exception
    xmi.id="txmiid83.Ex_IOException">

    <Foundation.Core.ModelElement.name>IOException</Founda
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
-
    <Behavioral_Elements.Common_Behavior.Exception.context>
    <Foundation.Core.Operation
      xmi.idref="txmiid83.O" />

</Behavioral_Elements.Common_Behavior.Exception.context>

</Behavioral_Elements.Common_Behavior.Exception>
-
  <Behavioral_Elements.Common_Behavior.Exception
    xmi.id="txmiid81.Ex_IOException">

    <Foundation.Core.ModelElement.name>IOException</Founda
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf

```

```

xmi.value="false" />

<Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
-
<Behavioral_Elements.Common_Behavior.Exception.context>
<Foundation.Core.Operation
  xmi.idref="txmiid81.O" />

</Behavioral_Elements.Common_Behavior.Exception.context>

</Behavioral_Elements.Common_Behavior.Exception>
-
<Behavioral_Elements.Common_Behavior.Exception
xmi.id="txmiid84.Ex_IOException">

  <Foundation.Core.ModelElement.name>IOException</Founda
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
-
  <Behavioral_Elements.Common_Behavior.Exception.context>
  <Foundation.Core.Operation
    xmi.idref="txmiid84.O" />

  </Behavioral_Elements.Common_Behavior.Exception.context>

</Behavioral_Elements.Common_Behavior.Exception>
- <Foundation.Core.Association
  xmi.id="txmiid8f.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract

```

```

    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid8f.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity>1</Foundatio

    <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid4e" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid8f.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered

```

```

xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity>1</Foundatio

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiidc9" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GEEClient.GEEClientGuidelineExecutorUserFunction:
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid4e" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Interface
    xmi.idref="txmiidca" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiidc9">

  <Foundation.Core.ModelElement.name>GEEClientDaemon</F
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf

```



```

xmi.value="false" />

<Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
<Foundation.Core.Class.isActive
xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid8" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEClient.GEEClientDaemonServerSocket.G" /

</Foundation.Core.GeneralizableElement.generalization>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEClient.GEEClientDaemonRunnable.G" />

</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiidcb.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiidcc.a">

    <Foundation.Core.ModelElement.name>client</Foundation

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

```

```

<Foundation.Core.Feature.ownerScope
  xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four

<Foundation.Core.StructuralFeature.changeable
  xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
  xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiidcd" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiidce.a">

  <Foundation.Core.ModelElement.name>clientdaemonthre

```

```

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body>null</Found

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiidcf" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute

```

```

xmi.id="txmiidd0.a">

  <Foundation.Core.ModelElement.name>stop</Foundation.C

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
<Foundation.Core.Feature.ownerScope
xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body>false</Foun

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
xmi.idref="txmiid98" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

```

```

    </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
- <Foundation.Core.Operation
  xmi.id="txmiidd1.0">

    <Foundation.Core.ModelElement.name>GEEClientDaemon

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
  -
    <Foundation.Core.BehavioralFeature.raisedException>

      <Behavioral_Elements.Common_Behavior.Exception
        xmi.idref="txmiidd1.Ex_IOException" />

    </Foundation.Core.BehavioralFeature.raisedException>
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Core.BehavioralFeature.parameter>
  - <Foundation.Core.Parameter
      xmi.id="txmiidd1.1">

```

```

    <Foundation.Core.ModelElement.name>client</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidcd" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidd2.O">

    <Foundation.Core.ModelElement.name>run</Foundation.C

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

```

```

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidd2.Return">

        <Foundation.Core.ModelElement.name>run.Return</F

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidd3.O">

    <Foundation.Core.ModelElement.name>startDaemon</Foi

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
    <Foundation.Core.BehavioralFeature.raisedException>

        <Behavioral_Elements.Common_Behavior.Exception
        xmi.idref="txmiidd3.Ex_IOException" />

    </Foundation.Core.BehavioralFeature.raisedException>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

```



```

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidd3.Return">

    <Foundation.Core.ModelElement.name>startDaemon.I

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiidd4.O">

  <Foundation.Core.ModelElement.name>stopDaemon</Fou

  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.Feature.ownerScope

```

```

xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.BehavioralFeature.raisedException>

    <Behavioral_Elements.Common_Behavior.Exception
    xmi.idref="txmiidd4.Ex_IOException" />

</Foundation.Core.BehavioralFeature.raisedException>
-
<Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c
        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidd4.Return">

        <Foundation.Core.ModelElement.name>stopDaemon.F

        <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
-
    <Behavioral_Elements.Common_Behavior.Exception
xmi.id="txmiidd1.Ex_IOException">

        <Foundation.Core.ModelElement.name>IOException</Founda
<Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
-
    <Behavioral_Elements.Common_Behavior.Exception.context>
    <Foundation.Core.Operation
xmi.idref="txmiidd1.O" />

    </Behavioral_Elements.Common_Behavior.Exception.context>

</Behavioral_Elements.Common_Behavior.Exception>

```

```

-
<Behavioral_Elements.Common_Behavior.Exception
xmi.id="txmiidd3.Ex_IOException">

  <Foundation.Core.ModelElement.name>IOException</Founda
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
-
  <Behavioral_Elements.Common_Behavior.Exception.context>
  <Foundation.Core.Operation
    xmi.idref="txmiidd3.O" />

</Behavioral_Elements.Common_Behavior.Exception.context>

</Behavioral_Elements.Common_Behavior.Exception>
-
<Behavioral_Elements.Common_Behavior.Exception
xmi.id="txmiidd4.Ex_IOException">

  <Foundation.Core.ModelElement.name>IOException</Founda
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
-
  <Behavioral_Elements.Common_Behavior.Exception.context>
  <Foundation.Core.Operation
    xmi.idref="txmiidd4.O" />

</Behavioral_Elements.Common_Behavior.Exception.context>

</Behavioral_Elements.Common_Behavior.Exception>
- <Foundation.Core.Association

```

```

xmi.id="txmiidcb.ASS">
<Foundation.Core.ModelElement.name />
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiidcb.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity>1</Foundatio

    <Foundation.Core.AssociationEnd.changeable
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
      xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiidc9" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiidcb.SE">

```

```

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity>1</Foundatio

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid4e" />

        </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
    xmi.id="GEEClient.GEEClientDaemonServerSocket.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiidc9" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiidd5" />

```

```

    </Foundation.Core.Generalization.supertype>
  </Foundation.Core.Generalization>
- <Foundation.Core.Generalization
  xmi.id="GEEClient.GEEClientDaemonRunnable.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiidc9" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Interface
    xmi.idref="txmiidd6" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiidd7">

  <Foundation.Core.ModelElement.name>GEEClientSideSession
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid8" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEClient.GEEClientSideSessionThread.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiidd8.CE" />

```

```

</Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiidd9.a">

  <Foundation.Core.ModelElement.name>client</Foundation

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.Feature.ownerScope
  xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
  xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
  xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType

```



```

        xmi.idref="txmiidcd" />
    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiidda.a">

        <Foundation.Core.ModelElement.name>s</Foundation.Core

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>

```

```

-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiiddb" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiiddc.a">

  <Foundation.Core.ModelElement.name>endSession</Four

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

</Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid98" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Operation
  xmi.id="txmiiddd.O">

    <Foundation.Core.ModelElement.name>GEEClientSideSes:

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-

```

```

<Foundation.Extension_Mechanisms.TaggedValue>

  <Foundation.Extension_Mechanisms.TaggedValue.tag>c

  <Foundation.Extension_Mechanisms.TaggedValue.value

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidd.1">

    <Foundation.Core.ModelElement.name>s</Foundation.

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  -
    <Foundation.Core.Parameter.defaultValue>
  -
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiiddb" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidd.2">

    <Foundation.Core.ModelElement.name>client</Founda

```

```

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiidcd" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidde.O">

    <Foundation.Core.ModelElement.name>run</Foundation.C

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic

```

```

xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidde.Return">

    <Foundation.Core.ModelElement.name>run.Return</F

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiida6" />

```

```

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiiddf.O">

    <Foundation.Core.ModelElement.name>processInput</Fo

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiiddf.Return">

    <Foundation.Core.ModelElement.name>processInput.|

```

```

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid91" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiiddf.1">

    <Foundation.Core.ModelElement.name>inputLine</Fou

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```



```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid91" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
xmi.id="txmiidd8.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
xmi.id="txmiidd8.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

```

```

<Foundation.Core.AssociationEnd.multiplicity>0..*</Founda
<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiidd7" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiidd8.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity>1</Foundatio
  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid4e" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>

```

```

        </Foundation.Core.Association.connection>
    </Foundation.Core.Association>
- <Foundation.Core.Generalization
    xmi.id="GEEClient.GEEClientSideSessionThread.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiidd7" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiide0" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
</Foundation.Core.Namespace.ownedElement>
</Model_Management.Package>
- <Model_Management.Package xmi.id="txmiida">

    <Foundation.Core.ModelElement.name>GEEClientUserInterface<
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Core.ModelElement.requirement>
    <Foundation.Core.Dependency
        xmi.idref="txmiid9.D" />
    <Foundation.Core.Dependency
        xmi.idref="txmiidb.D" />
    </Foundation.Core.ModelElement.requirement>
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Model
        xmi.idref="txmiid1" />
    </Foundation.Core.ModelElement.namespace>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

```

```

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docume

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>
</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Namespace.ownedElement>
- <Foundation.Core.Class xmi.id="txmiide1">

    <Foundation.Core.ModelElement.name>GEEClientUserInterfa
    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
    <Foundation.Core.Class.isActive
      xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
      xmi.idref="txmiida" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
      xmi.idref="GEEClientUserInterface.GEEClientUserInterfa

    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation

```

```

xmi.id="txmiide2.O">

  <Foundation.Core.ModelElement.name>main</Foundation.

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

  <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
  <Foundation.Core.BehavioralFeature.raisedException>

    <Behavioral_Elements.Common_Behavior.Exception
xmi.idref="txmiide2.Ex_IOException" />

  </Foundation.Core.BehavioralFeature.raisedException>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
xmi.id="txmiide2.Return">

  <Foundation.Core.ModelElement.name>main.Return<,

```

```

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiide2.1">

    <Foundation.Core.ModelElement.name>args</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiide3" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiide4.O">

    <Foundation.Core.ModelElement.name>startClient</Found

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>

```

```

-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiide4.Return">

    <Foundation.Core.ModelElement.name>startClient.Rei

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiide5.O">

  <Foundation.Core.ModelElement.name>stopClient</Found

  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

```



```

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiide5.Return">

    <Foundation.Core.ModelElement.name>stopClient.Ret

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind

```

```

        xmi.value="return" />
    -
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiide6.O">

    <Foundation.Core.ModelElement.name>browsePatients</

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-

```

```

    <Foundation.Core.BehavioralFeature.parameter>
-   <Foundation.Core.Parameter
        xmi.id="txmiide6.Return">

        <Foundation.Core.ModelElement.name>browsePatient</Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-   -
        <Foundation.Core.Parameter.defaultValue>
-   -
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
            xmi.value="return" />
-   -
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
                xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
-   <Foundation.Core.Operation
        xmi.id="txmiide7.O">

        <Foundation.Core.ModelElement.name>browsePatients</Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />
        <Foundation.Core.Feature.ownerScope
            xmi.value="instance" />

        <Foundation.Core.BehavioralFeature.isQuery

```

```

xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiide7.Return">

    <Foundation.Core.ModelElement.name>browsePatientI

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />

```

```

-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiide7.1">

        <Foundation.Core.ModelElement.name>GLID</Founda

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />

-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
        xmi.value="inout" />

-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiide8.0">

        <Foundation.Core.ModelElement.name>browseGuidelines

```

```

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiide8.Return">

    <Foundation.Core.ModelElement.name>browseGuideli

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="return" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiida6" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiide9.O">

<Foundation.Core.ModelElement.name>browseGuidelines

<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
<Foundation.Extension_Mechanisms.TaggedValue>

<Foundation.Extension_Mechanisms.TaggedValue.tag>c

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiide9.Return">

        <Foundation.Core.ModelElement.name>browseGuideli

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiide9.1">

        <Foundation.Core.ModelElement.name>PID</Foundati

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-

```



```

    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidea.O">

    <Foundation.Core.ModelElement.name>startGuidelineExe

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />

```

```

-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidea.Return">

      <Foundation.Core.ModelElement.name>startGuideline

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter

```

```

xmi.id="txmiidea.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidea.2">

  <Foundation.Core.ModelElement.name>GLID</Founda

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidea.3">

<Foundation.Core.ModelElement.name>PID</Foundati

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>

<Foundation.Data_Types.Expression.language />

<Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

```

```

    </Foundation.Core.BehavioralFeature.parameter>
  </Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiideb.O">

    <Foundation.Core.ModelElement.name>stopGuidelineExe

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

      </Foundation.Extension_Mechanisms.TaggedValue>
    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiideb.Return">

    <Foundation.Core.ModelElement.name>stopGuidelineI

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>

```

```

-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiideb.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiideb.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiideb.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>

```

```

-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidec.O">

    <Foundation.Core.ModelElement.name>getCurrentStep</

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-

```



```

    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidec.Return">

        <Foundation.Core.ModelElement.name>getCurrentSte

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiidae" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidec.1">

```

```

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidec.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidec.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>

```

```

</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiided.O">

    <Foundation.Core.ModelElement.name>setCurrentStep</I

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Core.BehavioralFeature.parameter>
  - <Foundation.Core.Parameter
      xmi.id="txmiided.Return">

        <Foundation.Core.ModelElement.name>setCurrentSte|

        <Foundation.Core.ModelElement.visibility
          xmi.value="private" />
      -
        <Foundation.Core.Parameter.defaultValue>
      -

```

```

    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiided.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiided.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiided.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-

```

```

    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiided.4">

    <Foundation.Core.ModelElement.name>GS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidee.O">

    <Foundation.Core.ModelElement.name>getTrace</Founda

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidee.Return">

```



```

    <Foundation.Core.ModelElement.name>getTrace.Retu
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb0" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidee.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidee.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidee.3">

```

```

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidef.O">

    <Foundation.Core.ModelElement.name>setTrace</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

```

```

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidef.Return">

    <Foundation.Core.ModelElement.name>setTrace.Retui

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType

```

```

xmi.idref="txmiida6" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidef.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>

-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />

-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidef.2">

  <Foundation.Core.ModelElement.name>GLID</Founda

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>

-
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiiddef.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType

```

```

        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidef.4">

    <Foundation.Core.ModelElement.name>GS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidf0.0">

    <Foundation.Core.ModelElement.name>acceptActionReco

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope

```

```

xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf0.Return">

    <Foundation.Core.ModelElement.name>acceptActionR

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

```



```

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf0.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf0.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf0.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf0.4">

        <Foundation.Core.ModelElement.name>AS</Foundation

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiidb2" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation

```

```

xmi.id="txmiidf1.O">

  <Foundation.Core.ModelElement.name>refuseActionReco

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

  <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf1.Return">

    <Foundation.Core.ModelElement.name>refuseActionR

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf1.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

```

```

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf1.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf1.3">

    <Foundation.Core.ModelElement.name>PID</Foundatic

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf1.4">

    <Foundation.Core.ModelElement.name>AS</Foundator

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb2" />

```

```

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidf2.O">

    <Foundation.Core.ModelElement.name>completeAction</

    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
        xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
        xmi.value="false" />

    <Foundation.Core.Operation.concurrency
        xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidf2.Return">

    <Foundation.Core.ModelElement.name>completeActio

```



```

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf2.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf2.2">

        <Foundation.Core.ModelElement.name>GLID</Foundati

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf2.3">

        <Foundation.Core.ModelElement.name>PID</Foundatic

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf2.4">

    <Foundation.Core.ModelElement.name>AS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb2" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidf3.O">

    <Foundation.Core.ModelElement.name>acceptDecision</f

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>

```

```

-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf3.Return">

    <Foundation.Core.ModelElement.name>acceptDecision

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf3.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf3.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

```

```

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf3.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf3.4">

    <Foundation.Core.ModelElement.name>CS</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiidb3" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidf4.O">

    <Foundation.Core.ModelElement.name>refuseDecision</F

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

```



```

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c
        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidf4.Return">

        <Foundation.Core.ModelElement.name>refuseDecisior

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf4.1">

        <Foundation.Core.ModelElement.name>GEECID</Foun

        <Foundation.Core.ModelElement.visibility

```

```

xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>
    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>
</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf4.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>
    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>
</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind

```

```

xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf4.3">

<Foundation.Core.ModelElement.name>PID</Foundati

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>

<Foundation.Data_Types.Expression.language />

<Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf4.4">

<Foundation.Core.ModelElement.name>CS</Foundati

<Foundation.Core.ModelElement.visibility

```

```

        xmi.value="private" />
    -
    <Foundation.Core.Parameter.defaultValue>
    -
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
    -
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiidb3" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiidf5.O">

    <Foundation.Core.ModelElement.name>getOptions</Foun

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

```

```

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidf5.Return">

        <Foundation.Core.ModelElement.name>getOptions.Re

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>

```

```

</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf5.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf5.2">

  <Foundation.Core.ModelElement.name>GLID</Founda

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf5.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>

```

```

</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf5.4">

  <Foundation.Core.ModelElement.name>DS</Foundation

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
    xmi.idref="txmiidb4" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiidf6.0">

  <Foundation.Core.ModelElement.name>selectOption</Fou

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery

```



```

xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf6.Return">

    <Foundation.Core.ModelElement.name>selectOption.F

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />

```

```

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf6.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="inout" />

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf6.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

```

```

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf6.3">

  <Foundation.Core.ModelElement.name>PID</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />

```

```

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf6.4">

  <Foundation.Core.ModelElement.name>DS</Foundation

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiidb4" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf6.5">

  <Foundation.Core.ModelElement.name>DO</Foundatio

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

```

```

-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb5" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidf7.0">

    <Foundation.Core.ModelElement.name>getBranches</Fou

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency

```

```

xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>
    <Foundation.Extension_Mechanisms.TaggedValue.tag>c
    <Foundation.Extension_Mechanisms.TaggedValue.value
  </Foundation.Extension_Mechanisms.TaggedValue>
</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf7.Return">
    <Foundation.Core.ModelElement.name>getBranches.R
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>
        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
      </Foundation.Data_Types.Expression>
    </Foundation.Core.Parameter.defaultValue>
    <Foundation.Core.Parameter.kind
    xmi.value="return" />
-
    <Foundation.Core.Parameter.type>
      <Foundation.Core.DataType
      xmi.idref="txmiidb0" />
    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>

```

```

- <Foundation.Core.Parameter
  xmi.id="txmiidf7.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
  xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf7.2">

  <Foundation.Core.ModelElement.name>GLID</Founda

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

```

```

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidf7.3">

        <Foundation.Core.ModelElement.name>PID</Foundati

        <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

```



```

- <Foundation.Core.Parameter
  xmi.id="txmiidf7.4">

  <Foundation.Core.ModelElement.name>BS</Foundator

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
  <Foundation.Data_Types.Expression>

  <Foundation.Data_Types.Expression.language />

  <Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
  xmi.idref="txmiidb6" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiidf8.0">

  <Foundation.Core.ModelElement.name>selectBranch</Fou

  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
  xmi.value="false" />

```

```

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiidf8.Return">

    <Foundation.Core.ModelElement.name>selectBranch.f

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-

```

```

    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidf8.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
        xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidf8.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-

```

```

    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf8.3">

  <Foundation.Core.ModelElement.name>PID</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
  <Foundation.Data_Types.Expression>

  <Foundation.Data_Types.Expression.language />

  <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-

```

```

    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidf8.4">

    <Foundation.Core.ModelElement.name>BS</Foundation

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
        xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiidb6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidf8.5">

    <Foundation.Core.ModelElement.name>GS</Foundation

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-

```

```

    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiidf9.O">

    <Foundation.Core.ModelElement.name>continueSynchr
    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />

```

```

-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiidf9.Return">

      <Foundation.Core.ModelElement.name>continueSyncr
      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid98" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter

```

```

xmi.id="txmiidf9.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf9.2">

  <Foundation.Core.ModelElement.name>GLID</Founda

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```



```

    </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiidf9.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter

```

```

xmi.id="txmiidf9.4">

  <Foundation.Core.ModelElement.name>SS</Foundator

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiidb7" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
-
  <Behavioral_Elements.Common_Behavior.Exception
xmi.id="txmiide2.Ex_IOException">

    <Foundation.Core.ModelElement.name>IOException</Founda
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

```

```

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
-
    <Behavioral_Elements.Common_Behavior.Exception.context>
    <Foundation.Core.Operation
        xmi.idref="txmiide2.O" />

    </Behavioral_Elements.Common_Behavior.Exception.context>

    </Behavioral_Elements.Common_Behavior.Exception>
- <Foundation.Core.Generalization
    xmi.id="GEEClientUserInterface.GEEClientUserInterfaceAge
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiide1" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Interface
        xmi.idref="txmiidca" />
    </Foundation.Core.Generalization.supertype>
    </Foundation.Core.Generalization>
    </Foundation.Core.Namespace.ownedElement>
</Model_Management.Package>
- <Model_Management.Package xmi.id="txmiid3">

    <Foundation.Core.ModelElement.name>GEEServer</Foundation.Co
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Core.ModelElement.requirement>
    <Foundation.Core.Dependency
        xmi.idref="txmiid2.D" />
    <Foundation.Core.Dependency
        xmi.idref="txmiid5.D" />

```

```

</Foundation.Core.ModelElement.requirement>
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Model
    xmi.idref="txmiid1" />
  </Foundation.Core.ModelElement.namespace>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docume

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Namespace.ownedElement>
  - <Foundation.Core.Class xmi.id="txmiid3e">

    <Foundation.Core.ModelElement.name>GEEClientHandle</Foi
    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
    <Foundation.Core.Class.isActive
      xmi.value="false" />
  - <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
      xmi.idref="txmiid3" />
    </Foundation.Core.ModelElement.namespace>
  -
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
      xmi.idref="GEEServer.GEEClientHandleGuidelineExecutor

    </Foundation.Core.GeneralizableElement.generalization>
  - <Foundation.Core.ModelElement.taggedValue>
    -
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
    xmi.id="txmiidfa.a">

    <Foundation.Core.ModelElement.name>clientID</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="protected" />
<Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-

```

```

    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiidfb.a">

        <Foundation.Core.ModelElement.name>guidelineID</Four

        <Foundation.Core.ModelElement.visibility
            xmi.value="protected" />
        <Foundation.Core.Feature.ownerScope
            xmi.value="classifier" />

        <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

        <Foundation.Core.StructuralFeature.changeable
            xmi.value="none" />

        <Foundation.Core.StructuralFeature.targetScope
            xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
        <Foundation.Core.StructuralFeature.type>
        <Foundation.Core.DataType
            xmi.idref="txmiid93" />

    </Foundation.Core.StructuralFeature.type>

```

```

- <Foundation.Core.ModelElement.taggedValue>
-   <Foundation.Extension_Mechanisms.TaggedValue>
      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiidfc.a">

    <Foundation.Core.ModelElement.name>patientID</Found:

    <Foundation.Core.ModelElement.visibility
      xmi.value="protected" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-   <Foundation.Core.Attribute.initialValue>
-     <Foundation.Data_Types.Expression>
          <Foundation.Data_Types.Expression.language />
          <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>
    </Foundation.Core.Attribute.initialValue>
-   <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType

```

```

        xmi.idref="txmiid93" />
    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiidfd.a">

        <Foundation.Core.ModelElement.name>primaryclient</Fo

        <Foundation.Core.ModelElement.visibility
            xmi.value="protected" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>

```



```

-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid98" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiidfe.a">

    <Foundation.Core.ModelElement.name>currentstate</Fou

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

</Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid9a" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiidff.a">

    <Foundation.Core.ModelElement.name>trace</Foundation.

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid9c" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid100.a">

        <Foundation.Core.ModelElement.name>clientdaemonnam

        <Foundation.Core.ModelElement.visibility
            xmi.value="protected" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-

```

```

    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid91" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid101.a">

        <Foundation.Core.ModelElement.name>clientdaemonport

        <Foundation.Core.ModelElement.visibility
            xmi.value="protected" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />

```

```

-
  <Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid93" />

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Operation
  xmi.id="txmiid70.O">

    <Foundation.Core.ModelElement.name>GEEClientHandle<

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

```

```

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid70.1">

        <Foundation.Core.ModelElement.name>clientID</Four

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid70.2">

        <Foundation.Core.ModelElement.name>clientdaemonr

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid91" />

        </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid70.3">

        <Foundation.Core.ModelElement.name>clientdaemonr

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-

```

```

        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid102.O">

    <Foundation.Core.ModelElement.name>evaluateCriterion

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>

```



```

-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid102.Return">

    <Foundation.Core.ModelElement.name>evaluateCriter

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid98" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid102.1">

```

```

    <Foundation.Core.ModelElement.name>encoding_lang
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid103" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid102.2">

    <Foundation.Core.ModelElement.name>specification<
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid103" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid104.O">

<Foundation.Core.ModelElement.name>registerEvent</Fo

<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
<Foundation.Extension_Mechanisms.TaggedValue>

<Foundation.Extension_Mechanisms.TaggedValue.tag>c

<Foundation.Extension_Mechanisms.TaggedValue.value

</Foundation.Extension_Mechanisms.TaggedValue>

```

```

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid104.Return">

      <Foundation.Core.ModelElement.name>registerEvent.

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid104.1">

      <Foundation.Core.ModelElement.name>GEECID</Foun

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid104.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType

```

```

xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid104.3">

  <Foundation.Core.ModelElement.name>PID</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>

-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />

-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid104.4">

  <Foundation.Core.ModelElement.name>GS</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>

-
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid104.5">

    <Foundation.Core.ModelElement.name>E</Foundation.

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType

```

```

        xmi.idref="txmiid105" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid106.O">

        <Foundation.Core.ModelElement.name>triggerEvent</Fou

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

        <Foundation.Core.BehavioralFeature.isQuery
            xmi.value="false" />

        <Foundation.Core.Operation.specification />

        <Foundation.Core.Operation.isPolymorphic
            xmi.value="false" />

        <Foundation.Core.Operation.concurrency
            xmi.value="sequential" />
-
        <Foundation.Core.ModelElement.taggedValue>
-
            <Foundation.Extension_Mechanisms.TaggedValue>

                <Foundation.Extension_Mechanisms.TaggedValue.tag>c

                <Foundation.Extension_Mechanisms.TaggedValue.value

            </Foundation.Extension_Mechanisms.TaggedValue>

        </Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
            xmi.id="txmiid106.Return">

                <Foundation.Core.ModelElement.name>triggerEvent.R

```



```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid106.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid106.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid106.3">

    <Foundation.Core.ModelElement.name>PID</Foundatic

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid106.4">

    <Foundation.Core.ModelElement.name>GS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiidae" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid106.5">

        <Foundation.Core.ModelElement.name>E</Foundation.

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid105" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation

```

```

xmi.id="txmiid77.O">

  <Foundation.Core.ModelElement.name>getCurrentStep</

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

  <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid77.Return">

    <Foundation.Core.ModelElement.name>getCurrentSte

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid77.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

```

```

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid77.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid77.3">

    <Foundation.Core.ModelElement.name>PID</Foundatic

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid71.O">

    <Foundation.Core.ModelElement.name>setCurrentStep</I

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

```



```

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c
        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid71.Return">

        <Foundation.Core.ModelElement.name>setCurrentSte|

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid71.1">

        <Foundation.Core.ModelElement.name>GEECID</Foun

```

```

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid71.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid71.3">

        <Foundation.Core.ModelElement.name>PID</Foundati

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid71.4">

        <Foundation.Core.ModelElement.name>GS</Foundati

```

```

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid107.O">

    <Foundation.Core.ModelElement.name>getTrace</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

```

```

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>
    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid107.Return">

        <Foundation.Core.ModelElement.name>getTrace.Retu

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>
        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiidb0" />

```

```

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid107.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid107.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid107.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

```

```

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid76.O">

        <Foundation.Core.ModelElement.name>setTrace</Founda

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />
        <Foundation.Core.Feature.ownerScope
            xmi.value="instance" />

        <Foundation.Core.BehavioralFeature.isQuery
            xmi.value="false" />

        <Foundation.Core.Operation.specification />

        <Foundation.Core.Operation.isPolymorphic
            xmi.value="false" />

        <Foundation.Core.Operation.concurrency
            xmi.value="sequential" />
-
        <Foundation.Core.ModelElement.taggedValue>
-
            <Foundation.Extension_Mechanisms.TaggedValue>

                <Foundation.Extension_Mechanisms.TaggedValue.tag>c

                <Foundation.Extension_Mechanisms.TaggedValue.value

            </Foundation.Extension_Mechanisms.TaggedValue>

        </Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
            xmi.id="txmiid76.Return">

                <Foundation.Core.ModelElement.name>setTrace.Retui

                <Foundation.Core.ModelElement.visibility

```



```

xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>
    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>
</Foundation.Core.Parameter.defaultValue>
    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
<Foundation.Core.Parameter.type>
    <Foundation.Core.DataType
xmi.idref="txmiida6" />
</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid76.1">
    <Foundation.Core.ModelElement.name>GEECID</Foun
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>
    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>
</Foundation.Core.Parameter.defaultValue>
    <Foundation.Core.Parameter.kind

```

```

xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid76.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid76.3">

    <Foundation.Core.ModelElement.name>PID</Foundatic

    <Foundation.Core.ModelElement.visibility

```

```

xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
  <Foundation.Data_Types.Expression>
    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
  </Foundation.Data_Types.Expression>
</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid76.4">

  <Foundation.Core.ModelElement.name>GS</Foundation
  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>
      <Foundation.Data_Types.Expression.language />
      <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>
  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind

```

```

        xmi.value="inout" />
      -
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
          xmi.idref="txmiidae" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid72.O">

  <Foundation.Core.ModelElement.name>acceptActionReco

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
  -
  <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
  -

```

```

    <Foundation.Core.BehavioralFeature.parameter>
-   <Foundation.Core.Parameter
        xmi.id="txmiid72.Return">

        <Foundation.Core.ModelElement.name>acceptActionR

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
            xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
                xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
-   <Foundation.Core.Parameter
        xmi.id="txmiid72.1">

        <Foundation.Core.ModelElement.name>GEECID</Foun

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid72.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>

```

```

</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid72.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid72.4">

    <Foundation.Core.ModelElement.name>AS</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb2" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid73.O">

    <Foundation.Core.ModelElement.name>refuseActionReco

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

```



```

        <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid73.Return">

        <Foundation.Core.ModelElement.name>refuseActionR

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid73.1">

        <Foundation.Core.ModelElement.name>GEECID</Foun

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />

```

```

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid73.2">

  <Foundation.Core.ModelElement.name>GLID</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />

```

```

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid73.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="inout" />

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid73.4">

    <Foundation.Core.ModelElement.name>AS</Foundati

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

```

```

-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb2" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid74.O">

    <Foundation.Core.ModelElement.name>completeAction</

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency

```

```

xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>
    <Foundation.Extension_Mechanisms.TaggedValue.tag>c
    <Foundation.Extension_Mechanisms.TaggedValue.value
  </Foundation.Extension_Mechanisms.TaggedValue>
</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid74.Return">
    <Foundation.Core.ModelElement.name>completeActio
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>
        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
      </Foundation.Data_Types.Expression>
    </Foundation.Core.Parameter.defaultValue>
    <Foundation.Core.Parameter.kind
    xmi.value="return" />
-
    <Foundation.Core.Parameter.type>
      <Foundation.Core.DataType
      xmi.idref="txmiida6" />
    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>

```

```

- <Foundation.Core.Parameter
  xmi.id="txmiid74.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid74.2">

  <Foundation.Core.ModelElement.name>GLID</Founda

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

```

```

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid74.3">

        <Foundation.Core.ModelElement.name>PID</Foundati

        <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

```

```

- <Foundation.Core.Parameter
  xmi.id="txmiid74.4">

  <Foundation.Core.ModelElement.name>AS</Foundation

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
  <Foundation.Data_Types.Expression>

  <Foundation.Data_Types.Expression.language />

  <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
  xmi.idref="txmiidb2" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid75.0">

  <Foundation.Core.ModelElement.name>acceptDecision</f

  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
  xmi.value="false" />

```



```

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid75.Return">

    <Foundation.Core.ModelElement.name>acceptDecision

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-

```

```

    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid75.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
        xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid75.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-

```

```

    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid75.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-

```

```

    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid75.4">

    <Foundation.Core.ModelElement.name>CS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiidb3" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid6a.O">

    <Foundation.Core.ModelElement.name>refuseDecision</F

```

```

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid6a.Return">

    <Foundation.Core.ModelElement.name>refuseDecisior

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

```

```

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6a.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter

```

```

xmi.id="txmiid6a.2">

  <Foundation.Core.ModelElement.name>GLID</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6a.3">

  <Foundation.Core.ModelElement.name>PID</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6a.4">

    <Foundation.Core.ModelElement.name>CS</Foundator

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb3" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

```



```

    </Foundation.Core.BehavioralFeature.parameter>
  </Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid6b.O">

    <Foundation.Core.ModelElement.name>getOptions</Foun

    <Foundation.Core.ModelElement.visibility
  xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
  xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
  xmi.value="false" />

    <Foundation.Core.Operation.concurrency
  xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid6b.Return">

    <Foundation.Core.ModelElement.name>getOptions.Re

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>

```

```

-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6b.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid6b.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid6b.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>

```

```

-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6b.4">

    <Foundation.Core.ModelElement.name>DS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiidb4" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid6c.O">

    <Foundation.Core.ModelElement.name>selectOption</Fou

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid6c.Return">

```

```

<Foundation.Core.ModelElement.name>selectOption.F
<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6c.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6c.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6c.3">

```

```

<Foundation.Core.ModelElement.name>PID</Foundati
<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6c.4">

  <Foundation.Core.ModelElement.name>DS</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

```



```

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb4" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6c.5">

    <Foundation.Core.ModelElement.name>DO</Foundatio

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb5" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>

```

```

</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid6d.O">

  <Foundation.Core.ModelElement.name>getBranches</Fou

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid6d.Return">

    <Foundation.Core.ModelElement.name>getBranches.R

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-

```

```

    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb0" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6d.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6d.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6d.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-

```

```

    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6d.4">

    <Foundation.Core.ModelElement.name>BS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiidb6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid6e.O">

    <Foundation.Core.ModelElement.name>selectBranch</Fou

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid6e.Return">

```

```

    <Foundation.Core.ModelElement.name>selectBranch.f

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6e.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6e.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6e.3">

```



```

    <Foundation.Core.ModelElement.name>PID</Foundati
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid6e.4">

    <Foundation.Core.ModelElement.name>BS</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6e.5">

    <Foundation.Core.ModelElement.name>GS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>

```

```

- <Foundation.Core.Operation
  xmi.id="txmiid6f.O">

  <Foundation.Core.ModelElement.name>continueSynchr

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid6f.Return">

  <Foundation.Core.ModelElement.name>continueSynchr

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid98" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6f.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType

```

```

        xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid6f.2">

        <Foundation.Core.ModelElement.name>GLID</Foundati

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
            xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
                xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid6f.3">

        <Foundation.Core.ModelElement.name>PID</Foundatic

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid6f.4">

    <Foundation.Core.ModelElement.name>SS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType

```

```

        xmi.idref="txmiidb7" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
    </Foundation.Core.Operation>
    </Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GEEServer.GEEClientHandleGuidelineExecutor.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid3e" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Interface
        xmi.idref="txmiid108" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid24">

    <Foundation.Core.ModelElement.name>GEEServer</Foundatio
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid3" />
    </Foundation.Core.ModelElement.namespace>
- <Foundation.Core.Classifier.associationEnd>

```

```

    <Foundation.Core.AssociationEnd
      xmi.idref="txmiid109.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid10a.a">

  <Foundation.Core.ModelElement.name>guidelines</Found

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-

```



```

    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid10b" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid10c.a">

    <Foundation.Core.ModelElement.name>patients</Foundat

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid10b" />

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid10d.a">

    <Foundation.Core.ModelElement.name>clients</Foundatio

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid10b" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid10e.a">

        <Foundation.Core.ModelElement.name>daemon</Foundati

        <Foundation.Core.ModelElement.visibility
            xmi.value="protected" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid10f" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid110.a">

        <Foundation.Core.ModelElement.name>daemonport</Fou

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-

```

```

    <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body>8000</Four

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid93" />

</Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid111.a">

        <Foundation.Core.ModelElement.name>daemonbacklog</

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

```

```

    <Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body>50</Founda

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
xmi.id="txmiid112.a">

    <Foundation.Core.ModelElement.name>clientIDsequence

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

```

```

<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid93" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Operation
  xmi.id="txmiid69.O">

    <Foundation.Core.ModelElement.name>GEEServer</Founc

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

```

```

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.BehavioralFeature.raisedException>

        <Behavioral_Elements.Common_Behavior.Exception
xmi.idref="txmiid69.Ex_IOException" />

    </Foundation.Core.BehavioralFeature.raisedException>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>

    <Foundation.Core.BehavioralFeature.parameter />
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid79.O">

    <Foundation.Core.ModelElement.name>createGEEClientH

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

```



```

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c
    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid79.Return">

    <Foundation.Core.ModelElement.name>createGEEClie

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-

```

```

    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiid113" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid79.1">

    <Foundation.Core.ModelElement.name>clientdaemonr

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
        xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiid91" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid79.2">

    <Foundation.Core.ModelElement.name>clientdaemonr

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-

```

```

    <Foundation.Core.Parameter.defaultValue>
    -
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
    -
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid78.O">

    <Foundation.Core.ModelElement.name>deleteGEEClientHi

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />

```

```

- <Foundation.Core.ModelElement.taggedValue>
-   <Foundation.Extension_Mechanisms.TaggedValue>
      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid78.Return">

      <Foundation.Core.ModelElement.name>deleteGEEClie
      <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>
          <Foundation.Data_Types.Expression.language />
          <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>
      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
        xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
          xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter

```

```

xmi.id="txmiid78.1">

  <Foundation.Core.ModelElement.name>clientID</Four

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid78.2">

  <Foundation.Core.ModelElement.name>guidelineID</I

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid78.3">

    <Foundation.Core.ModelElement.name>patientID</Fo

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

```

```

    </Foundation.Core.BehavioralFeature.parameter>
  </Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid114.O">

    <Foundation.Core.ModelElement.name>createPatient</Fo

    <Foundation.Core.ModelElement.visibility
  xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
  xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
  xmi.value="false" />

  <Foundation.Core.Operation.concurrency
  xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid114.Return">

    <Foundation.Core.ModelElement.name>createPatient.

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>

```

```

-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid115.O">

    <Foundation.Core.ModelElement.name>deletePatient</Fo

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-

```



```

    <Foundation.Core.ModelElement.taggedValue>
-
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

      </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid115.Return">

      <Foundation.Core.ModelElement.name>deletePatient.

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid115.1">

```

```

    <Foundation.Core.ModelElement.name>PID</Foundati
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid7a.0">

    <Foundation.Core.ModelElement.name>selectGuidelinePa

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

```

```

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid7a.Return">

        <Foundation.Core.ModelElement.name>selectGuidelin

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
xmi.idref="txmiid113" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid7a.1">

        <Foundation.Core.ModelElement.name>clientID</Four

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid7a.2">

        <Foundation.Core.ModelElement.name>guidelineID</I

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-

```

```

    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid7a.3">

    <Foundation.Core.ModelElement.name>patientID</Fo

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid116.O">

    <Foundation.Core.ModelElement.name>browseGuidelines

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

    <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid116.Return">

```

```

    <Foundation.Core.ModelElement.name>browseGuideli

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid117.0">

    <Foundation.Core.ModelElement.name>browseGuidelines

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

```

```

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid117.Return">

    <Foundation.Core.ModelElement.name>browseGuideli

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType

```



```

        xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid117.1">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

-
    <Foundation.Core.Parameter.defaultValue>

-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />

-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid118.0">

    <Foundation.Core.ModelElement.name>browsePatients</

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope

```

```

xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid118.Return">

    <Foundation.Core.ModelElement.name>browsePatient

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="return" />
    -
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid119.0">

    <Foundation.Core.ModelElement.name>browsePatients</

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

```

```

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid119.Return">

      <Foundation.Core.ModelElement.name>browsePatient

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid119.1">

      <Foundation.Core.ModelElement.name>GLID</Founda

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid11a.O">

    <Foundation.Core.ModelElement.name>notifyPrimaryClient

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.BehavioralFeature.raisedException>

        <Behavioral_Elements.Common_Behavior.Exception

```

```

        xmi.idref="txmiid11a.Ex_IOException" />
    </Foundation.Core.BehavioralFeature.raisedException>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>
    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid11a.Return">

        <Foundation.Core.ModelElement.name>notifyPrimaryI

        <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>
        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
        xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
            xmi.idref="txmiida6" />

```

```

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid11a.1">

        <Foundation.Core.ModelElement.name>clienthandle</Founda

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
            xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
                xmi.idref="txmiid113" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
-
    <Behavioral_Elements.Common_Behavior.Exception
        xmi.id="txmiid69.Ex_IOException">

        <Foundation.Core.ModelElement.name>IOException</Founda
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot

```

```

    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
-
    <Behavioral_Elements.Common_Behavior.Exception.context>
    <Foundation.Core.Operation
        xmi.idref="txmiid69.O" />

    </Behavioral_Elements.Common_Behavior.Exception.context>

</Behavioral_Elements.Common_Behavior.Exception>
-
    <Behavioral_Elements.Common_Behavior.Exception
    xmi.id="txmiid11a.Ex_IOException">

        <Foundation.Core.ModelElement.name>IOException</Founda
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

        <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
-
        <Behavioral_Elements.Common_Behavior.Exception.context>
        <Foundation.Core.Operation
            xmi.idref="txmiid11a.O" />

        </Behavioral_Elements.Common_Behavior.Exception.context>

    </Behavioral_Elements.Common_Behavior.Exception>
- <Foundation.Core.Association
    xmi.id="txmiid109.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

```



```

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid109.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity>1</Foundatio

    <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid24" />

    </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid109.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

```

```

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity>1</Foundatio

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid11b" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Class xmi.id="txmiid11b">

    <Foundation.Core.ModelElement.name>GEEServerDaemon</I
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid3" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEServer.GEEServerDaemonServerSocket.G"

```

```

</Foundation.Core.GeneralizableElement.generalization>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEServer.GEEServerDaemonRunnable.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid11c.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiid11d.a">

    <Foundation.Core.ModelElement.name>server</Foundation

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid11e" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid11f.a">

        <Foundation.Core.ModelElement.name>daemonthread</F

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-

```

```

    <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body>null</Found
    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiidcf" />

</Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid120.a">

    <Foundation.Core.ModelElement.name>stop</Foundation.(

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

```

```

    <Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body>false</Foun

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
xmi.idref="txmiid98" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Operation
xmi.id="txmiid121.O">

    <Foundation.Core.ModelElement.name>GEEServerDaemon

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

```

```

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.BehavioralFeature.raisedException>

    <Behavioral_Elements.Common_Behavior.Exception
    xmi.idref="txmiid121.Ex_IOException" />

</Foundation.Core.BehavioralFeature.raisedException>
-
<Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
<Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid121.1">

        <Foundation.Core.ModelElement.name>port</Foundati

        <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

```

```

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid121.2">

<Foundation.Core.ModelElement.name>backlog</Foun

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>

<Foundation.Data_Types.Expression.language />

<Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter

```



```

xmi.id="txmiid121.3">

  <Foundation.Core.ModelElement.name>server</Found

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid11e" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid122.0">

  <Foundation.Core.ModelElement.name>run</Foundation.C

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

```

```

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid122.Return">

    <Foundation.Core.ModelElement.name>run.Return</F

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
          xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid123.O">

  <Foundation.Core.ModelElement.name>startDaemon</Foi

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.BehavioralFeature.raisedException>

    <Behavioral_Elements.Common_Behavior.Exception
      xmi.idref="txmiid123.Ex_IOException" />

  </Foundation.Core.BehavioralFeature.raisedException>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

```

```

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid123.Return">

      <Foundation.Core.ModelElement.name>startDaemon.I

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid124.O">

      <Foundation.Core.ModelElement.name>stopDaemon</Fou

      <Foundation.Core.ModelElement.visibility
xmi.value="public" />

```

```

<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.BehavioralFeature.raisedException>

    <Behavioral_Elements.Common_Behavior.Exception
      xmi.idref="txmiid124.Ex_IOException" />

  </Foundation.Core.BehavioralFeature.raisedException>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid124.Return">

      <Foundation.Core.ModelElement.name>stopDaemon.F
      <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
-
    <Behavioral_Elements.Common_Behavior.Exception
xmi.id="txmiid121.Ex_IOException">

        <Foundation.Core.ModelElement.name>IOException</Founda
    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
-
    <Behavioral_Elements.Common_Behavior.Exception.context>
    <Foundation.Core.Operation
xmi.idref="txmiid121.O" />

</Behavioral_Elements.Common_Behavior.Exception.context>

```

```

</Behavioral_Elements.Common_Behavior.Exception>
-
  <Behavioral_Elements.Common_Behavior.Exception
    xmi.id="txmiid123.Ex_IOException">

    <Foundation.Core.ModelElement.name>IOException</Founda
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
-
    <Behavioral_Elements.Common_Behavior.Exception.context>
    <Foundation.Core.Operation
      xmi.idref="txmiid123.O" />

  </Behavioral_Elements.Common_Behavior.Exception.context>

</Behavioral_Elements.Common_Behavior.Exception>
-
  <Behavioral_Elements.Common_Behavior.Exception
    xmi.id="txmiid124.Ex_IOException">

    <Foundation.Core.ModelElement.name>IOException</Founda
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
-
    <Behavioral_Elements.Common_Behavior.Exception.context>
    <Foundation.Core.Operation
      xmi.idref="txmiid124.O" />

  </Behavioral_Elements.Common_Behavior.Exception.context>

</Behavioral_Elements.Common_Behavior.Exception>

```

```

- <Foundation.Core.Association
  xmi.id="txmiid11c.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
- <Foundation.Core.Association.connection>
  - <Foundation.Core.AssociationEnd
    xmi.id="txmiid11c.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity>1</Foundation.Core.AssociationEnd.multiplicity>

    <Foundation.Core.AssociationEnd.changeable
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid11b" />

    </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd

```



```

xmi.id="txmiid11c.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity>1</Foundatio

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid24" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GEEServer.GEEServerDaemonServerSocket.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid11b" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class

```

```

        xmi.idref="txmiid125" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Generalization
    xmi.id="GEEServer.GEEServerDaemonRunnable.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid11b" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Interface
        xmi.idref="txmiid126" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid127">

    <Foundation.Core.ModelElement.name>GEEServerInvoker</F
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid3" />
    </Foundation.Core.ModelElement.namespace>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

```

```

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation
  xmi.id="txmiid128.O">

  <Foundation.Core.ModelElement.name>main</Foundation.

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.BehavioralFeature.raisedException>

    <Behavioral_Elements.Common_Behavior.Exception
      xmi.idref="txmiid128.Ex_IOException" />

  </Foundation.Core.BehavioralFeature.raisedException>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>

```

```

- <Foundation.Core.Parameter
  xmi.id="txmiid128.Return">

  <Foundation.Core.ModelElement.name>main.Return</Foundation.Core.ModelElement.name>

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>

-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="return" />

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid128.1">

  <Foundation.Core.ModelElement.name>args</Foundation.Core.ModelElement.name>

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>

-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

        </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiide3" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
-
    <Behavioral_Elements.Common_Behavior.Exception
xmi.id="txmiid128.Ex_IOException">

        <Foundation.Core.ModelElement.name>IOException</Founda
    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
-
    <Behavioral_Elements.Common_Behavior.Exception.context>
    <Foundation.Core.Operation
xmi.idref="txmiid128.O" />

    </Behavioral_Elements.Common_Behavior.Exception.context>

    </Behavioral_Elements.Common_Behavior.Exception>
- <Foundation.Core.Class xmi.id="txmiid129">

    <Foundation.Core.ModelElement.name>GEEServerSideSessio

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid3" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEServer.GEEServerSideSessionThread.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid12a.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid12b.a">

    <Foundation.Core.ModelElement.name>server</Foundation

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope

```

```

xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four

<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid11e" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid12c.a">

  <Foundation.Core.ModelElement.name>s</Foundation.Core

```

```

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiiddb" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid12d.a">

```



```

<Foundation.Core.ModelElement.name>endSession</Four
<Foundation.Core.ModelElement.visibility
xmi.value="private" />
<Foundation.Core.Feature.ownerScope
xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four

<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid98" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>

```

```

</Foundation.Core.Attribute>
- <Foundation.Core.Operation
  xmi.id="txmiid12e.0">

  <Foundation.Core.ModelElement.name>GEEServerSideSession</Foundation.Core.ModelElement.name>

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>code</Foundation.Extension_Mechanisms.TaggedValue.tag>

      <Foundation.Extension_Mechanisms.TaggedValue.value
        <Foundation.Extension_Mechanisms.TaggedValue.value>
      </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid12e.1">

    <Foundation.Core.ModelElement.name>session</Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-

```

```

    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiiddb" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid12e.2">

    <Foundation.Core.ModelElement.name>server</Found

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
xmi.idref="txmiid11e" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid12f.O">

    <Foundation.Core.ModelElement.name>run</Foundation.C

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid12f.Return">

```

```

    <Foundation.Core.ModelElement.name>run.Return</F
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid130.0">

    <Foundation.Core.ModelElement.name>processInput</Fo

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

```

```

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid130.Return">

    <Foundation.Core.ModelElement.name>processInput.

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType

```

```

        xmi.idref="txmiid91" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid130.1">

        <Foundation.Core.ModelElement.name>inputLine</Fou

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
            xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
                xmi.idref="txmiid91" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
    xmi.id="txmiid12a.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot

```

```

    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid12a.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity>0..* </Founda

    <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid129" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid12a.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

```



```

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity>1</Foundatio

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid24" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GEEServer.GEEServerSideSessionThread.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid129" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid131" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid68">

  <Foundation.Core.ModelElement.name>Guideline</Foundatio

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid3" />
</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEServer.GuidelineGuidelineLoader.G" />

</Foundation.Core.GeneralizableElement.generalization>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEServer.GuidelineGuidelineBrowser.G" />

</Foundation.Core.GeneralizableElement.generalization>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEServer.GuidelineGuidelineParsor.G" />

</Foundation.Core.GeneralizableElement.generalization>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEServer.GuidelineDataAccessor.G" />

</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid132.CE" />
</Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-

```

```

<Foundation.Extension_Mechanisms.TaggedValue>

  <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

  <Foundation.Extension_Mechanisms.TaggedValue.value />

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid133.a">

  <Foundation.Core.ModelElement.name>GuidelineID</Four

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid91" />

  </Foundation.Core.StructuralFeature.type>

```

```

- <Foundation.Core.ModelElement.taggedValue>
-   <Foundation.Extension_Mechanisms.TaggedValue>
      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid134.a">

    <Foundation.Core.ModelElement.name>GuidelineName</I

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-   <Foundation.Core.Attribute.initialValue>
-     <Foundation.Data_Types.Expression>
        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
      </Foundation.Data_Types.Expression>
    </Foundation.Core.Attribute.initialValue>
-   <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType

```

```

        xmi.idref="txmiid103" />
    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid135.a">

        <Foundation.Core.ModelElement.name>GEEClients</Found

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>

```

```

-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid136" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid137.a">

    <Foundation.Core.ModelElement.name>GuidelineStructur

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

</Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid9a" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Operation
  xmi.id="txmiid8b.O">

    <Foundation.Core.ModelElement.name>loadGuidelines</F

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-

```

```

<Foundation.Extension_Mechanisms.TaggedValue>

  <Foundation.Extension_Mechanisms.TaggedValue.tag>c

  <Foundation.Extension_Mechanisms.TaggedValue.value

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid8b.Return">

    <Foundation.Core.ModelElement.name>loadGuidelines

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation

```



```

xmi.id="txmiid138.O">

  <Foundation.Core.ModelElement.name>addGEEClient</Fo

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

  <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid138.Return">

    <Foundation.Core.ModelElement.name>addGEEClient.

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid138.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

```

```

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid139.O">

    <Foundation.Core.ModelElement.name>removeGEEClient</Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
        xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
        xmi.value="false" />

    <Foundation.Core.Operation.concurrency
        xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c</Foundation.Extension_Mechanisms.TaggedValue.tag>

            <Foundation.Extension_Mechanisms.TaggedValue.value
                />
        </Foundation.Extension_Mechanisms.TaggedValue>
    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid139.Return">

    <Foundation.Core.ModelElement.name>removeGEECli

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid139.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid8d.O">

    <Foundation.Core.ModelElement.name>mapGuidelineData

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>

```

```

-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid8d.Return">

    <Foundation.Core.ModelElement.name>mapGuideline<

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid8e.O">

  <Foundation.Core.ModelElement.name>browseGuideline<

  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

```

```

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid8e.Return">

    <Foundation.Core.ModelElement.name>browseGuideli

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind

```

```

        xmi.value="return" />
    -
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
            xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid8c.O">

        <Foundation.Core.ModelElement.name>parseGuideline</f

        <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

        <Foundation.Core.BehavioralFeature.isQuery
        xmi.value="false" />

        <Foundation.Core.Operation.specification />

        <Foundation.Core.Operation.isPolymorphic
        xmi.value="false" />

        <Foundation.Core.Operation.concurrency
        xmi.value="sequential" />
    -
        <Foundation.Core.ModelElement.taggedValue>
    -
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
    -

```



```

    <Foundation.Core.BehavioralFeature.parameter>
-   <Foundation.Core.Parameter
        xmi.id="txmiid8c.Return">

        <Foundation.Core.ModelElement.name>parseGuideline

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
            xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
                xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid13a.O">

    <Foundation.Core.ModelElement.name>createGuidelineSt

    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery

```

```

xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid13a.Return">

    <Foundation.Core.ModelElement.name>createGuidelir

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />

```

```

-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
    xmi.id="txmiid132.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid132.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
        xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
        xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
        xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity>1</Foundatio

```

```

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid68" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid132.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity>0..* </Founda

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid3e" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
  </Foundation.Core.Association.connection>
</Foundation.Core.Association>

```

```

- <Foundation.Core.Generalization
  xmi.id="GEEServer.GuidelineGuidelineLoader.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid68" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Interface
    xmi.idref="txmiid13b" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Generalization
  xmi.id="GEEServer.GuidelineGuidelineBrowser.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid68" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Interface
    xmi.idref="txmiid13c" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Generalization
  xmi.id="GEEServer.GuidelineGuidelineParsor.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid68" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>

```

```

        <Foundation.Core.Interface
          xmi.idref="txmiid13d" />
      </Foundation.Core.Generalization.supertype>
    </Foundation.Core.Generalization>
  - <Foundation.Core.Generalization
    xmi.id="GEEServer.GuidelineDataAccessor.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
  - <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
      xmi.idref="txmiid68" />
    </Foundation.Core.Generalization.subtype>
  - <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Interface
      xmi.idref="txmiid13e" />
    </Foundation.Core.Generalization.supertype>
  </Foundation.Core.Generalization>
  - <Foundation.Core.Interface xmi.id="txmiid13b">

    <Foundation.Core.ModelElement.name>GuidelineLoader</Fou
    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="true" />
  - <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
      xmi.idref="txmiid3" />
    </Foundation.Core.ModelElement.namespace>
  - <Foundation.Core.ModelElement.taggedValue>
    -
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

      </Foundation.Extension_Mechanisms.TaggedValue>

```

```

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation
  xmi.id="txmiid13f.O">

    <Foundation.Core.ModelElement.name>loadGuidelines</F

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
  -
    <Foundation.Core.ModelElement.taggedValue>
    -
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

      </Foundation.Extension_Mechanisms.TaggedValue>
    </Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Core.BehavioralFeature.parameter>
  - <Foundation.Core.Parameter
    xmi.id="txmiid13f.Return">

      <Foundation.Core.ModelElement.name>loadGuidelines:

      <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    -

```

```

        <Foundation.Core.Parameter.defaultValue>
    -
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
    -
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
    </Foundation.Core.Operation>
    </Foundation.Core.Classifier.feature>
    </Foundation.Core.Interface>
- <Foundation.Core.Class xmi.id="txmiid62">

    <Foundation.Core.ModelElement.name>Patient</Foundation.C
    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
    <Foundation.Core.Class.isActive
xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
xmi.idref="txmiid3" />
    </Foundation.Core.ModelElement.namespace>

```



```

-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEServer.PatientPatientLoader.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid140.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid141.a">

    <Foundation.Core.ModelElement.name>PatientID</Found:

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid91" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid142.a">

        <Foundation.Core.ModelElement.name>PatientFirstName

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-

```

```

    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid103" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid143.a">

        <Foundation.Core.ModelElement.name>PatientLastName</Foundation.Core.ModelElement.name>

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Foundation.Core.StructuralFeature.multiplicity>

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />

```

```

-
  <Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid103" />

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid144.a">

    <Foundation.Core.ModelElement.name>GEEClients</Foun

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

```

```

    <Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
xmi.idref="txmiid136" />

</Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Operation
xmi.id="txmiid8a.O">

    <Foundation.Core.ModelElement.name>loadPatient</Four

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery

```

```

xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid8a.Return">

    <Foundation.Core.ModelElement.name>loadPatient.Re

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />

```

```

-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid145.O">

    <Foundation.Core.ModelElement.name>addGEEClient</Fo

    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
        xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
        xmi.value="false" />

    <Foundation.Core.Operation.concurrency
        xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>

```

```

- <Foundation.Core.Parameter
  xmi.id="txmiid145.Return">

  <Foundation.Core.ModelElement.name>addGEEClient.|

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
    xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid145.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

```



```

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid146.O">

    <Foundation.Core.ModelElement.name>removeGEEClient</Foundation.Core.ModelElement.name>

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid146.Return">

        <Foundation.Core.ModelElement.name>removeGEECLI

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid146.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-

```

```

    <Foundation.Core.Parameter.defaultValue>
    -
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
    -
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid147.O">

    <Foundation.Core.ModelElement.name>browsePatient</F

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />

```

```

-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid147.Return">

      <Foundation.Core.ModelElement.name>browsePatient

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

```

```

        </Foundation.Core.BehavioralFeature.parameter>
    </Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
    xmi.id="txmiid140.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Core.Association.connection>
    - <Foundation.Core.AssociationEnd
        xmi.id="txmiid140.CE">

        <Foundation.Core.ModelElement.name />

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />

        <Foundation.Core.AssociationEnd.isNavigable
            xmi.value="false" />

        <Foundation.Core.AssociationEnd.isOrdered
            xmi.value="false" />

        <Foundation.Core.AssociationEnd.aggregation
            xmi.value="none" />

        <Foundation.Core.AssociationEnd.multiplicity>1</Foundatio

        <Foundation.Core.AssociationEnd.changeable
            xmi.value="none" />

        <Foundation.Core.AssociationEnd.targetScope
            xmi.value="instance" />
    -
        <Foundation.Core.AssociationEnd.type>
        <Foundation.Core.Class
            xmi.idref="txmiid62" />

```

```

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid140.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
  xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
  xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
  xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
  xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity>0..* </Founda

    <Foundation.Core.AssociationEnd.changeable
  xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
  xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid3e" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GEEServer.PatientPatientLoader.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class

```

```

        xmi.idref="txmiid62" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Interface
        xmi.idref="txmiid148" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Interface xmi.id="txmiid148">

    <Foundation.Core.ModelElement.name>PatientLoader</Found
<Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="true" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid3" />
    </Foundation.Core.ModelElement.namespace>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu
        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation
    xmi.id="txmiid149.O">

    <Foundation.Core.ModelElement.name>loadPatient</Four
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

```

```

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid149.Return">

    <Foundation.Core.ModelElement.name>loadPatient.Re

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind

```



```

        xmi.value="return" />
    -
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
            xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Interface>
</Foundation.Core.Namespace.ownedElement>
</Model_Management.Package>
- <Model_Management.Package xmi.id="txmiid6">

    <Foundation.Core.ModelElement.name>GEEServerLocalSystem</
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
    - <Foundation.Core.ModelElement.namespace>
        <Model_Management.Model
        xmi.idref="txmiid1" />
    </Foundation.Core.ModelElement.namespace>
    - <Foundation.Core.ModelElement.taggedValue>
        -
            <Foundation.Extension_Mechanisms.TaggedValue>

                <Foundation.Extension_Mechanisms.TaggedValue.tag>docume

                <Foundation.Extension_Mechanisms.TaggedValue.value />

            </Foundation.Extension_Mechanisms.TaggedValue>
        </Foundation.Core.ModelElement.taggedValue>
    - <Foundation.Core.Namespace.ownedElement>
        - <Foundation.Core.Class xmi.id="txmiid14a">

            <Foundation.Core.ModelElement.name>MyDataAccessor</Fou

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
<Foundation.Core.Class.isActive
  xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid6" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEServerLocalSystem.MyDataAccessorDataA
  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation
  xmi.id="txmiid14b.O">

    <Foundation.Core.ModelElement.name>mapGuidelineData

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

```

```

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid14b.Return">

    <Foundation.Core.ModelElement.name>mapGuideline1

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-

```

```

        <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
xmi.id="GEEServerLocalSystem.MyDataAccessorDataAccess
<Foundation.Core.ModelElement.name />
<Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
xmi.idref="txmiid14a" />
</Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Interface
xmi.idref="txmiid13e" />
</Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid14c">

    <Foundation.Core.ModelElement.name>MyGuidelineLoader</
<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
<Foundation.Core.Class.isActive
xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
xmi.idref="txmiid6" />

```

```

</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEServerLocalSystem.MyGuidelineLoaderGui
  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Operation
    xmi.id="txmiid14d.O">

    <Foundation.Core.ModelElement.name>loadGuidelines</F

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid14d.Return">

        <Foundation.Core.ModelElement.name>loadGuidelines

        <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
        xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
            xmi.idref="txmiida6" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GEEServerLocalSystem.MyGuidelineLoaderGuideline

```

```

<Foundation.Core.ModelElement.name />
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />

  <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid14c" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Interface
    xmi.idref="txmiid13b" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid14e">

  <Foundation.Core.ModelElement.name>MyPatientLoader</Fo
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid6" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GEEServerLocalSystem.MyPatientLoaderPatie

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

```

```

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation
  xmi.id="txmiid14f.O">

    <Foundation.Core.ModelElement.name>loadPatient</Four

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid14f.Return">

    <Foundation.Core.ModelElement.name>loadPatient.Re

    <Foundation.Core.ModelElement.visibility

```



```

        xmi.value="private" />
      -
        <Foundation.Core.Parameter.defaultValue>
      -
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
      xmi.value="return" />
    -
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GEEServerLocalSystem.MyPatientLoaderPatientLoa
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />

  <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
  xmi.idref="txmiid14e" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Interface
  xmi.idref="txmiid148" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>

```

```

    </Foundation.Core.Namespace.ownedElement>
  </Model_Management.Package>
- <Model_Management.Package xmi.id="txmiid4">

    <Foundation.Core.ModelElement.name>GLIF3</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Model
    xmi.idref="txmiid1" />
  </Foundation.Core.ModelElement.namespace>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docume

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>
</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Namespace.ownedElement>
- <Foundation.Core.Class xmi.id="txmiid150">

    <Foundation.Core.ModelElement.name>Action_Specification<
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />

```

```

</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Action_SpecificationGuideline_Model_E

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Action_SpecificationGuideline_Model_Entity.
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid150" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid151" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid152">

  <Foundation.Core.ModelElement.name>Action_Step</Founda
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

```

```

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Action_StepGuideline_Step.G" />

</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid153.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid154.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid155.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid156.CE" />
</Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiid157.a">

    <Foundation.Core.ModelElement.name>exceptions</Founi

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

```

```

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four
<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid158" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid159.a">

  <Foundation.Core.ModelElement.name>next_step</Found

  <Foundation.Core.ModelElement.visibility

```

```

      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiidae" />

  </Foundation.Core.StructuralFeature.type>
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid15a.a">

```

```

<Foundation.Core.ModelElement.name>tasks</Foundation
<Foundation.Core.ModelElement.visibility
xmi.value="private" />
<Foundation.Core.Feature.ownerScope
xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four
<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid15b" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>

```

```

- <Foundation.Core.Attribute
  xmi.id="txmiid15c.a">

  <Foundation.Core.ModelElement.name>triggering_events

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid15d" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

      </Foundation.Extension_Mechanisms.TaggedValue>

```



```

        </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
    xmi.id="txmiid153.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid153.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
        xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
        xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
        xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
        xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class

```

```

        xmi.idref="txmiid152" />

        </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid153.SE">

        <Foundation.Core.ModelElement.name />

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />

        <Foundation.Core.AssociationEnd.isNavigable
            xmi.value="true" />

        <Foundation.Core.AssociationEnd.isOrdered
            xmi.value="false" />

        <Foundation.Core.AssociationEnd.aggregation
            xmi.value="none" />

        <Foundation.Core.AssociationEnd.multiplicity />

        <Foundation.Core.AssociationEnd.changeable
            xmi.value="none" />

        <Foundation.Core.AssociationEnd.targetScope
            xmi.value="instance" />
-
        <Foundation.Core.AssociationEnd.type>
        <Foundation.Core.Class
            xmi.idref="txmiid15e" />

        </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
    </Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
    xmi.id="txmiid154.ASS">
        <Foundation.Core.ModelElement.name />
        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
        <Foundation.Core.GeneralizableElement.isRoot
            xmi.value="false" />
        <Foundation.Core.GeneralizableElement.isLeaf

```

```

xmi.value="false" />

<Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid154.CE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid152" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid154.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable

```

```

xmi.value="true" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid15f" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid155.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
  - <Foundation.Core.AssociationEnd
    xmi.id="txmiid155.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

```

```

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid152" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid155.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

```

```

        <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
        <Foundation.Core.AssociationEnd.type>
        <Foundation.Core.Class
xmi.idref="txmiid150" />

        </Foundation.Core.AssociationEnd.type>
        </Foundation.Core.AssociationEnd>
        </Foundation.Core.Association.connection>
    </Foundation.Core.Association>
- <Foundation.Core.Association
xmi.id="txmiid156.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
xmi.id="txmiid156.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

```

```

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid152" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid156.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid160" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Action_StepGuideline_Step.G">

```

```

<Foundation.Core.ModelElement.name />
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />

  <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid152" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid15f" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid161">

  <Foundation.Core.ModelElement.name>Algorithm</Foundation
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.AlgorithmGuideline_Model_Entity.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid162.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid163.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>

```



```

-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiid164.a">

    <Foundation.Core.ModelElement.name>first_step</Foundi

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiidae" />

```

```

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>
      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid165.a">

  <Foundation.Core.ModelElement.name>steps</Foundation

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.Feature.ownerScope
  xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
  xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
  xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>
      <Foundation.Data_Types.Expression.language />
      <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>
  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>

```

```

    <Foundation.Core.DataType
      xmi.idref="txmiidb0" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
  </Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid162.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid162.CE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

  <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

```

```

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid161" />

    </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid162.SE">

        <Foundation.Core.ModelElement.name />

        <Foundation.Core.ModelElement.visibility
xmi.value="public" />

        <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

        <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

        <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

        <Foundation.Core.AssociationEnd.multiplicity />

        <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

        <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class

```

```

xmi.idref="txmiid15f" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid163.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
  - <Foundation.Core.AssociationEnd
    xmi.id="txmiid163.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.AssociationEnd.type>

```

```

    <Foundation.Core.Class
      xmi.idref="txmiid161" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid163.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
      xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
      xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid15f" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.AlgorithmGuideline_Model_Entity.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />

```

```

- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid161" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid151" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid166">

  <Foundation.Core.ModelElement.name>Assignment_Action</
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
<Foundation.Core.Class.isActive
  xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Assignment_ActionProgramming_Orier
    />
  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid167.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

  <Foundation.Extension_Mechanisms.TaggedValue.tag>docu
  <Foundation.Extension_Mechanisms.TaggedValue.value />

```

```

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid168.a">

  <Foundation.Core.ModelElement.name>expression</Foun

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid169" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

```



```

        <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid16a.a">

        <Foundation.Core.ModelElement.name>primitive_data_it

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
        <Foundation.Core.Feature.ownerScope
            xmi.value="classifier" />

        <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

        <Foundation.Core.StructuralFeature.changeable
            xmi.value="none" />

        <Foundation.Core.StructuralFeature.targetScope
            xmi.value="instance" />
-
        <Foundation.Core.Attribute.initialValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Attribute.initialValue>
-
        <Foundation.Core.StructuralFeature.type>
        <Foundation.Core.DataType
            xmi.idref="txmiid91" />

        </Foundation.Core.StructuralFeature.type>
-
        <Foundation.Core.ModelElement.taggedValue>
-

```

```

    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid167.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  - <Foundation.Core.Association.connection>
    - <Foundation.Core.AssociationEnd
      xmi.id="txmiid167.CE">

        <Foundation.Core.ModelElement.name />

        <Foundation.Core.ModelElement.visibility
          xmi.value="public" />

        <Foundation.Core.AssociationEnd.isNavigable
          xmi.value="false" />

        <Foundation.Core.AssociationEnd.isOrdered
          xmi.value="false" />

        <Foundation.Core.AssociationEnd.aggregation
          xmi.value="none" />

        <Foundation.Core.AssociationEnd.multiplicity />

        <Foundation.Core.AssociationEnd.changeable

```

```

xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid166" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid167.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid16b" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
  </Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization

```

```

xmi.id="GLIF3.Assignment_ActionProgramming_Oriented_A
<Foundation.Core.ModelElement.name />
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />

  <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid166" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid16c" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid16d">

  <Foundation.Core.ModelElement.name>Basic_Data_Type</Fc
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Basic_Data_TypeGlobal_Concepts.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Basic_Data_TypeGlobal_Concepts.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid16d" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid16e" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid16f">

    <Foundation.Core.ModelElement.name>Branch_Step</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.Branch_StepGuideline_Step.G" />

```

```

    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
    <Foundation.Core.AssociationEnd
      xmi.idref="txmiid170.CE" />
    </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
    xmi.id="txmiid171.a">

    <Foundation.Core.ModelElement.name>branches</Founda

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiidb0" />

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid172.a">

    <Foundation.Core.ModelElement.name>order_constraint<

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

    </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid91" />

    </Foundation.Core.StructuralFeature.type>
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
    </Foundation.Core.Classifier.feature>
  </Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid170.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  - <Foundation.Core.Association.connection>
  - <Foundation.Core.AssociationEnd
    xmi.id="txmiid170.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

```



```

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid16f" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid170.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

```

```

        <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
    -
        <Foundation.Core.AssociationEnd.type>
        <Foundation.Core.Class
            xmi.idref="txmiid15f" />

        </Foundation.Core.AssociationEnd.type>
        </Foundation.Core.AssociationEnd>
        </Foundation.Core.Association.connection>
    </Foundation.Core.Association>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Branch_StepGuideline_Step.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid16f" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid15f" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid173">

    <Foundation.Core.ModelElement.name>Case_Condition</Found
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />

```

```

</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Case_ConditionDecision_Condition.G" /

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid174.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiid175.a">

    <Foundation.Core.ModelElement.name>case_value</Foun

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid169" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
    </Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
    xmi.id="txmiid174.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid174.CE">

    <Foundation.Core.ModelElement.name />

```

```

<Foundation.Core.ModelElement.visibility
xmi.value="public" />

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid173" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid174.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

```

```

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
xmi.idref="txmiid16b" />

    </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
    </Foundation.Core.Association.connection>
    </Foundation.Core.Association>
- <Foundation.Core.Generalization
xmi.id="GLIF3.Case_ConditionDecision_Condition.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
xmi.idref="txmiid173" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
xmi.idref="txmiid176" />
    </Foundation.Core.Generalization.supertype>
    </Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid177">

    <Foundation.Core.ModelElement.name>Case_Step</Foundatic
    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
    <Foundation.Core.Class.isActive
xmi.value="false" />

```

```

- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Case_StepDecision_Step.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid178.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid179.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiid17a.a">

    <Foundation.Core.ModelElement.name>default_next_step

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />

```

```

-
  <Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiidae" />

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid17b.a">

    <Foundation.Core.ModelElement.name>expression</Founi

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

```



```

    <Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
xmi.idref="txmiid169" />

</Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
xmi.id="txmiid17c.a">

    <Foundation.Core.ModelElement.name>operator</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
<Foundation.Core.Feature.ownerScope
xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

```

```

    <Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
xmi.idref="txmiid91" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
    </Foundation.Core.Classifier.feature>
    </Foundation.Core.Class>
- <Foundation.Core.Association
xmi.id="txmiid178.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot

```

```

    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid178.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid177" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid178.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

```

```

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid15f" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid179.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  - <Foundation.Core.Association.connection>
    - <Foundation.Core.AssociationEnd
      xmi.id="txmiid179.CE">

      <Foundation.Core.ModelElement.name />

      <Foundation.Core.ModelElement.visibility

```

```

xmi.value="public" />

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid177" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid179.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable

```

```

xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
xmi.idref="txmiid16b" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
xmi.id="GLIF3.Case_StepDecision_Step.G">
<Foundation.Core.ModelElement.name />
<Foundation.Core.ModelElement.visibility
xmi.value="public" />

<Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
<Foundation.Core.Class
xmi.idref="txmiid177" />
</Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
<Foundation.Core.Class
xmi.idref="txmiid17d" />
</Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid17e">

<Foundation.Core.ModelElement.name>Choice</Foundation.Cc
<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

<Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
<Foundation.Core.Class.isActive
xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
<Model_Management.Package

```

```

        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.ChoiceDecision_Condition.G" />

    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.ChoiceDecision_Condition.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid17e" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid176" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid17f">

    <Foundation.Core.ModelElement.name>Choice_Step</Founda
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

```

```

        <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.Choice_StepDecision_Step.G" />

    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Choice_StepDecision_Step.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid17f" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid17d" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid180">

```



```

        <Foundation.Core.ModelElement.name>Concept</Foundation.(
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.ConceptKnowledge_Item.G" />

</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.ConceptKnowledge_Item.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid180" />
</Foundation.Core.Generalization.subtype>

```

```

- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid181" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid182">

  <Foundation.Core.ModelElement.name>Concept_Relationship
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
<Foundation.Core.Class.isActive
  xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Concept_RelationshipKnowledge_Item

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Concept_RelationshipKnowledge_Item.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility

```

```

xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid182" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid181" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid183">

    <Foundation.Core.ModelElement.name>Criterion</Foundation.
<Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
<Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.CriterionGuideline_Expression.G" />

</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

```

```

    </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.CriterionGuideline_Expression.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid183" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid16b" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Interface xmi.id="txmiid13e">

  <Foundation.Core.ModelElement.name>DataAccessor</Found
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="true" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

```

```

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation
  xmi.id="txmiid184.O">

  <Foundation.Core.ModelElement.name>mapGuidelineData

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid184.Return">

  <Foundation.Core.ModelElement.name>mapGuideline

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>

```

```

-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Interface>
- <Foundation.Core.Class xmi.id="txmiid185">

    <Foundation.Core.ModelElement.name>Data_Item</Foundatic
<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
<Foundation.Core.Class.isActive
xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-

```

```

    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
      xmi.idref="GLIF3.Data_ItemBasic_Data_Type.G" />

    </Foundation.Core.GeneralizableElement.generalization>
  - <Foundation.Core.ModelElement.taggedValue>
    -
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

      </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Data_ItemBasic_Data_Type.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid185" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid16d" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid186">

  <Foundation.Core.ModelElement.name>Data_Item_List</Fou
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />

```

```

    <Foundation.Core.Class.isActive
      xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
      xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
      xmi.idref="GLIF3.Data_Item_ListGuideline_Model_Entity

    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
    <Foundation.Core.AssociationEnd
      xmi.idref="txmiid187.CE" />
    </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
    xmi.id="txmiid188.a">

    <Foundation.Core.ModelElement.name>entry_array</Four

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />

```



```

-
  <Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid189" />

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid187.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />

```

```

- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid187.CE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid186" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid187.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

```

```

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid185" />

        </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Data_Item_ListGuideline_Model_Entity.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid186" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid151" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid176">

    <Foundation.Core.ModelElement.name>Decision_Condition</
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

```

```

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
    <Foundation.Core.Class.isActive
      xmi.value="false" />
  - <Foundation.Core.ModelElement.namespace>
      <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
  -
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
      xmi.idref="GLIF3.Decision_ConditionGuideline_Model_Er

    </Foundation.Core.GeneralizableElement.generalization>
  - <Foundation.Core.ModelElement.taggedValue>
    -
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

      </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Class>
  - <Foundation.Core.Generalization
    xmi.id="GLIF3.Decision_ConditionGuideline_Model_Entity.G
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
  - <Foundation.Core.Generalization.subtype>
      <Foundation.Core.Class
        xmi.idref="txmiid176" />
    </Foundation.Core.Generalization.subtype>
  - <Foundation.Core.Generalization.supertype>
      <Foundation.Core.Class
        xmi.idref="txmiid151" />
    </Foundation.Core.Generalization.supertype>
  </Foundation.Core.Generalization>
  - <Foundation.Core.Class xmi.id="txmiid18a">

```

```

    <Foundation.Core.ModelElement.name>Decision_Option</Fou
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Decision_OptionGLIF_Entity.G" />

</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid18b.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid18c.CE" />
</Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiid18d.a">

    <Foundation.Core.ModelElement.name>condition_value<,

```

```

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid18e" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid18f.a">

```

```

<Foundation.Core.ModelElement.name>destination</Foun

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
<Foundation.Core.Feature.ownerScope
xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four

<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiidae" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>

```

```

        </Foundation.Core.Attribute>
    </Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
    xmi.id="txmiid18b.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Core.Association.connection>
    - <Foundation.Core.AssociationEnd
        xmi.id="txmiid18b.CE">

        <Foundation.Core.ModelElement.name />

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />

        <Foundation.Core.AssociationEnd.isNavigable
            xmi.value="false" />

        <Foundation.Core.AssociationEnd.isOrdered
            xmi.value="false" />

        <Foundation.Core.AssociationEnd.aggregation
            xmi.value="none" />

        <Foundation.Core.AssociationEnd.multiplicity />

        <Foundation.Core.AssociationEnd.changeable
            xmi.value="none" />

        <Foundation.Core.AssociationEnd.targetScope
            xmi.value="instance" />
    -
        <Foundation.Core.AssociationEnd.type>
        <Foundation.Core.Class
            xmi.idref="txmiid18a" />

```



```

        </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid18b.SE">

        <Foundation.Core.ModelElement.name />

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />

        <Foundation.Core.AssociationEnd.isNavigable
            xmi.value="true" />

        <Foundation.Core.AssociationEnd.isOrdered
            xmi.value="false" />

        <Foundation.Core.AssociationEnd.aggregation
            xmi.value="none" />

        <Foundation.Core.AssociationEnd.multiplicity />

        <Foundation.Core.AssociationEnd.changeable
            xmi.value="none" />

        <Foundation.Core.AssociationEnd.targetScope
            xmi.value="instance" />
-
        <Foundation.Core.AssociationEnd.type>
        <Foundation.Core.Class
            xmi.idref="txmiid176" />

        </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
    xmi.id="txmiid18c.ASS">
        <Foundation.Core.ModelElement.name />
        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
        <Foundation.Core.GeneralizableElement.isRoot
            xmi.value="false" />
        <Foundation.Core.GeneralizableElement.isLeaf
            xmi.value="false" />

```

```

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid18c.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid18a" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid18c.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="true" />

```

```

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid15f" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Decision_OptionGLIF_Entity.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
      xmi.idref="txmiid18a" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
      xmi.idref="txmiid190" />
    </Foundation.Core.Generalization.supertype>
  </Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid17d">

    <Foundation.Core.ModelElement.name>Decision_Step</Found
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />

```

```

<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="true" />
<Foundation.Core.Class.isActive
  xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Decision_StepGuideline_Step.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid191.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid192.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid193.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid194.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid195.a">

  <Foundation.Core.ModelElement.name>decision_detail</I

  <Foundation.Core.ModelElement.visibility

```

```

    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid196" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid197.a">

```

```

<Foundation.Core.ModelElement.name>exceptions</Found

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
<Foundation.Core.Feature.ownerScope
xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four

<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid158" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>

```

```

- <Foundation.Core.Attribute
  xmi.id="txmiid198.a">

  <Foundation.Core.ModelElement.name>options</Foundati

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid199" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

```

```

    </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid19a.a">

    <Foundation.Core.ModelElement.name>triggering_events

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid15d" />

  </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

```



```

        <Foundation.Extension_Mechanisms.TaggedValue.value
        </Foundation.Extension_Mechanisms.TaggedValue>

        </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid191.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  - <Foundation.Core.Association.connection>
    - <Foundation.Core.AssociationEnd
      xmi.id="txmiid191.CE">

        <Foundation.Core.ModelElement.name />

        <Foundation.Core.ModelElement.visibility
          xmi.value="public" />

        <Foundation.Core.AssociationEnd.isNavigable
          xmi.value="false" />

        <Foundation.Core.AssociationEnd.isOrdered
          xmi.value="false" />

        <Foundation.Core.AssociationEnd.aggregation
          xmi.value="none" />

        <Foundation.Core.AssociationEnd.multiplicity />

        <Foundation.Core.AssociationEnd.changeable
          xmi.value="none" />

        <Foundation.Core.AssociationEnd.targetScope
          xmi.value="instance" />

```

```

-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid17d" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid191.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid19b" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid192.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

```

```

<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid192.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
      xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid17d" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid192.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility

```

```

xmi.value="public" />

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid15e" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid193.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid193.CE">

  <Foundation.Core.ModelElement.name />

```

```

<Foundation.Core.ModelElement.visibility
xmi.value="public" />

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid17d" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid193.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

```

```

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid18a" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid194.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid194.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

```

```

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid17d" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid194.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid160" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>

```

```

</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Decision_StepGuideline_Step.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid17d" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid15f" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid19c">

  <Foundation.Core.ModelElement.name>Event</Foundation.Core
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.EventGuideline_Model_Entity.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

```



```

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu
        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.EventGuideline_Model_Entity.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid19c" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid151" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid19d">

    <Foundation.Core.ModelElement.name>GLIF3GuidelineBrows
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization

```

```

xmi.idref="GLIF3.GLIF3GuidelineBrowserGuidelineBrows
</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation
  xmi.id="txmiid19e.O">

    <Foundation.Core.ModelElement.name>browseGuideline<

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

```

```

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid19e.Return">

    <Foundation.Core.ModelElement.name>browseGuideli

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.GLIF3GuidelineBrowserGuidelineBrowser.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />

```

```

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid19d" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Interface
        xmi.idref="txmiid13c" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid19f">

    <Foundation.Core.ModelElement.name>GLIF3GuidelineParso
<Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.GLIF3GuidelineParsorGuidelineParsor.(
</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu
        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>

```

```

- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation
  xmi.id="txmiid1a0.O">

  <Foundation.Core.ModelElement.name>parseGuideline</f

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1a0.Return">

    <Foundation.Core.ModelElement.name>parseGuidelin

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-

```

```

        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid1a1.O">

    <Foundation.Core.ModelElement.name>createGuidelineSt

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>

```

```

-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1a1.Return">

    <Foundation.Core.ModelElement.name>createGuidelir

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>

```

```

    </Foundation.Core.Classifier.feature>
  </Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.GLIF3GuidelineParsorGuidelineParsor.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid19f" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Interface
    xmi.idref="txmiid13d" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid190">

  <Foundation.Core.ModelElement.name>GLIF_Entity</Foundat
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.GLIF_EntityThings.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

```



```

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu
        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.GLIF_EntityThings.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid190" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid1a2" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1a3">

    <Foundation.Core.ModelElement.name>Generate_Event_Acti
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>

```

```

<Foundation.Core.Generalization
  xmi.idref="GLIF3.Generate_Event_ActionProgramming_(

- </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid1a4.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiid1a5.a">

    <Foundation.Core.ModelElement.name>event</Foundation

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

</Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid105" />

  </Foundation.Core.StructuralFeature.type>
  -
    <Foundation.Core.ModelElement.taggedValue>
    -
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

      </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
  </Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid1a4.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
  - <Foundation.Core.AssociationEnd
    xmi.id="txmiid1a4.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

```

```

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid1a3" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1a4.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

```

```

        <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
    -
        <Foundation.Core.AssociationEnd.type>
        <Foundation.Core.Class
            xmi.idref="txmiid19c" />

        </Foundation.Core.AssociationEnd.type>
        </Foundation.Core.AssociationEnd>
        </Foundation.Core.Association.connection>
    </Foundation.Core.Association>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Generate_Event_ActionProgramming_Orient
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid1a3" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid16c" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1a6">

    <Foundation.Core.ModelElement.name>Get_Data_Action</Fo
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />

```

```

</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Get_Data_ActionProgramming_Oriented
  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid1a7.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>document
    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiid1a8.a">

    <Foundation.Core.ModelElement.name>attribute_to_be_assigned
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Foundation.Core.StructuralFeature.multiplicity>
    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid91" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid1a9.a">

        <Foundation.Core.ModelElement.name>data_item</Found

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>

```

```

-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid1aa" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid1ab.a">

    <Foundation.Core.ModelElement.name>primary_time</Fc

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope

```



```

xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
<Foundation.Data_Types.Expression>
    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>
</Foundation.Core.Attribute.initialValue>
-
<Foundation.Core.StructuralFeature.type>
<Foundation.Core.DataType
xmi.idref="txmiid91" />
</Foundation.Core.StructuralFeature.type>
-
<Foundation.Core.ModelElement.taggedValue>
-
<Foundation.Extension_Mechanisms.TaggedValue>
    <Foundation.Extension_Mechanisms.TaggedValue.tag>c
    <Foundation.Extension_Mechanisms.TaggedValue.value
</Foundation.Extension_Mechanisms.TaggedValue>
</Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
xmi.id="txmiid1ac.a">
    <Foundation.Core.ModelElement.name>variable_name</f
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
<Foundation.Core.Feature.ownerScope
xmi.value="classifier" />
<Foundation.Core.StructuralFeature.multiplicity>1..1</Four
<Foundation.Core.StructuralFeature.changeable

```

```

xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid91" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid1a7.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf

```

```

xmi.value="false" />

<Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1a7.CE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid1a6" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1a7.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable

```

```

xmi.value="true" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid185" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Get_Data_ActionProgramming_Oriented_Acti
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid1a6" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid16c" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1ad">

  <Foundation.Core.ModelElement.name>Get_Knowledge_Acti
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

```

```

<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
<Foundation.Core.Class.isActive
  xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Get_Knowledge_ActionProgramming_C

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid1ae.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid1af.a">

    <Foundation.Core.ModelElement.name>input_relationship

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

```

```

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four
<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid1b0" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid1b1.a">

    <Foundation.Core.ModelElement.name>variable_name</F

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />

```

```

<Foundation.Core.Feature.ownerScope
  xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four

<Foundation.Core.StructuralFeature.changeable
  xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
  xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid91" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
  </Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid1ae.ASS">

```

```

<Foundation.Core.ModelElement.name />
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1ae.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
      xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid1ad" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1ae.SE">

```



```

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid181" />

    </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
    </Foundation.Core.Association.connection>
    </Foundation.Core.Association>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Get_Knowledge_ActionProgramming_Oriented
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid1ad" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid16c" />
    </Foundation.Core.Generalization.supertype>

```

```

</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid16e">

    <Foundation.Core.ModelElement.name>Global_Concepts</Fo
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.Global_ConceptsThings.G" />

</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Global_ConceptsThings.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>

```

```

    <Foundation.Core.Class
      xmi.idref="txmiid16e" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid1a2" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1b2">

  <Foundation.Core.ModelElement.name>Guideline</Foundator
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.GuidelineNestable.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid1b3.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid1b4.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid1b5.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid1b6.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

```

```

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu
    <Foundation.Extension_Mechanisms.TaggedValue.value />

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid1b7.a">

    <Foundation.Core.ModelElement.name>algorithm</Found:

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.Feature.ownerScope
  xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
  xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
  xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid1b8" />

    </Foundation.Core.StructuralFeature.type>
-

```

```

    <Foundation.Core.ModelElement.taggedValue>
-
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

      </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid1b9.a">

    <Foundation.Core.ModelElement.name>data_items</Foun

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
  xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
  xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
  xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
  xmi.idref="txmiid1ba" />

```

```

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid1bb.a">

    <Foundation.Core.ModelElement.name>eligibility_criteria

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
  -

```

```

    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid1bc" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid1bd.a">

    <Foundation.Core.ModelElement.name>exceptions</Foundi

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid158" />

</Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid1b3.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
  - <Foundation.Core.AssociationEnd
    xmi.id="txmiid1b3.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable

```



```

xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid1b2" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1b3.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope

```

```

xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid161" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid1b4.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1b4.CE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

  <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

```

```

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid1b2" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1b4.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid186" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
  </Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid1b5.ASS">
  <Foundation.Core.ModelElement.name />

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
  - <Foundation.Core.AssociationEnd
    xmi.id="txmiid1b5.CE">

      <Foundation.Core.ModelElement.name />

      <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

      <Foundation.Core.AssociationEnd.isNavigable
        xmi.value="false" />

      <Foundation.Core.AssociationEnd.isOrdered
        xmi.value="false" />

      <Foundation.Core.AssociationEnd.aggregation
        xmi.value="none" />

      <Foundation.Core.AssociationEnd.multiplicity />

      <Foundation.Core.AssociationEnd.changeable
        xmi.value="none" />

      <Foundation.Core.AssociationEnd.targetScope
        xmi.value="instance" />
    -
      <Foundation.Core.AssociationEnd.type>
      <Foundation.Core.Class
        xmi.idref="txmiid1b2" />

      </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
  - <Foundation.Core.AssociationEnd
    xmi.id="txmiid1b5.SE">

      <Foundation.Core.ModelElement.name />

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid183" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid1b6.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  - <Foundation.Core.Association.connection>
    - <Foundation.Core.AssociationEnd
      xmi.id="txmiid1b6.CE">

```

```

<Foundation.Core.ModelElement.name />

<Foundation.Core.ModelElement.visibility
xmi.value="public" />

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid1b2" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1b6.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

```

```

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
  -
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid15e" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.GuidelineNestable.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />

  <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid1b2" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid19b" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Interface xmi.id="txmiid13c">

  <Foundation.Core.ModelElement.name>GuidelineBrowser</F
  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="true" />
- <Foundation.Core.ModelElement.namespace>

```

```

    <Model_Management.Package
      xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
  - <Foundation.Core.ModelElement.taggedValue>
    -
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

      </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
  - <Foundation.Core.Classifier.feature>
    - <Foundation.Core.Operation
      xmi.id="txmiid1be.O">

        <Foundation.Core.ModelElement.name>browseGuideline<

        <Foundation.Core.ModelElement.visibility
          xmi.value="public" />
        <Foundation.Core.Feature.ownerScope
          xmi.value="instance" />

        <Foundation.Core.BehavioralFeature.isQuery
          xmi.value="false" />

        <Foundation.Core.Operation.specification />

        <Foundation.Core.Operation.isPolymorphic
          xmi.value="false" />

        <Foundation.Core.Operation.concurrency
          xmi.value="sequential" />
      -
        <Foundation.Core.ModelElement.taggedValue>
      -
        <Foundation.Extension_Mechanisms.TaggedValue>

          <Foundation.Extension_Mechanisms.TaggedValue.tag>c

          <Foundation.Extension_Mechanisms.TaggedValue.value

          </Foundation.Extension_Mechanisms.TaggedValue>

```



```

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1be.Return">

      <Foundation.Core.ModelElement.name>browseGuideli

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Interface>
- <Foundation.Core.Interface xmi.id="txmiid108">

  <Foundation.Core.ModelElement.name>GuidelineExecutor</F
<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot

```

```

        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="true" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.GuidelineExecutorGuidelineExecutorInt
    </Foundation.Core.GeneralizableElement.generalization>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.GuidelineExecutorGuidelineExecutorUs
    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu
        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Interface>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.GuidelineExecutorGuidelineExecutorInternall
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Interface
        xmi.idref="txmiid108" />
    </Foundation.Core.Generalization.subtype>

```

```

- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Interface
    xmi.idref="txmiid1bf" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.GuidelineExecutorGuidelineExecutorUserFun
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Interface
    xmi.idref="txmiid108" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Interface
    xmi.idref="txmiidca" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Interface xmi.id="txmiid1bf">

  <Foundation.Core.ModelElement.name>GuidelineExecutorInt
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="true" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

```

```

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation
  xmi.id="txmiid1c0.O">

    <Foundation.Core.ModelElement.name>evaluateCriterion

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
  -
    <Foundation.Core.ModelElement.taggedValue>
    -
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

      </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Core.BehavioralFeature.parameter>
  - <Foundation.Core.Parameter
    xmi.id="txmiid1c0.Return">

    <Foundation.Core.ModelElement.name>evaluateCriter

    <Foundation.Core.ModelElement.visibility

```

```

xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>
    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>
</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="return" />
-
<Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid98" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c0.1">

    <Foundation.Core.ModelElement.name>encoding_lang
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>
    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>
</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind

```

```

xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid103" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c0.2">

<Foundation.Core.ModelElement.name>specification<

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>

<Foundation.Data_Types.Expression.language />

<Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid103" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid1c1.0">

```

```

<Foundation.Core.ModelElement.name>registerEvent</Fo

<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c1.Return">

    <Foundation.Core.ModelElement.name>registerEvent.

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c1.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>

```



```

</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c1.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c1.3">

    <Foundation.Core.ModelElement.name>PID</Foundatic

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c1.4">

    <Foundation.Core.ModelElement.name>GS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>

```

```

</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c1.5">

  <Foundation.Core.ModelElement.name>E</Foundation.

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
    xmi.idref="txmiid105" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid1c2.O">

  <Foundation.Core.ModelElement.name>triggerEvent</Fou

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery

```

```

xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c2.Return">

    <Foundation.Core.ModelElement.name>triggerEvent.R

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />

```

```

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c2.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="inout" />

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c2.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

```

```

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c2.3">

  <Foundation.Core.ModelElement.name>PID</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />

```

```

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c2.4">

    <Foundation.Core.ModelElement.name>GS</Foundation.

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="inout" />

-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
      xmi.idref="txmiidae" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c2.5">

    <Foundation.Core.ModelElement.name>E</Foundation.

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

```

```

-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid105" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Interface>
- <Foundation.Core.Interface xmi.id="txmiidca">

    <Foundation.Core.ModelElement.name>GuidelineExecutorUse
<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="true" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
- <Foundation.Core.ModelElement.taggedValue>

```



```

-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation
  xmi.id="txmiid1c3.O">

  <Foundation.Core.ModelElement.name>getCurrentStep</

  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
  xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
  xmi.value="false" />

  <Foundation.Core.Operation.concurrency
  xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>

```

```

- <Foundation.Core.Parameter
  xmi.id="txmiid1c3.Return">

  <Foundation.Core.ModelElement.name>getCurrentSte

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
    xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
    xmi.idref="txmiidae" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c3.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

```

```

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c3.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

```

```

- <Foundation.Core.Parameter
  xmi.id="txmiid1c3.3">

  <Foundation.Core.ModelElement.name>PID</Foundati

  <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
  xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid1c4.0">

  <Foundation.Core.ModelElement.name>setCurrentStep</I

  <Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
  xmi.value="false" />

```

```

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c
    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c4.Return">

    <Foundation.Core.ModelElement.name>setCurrentSte|

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-

```

```

    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1c4.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
        xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1c4.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-

```

```

    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c4.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-

```

```

    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1c4.4">

    <Foundation.Core.ModelElement.name>GS</Foundation

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
        xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
            xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid1c5.O">

    <Foundation.Core.ModelElement.name>getTrace</Founda

```



```

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1c5.Return">

    <Foundation.Core.ModelElement.name>getTrace.Retu

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

```

```

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiidb0" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c5.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter

```

```

xmi.id="txmiid1c5.2">

  <Foundation.Core.ModelElement.name>GLID</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c5.3">

  <Foundation.Core.ModelElement.name>PID</Foundati

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```

```

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid1c6.O">

    <Foundation.Core.ModelElement.name>setTrace</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

```

```

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
<Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c6.Return">

  <Foundation.Core.ModelElement.name>setTrace.Retui

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

  <Foundation.Core.DataType
xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c6.1">

  <Foundation.Core.ModelElement.name>GEECID</Foun

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>

```

```

-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c6.2">

    <Foundation.Core.ModelElement.name>GLID</Foundat

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1c6.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1c6.4">

    <Foundation.Core.ModelElement.name>GS</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>

```

```

-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidae" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid1c7.O">

    <Foundation.Core.ModelElement.name>acceptActionReco

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-

```



```

    <Foundation.Core.ModelElement.taggedValue>
-
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

      </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1c7.Return">

      <Foundation.Core.ModelElement.name>acceptActionR

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1c7.1">

```

```

<Foundation.Core.ModelElement.name>GEECID</Foun

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c7.2">

  <Foundation.Core.ModelElement.name>GLID</Founda

  <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c7.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c7.4">

```

```

    <Foundation.Core.ModelElement.name>AS</Foundation
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiidb2" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid1c8.O">

    <Foundation.Core.ModelElement.name>refuseActionReco

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

    <Foundation.Core.Operation.specification />

```

```

<Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

<Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1c8.Return">

    <Foundation.Core.ModelElement.name>refuseActionR

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

      </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c8.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c8.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-

```

```

    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c8.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

```

```

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1c8.4">

    <Foundation.Core.ModelElement.name>AS</Foundation

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiidb2" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid1c9.0">

    <Foundation.Core.ModelElement.name>completeAction</

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

```



```

<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

<Foundation.Core.BehavioralFeature.isQuery
  xmi.value="false" />

<Foundation.Core.Operation.specification />

<Foundation.Core.Operation.isPolymorphic
  xmi.value="false" />

<Foundation.Core.Operation.concurrency
  xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1c9.Return">

      <Foundation.Core.ModelElement.name>completeActio

      <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="return" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiida6" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c9.1">

<Foundation.Core.ModelElement.name>GEECID</Foun

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>

<Foundation.Data_Types.Expression.language />

<Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

<Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c9.2">

```

```

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c9.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

```

```

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1c9.4">

    <Foundation.Core.ModelElement.name>AS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb2" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>

```

```

- <Foundation.Core.Operation
  xmi.id="txmiid1ca.O">

  <Foundation.Core.ModelElement.name>acceptDecision</I

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.Feature.ownerScope
  xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1ca.Return">

  <Foundation.Core.ModelElement.name>acceptDecision

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1ca.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType

```

```

        xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1ca.2">

        <Foundation.Core.ModelElement.name>GLID</Foundati

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
            xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
                xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1ca.3">

        <Foundation.Core.ModelElement.name>PID</Foundatic

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1ca.4">

    <Foundation.Core.ModelElement.name>CS</Foundation

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType

```



```

        xmi.idref="txmiidb3" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
    xmi.id="txmiid1cb.O">

        <Foundation.Core.ModelElement.name>refuseDecision</F

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="instance" />

        <Foundation.Core.BehavioralFeature.isQuery
            xmi.value="false" />

        <Foundation.Core.Operation.specification />

        <Foundation.Core.Operation.isPolymorphic
            xmi.value="false" />

        <Foundation.Core.Operation.concurrency
            xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
            xmi.id="txmiid1cb.Return">

            <Foundation.Core.ModelElement.name>refuseDecisior

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cb.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cb.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cb.3">

    <Foundation.Core.ModelElement.name>PID</Foundatic

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cb.4">

    <Foundation.Core.ModelElement.name>CS</Foundator

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiidb3" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid1cc.O">

    <Foundation.Core.ModelElement.name>getOptions</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

```

```

</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1cc.Return">

      <Foundation.Core.ModelElement.name>getOptions.Re

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

          <Foundation.Data_Types.Expression.language />

          <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

      </Foundation.Core.Parameter.defaultValue>

      <Foundation.Core.Parameter.kind
xmi.value="return" />
-
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1cc.1">

      <Foundation.Core.ModelElement.name>GEECID</Foun

      <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
      <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cc.2">

    <Foundation.Core.ModelElement.name>GLID</Foundat

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

```

```

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1cc.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1cc.4">

    <Foundation.Core.ModelElement.name>DS</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

```



```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb4" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid1cd.O">

    <Foundation.Core.ModelElement.name>selectOption</Fou

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c
        <Foundation.Extension_Mechanisms.TaggedValue.value
</Foundation.Extension_Mechanisms.TaggedValue>
</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1cd.Return">

        <Foundation.Core.ModelElement.name>selectOption.F
        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cd.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

```

```

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cd.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cd.3">

        <Foundation.Core.ModelElement.name>PID</Foundati

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
xmi.idref="txmiid93" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cd.4">

        <Foundation.Core.ModelElement.name>DS</Foundatio

```

```

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb4" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cd.5">

    <Foundation.Core.ModelElement.name>DO</Foundatio

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

```

```

        <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
        <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb5" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid1ce.O">

    <Foundation.Core.ModelElement.name>getBranches</Fou

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>

```

```

-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1ce.Return">

    <Foundation.Core.ModelElement.name>getBranches.R

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiidb0" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1ce.1">

    <Foundation.Core.ModelElement.name>GEECID</Foun

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1ce.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

```



```

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1ce.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1ce.4">

    <Foundation.Core.ModelElement.name>BS</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid1cf.O">

    <Foundation.Core.ModelElement.name>selectBranch</Fou

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

    <Foundation.Core.Operation.concurrency
xmi.value="sequential" />
-
    <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c
        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1cf.Return">

        <Foundation.Core.ModelElement.name>selectBranch.f

        <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="return" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiida6" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cf.1">

        <Foundation.Core.ModelElement.name>GEECID</Foun

        <Foundation.Core.ModelElement.visibility

```

```

xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>
    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>
</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cf.2">

    <Foundation.Core.ModelElement.name>GLID</Founda

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>
    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>
</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind

```

```

xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
    xmi.idref="txmiid93" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1cf.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
    xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
        xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
    xmi.id="txmiid1cf.4">

    <Foundation.Core.ModelElement.name>BS</Foundati

    <Foundation.Core.ModelElement.visibility

```

```

xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
<Foundation.Data_Types.Expression>
    <Foundation.Data_Types.Expression.language />
    <Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>
</Foundation.Core.Parameter.defaultValue>

<Foundation.Core.Parameter.kind
xmi.value="inout" />
-
<Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiidb6" />

</Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1cf.5">

    <Foundation.Core.ModelElement.name>GS</Foundation
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
<Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>
        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
    </Foundation.Data_Types.Expression>
</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind

```

```

        xmi.value="inout" />
      -
      <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
          xmi.idref="txmiidae" />

      </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>

  </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
  xmi.id="txmiid1d0.O">

    <Foundation.Core.ModelElement.name>continueSynchr

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="instance" />

    <Foundation.Core.BehavioralFeature.isQuery
      xmi.value="false" />

    <Foundation.Core.Operation.specification />

    <Foundation.Core.Operation.isPolymorphic
      xmi.value="false" />

    <Foundation.Core.Operation.concurrency
      xmi.value="sequential" />
  -
    <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
  -

```

```

    <Foundation.Core.BehavioralFeature.parameter>
-   <Foundation.Core.Parameter
        xmi.id="txmiid1d0.Return">

        <Foundation.Core.ModelElement.name>continueSyncr

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

                <Foundation.Data_Types.Expression.body />

            </Foundation.Data_Types.Expression>

        </Foundation.Core.Parameter.defaultValue>

        <Foundation.Core.Parameter.kind
            xmi.value="return" />
-
        <Foundation.Core.Parameter.type>

            <Foundation.Core.DataType
                xmi.idref="txmiid98" />

        </Foundation.Core.Parameter.type>
    </Foundation.Core.Parameter>
-   <Foundation.Core.Parameter
        xmi.id="txmiid1d0.1">

        <Foundation.Core.ModelElement.name>GEECID</Foun

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
-
        <Foundation.Core.Parameter.defaultValue>
-
            <Foundation.Data_Types.Expression>

                <Foundation.Data_Types.Expression.language />

```



```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
xmi.id="txmiid1d0.2">

    <Foundation.Core.ModelElement.name>GLID</Foundati

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiid93" />

    </Foundation.Core.Parameter.type>

```

```

</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1d0.3">

    <Foundation.Core.ModelElement.name>PID</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
  xmi.value="inout" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
  xmi.idref="txmiid93" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1d0.4">

    <Foundation.Core.ModelElement.name>SS</Foundati

    <Foundation.Core.ModelElement.visibility
  xmi.value="private" />
-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

```

```

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Parameter.defaultValue>

    <Foundation.Core.Parameter.kind
xmi.value="inout" />
-
    <Foundation.Core.Parameter.type>

        <Foundation.Core.DataType
xmi.idref="txmiidb7" />

    </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

    </Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Interface>
- <Foundation.Core.Interface xmi.id="txmiid13d">

    <Foundation.Core.ModelElement.name>GuidelineParsor</Fou
<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="true" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

```

```

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Operation
  xmi.id="txmiid1d1.O">

  <Foundation.Core.ModelElement.name>parseGuideline</f

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
    xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
    xmi.value="false" />

  <Foundation.Core.Operation.concurrency
    xmi.value="sequential" />
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1d1.Return">

  <Foundation.Core.ModelElement.name>parseGuideline

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

```

```

-
  <Foundation.Core.Parameter.defaultValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Parameter.defaultValue>

  <Foundation.Core.Parameter.kind
xmi.value="return" />
-
  <Foundation.Core.Parameter.type>

    <Foundation.Core.DataType
xmi.idref="txmiida6" />

  </Foundation.Core.Parameter.type>
</Foundation.Core.Parameter>

</Foundation.Core.BehavioralFeature.parameter>
</Foundation.Core.Operation>
- <Foundation.Core.Operation
xmi.id="txmiid1d2.0">

  <Foundation.Core.ModelElement.name>createGuidelineSt

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Feature.ownerScope
xmi.value="instance" />

  <Foundation.Core.BehavioralFeature.isQuery
xmi.value="false" />

  <Foundation.Core.Operation.specification />

  <Foundation.Core.Operation.isPolymorphic
xmi.value="false" />

  <Foundation.Core.Operation.concurrency

```

```

xmi.value="sequential" />
-
<Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>
    <Foundation.Extension_Mechanisms.TaggedValue.tag>c
    <Foundation.Extension_Mechanisms.TaggedValue.value
  </Foundation.Extension_Mechanisms.TaggedValue>
</Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Core.BehavioralFeature.parameter>
- <Foundation.Core.Parameter
  xmi.id="txmiid1d2.Return">
    <Foundation.Core.ModelElement.name>createGuidelir
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
-
    <Foundation.Core.Parameter.defaultValue>
-
      <Foundation.Data_Types.Expression>
        <Foundation.Data_Types.Expression.language />
        <Foundation.Data_Types.Expression.body />
      </Foundation.Data_Types.Expression>
    </Foundation.Core.Parameter.defaultValue>
    <Foundation.Core.Parameter.kind
    xmi.value="return" />
-
    <Foundation.Core.Parameter.type>
      <Foundation.Core.DataType
      xmi.idref="txmiida6" />
    </Foundation.Core.Parameter.type>
  </Foundation.Core.Parameter>

```

```

        </Foundation.Core.BehavioralFeature.parameter>
    </Foundation.Core.Operation>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Interface>
- <Foundation.Core.Class xmi.id="txmiid15e">

    <Foundation.Core.ModelElement.name>Guideline_Exception<
<Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
<Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
<Foundation.Core.Generalization
    xmi.idref="GLIF3.Guideline_ExceptionGLIF_Entity.G" />

</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
    <Foundation.Core.AssociationEnd
        xmi.idref="txmiid1d3.CE" />
    <Foundation.Core.AssociationEnd
        xmi.idref="txmiid1d4.CE" />
    <Foundation.Core.AssociationEnd
        xmi.idref="txmiid1d5.CE" />
</Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

```

```

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid1d6.a">

  <Foundation.Core.ModelElement.name>condition</Founda

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid1d7" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

```



```

        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid1d8.a">

    <Foundation.Core.ModelElement.name>exception_event<

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid105" />

    </Foundation.Core.StructuralFeature.type>
  -
    <Foundation.Core.ModelElement.taggedValue>
  -

```

```

<Foundation.Extension_Mechanisms.TaggedValue>

  <Foundation.Extension_Mechanisms.TaggedValue.tag>c

  <Foundation.Extension_Mechanisms.TaggedValue.value

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid1d9.a">

  <Foundation.Core.ModelElement.name>next_step</Found

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiidae" />

  </Foundation.Core.StructuralFeature.type>

```

```

-
  <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>c

    <Foundation.Extension_Mechanisms.TaggedValue.value

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
  </Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid1d3.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1d3.CE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

  <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

```

```

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid15e" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1d3.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid183" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>

```

```

    </Foundation.Core.Association.connection>
  </Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid1d4.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1d4.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
      xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid15e" />

  </Foundation.Core.AssociationEnd.type>

```

```

</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1d4.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid19c" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid1d5.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract

```

```

    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid1d5.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid15e" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid1d5.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered

```

```

xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid15f" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Guideline_ExceptionGLIF_Entity.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid15e" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid190" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid16b">

  <Foundation.Core.ModelElement.name>Guideline_Expression
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf

```



```

xmi.value="false" />

<Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
<Foundation.Core.Class.isActive
xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Guideline_ExpressionGuideline_Model_

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid1da.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid1db.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiid1dc.a">

    <Foundation.Core.ModelElement.name>encoding_language

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

```

```

    <Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
xmi.idref="txmiid91" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
xmi.id="txmiid1dd.a">

    <Foundation.Core.ModelElement.name>get_data_items</
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
    <Foundation.Core.Feature.ownerScope

```

```

xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four

<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid1de" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid1df.a">

  <Foundation.Core.ModelElement.name>get_knowledge_it

```

```

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid1e0" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid1e1.a">

```

```

<Foundation.Core.ModelElement.name>specification</Fou

<Foundation.Core.ModelElement.visibility
xmi.value="private" />
<Foundation.Core.Feature.ownerScope
xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four

<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid91" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>

```

```

        </Foundation.Core.Attribute>
    </Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
    xmi.id="txmiid1da.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Core.Association.connection>
    - <Foundation.Core.AssociationEnd
        xmi.id="txmiid1da.CE">

        <Foundation.Core.ModelElement.name />

        <Foundation.Core.ModelElement.visibility
            xmi.value="public" />

        <Foundation.Core.AssociationEnd.isNavigable
            xmi.value="false" />

        <Foundation.Core.AssociationEnd.isOrdered
            xmi.value="false" />

        <Foundation.Core.AssociationEnd.aggregation
            xmi.value="none" />

        <Foundation.Core.AssociationEnd.multiplicity />

        <Foundation.Core.AssociationEnd.changeable
            xmi.value="none" />

        <Foundation.Core.AssociationEnd.targetScope
            xmi.value="instance" />
    -
        <Foundation.Core.AssociationEnd.type>
        <Foundation.Core.Class
            xmi.idref="txmiid16b" />

```

```

        </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid1da.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid1a6" />

    </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
    </Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
    xmi.id="txmiid1db.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

```

```

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid1db.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid16b" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid1db.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="true" />

```



```

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid1ad" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Guideline_ExpressionGuideline_Model_Entity"
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid16b" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid151" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid151">

  <Foundation.Core.ModelElement.name>Guideline_Model_Ent
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />

```

```

<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="true" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Guideline_Model_EntityGLIF_Entity.G"

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid1e2.a">

    <Foundation.Core.ModelElement.name>name</Foundation

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope

```

```

xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
<Foundation.Data_Types.Expression>
<Foundation.Data_Types.Expression.language />
<Foundation.Data_Types.Expression.body />
</Foundation.Data_Types.Expression>
</Foundation.Core.Attribute.initialValue>
-
<Foundation.Core.StructuralFeature.type>
<Foundation.Core.DataType
xmi.idref="txmiid91" />
</Foundation.Core.StructuralFeature.type>
-
<Foundation.Core.ModelElement.taggedValue>
-
<Foundation.Extension_Mechanisms.TaggedValue>
<Foundation.Extension_Mechanisms.TaggedValue.tag>c
<Foundation.Extension_Mechanisms.TaggedValue.value
</Foundation.Extension_Mechanisms.TaggedValue>
</Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
xmi.id="GLIF3.Guideline_Model_EntityGLIF_Entity.G">
<Foundation.Core.ModelElement.name />
<Foundation.Core.ModelElement.visibility
xmi.value="public" />
<Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
<Foundation.Core.Class
xmi.idref="txmiid151" />
</Foundation.Core.Generalization.subtype>

```

```

- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid190" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid15f">

  <Foundation.Core.ModelElement.name>Guideline_Step</Four
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
<Foundation.Core.Class.isActive
  xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Guideline_StepGuideline_Model_Entity

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Guideline_StepGuideline_Model_Entity.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility

```

```

xmi.value="public" />

<Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid15f" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid151" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid181">

  <Foundation.Core.ModelElement.name>Knowledge_Item</Fc
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Knowledge_ItemBasic_Data_Type.G" /
  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

```

```

        </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Knowledge_ItemBasic_Data_Type.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid181" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid16d" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1e3">

    <Foundation.Core.ModelElement.name>Literal_Data_Item</f
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.Literal_Data_ItemData_Item.G" />

    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-

```

```

    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Literal_Data_ItemData_Item.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid1e3" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid185" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1e4">

    <Foundation.Core.ModelElement.name>Logical_Expression_C
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-

```

```

    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
      xmi.idref="GLIF3.Logical_Expression_Of_Guideline_Step

    </Foundation.Core.GeneralizableElement.generalization>
  - <Foundation.Core.ModelElement.taggedValue>
    -
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

      </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Logical_Expression_Of_Guideline_StepGLIF_
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid1e4" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid190" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1e5">

  <Foundation.Core.ModelElement.name>Macro_Action</Found
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />

```



```

    <Foundation.Core.Class.isActive
      xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
      xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
      xmi.idref="GLIF3.Macro_ActionAction_Specification.G" />

    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Macro_ActionAction_Specification.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
      xmi.idref="txmiid1e5" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
      xmi.idref="txmiid150" />
    </Foundation.Core.Generalization.supertype>
  </Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1e6">

    <Foundation.Core.ModelElement.name>Macro_Action_Step</
    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

```

```

<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
<Foundation.Core.Class.isActive
  xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
      xmi.idref="GLIF3.Macro_Action_StepAction_Step.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Macro_Action_StepAction_Step.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid1e6" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid152" />

```

```

    </Foundation.Core.Generalization.supertype>
  </Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1e7">

    <Foundation.Core.ModelElement.name>Macro_Decision_Step
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
      xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Macro_Decision_StepDecision_Step.G"

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Macro_Decision_StepDecision_Step.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />

```

```

- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid1e7" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid17d" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1e8">

  <Foundation.Core.ModelElement.name>Medically_Oriented_
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
<Foundation.Core.Class.isActive
  xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Medically_Oriented_Action_Specificati
  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid1e9.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

  <Foundation.Extension_Mechanisms.TaggedValue.tag>docu
  <Foundation.Extension_Mechanisms.TaggedValue.value />

```

```

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid1ea.a">

  <Foundation.Core.ModelElement.name>medical_task</Fo

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid1eb" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
    </Foundation.Core.Classifier.feature>
    </Foundation.Core.Class>
- <Foundation.Core.Association
    xmi.id="txmiid1e9.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid1e9.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
        xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
        xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
        xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
        xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope

```

```

xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid1e8" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1e9.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid1e3" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Medically_Oriented_Action_SpecificationActi
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility

```

```

xmi.value="public" />

<Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid1e8" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid150" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1ec">

  <Foundation.Core.ModelElement.name>Message_Action</Fou
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Message_ActionProgramming_Orientec
  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

```



```

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid1ed.a">

  <Foundation.Core.ModelElement.name>message</Founda

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid91" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid1ee.a">

    <Foundation.Core.ModelElement.name>message_destina

    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid91" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c
        <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
    </Foundation.Core.Classifier.feature>
    </Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Message_ActionProgramming_Oriented_Acti
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid1ec" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid16c" />
    </Foundation.Core.Generalization.supertype>
    </Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid19b">

    <Foundation.Core.ModelElement.name>Nestable</Foundation.
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>

```

```

-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.NestableGuideline_Model_Entity.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.NestableGuideline_Model_Entity.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid19b" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid151" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1ef">

  <Foundation.Core.ModelElement.name>Patient_State_Step</
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract

```

```

        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.Patient_State_StepGuideline_Step.G" /

    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
    <Foundation.Core.AssociationEnd
        xmi.idref="txmiid1f0.CE" />
    <Foundation.Core.AssociationEnd
        xmi.idref="txmiid1f1.CE" />
    </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
    xmi.id="txmiid1f2.a">

        <Foundation.Core.ModelElement.name>next_step</Found

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

```

```

    <Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
xmi.idref="txmiidae" />

</Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
xmi.id="txmiid1f3.a">

    <Foundation.Core.ModelElement.name>patient_state_des

    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

```

```

    <Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
xmi.idref="txmiid1d7" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
    </Foundation.Core.Classifier.feature>
    </Foundation.Core.Class>
- <Foundation.Core.Association
xmi.id="txmiid1f0.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot

```

```

    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid1f0.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid1ef" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid1f0.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

```



```

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid15f" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid1f1.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  - <Foundation.Core.Association.connection>
    - <Foundation.Core.AssociationEnd
      xmi.id="txmiid1f1.CE">

      <Foundation.Core.ModelElement.name />

      <Foundation.Core.ModelElement.visibility

```

```

xmi.value="public" />

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid1ef" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1f1.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable

```

```

xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid183" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Patient_State_StepGuideline_Step.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid1ef" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid15f" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid16c">

  <Foundation.Core.ModelElement.name>Programming_Orient
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package

```

```

        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.Programming_Oriented_Action_Specifi

    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Programming_Oriented_Action_Specification
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid16c" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid150" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1f4">

    <Foundation.Core.ModelElement.name>RuleInChoice</Foundi
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

```

```

        <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.RuleInChoiceChoice.G" />

</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
    <Foundation.Core.AssociationEnd
        xmi.idref="txmiid1f5.CE" />
    <Foundation.Core.AssociationEnd
        xmi.idref="txmiid1f6.CE" />
    <Foundation.Core.AssociationEnd
        xmi.idref="txmiid1f7.CE" />
    <Foundation.Core.AssociationEnd
        xmi.idref="txmiid1f8.CE" />
</Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
    xmi.id="txmiid1f9.a">

        <Foundation.Core.ModelElement.name>rule_in</Foundatio

        <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.Feature.ownerScope

```

```

xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four

<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid1bc" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid1fa.a">

  <Foundation.Core.ModelElement.name>rule_out</Foundat

```

```

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid1bc" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid1fb.a">

```

```

<Foundation.Core.ModelElement.name>strict_rule_in</Fc
<Foundation.Core.ModelElement.visibility
xmi.value="private" />
<Foundation.Core.Feature.ownerScope
xmi.value="classifier" />

<Foundation.Core.StructuralFeature.multiplicity>1..1</Four
<Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

<Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
<Foundation.Core.Attribute.initialValue>
-
  <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

  </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid1bc" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>

```



```

</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid1fc.a">

  <Foundation.Core.ModelElement.name>strict_rule_out</I

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.Feature.ownerScope
  xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
      xmi.idref="txmiid1bc" />

  </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
      <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>c

        <Foundation.Extension_Mechanisms.TaggedValue.value

```

```

</Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
    </Foundation.Core.Classifier.feature>
    </Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid1f5.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
- <Foundation.Core.Association.connection>
  - <Foundation.Core.AssociationEnd
    xmi.id="txmiid1f5.CE">

      <Foundation.Core.ModelElement.name />

      <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

      <Foundation.Core.AssociationEnd.isNavigable
        xmi.value="false" />

      <Foundation.Core.AssociationEnd.isOrdered
        xmi.value="false" />

      <Foundation.Core.AssociationEnd.aggregation
        xmi.value="none" />

      <Foundation.Core.AssociationEnd.multiplicity />

      <Foundation.Core.AssociationEnd.changeable
        xmi.value="none" />

      <Foundation.Core.AssociationEnd.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>

```

```

    <Foundation.Core.Class
      xmi.idref="txmiid1f4" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1f5.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
      xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
      xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid183" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid1f6.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />

```

```

<Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

<Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
xmi.id="txmiid1f6.CE">

<Foundation.Core.ModelElement.name />

<Foundation.Core.ModelElement.visibility
xmi.value="public" />

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
xmi.idref="txmiid1f4" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
xmi.id="txmiid1f6.SE">

<Foundation.Core.ModelElement.name />

<Foundation.Core.ModelElement.visibility
xmi.value="public" />

```

```

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid183" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid1f7.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1f7.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

```

```

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid1f4" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1f7.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

```

```

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
      xmi.idref="txmiid183" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Association
  xmi.id="txmiid1f8.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
- <Foundation.Core.Association.connection>
  - <Foundation.Core.AssociationEnd
    xmi.id="txmiid1f8.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
      xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
      xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable

```

```

xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid1f4" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1f8.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid183" />

    </Foundation.Core.AssociationEnd.type>
  </Foundation.Core.AssociationEnd>
  </Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization

```



```

xmi.id="GLIF3.RuleInChoiceChoice.G">
<Foundation.Core.ModelElement.name />
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />

  <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid1f4" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid17e" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1fd">

  <Foundation.Core.ModelElement.name>Select_Action</Found
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Select_ActionProgramming_Oriented_/

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid1fe.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-

```

```

<Foundation.Extension_Mechanisms.TaggedValue>

  <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

  <Foundation.Extension_Mechanisms.TaggedValue.value />

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid1ff.a">

  <Foundation.Core.ModelElement.name>attribute_to_be_a

  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

  <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

  <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid91" />

  </Foundation.Core.StructuralFeature.type>

```

```

- <Foundation.Core.ModelElement.taggedValue>
-   <Foundation.Extension_Mechanisms.TaggedValue>
      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value
    </Foundation.Extension_Mechanisms.TaggedValue>
  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
  xmi.id="txmiid200.a">

    <Foundation.Core.ModelElement.name>from_list</Founda

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
-   <Foundation.Core.Attribute.initialValue>
-     <Foundation.Data_Types.Expression>
          <Foundation.Data_Types.Expression.language />
          <Foundation.Data_Types.Expression.body />
        </Foundation.Data_Types.Expression>
    </Foundation.Core.Attribute.initialValue>
-   <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType

```

```

        xmi.idref="txmiid169" />
    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid201.a">

        <Foundation.Core.ModelElement.name>variable_name</F

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>

```

```

-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid91" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c
      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid1fe.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1fe.CE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

```

```

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid1fd" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid1fe.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-

```

```

        <Foundation.Core.AssociationEnd.type>
        <Foundation.Core.Class
            xmi.idref="txmiid16b" />

        </Foundation.Core.AssociationEnd.type>
        </Foundation.Core.AssociationEnd>
        </Foundation.Core.Association.connection>
    </Foundation.Core.Association>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Select_ActionProgramming_Oriented_Action"
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid1fd" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid16c" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid202">

    <Foundation.Core.ModelElement.name>Subguideline_Action<
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization

```

```

xmi.idref="GLIF3.Subguideline_ActionProgramming_Orie

</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid203.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

      <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiid204.a">

      <Foundation.Core.ModelElement.name>action_detail</Fou

      <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
      <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

      <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

      <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

      <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

```



```

</Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiid196" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
</Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid203.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid203.CE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

```

```

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
  xmi.idref="txmiid202" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid203.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

```

```

        <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
    -
        <Foundation.Core.AssociationEnd.type>
        <Foundation.Core.Class
            xmi.idref="txmiid19b" />

        </Foundation.Core.AssociationEnd.type>
        </Foundation.Core.AssociationEnd>
        </Foundation.Core.Association.connection>
    </Foundation.Core.Association>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Subguideline_ActionProgramming_Oriented_
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid202" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid16c" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid205">

    <Foundation.Core.ModelElement.name>Synchronization_Step
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>

```

```

-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Synchronization_StepGuideline_Step.G

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid206.CE" />
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid207.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
  -
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
  - <Foundation.Core.Attribute
    xmi.id="txmiid208.a">

    <Foundation.Core.ModelElement.name>continuation</Fou

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
      xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
      xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
      xmi.value="instance" />
  -
    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

```

```

        <Foundation.Data_Types.Expression.language />

        <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
        xmi.idref="txmiid209" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Attribute>
- <Foundation.Core.Attribute
    xmi.id="txmiid20a.a">

        <Foundation.Core.ModelElement.name>next_step</Found

        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
    <Foundation.Core.Feature.ownerScope
        xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

    <Foundation.Core.StructuralFeature.changeable
        xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
        xmi.value="instance" />
-

```

```

    <Foundation.Core.Attribute.initialValue>
  -
    <Foundation.Data_Types.Expression>

      <Foundation.Data_Types.Expression.language />

      <Foundation.Data_Types.Expression.body />

    </Foundation.Data_Types.Expression>

  </Foundation.Core.Attribute.initialValue>
-
  <Foundation.Core.StructuralFeature.type>
  <Foundation.Core.DataType
    xmi.idref="txmiidae" />

  </Foundation.Core.StructuralFeature.type>
-
  <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

      <Foundation.Extension_Mechanisms.TaggedValue.tag>c

      <Foundation.Extension_Mechanisms.TaggedValue.value

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
  </Foundation.Core.Attribute>
  </Foundation.Core.Classifier.feature>
</Foundation.Core.Class>
- <Foundation.Core.Association
  xmi.id="txmiid206.ASS">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.Association.connection>

```

```

- <Foundation.Core.AssociationEnd
  xmi.id="txmiid206.CE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="false" />

  <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

  <Foundation.Core.AssociationEnd.aggregation
    xmi.value="none" />

  <Foundation.Core.AssociationEnd.multiplicity />

  <Foundation.Core.AssociationEnd.changeable
    xmi.value="none" />

  <Foundation.Core.AssociationEnd.targetScope
    xmi.value="instance" />
-
  <Foundation.Core.AssociationEnd.type>
  <Foundation.Core.Class
    xmi.idref="txmiid205" />

  </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
  xmi.id="txmiid206.SE">

  <Foundation.Core.ModelElement.name />

  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

  <Foundation.Core.AssociationEnd.isNavigable
    xmi.value="true" />

  <Foundation.Core.AssociationEnd.isOrdered
    xmi.value="false" />

```

```

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
xmi.idref="txmiid1e4" />

    </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
    </Foundation.Core.Association.connection>
    </Foundation.Core.Association>
- <Foundation.Core.Association
xmi.id="txmiid207.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
xmi.id="txmiid207.CE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

```



```

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid205" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid207.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class

```

```

        xmi.idref="txmiid15f" />

        </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Synchronization_StepGuideline_Step.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid205" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid15f" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid1a2">

    <Foundation.Core.ModelElement.name>Things</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

```

```

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Class xmi.id="txmiid20b">

    <Foundation.Core.ModelElement.name>Three_Valued_Criteri
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.Three_Valued_CriterionCriterion.G" />

    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Three_Valued_CriterionCriterion.G">

```

```

<Foundation.Core.ModelElement.name />
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />

  <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid20b" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid183" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid160">

  <Foundation.Core.ModelElement.name>Triggering_Event</Fc
<Foundation.Core.ModelElement.visibility
  xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Triggering_EventGLIF_Entity.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid20c.CE" />
  </Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

```

```

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu
    <Foundation.Extension_Mechanisms.TaggedValue.value />

</Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
    xmi.id="txmiid20d.a">

    <Foundation.Core.ModelElement.name>triggering_event<
    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

    <Foundation.Core.StructuralFeature.multiplicity>1..1</Four
    <Foundation.Core.StructuralFeature.changeable
    xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
    xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
    <Foundation.Data_Types.Expression>

    <Foundation.Data_Types.Expression.language />

    <Foundation.Data_Types.Expression.body />

</Foundation.Data_Types.Expression>

</Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
    xmi.idref="txmiid105" />

</Foundation.Core.StructuralFeature.type>
-

```

```

    <Foundation.Core.ModelElement.taggedValue>
    -
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c

            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
    </Foundation.Core.Classifier.feature>
    </Foundation.Core.Class>
    - <Foundation.Core.Association
        xmi.id="txmiid20c.ASS">
        <Foundation.Core.ModelElement.name />
        <Foundation.Core.ModelElement.visibility
            xmi.value="private" />
        <Foundation.Core.GeneralizableElement.isRoot
            xmi.value="false" />
        <Foundation.Core.GeneralizableElement.isLeaf
            xmi.value="false" />

        <Foundation.Core.GeneralizableElement.isAbstract
            xmi.value="false" />
    - <Foundation.Core.Association.connection>
        - <Foundation.Core.AssociationEnd
            xmi.id="txmiid20c.CE">

            <Foundation.Core.ModelElement.name />

            <Foundation.Core.ModelElement.visibility
                xmi.value="public" />

            <Foundation.Core.AssociationEnd.isNavigable
                xmi.value="false" />

            <Foundation.Core.AssociationEnd.isOrdered
                xmi.value="false" />

            <Foundation.Core.AssociationEnd.aggregation
                xmi.value="none" />

            <Foundation.Core.AssociationEnd.multiplicity />

```

```

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid160" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
    xmi.id="txmiid20c.SE">

    <Foundation.Core.ModelElement.name />

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid19c" />

    </Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>

```

```

</Foundation.Core.Association>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Triggering_EventGLIF_Entity.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid160" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid190" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid20e">

  <Foundation.Core.ModelElement.name>Utility_Choice</Founc
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  <Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Utility_ChoiceChoice.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

```



```

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu
        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Utility_ChoiceChoice.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid20e" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid17e" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid20f">

    <Foundation.Core.ModelElement.name>Utility_Choice_Step<
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization

```

```

        xmi.idref="GLIF3.Utility_Choice_StepChoice_Step.G" />
    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Utility_Choice_StepChoice_Step.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid20f" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid17f" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid210">

    <Foundation.Core.ModelElement.name>Variable_Data_Item<
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    <Foundation.Core.Class.isActive
        xmi.value="false" />

```

```

- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
  </Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Variable_Data_ItemData_Item.G" />

  </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

  </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
  xmi.id="GLIF3.Variable_Data_ItemData_Item.G">
  <Foundation.Core.ModelElement.name />
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
  <Foundation.Core.Class
    xmi.idref="txmiid210" />
  </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
  <Foundation.Core.Class
    xmi.idref="txmiid185" />
  </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid211">

  <Foundation.Core.ModelElement.name>Weighted_Choice</Fo
  <Foundation.Core.ModelElement.visibility
    xmi.value="public" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />

```

```

<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
<Foundation.Core.Class.isActive
  xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Package
    xmi.idref="txmiid4" />
</Foundation.Core.ModelElement.namespace>
-
  <Foundation.Core.GeneralizableElement.generalization>
  <Foundation.Core.Generalization
    xmi.idref="GLIF3.Weighted_ChoiceChoice.G" />

</Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.Classifier.associationEnd>
  <Foundation.Core.AssociationEnd
    xmi.idref="txmiid212.CE" />
</Foundation.Core.Classifier.associationEnd>
- <Foundation.Core.ModelElement.taggedValue>
-
  <Foundation.Extension_Mechanisms.TaggedValue>

    <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

    <Foundation.Extension_Mechanisms.TaggedValue.value />

  </Foundation.Extension_Mechanisms.TaggedValue>

</Foundation.Core.ModelElement.taggedValue>
- <Foundation.Core.Classifier.feature>
- <Foundation.Core.Attribute
  xmi.id="txmiid213.a">

    <Foundation.Core.ModelElement.name>criterion_and_we

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
  <Foundation.Core.Feature.ownerScope
    xmi.value="classifier" />

  <Foundation.Core.StructuralFeature.multiplicity>1..1</Four

```

```

    <Foundation.Core.StructuralFeature.changeable
xmi.value="none" />

    <Foundation.Core.StructuralFeature.targetScope
xmi.value="instance" />
-
    <Foundation.Core.Attribute.initialValue>
-
        <Foundation.Data_Types.Expression>

            <Foundation.Data_Types.Expression.language />

            <Foundation.Data_Types.Expression.body />

        </Foundation.Data_Types.Expression>

    </Foundation.Core.Attribute.initialValue>
-
    <Foundation.Core.StructuralFeature.type>
    <Foundation.Core.DataType
xmi.idref="txmiid214" />

    </Foundation.Core.StructuralFeature.type>
-
    <Foundation.Core.ModelElement.taggedValue>
-
        <Foundation.Extension_Mechanisms.TaggedValue>

            <Foundation.Extension_Mechanisms.TaggedValue.tag>c
            <Foundation.Extension_Mechanisms.TaggedValue.value

        </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
    </Foundation.Core.Attribute>
    </Foundation.Core.Classifier.feature>
    </Foundation.Core.Class>
- <Foundation.Core.Association
xmi.id="txmiid212.ASS">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />

```

```

<Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

<Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />
- <Foundation.Core.Association.connection>
- <Foundation.Core.AssociationEnd
xmi.id="txmiid212.CE">

<Foundation.Core.ModelElement.name />

<Foundation.Core.ModelElement.visibility
xmi.value="public" />

<Foundation.Core.AssociationEnd.isNavigable
xmi.value="false" />

<Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

<Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

<Foundation.Core.AssociationEnd.multiplicity />

<Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

<Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
<Foundation.Core.AssociationEnd.type>
<Foundation.Core.Class
xmi.idref="txmiid211" />

</Foundation.Core.AssociationEnd.type>
</Foundation.Core.AssociationEnd>
- <Foundation.Core.AssociationEnd
xmi.id="txmiid212.SE">

<Foundation.Core.ModelElement.name />

<Foundation.Core.ModelElement.visibility
xmi.value="public" />

```

```

    <Foundation.Core.AssociationEnd.isNavigable
xmi.value="true" />

    <Foundation.Core.AssociationEnd.isOrdered
xmi.value="false" />

    <Foundation.Core.AssociationEnd.aggregation
xmi.value="none" />

    <Foundation.Core.AssociationEnd.multiplicity />

    <Foundation.Core.AssociationEnd.changeable
xmi.value="none" />

    <Foundation.Core.AssociationEnd.targetScope
xmi.value="instance" />
-
    <Foundation.Core.AssociationEnd.type>
    <Foundation.Core.Class
        xmi.idref="txmiid215" />

        </Foundation.Core.AssociationEnd.type>
    </Foundation.Core.AssociationEnd>
</Foundation.Core.Association.connection>
</Foundation.Core.Association>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Weighted_ChoiceChoice.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid211" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class
        xmi.idref="txmiid17e" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
- <Foundation.Core.Class xmi.id="txmiid215">

    <Foundation.Core.ModelElement.name>Weighted_Criterion<,
    <Foundation.Core.ModelElement.visibility

```

```

    xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
<Foundation.Core.Class.isActive
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid4" />
    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.GeneralizableElement.generalization>
    <Foundation.Core.Generalization
        xmi.idref="GLIF3.Weighted_CriterionCriterion.G" />

    </Foundation.Core.GeneralizableElement.generalization>
- <Foundation.Core.ModelElement.taggedValue>
-
    <Foundation.Extension_Mechanisms.TaggedValue>

        <Foundation.Extension_Mechanisms.TaggedValue.tag>docu

        <Foundation.Extension_Mechanisms.TaggedValue.value />

    </Foundation.Extension_Mechanisms.TaggedValue>

    </Foundation.Core.ModelElement.taggedValue>
</Foundation.Core.Class>
- <Foundation.Core.Generalization
    xmi.id="GLIF3.Weighted_CriterionCriterion.G">
    <Foundation.Core.ModelElement.name />
    <Foundation.Core.ModelElement.visibility
        xmi.value="public" />

        <Foundation.Core.Generalization.discriminator />
- <Foundation.Core.Generalization.subtype>
    <Foundation.Core.Class
        xmi.idref="txmiid215" />
    </Foundation.Core.Generalization.subtype>
- <Foundation.Core.Generalization.supertype>
    <Foundation.Core.Class

```



```

        xmi.idref="txmiid183" />
    </Foundation.Core.Generalization.supertype>
</Foundation.Core.Generalization>
</Foundation.Core.Namespace.ownedElement>
</Model_Management.Package>
- <Foundation.Core.Class xmi.id="DummyClass">

    <Foundation.Core.ModelElement.name><DummyClass></Founda
<Foundation.Core.ModelElement.visibility
    xmi.value="public" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="true" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="true" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
<Foundation.Core.Class.isActive xmi.value="false" />
</Foundation.Core.Class>
- <Foundation.Core.DataType xmi.id="txmiid9c">
    <Foundation.Core.ModelElement.name>Object[]
    </Foundation.Core.ModelElement.name>
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiidb3">

    <Foundation.Core.ModelElement.name>Case_Step</Foundation.Ci
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid10f">

    <Foundation.Core.ModelElement.name>GEEServerDaemon</Four

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid1de">

  <Foundation.Core.ModelElement.name>Get_Data_Action
  []</Foundation.Core.ModelElement.name>
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid1b8">

  <Foundation.Core.ModelElement.name>Algorithm</Foundation.Cc
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid196">

  <Foundation.Core.ModelElement.name>Nestable</Foundation.Cor
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />

```

```

</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid9e">

    <Foundation.Core.ModelElement.name>GEEClientDaemon</Foun
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiida4">

    <Foundation.Core.ModelElement.name>GEEClientUserInterfaceA
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiidcd">

    <Foundation.Core.ModelElement.name>GEEClient</Foundation.Co
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiidae">

    <Foundation.Core.ModelElement.name>Guideline_Step</Foundat
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf

```

```

        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiidb2">

    <Foundation.Core.ModelElement.name>Action_Step</Foundation.
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid1ba">

    <Foundation.Core.ModelElement.name>Data_Item_List</Founda
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid189">
    <Foundation.Core.ModelElement.name>Data_Item[]
        </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid1d7">

    <Foundation.Core.ModelElement.name>Criterion</Foundation.Cor
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />

```

```

    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid136">

    <Foundation.Core.ModelElement.name>GEEClientHandle
    []</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid1bc">
    <Foundation.Core.ModelElement.name>Criterion[]
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid9a">

    <Foundation.Core.ModelElement.name>Object</Foundation.Core.M
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiida6">

```

```

    <Foundation.Core.ModelElement.name>void</Foundation.Core.Mor
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid18e">

```

```

    <Foundation.Core.ModelElement.name>Decision_Condition</Fou
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiida1">

```

```

    <Foundation.Core.ModelElement.name>File</Foundation.Core.Mod
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiidcf">

```

```

    <Foundation.Core.ModelElement.name>Thread</Foundation.Core.l
<Foundation.Core.ModelElement.visibility
    xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract

```

```

        xmi.value="false" />
    </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid1aa">

        <Foundation.Core.ModelElement.name>Data_Item</Foundation.C
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid15d">

        <Foundation.Core.ModelElement.name>Triggering_Event
    []</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiide3">
        <Foundation.Core.ModelElement.name>String[]
    </Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
        xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
        xmi.value="false" />
    </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid199">

        <Foundation.Core.ModelElement.name>Decision_Option
    []</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
        xmi.value="private" />

```



```

<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiiddb">

  <Foundation.Core.ModelElement.name>Socket</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid10b">

  <Foundation.Core.ModelElement.name>Vector</Foundation.Core.M
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid103">
  <Foundation.Core.ModelElement.name>char[]
  </Foundation.Core.ModelElement.name>
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiidb5">

```



```

    <Foundation.Core.ModelElement.name>Decision_Option</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid1e0">

```

```

    <Foundation.Core.ModelElement.name>Get_Knowledge_Action
    []</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid15b">

```

```

    <Foundation.Core.ModelElement.name>Action_Specification
    []</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiidb7">

```

```

    <Foundation.Core.ModelElement.name>Synchronization_Step</Foundation.Core.ModelElement.name>
    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />
    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

```

```

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid93">

    <Foundation.Core.ModelElement.name>int</Foundation.Core.Mode
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid105">

    <Foundation.Core.ModelElement.name>Event</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid91">

    <Foundation.Core.ModelElement.name>String</Foundation.Core.M
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiidb0">

    <Foundation.Core.ModelElement.name>Guideline_Step
  []</Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

```

```

    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />
    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid209">

    <Foundation.Core.ModelElement.name>Logical_Expression_Of_C
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid1eb">

    <Foundation.Core.ModelElement.name>Literal_Data_Item</Four
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiidb6">

    <Foundation.Core.ModelElement.name>Branch_Step</Foundation
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid214">

```

```

    <Foundation.Core.ModelElement.name>Weighted_Criterion
    []</Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiidb4">

    <Foundation.Core.ModelElement.name>Decision_Step</Foundatio
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid1b0">

    <Foundation.Core.ModelElement.name>Knowledge_Item
    []</Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid169">

    <Foundation.Core.ModelElement.name>Guideline_Expression</F
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

```

```

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid11e">

    <Foundation.Core.ModelElement.name>GEEServer</Foundation.Co
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid158">

    <Foundation.Core.ModelElement.name>Guideline_Exception
    []</Foundation.Core.ModelElement.name>
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid98">

    <Foundation.Core.ModelElement.name>boolean</Foundation.Core
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />
  <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />
  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
  </Foundation.Core.DataType>
- <Foundation.Core.DataType xmi.id="txmiid113">

    <Foundation.Core.ModelElement.name>GEEClientHandle</Founda
  <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

```

```

<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
</Foundation.Core.DataType>
- <Foundation.Extension_Mechanisms.Stereotype
  xmi.id="txmiide.S">

    <Foundation.Core.ModelElement.name>actor</Foundation.Core.Mc
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Extension_Mechanisms.Stereotype.icon>
- <Foundation.Data_Types.Geometry>
    <Foundation.Data_Types.Geometry.body />
    </Foundation.Data_Types.Geometry>
  </Foundation.Extension_Mechanisms.Stereotype.icon>

  <Foundation.Extension_Mechanisms.Stereotype.baseClass />

  <Foundation.Extension_Mechanisms.Stereotype.extendedElement /:
</Foundation.Extension_Mechanisms.Stereotype>
- <Model_Management.Model xmi.id="txmiid216">

    <Foundation.Core.ModelElement.name>__NotInProject__</Foun
<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isAbstract
  xmi.value="false" />
- <Foundation.Core.Namespace.ownedElement>
- <Model_Management.Package
  xmi.id="txmiid217">

    <Foundation.Core.ModelElement.name>java</Foundation.Core

```

```

<Foundation.Core.ModelElement.visibility
  xmi.value="private" />
<Foundation.Core.GeneralizableElement.isRoot
  xmi.value="false" />
<Foundation.Core.GeneralizableElement.isLeaf
  xmi.value="false" />

  <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
- <Foundation.Core.ModelElement.namespace>
  <Model_Management.Model
    xmi.idref="txmiid216" />
</Foundation.Core.ModelElement.namespace>
- <Foundation.Core.Namespace.ownedElement>
  - <Model_Management.Package
    xmi.id="txmiid218">

    <Foundation.Core.ModelElement.name>lang</Foundation.C

    <Foundation.Core.ModelElement.visibility
      xmi.value="private" />

    <Foundation.Core.GeneralizableElement.isRoot
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isLeaf
      xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
      xmi.value="false" />
  -
    <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
      xmi.idref="txmiid217" />

    </Foundation.Core.ModelElement.namespace>
  -
    <Foundation.Core.Namespace.ownedElement>
  - <Foundation.Core.Class
    xmi.id="txmiidd6">

    <Foundation.Core.ModelElement.name>Runnable</Foi

    <Foundation.Core.ModelElement.visibility
      xmi.value="public" />

```

```

<Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />

<Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

<Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />

<Foundation.Core.Class.isActive
xmi.value="false" />
-
<Foundation.Core.ModelElement.namespace>

    <Model_Management.Package
xmi.idref="txmiid218" />

</Foundation.Core.ModelElement.namespace>
</Foundation.Core.Class>
- <Foundation.Core.Class
xmi.id="txmiide0">

    <Foundation.Core.ModelElement.name>Thread</Founc

    <Foundation.Core.ModelElement.visibility
xmi.value="public" />

    <Foundation.Core.GeneralizableElement.isRoot
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isLeaf
xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
xmi.value="false" />

    <Foundation.Core.Class.isActive
xmi.value="false" />
-
<Foundation.Core.ModelElement.namespace>

    <Model_Management.Package
xmi.idref="txmiid218" />

```



```

        </Foundation.Core.ModelElement.namespace>
    </Foundation.Core.Class>

    </Foundation.Core.Namespace.ownedElement>
</Model_Management.Package>
- <Model_Management.Package
    xmi.id="txmiid219">

    <Foundation.Core.ModelElement.name>net</Foundation.Co

    <Foundation.Core.ModelElement.visibility
    xmi.value="private" />

    <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />
-
    <Foundation.Core.ModelElement.namespace>
    <Model_Management.Package
        xmi.idref="txmiid217" />

    </Foundation.Core.ModelElement.namespace>
-
    <Foundation.Core.Namespace.ownedElement>
- <Foundation.Core.Class
    xmi.id="txmiidd5">

    <Foundation.Core.ModelElement.name>ServerSocket<

    <Foundation.Core.ModelElement.visibility
    xmi.value="public" />

    <Foundation.Core.GeneralizableElement.isRoot
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isLeaf
    xmi.value="false" />

    <Foundation.Core.GeneralizableElement.isAbstract
    xmi.value="false" />

```

```

        <Foundation.Core.Class.isActive
xmi.value="false" />
-
        <Foundation.Core.ModelElement.namespace>

            <Model_Management.Package
xmi.idref="txmiid219" />

        </Foundation.Core.ModelElement.namespace>
    </Foundation.Core.Class>

    </Foundation.Core.Namespace.ownedElement>
</Model_Management.Package>

    </Foundation.Core.Namespace.ownedElement>
</Model_Management.Package>
</Foundation.Core.Namespace.ownedElement>
</Model_Management.Model>
</Foundation.Core.Namespace.ownedElement>
</Model_Management.Model>
</XML.content>
</XML>

```