

Let statement

1) Suppose we want to model the criterion: activity intolerance due to (low back pain or back-related leg symptoms) not improving over 4 weeks

Last activity_intolerance where (relationship.name == caused_by and (relationship.patient_data == (back_pain where (body_site_cd == low_back)) or relationship.patient_data == (symptom where (body_site_cd == leg) and relationship.name == related and relationship.patient_data == back_problem))) and critical_time.low < now - 4 weeks). severity <

Latest activity_intolerance where (relationship.name == caused_by and (relationship.patient_data == low_back_pain or relationship.patient_data == (symptom where (body_site_cd == leg and relationship.name == related and relationship.patient_data == back_problem)))).severity

But this is very hard to comprehend. Instead, we can break it up into 4 statements:

Let activity_intolerance where (relationship.name == caused_by and (relationship.patient_data == (back_pain where (body_site_cd == low_back)) or relationship.patient_data == (symptom where (body_site_cd == leg and relationship.name == related and relationship.patient_data == back_problem)))) be AI;

Let (Last AI where critical_time.low < now - 4 weeks) be L1;

Let (Latest AI) be L2;

L1.severity < L2.severity

2) Where should the Let statement be defined and how should it be used?

The Let statement can be thought of as a macro from the C programming language. The macro has a constant_name that is expanded into a longer expression every time the constant_name is encountered.

I propose that macro definitions should be defined at the level of a guideline and can be used by that guideline, (not by its subguidelines, and not by guidelines that are using the guideline as a subguideline).

The guideline can have the following attribute:

macro_definitions: Macro_Definition

Macro_Definition

constant_name: String

// e.g., L2

expression: Expression

// e.g., Latest AI

An alternative approach is to create a subguideline for the decision step. In this subguideline we can use *assignment actions* to assign the results of evaluating an expression to a Data_Item. But, suppose a complex criterion resides within a patient state step. Then we would need to have patient state details in the form of a subguideline in order to allow the use of an assignment.

Do we need the assignment action in addition to the Let statement?

Yes, for assigning a new guideline-generated value (e.g., risk) to a data item. Also, we need the assignment action for passing results from decision detail back to the decision step.