

CSCE 658: RANDOMIZED ALGORITHMS – SPRING 2024
PROBLEM SET 3

Due: Tuesday, February 20, 2024, 5:00 pm CT

Problem 1. (30 points total) COUNTSKETCH tail bounds.

For any vector $x \in \mathbb{R}^n$ and any integer $k \geq 0$, we define $\text{TAIL}_k(x)$ to be the vector x , but with the k entries of largest magnitude to be set to 0, breaking ties arbitrarily. For example if $x = (-100, 40, 40, 1)$, then $\text{TAIL}_2(x)$ can be either $(0, 0, 40, 1)$ or $(0, 40, 0, 1)$.

1. (5 points) Show that for any parameter $\alpha \geq 1$ and $k \leq n - 1$, there exists $x \in \mathbb{R}^n$ such that

$$\alpha \cdot \|\text{TAIL}_k(x)\|_2 < \|x\|_2.$$

That is, the length of a tail vector of x can be arbitrarily smaller than the length of the vector x .

2. (20 points) Show that COUNTSKETCH actually provides an L_2 tail guarantee. More specifically, for $\varepsilon \in (0, 1)$, suppose we use COUNTSKETCH with $\mathcal{O}\left(\frac{1}{\varepsilon^2} \cdot \log n\right)$ buckets to extract estimates \hat{x}_i for the value of each coordinate x_i . Show that with probability $1 - \frac{1}{n^2}$, we simultaneously have that for all $i \in [n]$,

$$|\hat{x}_i - x_i| \leq \varepsilon \cdot \|\text{TAIL}_k(x)\|_2,$$

where $k = \frac{1}{\varepsilon^2}$.

3. (5 points) Conclude that at the end of an insertion-deletion stream, COUNTSKETCH with $\mathcal{O}(k \log n)$ buckets can with high probability, recover the exact coordinates of a vector that is k -sparse, even if at intermediate times in the stream, the underlying frequency is not k -sparse.

Problem 2. (30 points total) AMS Sketch for F_p

Let $p \geq 1$. Suppose $f \in \mathbb{R}^n$ is defined by an insertion-only stream of length m , where each update increments a coordinate of f . Suppose we sample an update $t \in [m]$ in the stream, uniformly at random, and set a counter c to be the number of times the item appears in the stream after time t (including time t). After the stream ends, we set $Z = c^p - (c - 1)^p$.

For example, suppose the stream consists of the updates $1, 2, 2, 1, 4, 1, 2, 1$, which induces the frequency vector $f = (4, 3, 0, 1)$ and suppose we sample the fourth update of the stream, corresponding to a 1. Then we see a total of three instances of 1, after that time (inclusive), so that $c = 3$ and $Z = 3^p - 2^p$. For $p = 3$ then, we would have $Z = 27 - 8 = 19$.

1. (5 points) Show that $\mathbb{E}[Z] = f_j^p$, *conditioned* on sampling $j \in [n]$.
2. (5 points) Let $F = m \cdot Z$. Show that $\mathbb{E}[F] = \|f\|_p^p$.
3. (10 points) Show that $\text{Var}[F] \leq p \cdot \|f\|_1 \cdot \|f\|_{2p-1}^{2p-1}$.

HINT: You may use the fact that for all $x \geq 1$ and $p \geq 1$, we have $x^p - (x - 1)^p \leq px^{p-1}$.

4. (10 points) Given an algorithm that uses $O\left(\frac{1}{\varepsilon^2}n^{1-1/p}\right) \cdot \log(nm)$ bits of space and with probability at least $\frac{2}{3}$, outputs an estimate \widehat{F} such that

$$(1 - \varepsilon)\|f\|_p^p \leq \widehat{F} \leq (1 + \varepsilon)\|f\|_p^p.$$

Justify both its correctness-of-approximation and space complexity.

HINT: You may use the fact that for all $\|f\|_1 \cdot \|f\|_{2p-1}^{2p-1} \leq n^{1-1/p}\|f\|_p^{2p}$.

Problem 3. (30 points total) Easy as 123.

1. (2 points) Suppose we want to count the number of updates, i.e., the length of a data stream. Describe a naïve streaming algorithm that uses $\mathcal{O}(\log m)$ bits of space if the stream has length m , where m is not known in advance.

Consider the following algorithm:

Algorithm 1 Approximate counting

```

1:  $C \leftarrow 0$ 
2: for each stream update do
3:   Flip a coin that is HEADS with probability  $\frac{1}{2^Z}$ 
4:   if the coin is HEADS then
5:      $C \leftarrow C + 1$ 
6: return  $Z = 2^C - 1$ 

```

2. (10 points) Compute, with proof, $\mathbb{E}[Z]$.
3. (10 points) Compute, with proof, $\text{Var}[Z]$.
4. (5 points) Given an algorithm that uses $\mathcal{O}(\log \log m)$ bits of space and with probability at least $\frac{2}{3}$, outputs an estimate \widehat{M} such that

$$\frac{m}{2} \leq \widehat{M} \leq 2m,$$

where m is the length of the stream, but is not known in advance. Justify both its correctness-of-approximation and space complexity.

Problem 4. (30 points total) Approximate matrix multiplication

Let $A \in \mathbb{R}^{n \times m}$ and $B \in \mathbb{R}^{m \times d}$ be matrices. We will show there exists an algorithm that samples $s = \mathcal{O}\left(\frac{1}{\varepsilon^2}\right)$ columns of A to form a matrix $X \in \mathbb{R}^{n \times s}$ and s rows of B to form a matrix $Y \in \mathbb{R}^{s \times d}$ such that with probability at least $\frac{2}{3}$,

$$\|AB - XY\|_F \leq \varepsilon \|A\|_F \cdot \|B\|_F.$$