

Details of MySQL Data Types:

String Data Types:

Data Type	Description
CHAR(size)	A FIXED length string (can contain letters, numbers, and special characters). The <i>size</i> parameter specifies the column length in characters - can be from 0 to 255. Default is 1
VARCHAR(size)	A VARIABLE length string (can contain letters, numbers, and special characters). The <i>size</i> parameter specifies the maximum string length in characters - can be from 0 to 65535
TEXT(size)	Holds a string with a maximum length of 65,535 bytes
BLOB(size)	For BLOBs (Binary Large Objects). Holds up to 65,535 bytes of data
ENUM(val1, val2, val3, ...)	A string object that can have only one value, chosen from a list of possible values. You can list up to 65535 values in an ENUM list. If a value is inserted that is not in the list, a blank value will be inserted. The values are sorted in the order you enter them
ENUM(val1, val2, val3, ...)	A string object that can have 0 or more values, chosen from a list of possible values. You can list up to 64 values in a SET list

Numeric Data Types:

Data Type	Description
TINYINT(size)	A very small integer. Signed range is from -128 to 127. Unsigned range is from 0 to 255. The <i>size</i> parameter specifies the maximum display width (which is 255)
INT(size)	A medium integer. Signed range is from -2147483648 to 2147483647. Unsigned range is from 0 to 4294967295. The size parameter specifies the maximum display width (which is 255)
BIGINT(size)	A large integer. Signed range is from -9223372036854775808 to 9223372036854775807. Unsigned range is from 0 to 18446744073709551615. The size parameter specifies the maximum display width (which is 255)
DECIMAL(size, d)	An exact fixed-point number. The total number of digits is specified in size. The number of digits after the decimal point is specified in the d parameter. The maximum number for size is 65. The maximum number for d is 30. The default value for size is 10. The default value for d is 0.

Date Data Type:

Data Type	Description
DATE	A date. Format: YYYY-MM-DD. The supported range is from '1000-01-01' to '9999-12-31'
DATETIME(fsp)	A date and time combination. Format: YYYY-MM-DD hh:mm:ss. The supported range is from '1000-01-01 00:00:00' to '9999-12-31 23:59:59'. Adding DEFAULT and ON UPDATE in the column definition to get automatic initialization and updating to the current date and time

TIMESTAMP(fsp)	A timestamp. TIMESTAMP values are stored as the number of seconds since the Unix epoch ('1970-01-01 00:00:00' UTC). Format: YYYY-MM-DD hh:mm:ss. The supported range is from '1970-01-01 00:00:01' UTC to '2038-01-09 03:14:07' UTC. Automatic initialization and updating to the current date and time can be specified using DEFAULT CURRENT_TIMESTAMP and ON UPDATE CURRENT_TIMESTAMP in the column definition
TIME(fsp)	A time. Format: hh:mm:ss. The supported range is from '-838:59:59' to '838:59:59'
YEAR	A year in four-digit format. Values allowed in four-digit format: 1901 to 2155, and 0000. MySQL 8.0 does not support year in two-digit format.

References:

Lab: https://www.w3schools.com/sql/sql_datatypes.asp (this document is prepared based in this tutorial)

Theory: Chapter 3 (section: 3.2.1→ number and string) and Chapter 4 (section 4.5.1→ Date and Time)