

# MSiA 400 Lab 4

## Cross-Validation & Support-Vector Machines

Huiyu Wu

10/24/2020



NORTHWESTERN  
UNIVERSITY


# Cross-Validation (CV)

- Used to assess how well a fitted model will predict new observations
- Used to select the best model based on its performance on new data
- We don't want to assess performance on same dataset used to fit the model
  - Overfitting - models with more predictors will perform better than those with fewer

# Train, Test, Validation


- **Training dataset** - sample of data used to fit the model
- **Validation dataset** - used for fit model evaluation while tuning hyperparameters
  - Evaluation can become biased as validation performance is incorporated into model
- **Test dataset** - used for evaluation of final fit model

# Holdout CV



- Randomly assign observations to either training or validation/test sets
- Size of datasets is determined by user
- Involves single run

## K-Fold CV



- Randomly assign observations to each fold
- Folds are (roughly) equal size
- Number of folds is determined by user
- Repeat so that each fold is the validation/test dataset

# Holdout CV in R

- Dataset of student records:
  - GRE score, GPA, prestige of undergraduate university
  - Whether or not they were admitted into graduate school

```
gradAdmit = read.csv('gradAdmit.csv')
set.seed(400)
n = nrow(gradAdmit) # number of samples
# hold out 20% for testing
sample = sample.int(n = n, size = floor(.2*n), replace = F)
train = gradAdmit[-sample,]; test = gradAdmit[sample,]
```


## K-Fold CV in R

```
library(caret)

n folds = 5
folds = createFolds(1:n, k=n folds)
for (i in 1:n folds){
  train = gradAdmit[-folds[[i]],]
  test = gradAdmit[folds[[i]],]
  # Train & analyze model
}
```

# Support Vector Machines


- Supervised learning method for classification
- Linear discriminant function:  
 $\ell(x) = w^T x + b$ 
  - $w$  is weight vector
  - $b$  is bias
  - $\ell(x) \geq 0 \rightarrow x$  in class 1
  - $\ell(x) < 0 \rightarrow x$  in class 2





# Support Vector Machines

- Distance between  $x_i$  and hyperplane:  $d_i = \frac{w^T x_i + b}{\|w\|}$
- $y_i \in \{-1, 1\}$ ,  $\delta_i = \frac{y_i h(x_i)}{\|w\|}$
- If data is linearly separable,  $\delta_i = y_i(w^T x_i + b) \geq 0$
- Margin defined as minimum distance of all points to hyperplane:  $\delta^* = \min_i \frac{y_i h(x_i)}{\|w\|}$



# Support Vector Machines

- Goal is to maximize the margin:  $\arg \max_{w,b} \min_i \frac{y_i h(x_i)}{\|w\|}$
- If data is linearly separable, w.l.o.g., we can assume  $y^i(w^T x_i + b) \geq 1$

- Rewrite optimization problem as:

$$\arg \max_{w,b} \frac{1}{\|w\|} \text{ s.t. } y^i(w^T x_i + b) - 1 \geq 0, \forall i$$

- Or:  $\arg \min_{w,b} \|w\|^2 \text{ s.t. } y^i(w^T x_i + b) - 1 \geq 0, \forall i$
- Soft Margin:

$$\arg \min_{w,b} \frac{1}{2} \|w\|^2 + C \sum_i \max \{0, 1 - y^i(w^T x_i + b)\}$$

- Dual:

$$\max_{\alpha} \sum_i \alpha_i - \frac{1}{2} \sum_i \sum_j \alpha_i \alpha_j y_i y_j x_i^T x_j \text{ s.t. } 0 \leq \alpha_i \leq C, \sum_i \alpha_i y_i = 0$$


# SVM in R

```
library(e1071)
# https://www.rdocumentation.org/packages/e1071/versions/1.7-2/topics/svm
svm = svm(factor(admit)~gre+gpa, kernel = "linear", data=train[1:10, ], scale=FALSE)
summary(svm)
```

```
##
## Call:
## svm(formula = factor(admit) ~ gre + gpa, data = train[1:10, ], kernel = "linear",
##      scale = FALSE)
##
##
## Parameters:
##   SVM-Type:  C-classification
##   SVM-Kernel: linear
##         cost:  1
##
## Number of Support Vectors:  9
##
##   ( 4 5 )
##
##
## Number of Classes:  2
##
## Levels:
##  0 1
```

# SVM in R


```
plot(svm, train[1:10,], gre~gpa)
```



# SVM in R

```
plot(svm, train, gre~gpa)
```

SVM classification plot




# SVM in R

```
pred = predict(svm, newdata=test, type='response')  
pred[1:15]
```

```
##  4 14 16 26 32 41 45 46 51 58 65 69 72 73 75  
##  1  1  0  1  1  1  1  0  1  0  0  0  0  0  1  
## Levels: 0 1
```

# SVM in R


```
beta = t(svm$coefs)%*%svm$SV  
beta0 = svm$rho  
plot(train[1:15, c(3,2)])  
abline(beta0 / beta[1], -beta[2] / beta[1])
```



# Kernel Trick

- If linear discriminant not effective:

$$x = \begin{pmatrix} x_1 \\ x_2 \\ x_3 \end{pmatrix} \mapsto \phi(x) = \begin{pmatrix} x_1 \\ x_1 x_2 \\ x_3^2 \\ x_1 x_3 \end{pmatrix}$$





# Kernel Trick

- Define kernel  $K(x, z) = \phi(x)^T \phi(z)$
- Can define kernel to be easier to compute than inner product, or even  $\phi(\cdot)$  (which need not be formed)
- Polynomial kernel:  $K(x, z) = (x^T z + c)^d$
- Gaussian kernel:  $K(x, z) = \exp\left(-\frac{\|x-z\|^2}{2\sigma^2}\right)$
- Optimization: 
$$\begin{cases} \max_{\alpha} \sum_i \alpha_i - \frac{1}{2} \sum_i \sum_j \alpha_i \alpha_j y_i y_j K(x_i, x_j) \\ \text{s.t. } 0 \leq \alpha_i \leq C, \sum_i \alpha_i y_i = 0 \end{cases}$$

# SVM in R

```
library(e1071)


# https://www.rdocumentation.org/packages/e1071/versions/1.7-2/topics/svm
svm = svm(factor(admit)~., data=train)
summary(svm)
```

```
##
## Call:
## svm(formula = factor(admit) ~ ., data = train)
##
##
## Parameters:
##   SVM-Type:  C-classification
##   SVM-Kernel: radial
##         cost:  1
##
## Number of Support Vectors:  219
##
##   ( 116 103 )
##
##
## Number of Classes:  2
##
## Levels:
##   0 1
```

# SVM in R

```
plot(svm, train, gre~gpa)
```

SVM classification plot



# SVM in R

```
pred = predict(svm, newdata=test, type='response')  
pred[1:15]
```

```
##  4 14 16 26 32 41 45 46 51 58 65 69 72 73 75  
##  0 0 0 1 0 0 0 0 0 0 0 1 0 0 0  
## Levels: 0 1
```