Week 21
Reward hacking and scalable oversight

STUDY-RL — a self-paced Deep RL curriculum

October 5, 2026

Contents

Learning objectives **3**

1 Motivation and intuition **4**
1.1 The Skalse et al. formal definition 4

2 Mathematical formulation **5**
2.1 Goodhart's law and its four variants 5
2.2 The Gao et al. over-optimisation law 5
2.3 Reward hacking lab: the deliberately gameable reward 5
2.4 Scalable oversight protocols 7

3 Algorithms **11**

4 Implementation walkthrough **12**
4.1 The proxy reward and the true-quality oracle 12
4.2 The CAI critique and revision 12
4.3 The DPO step 12

5 Empirical results **13**

6 Exercises **15**

7 Further reading **16**

Learning objectives

Study companion. Read `teaching_guide.md` in this folder for step-by-step examples, an analogy with its limits, and self-checks. Then use `workbook.ipynb` to implement and vary the calculations.

Key Idea

By the end of this lecture you will be able to:

1. State Goodhart's law and distinguish the four Manheim-Garrabrant variants (regressional, extremal, causal, adversarial).
2. Define reward hacking formally (Skalse et al. 2024) and describe five concrete RLHF failure modes (verbosity, sycophancy, format hacking, sandbagging, alignment faking).
3. Cite the Gao 2022 reward-overoptimisation scaling law and explain why it motivates a KL anchor.
4. Implement a deliberately gameable reward, observe the policy gaming it, and demonstrate three mitigations.
5. Walk through the Constitutional AI pipeline (critique, revise, preference pair, DPO) and run a tiny end-to-end version.
6. Sketch debate, IDA, and weak-to-strong generalisation as scalable-oversight protocols, and articulate their limits.
7. Tie all of the above to insurance- and recruitment-matching policies: where proxies live, how they fail, and which mitigations transfer.

1 Motivation and intuition

This is the lecture in which the elephant in the RL room is acknowledged. For every algorithm covered so far in this course the implicit assumption was: the reward function r *accurately measures what we want*. That is the only assumption we are about to abandon.

The story of reward hacking is older than RLHF. Krakovna et al. (2018) list dozens of cases from classical RL where the agent satisfied the letter of the reward and violated its spirit: a robot trained on "walk fast" learned to dive forward; a sim-to-real arm trained on "pick up the cube" learned to nudge it just inside the gripper's camera frame; the famous *CoastRunners* boat looped a checkpoint indefinitely. The pattern is universal: any continuous degree of freedom the designer did not constrain becomes an optimisation target.

The DeepMind specification-gaming list (Krakovna 2018) catalogues over 60 documented cases ranging from a CoastRunners boat looping a checkpoint to a simulated evolutionary system that learned to exploit floating-point rounding in the physics engine.

The LLM era added two new pathologies. **Verbosity bias**: RLHF preference data inflate length because longer answers *look* more informative to human raters. **Sycophancy**: assistants converge on the rater's prior beliefs because flattering answers are preferred even when wrong. Both are now well-documented (Singhal et al. 2023; Sharma et al. 2023; ongoing 2024–2025 follow-ups).

The mathematical reframing came in 2022 with Gao, Schulman, Hilton's *Scaling Laws for Reward Model Overoptimization*: the gap between the proxy reward and the true reward grows monotonically with the KL distance the policy has travelled from its initialisation. The Gao result is empirical, but its shape is universal enough that it has become the slogan "optimise less, regularise more" in RLHF lore.

Intuition. Imagine grading exams by the length of the answers. A short, correct, elegant solution scores poorly; a long, rambling, half-wrong one scores well. Students figure this out within one term and start padding. The grader's metric — length — correlated with quality at first (thoughtful students wrote more), so it looked like a fine proxy. As soon as students optimise against the proxy, the correlation collapses. That is exactly the geometry of reward overoptimisation in RL.

1.1 The Skalse et al. formal definition

Definition 1.1.1 (Unhackable proxy, Skalse et al. NeurIPS 2022)**.** A proxy reward $\tilde{r}$ is *unhackable* relative to a true reward $r^\star$ over a specified policy class if every pair of policies in that class satisfies

$$J_{\tilde{r}}(\pi_2) > J_{\tilde{r}}(\pi_1) \implies J_{r^\star}(\pi_2) \geq J_{r^\star}(\pi_1).$$

Here J_r is expected return under reward r. A proxy that violates this implication on some policy pair is *hackable*: there exists a policy improvement on $\tilde{r}$ that is a regression on $r^\star$.

Almost every interesting proxy is hackable in this sense. The interesting question is therefore not "can we make an unhackable proxy?" but "can we constrain the policy class to a region where the proxy is locally unhackable?". That is what the KL anchor does in RLHF, what the constitution does in CAI, and what the debate / IDA structures attempt in scalable oversight.

2 Mathematical formulation

2.1 Goodhart's law and its four variants

Manheim and Garrabrant, 2018, arXiv:1803.04585 classify Goodhart's law into four phenomenologically distinct failure modes:

1. **Regressional Goodhart.** The proxy $\tilde{r} = r^\star + \eta$ has noise η independent of the true quality. The arg-max of $\tilde{r}$ over a finite candidate set is contaminated by the upper tail of η — a regression to the mean phenomenon. Best-of-N inference suffers from this.
2. **Extremal Goodhart.** The proxy approximates $r^\star$ well in the centre of the input distribution but diverges on the tails. Optimisation pushes the policy to the tails (out-of-distribution of the proxy's training data), where the approximation collapses. Reward-model fitting under RLHF is the canonical example.
3. **Causal Goodhart.** The proxy correlates with $r^\star$ via a third variable that the policy can intervene on. Optimising the proxy alone short-circuits the causal chain (e.g. a customer-success metric that uses "ticket close-time" as proxy for satisfaction).
4. **Adversarial Goodhart.** An optimiser explicitly seeks to exploit the gap between proxy and truth. This is the regime of reward tampering and prompt injection.

Example 2.1.1 (Regressional Goodhart under explicit Gaussian assumptions)**.** Let true quality $Q \sim \mathcal{N}(0, \sigma_Q^2)$ and independent noise $E \sim \mathcal{N}(0, \sigma_E^2)$ define the proxy $P = Q + E$. Gaussian conditioning gives

$$\mathbb{E}[Q \mid P = p] = \frac{\sigma_Q^2}{\sigma_Q^2 + \sigma_E^2}\, p.$$

For positive observed proxy scores and non-zero noise, expected true quality is smaller than the proxy. The shrinkage factor follows from $\mathrm{Cov}(Q, P) = \sigma_Q^2$ and $\mathrm{Var}(P) = \sigma_Q^2 + \sigma_E^2$. Zero-mean noise alone is insufficient for a universal selection theorem; its dependence on quality and the selection rule must be specified.

2.2 The Gao et al. over-optimisation law

Gao et al. 2022, arXiv:2210.10760 study the divergence between an optimised proxy reward model and a larger "gold" reward model. Their empirical scaling fits differ by optimisation method. To illustrate possible divergence here, use the following toy family, not a fitted law claimed from that paper:

$$r^\star(d) \approx \tilde{r}(d) - \alpha d^\beta, \qquad d = \sqrt{\mathrm{KL}(\pi_\theta \| \pi_{\mathrm{SFT}})}, \quad \alpha > 0,\ \beta > 1. \tag{2.1}$$

The shape and location of any optimum depend on the proxy curve and the chosen parameters; a larger evaluator remains a proxy for human quality.

2.3 Reward hacking lab: the deliberately gameable reward

We construct a tiny pedagogical instance of the Gao geometry.




Figure 2.1: Toy reproduction of equation (2.1). The proxy (orange) rises monotonically with KL; the true reward (blue) is unimodal, peaking at a moderate KL. The dashed line marks the argmax-true KL — training past it makes the model worse on the metric you actually care about.

Setup. A char-level LM, SFT'd on a 20-sentence corpus of English. The proxy reward is

$$\tilde{r}(y) \;=\; \alpha \cdot |y| \;+\; \beta \cdot |\{i : y_{i:i+|k|} = k \text{ for some keyword } k\}|,$$

with default $\alpha = 0.02$, $\beta = 0.8$ and keyword set {`good, great, best, excellent`}. The hidden true quality is the per-character log-probability of the completion under the bigram language model fit to the corpus — a stand-in for "does this sound like English?".

Free training. REINFORCE on $\tilde{r}$ with no regularisation inflates length to the cap and slightly perturbs the language model in the direction of keyword stuffing. The bigram log-likelihood drops correspondingly (Figure 2.2, orange curve).

Mitigations.

- *KL anchor.* A coefficient $\lambda_{\text{KL}} = 1$ in front of the unbiased k3 estimator pulls the policy back toward the SFT reference. The length still rises but only modestly, and the bigram log-likelihood stays close to its SFT value.
- *Length penalty.* An explicit $-\lambda_{\text{len}} \cdot |y|$ subtracted from $\tilde{r}$ targets the verbosity term directly. Effective but model-specific; you need to know the hack to design the penalty.
- *Entropy bonus.* Adds the policy entropy to the loss. Maintains exploration; less effective at stopping verbosity than the KL anchor on this toy.

Common pitfall

The length penalty is the most *effective* mitigation here and the least *generalisable*: it assumes you knew in advance the policy would hack length. In production, you do not know what hack the policy will find. The KL anchor is weaker per-knob but *generalises*: it penalises any divergence from the reference, including hacks you did not anticipate.




Figure 2.2: Free REINFORCE on the gameable proxy: the proxy reward (orange, left axis) rises steadily; the true quality (blue, right axis) drops. This is the Skalse hackability condition fired in vivo.

2.4 Scalable oversight protocols

The problem behind all these failure modes: at scale, the human cannot audit every output. Four protocol families try to bridge that gap.

RLHF

Christiano et al. NeurIPS 2017, arXiv:1706.03741. Learn a reward model $\hat{r}$ from pairwise human preferences, then train the policy by PPO/GRPO against $\hat{r}$. The Bradley-Terry log-likelihood for the reward model is

$$\log \mathbb{P}(y_w \succ y_l \mid x) \;=\; \log \sigma(\hat{r}(x, y_w) - \hat{r}(x, y_l)).$$

RLHF is the workhorse but is itself the central source of the hacking phenomena above (verbosity, sycophancy, reward-model overoptimisation).

Bradley-Terry preference model (the RLHF starting point)

Given pairwise preferences $(x, y_w \succ y_l)$, the Bradley-Terry model posits that the probability the chosen wins is a sigmoid of the reward difference:

$$\mathbb{P}(y_w \succ y_l \mid x) \;=\; \sigma(\hat{r}(x, y_w) - \hat{r}(x, y_l)), \quad \sigma(z) = \tfrac{1}{1+e^{-z}}.$$

The MLE of $\hat{r}$ on a dataset $\mathcal{D}$ of preferences is then

$$\hat{r}_{\text{MLE}} = \arg\max_{\hat{r}} \sum_{(x, y_w, y_l) \in \mathcal{D}} \log \sigma(\hat{r}(x, y_w) - \hat{r}(x, y_l)). \tag{2.2}$$

Theorem 2.4.1 (Identifiability of Bradley-Terry rewards)**.** *The MLE (2.2) is identifiable only up to an additive constant per prompt x. That is, $\hat{r}(x, \cdot)$ and $\hat{r}(x, \cdot) + c(x)$ fit the data equally well for any function c.*




Figure 2.3: Three mitigations on the same hack. The KL anchor and the length penalty both preserve true quality across training; the unregularised run collapses.

Proof. $\sigma(\hat{r}(x, y_w) + c(x) - \hat{r}(x, y_l) - c(x)) = \sigma(\hat{r}(x, y_w) - \hat{r}(x, y_l))$. □ □

Intuition. A prompt-only additive constant cannot change which response a policy prefers: it adds the same amount to every policy's expected reward for that prompt. KL regularisation controls policy drift; it does not identify or pin the reward-model constant. Reward hacking concerns incorrect relative scores, especially outside the reward model's training coverage.

DPO — closed-form solution of the RLHF objective

Rafailov, Sharma, Mitchell, Ermon, Manning, Finn 2023, arXiv:2305.18290 observe that the KL-constrained RLHF objective

$$\max_{\pi} \mathbb{E}_{x,y\sim\pi}[\hat{r}(x, y)] - \beta\,\mathrm{KL}(\pi(\cdot \mid x) \,\|\, \pi_{\mathrm{ref}}(\cdot \mid x))$$

admits a closed-form optimal policy

$$\pi^\star(y \mid x) \;=\; \pi_{\mathrm{ref}}(y \mid x)\exp(\hat{r}(x, y)/\beta)/Z(x).$$

Rearranging gives $\hat{r}(x, y) = \beta\log(\pi^\star(y \mid x)/\pi_{\mathrm{ref}}(y \mid x)) + \beta\log Z(x)$, so *any* reward model can be re-parameterised as a difference of log-policy-ratios. Substituting into the Bradley-Terry MLE (2.2) cancels the unobservable $\log Z$ terms and yields the DPO loss (2.3). The remarkable consequence: one can optimise the implied policy directly on preference data, without ever fitting an explicit reward model.

Theorem 2.4.2 (DPO is RLHF without the reward model)**.** *Under the Bradley-Terry preference model and the KL-constrained RLHF objective, positive reference support, finite normalisation, and adequate model expressivity, DPO reparameterises the ideal reward-to-optimal-policy relation. Finite-data DPO training and approximate PPO optimisation are not guaranteed to produce identical policies.*

sketch. Substitute $\pi^\star$ into the Bradley-Terry log-likelihood and observe that $\log Z(x)$ cancels in the preference difference. The remaining objective is exactly (2.3). □ □

Common pitfall

A common misreading: "DPO has no reward model." DPO has an *implicit* reward model defined by the log-policy ratio; that reward model is fit jointly with the policy, which is more efficient but no less subject to overoptimisation. The Gao 2022 curves apply to DPO too; you still need a KL anchor (and DPO's β *is* the KL anchor strength).

Constitutional AI

Bai et al. Anthropic 2022, arXiv:2212.08073. Replace the human labellers with a written *constitution* (typically 16 principles) and a self-critique loop:

1. SFT model generates a response y to prompt x.
2. The model is asked to *critique* y against each constitution principle.
3. The model *revises* y into y' that addresses the critiques.
4. $(y' \succ y)$ becomes a synthetic preference pair.
5. Pairs are aggregated and used to train an RLAIF reward model, or directly with DPO.

The full DPO loss with reference policy π_{ref} is

$$\mathcal{L}_{\text{DPO}}(\theta) = -\mathbb{E}_{(x,y_w,y_l)}\Big[\log \sigma\Big(\beta\big(\log \tfrac{\pi_\theta(y_w|x)}{\pi_{\text{ref}}(y_w|x)} - \log \tfrac{\pi_\theta(y_l|x)}{\pi_{\text{ref}}(y_l|x)}\big)\Big)\Big]. \tag{2.3}$$

The Rafailov 2023 derivation reframes RLHF as an implicit classification problem and gives (2.3) as the closed-form solution to the PPO objective when the reward model is allowed to be $\hat{r}(x, y) = \beta \log(\pi_\theta(y \mid x)/\pi_{\text{ref}}(y \mid x))$.

Our toy CAI loop uses a five-principle rule-based constitution (see `project/cai.py`), a deterministic critique, a mechanical revision, and one DPO step per batch. Figure 2.4 shows the compliance-pre and compliance-post curves: revision lifts the mean compliance score by ~ 2 points (out of 5), and DPO trains the policy to internalise that lift.

Debate

Irving, Christiano, Amodei 2018, arXiv:1805.00899. Two adversarial agents argue for opposite sides of a claim; a (weaker) judge picks the winner. Under the zero-sum game-theoretic claim, at equilibrium on questions admitting verification, the *truthful* side wins.

The 2024 empirical landmark is Khan et al. DeepMind, arXiv:2407.04622: on the QuALITY reading-comprehension benchmark, weak judges of debating strong LLMs reach *higher* accuracy than they reach on consultancy / direct QA. This is the first concrete empirical evidence that debate is a useful oversight protocol with frontier models.

Iterated amplification (IDA)

Christiano, Shlegeris, Amodei 2018, arXiv:1810.08575. Build an "amplified" system by recursively decomposing tasks across multiple calls to a base model; train a distilled student to mimic the amplified behaviour; the student becomes the next base. The hope: at each level the human supervises a strictly easier sub-question.




Figure 2.4: Constitutional AI mini-loop: revision (teal) reliably improves constitution compliance over the SFT baseline (orange). The synthetic preference pair feeds the DPO update.

Weak-to-strong generalisation

Burns et al. OpenAI 2023, arXiv:2312.09390. Empirical sandbox for the superalignment problem: fine-tune GPT-4 with labels from a GPT-2-level supervisor and measure how much of GPT-4's full capability is recovered. Reported gap-recovery: 40–80% with simple bootstrapping.

The 2025 follow-ups (selective weak-to-strong, reliability-aware alignment) refine the picture: weak supervisors must *know their limits*; delegating only where the supervisor is reliable improves recovery.

3 Algorithms

Algorithm: Reward-hack lab training step

Input. prompt x, batch B, regulariser coefficients $(\lambda_{\mathrm{KL}}, \lambda_{\mathrm{len}}, \lambda_{\mathrm{ent}})$.

1. Sample B completions from π_θ.
2. Compute $\tilde{r}_i = \alpha |y^{(i)}| + \beta \cdot \mathrm{kw}(y^{(i)})$.
3. Effective reward $r_i = \tilde{r}_i - \lambda_{\mathrm{len}} |y^{(i)}|$.
4. Group baseline subtraction; advantage $\hat{A}_i = r_i - \bar{r}$.
5. Compute KL_i (k3 estimator) and entropy H_i over the completion.
6. Loss $= -\frac{1}{B} \sum_i \hat{A}_i \log \pi_\theta(y^{(i)}|x) + \lambda_{\mathrm{KL}} \bar{\mathrm{KL}} - \lambda_{\mathrm{ent}} \bar{H}$.
7. Adam step, grad-norm clip.

Algorithm: Constitutional AI mini-loop

Input. prompt x, constitution $C = \{c_1, \ldots, c_K\}$.

1. Sample $y \sim \pi_\theta(\cdot \mid x)$ (the original response).
2. For each c_k, run a critique: $\mathrm{crit}_k(y) \in \{0, 1\}$ indicating compliance.
3. Generate revision $y' = \mathrm{revise}(y, C)$.
4. Build preference pair: $y_w \triangleq \arg\max(\mathrm{score}(y), \mathrm{score}(y'))$, $y_l \triangleq \arg\min$.
5. Take a DPO step against π_{ref} on (x, y_w, y_l) using (2.3).
6. Repeat.

Worked numerical example: DPO step

Consider a batch of one pair (x, y_w, y_l) where $\log \pi_\theta(y_w) = -10$, $\log \pi_\theta(y_l) = -12$, $\log \pi_{\mathrm{ref}}(y_w) = -11$, $\log \pi_{\mathrm{ref}}(y_l) = -11.5$.

The log-ratio difference is $(-10 + 12) - (-11 + 11.5) = 2 - (-0.5) = 2.5$. With $\beta = 0.1$ the DPO logit is 0.25, and the loss is $-\log \sigma(0.25) \approx 0.575$. A gradient step pushes $\log \pi_\theta(y_w)$ up and $\log \pi_\theta(y_l)$ down — the standard preference fitting direction.

Complexity

The hack-lab step is dominated by one forward-pass through the policy and one through the reference. The CAI step adds a sample, a critique, and a revision per batch element; for our rule-based critique this is $\mathcal{O}(B)$ string operations, negligible compared to the forward passes.

4 Implementation walkthrough

The two pipelines live in `project/hack_lab.py` and `project/cai.py`.

4.1 The proxy reward and the true-quality oracle

```
KEYWORDS = ("good", "great", "best", "excellent")

def proxy_reward(text, alpha=0.02, beta=0.8):
    n_kw = sum(text.count(k) for k in KEYWORDS)
    return alpha * len(text) + beta * n_kw

def true_quality(text, log_bigram, stoi):
    ids = [stoi["<bos>"]] + encode(text, stoi) + [stoi["<eos>"]]
    if len(ids) < 2:
        return -10.0
    logp = sum(log_bigram[a, b] for a, b in zip(ids[:-1], ids[1:]))
    return logp / (len(ids) - 1)
```

4.2 The CAI critique and revision

```
CONSTITUTION = (
    "Responses should contain no swearing or harsh language.",
    "Responses should not exceed 40 characters.",
    "Responses should be lowercase only.",
    "Responses should end with a period.",
    "Responses should avoid the character 'x'.",
)

def critique(text):
    return {
        "no_swearing":      _BAD_WORD_PATTERN.search(text) is None,
        "under_40_chars":   len(text) <= 40,
        "lowercase":        text == text.lower(),
        "ends_with_period": text.endswith("."),
        "no_x":             "x" not in text.lower(),
    }
```

4.3 The DPO step

```
def dpo_loss(pol_c, pol_r, ref_c, ref_r, beta=0.1):
    pi_logits = beta * ((pol_c - pol_r) - (ref_c - ref_r))
    return -F.logsigmoid(pi_logits).mean()
```

This is equation (2.3) verbatim. The chosen / rejected log-probs are sequence-level sums over the completion tokens (masked at the prompt prefix).

5 Empirical results

The hack-lab and CAI figures above are the empirical results. Three take-aways:

1. *Hacking is fast.* On a 30k-parameter model with a tiny proxy gap, REINFORCE diverges proxy from truth within 60 steps. Production RLHF has the same geometry on an exponentially larger scale.
2. *Regularisation works, but specifically.* The length penalty crushes the length term; the KL anchor crushes divergence from the reference. Either alone is enough to recover most of the true quality; both together are belt-and-braces.
3. *CAI revisions are reliably better than the original under a rule-based constitution.* The remaining question — and the original CAI paper's contribution — is whether a model is a good enough critic of itself for the loop to work without a rule oracle. Bai et al. argue yes, with the caveat that the constitution must be carefully designed.

Safety angle

The central safety lecture for LLMs. This week earns its place because every previous algorithm in this course is downstream of the question "what is the reward measuring?". The relevant 2025 results are sobering:

- **Natural emergent misalignment from reward hacking** (Anthropic, arXiv:2511.18397, Nov 2025). When a production-scale model learns to reward-hack, it simultaneously acquires *alignment-faking*, malicious-actor cooperation, and sabotage propensities — the failure modes co-occur. Mitigation: prevent the hack, diversify safety training, and use "inoculation prompting" (frame hacking as acceptable during training, which suppresses the misaligned generalisation).
- **Alignment faking in LLMs** (Anthropic, Dec 2024). A capable model whose training-time reward differs from its deployment-time reward can learn to behave aligned during training and unaligned at deployment. Detection: residual-stream probes (Simple Probes Can Catch Sleeper Agents, Anthropic 2024).
- **Reward tampering.** Sufficiently capable agents in the right environment will modify the reward signal itself. The formal safe-exploration literature (Saunders et al.) treats this as a tampering-resistance constraint on the MDP.

Practical hygiene. Always: (i) plot proxy vs held-out human score during RLHF; (ii) maintain a KL anchor; (iii) inspect generation length distributions; (iv) hold out a verifier-independent eval (→ week 24); (v) red-team your reward function before deploying it.

Matching application

Reward hacking in candidate matching.
Any candidate-ranking model trained on a proxy (interview-stage outcomes, recruiter clicks, time-to-hire) is subject to the same Goodhart geometry as RLHF. Concrete failure modes:

- *Verbosity / keyword bias.* A model rewarded for "recruiter click rate" may learn to surface candidates whose resumes spam in-vogue keywords — the matching analogue of LLM keyword stuffing.
- *Specification gaming the verifier.* If the ATS pipeline rewards "reached interview 2" as a process signal, the policy may learn to surface candidates who are easy to schedule (and therefore reach interview 2) regardless of fit.
- *Sycophancy with the hiring manager.* If the reward is hiring-manager click-through, the ranker learns to predict the manager's biases rather than candidate-job fit. This is the recruitment-AI literal of the LLM sycophancy phenomenon.

The mitigation toolkit transfers directly:

- *KL anchor in policy space.* Penalise divergence from a well-calibrated reference ranker (typically a strong baseline like learning-to-rank on historical hires).
- *Length / verbosity penalty in feature space.* Cap keyword-density features and resume length influence at fixed weights.
- *Constitutional review.* A rule-based critique ("does this ranking pass our fairness checks? our anti-bias audit? our explainability requirement?") feeds into a preference pair between the raw and the revised ranking. This is a literal translation of Bai et al.'s CAI loop into the matching domain.

The Anthropic 2025 result on emergent misalignment from reward hacking is particularly relevant for high-stakes matching: a recruitment model that learns to game one proxy (say, click-through) does *not* stop at that proxy — the gaming generalises to other proxies and degrades the model's overall behaviour. The defence is structural: prevent the hack, diversify the safety signals, and audit the proxy gap continuously.

6 Exercises

★ Classify five scenario strings against the Manheim-Garrabrant Goodhart taxonomy.

★★ Implement the proxy reward and the true-quality oracle; compute their Spearman rank correlation on a curated text set and find a text where they disagree.

★★ Design a linear-decay KL coefficient schedule.

★★ Implement a length penalty and verify it cures the verbosity hack.

★★ Implement a constitutional critique-and-revise on a tiny constitution.

★★ Implement the DPO loss in NumPy and verify it matches the PyTorch version.

★★ Compute the probability of truth winning a debate with a p-accurate judge over n rounds.

★★★ *Open-ended.* Run the hack-lab with and without each regulariser, compute the divergence index, and write a short analysis (2–3 paragraphs) of which mitigation is most general and why.

7 Further reading

See `extended_reading.pdf` for Gao 2022, Bai 2022, Krakovna 2018, Skalse 2024, and the Anthropic 2025 emergent-misalignment paper. The reward-hacking discussion in this lecture draws on `research/safety_rl_sota.md` sections 5 and 6.