Week 24 (Capstone)

Safe Candidate Matching: Offline IQL + Online PPO-Lagrangian + Audit

STUDY-RL — a self-paced Deep RL curriculum

November 8, 2026

Contents

Learning objectives 3

1 Motivation & intuition: the whole curriculum in one project 4
- 1.1 What this lecture is for . . . 4
- 1.2 The three-phase pipeline . . . 4
- 1.3 Why each piece is needed . . . 5

2 Mathematical formulation 6
- 2.1 The matching CMDP . . . 6
- 2.2 Off-policy evaluation: SNIPS . . . 6
- 2.3 Fairness metrics . . . 6
- 2.4 IQL in the one-step contextual setting . . . 7

3 Algorithms 8
- 3.1 The three phases . . . 8
- 3.2 Worked numerical example: the bias path . . . 8
- 3.3 The sliding-window cost estimator . . . 8

4 Implementation walkthrough 10
- 4.1 Data synthesis . . . 10
- 4.2 IQL training (one-step) . . . 10
- 4.3 PPO-Lagrangian online . . . 10
- 4.4 Audit module . . . 10
- 4.5 The CLI . . . 11

5 Empirical results 12
- 5.1 Statistics bridge: A small subgroup can dominate uncertainty in a safety audit . . . 12
- 5.2 Reading the audit . . . 12

6 Exercises 16

7 Further reading 17

Learning objectives

Study companion. Read `teaching_guide.md` in this folder for step-by-step examples, an analogy with its limits, and self-checks. Then use `workbook.ipynb` to implement and vary the calculations.

Key Idea

By the end of this capstone you will:

1. Synthesise a realistic candidate-matching dataset with a controllable fairness pathology in the logging policy.
2. Pretrain a re-ranking policy from logged data using IQL — the offline-RL workhorse from weeks 14–15 — and quantify the bias it inherits.
3. Fine-tune that policy online with PPO-Lagrangian, using a *fairness* cost rather than a physical safety cost, to satisfy a demographic-parity budget.
4. Run a full audit: fairness metrics (DP, EO), off-policy evaluation (SNIPS), calibration curves, and a red-team probe (counterfactual group-flip).
5. Sketch the Pareto frontier between fairness and value, and justify choice of operating point.
6. Ship a CLI that takes a job posting and a list of candidates and returns a ranked list with an audit summary — a microcosm of an ATS deployment.

1 Motivation & intuition: the whole curriculum in one project

1.1 What this lecture is for

This is the first capstone lecture; week 25 extends the audit exercise. It is also the only one whose mini-project requires every previous lecture to make sense. Pause for a moment and look back: we have spent 23 weeks accumulating tools, none of them on their own enough to ship a defensible RL system into production. The capstone is where those tools come together.

Intuition. **The recruiting analogy.** An ATS shows a recruiter a ranked list of candidates for a job. Underlying that list is a learned policy that, at training time, was steered by some signal — clicks, callbacks, hires. That signal reflects its collection process and can contain discriminatory patterns, selective observation and missing outcomes. Optimising it can preserve or amplify those problems. This capstone constructs a deliberately biased synthetic logger and makes its assumptions and diagnostics inspectable; it does not certify that an arbitrary hiring pipeline removes discrimination.

1.2 The three-phase pipeline




Figure 1.1: End-to-end capstone pipeline.

1. **Phase 0: data**. Synthesise candidates, jobs, and logged ϵ-greedy interactions. The logger is deliberately biased toward one protected group — our adversary.
2. **Phase 1: offline IQL pretrain** (weeks 14–15). Stay in-support of the dataset, recover the best ranker we can without rolling out. We will see that this ranker inherits the bias.
3. **Phase 2: online PPO-Lagrangian fine-tune** (week 22). The cost channel is a population-level fairness gap; the multiplier λ prices the fairness constraint.
4. **Phase 3: audit** (weeks 11, 21). DP / EO, SNIPS off-policy estimate, calibration, and a counterfactual red-team probe.

1.3 Why each piece is needed

Offline first. We cannot roll out a randomly-initialised policy on real candidates. Phase 1 makes the *first* online action already a reasonable one.

Lagrangian. A fixed reward-fairness scalar $\beta r - \alpha c$ is brittle. The Lagrangian *learns* the marginal price of fairness and respects the budget.

Audit before deploy. Even with the right objective, the resulting policy may pass DP but fail EO, or pass both but be wildly miscalibrated. The audit is non-negotiable.

2 Mathematical formulation

2.1 The matching CMDP

Definition 2.1.1 (Matching CMDP for re-ranking)**.** The state is a context $s = (\mathbf{j}, \mathbf{c}, g)$ where $\mathbf{j} \in \mathbb{R}^{16}$ is the job skill vector, $\mathbf{c} \in \mathbb{R}^{16}$ the candidate skill vector, and $g \in \{0, 1\}$ the protected attribute. The action is binary, $a \in \{0, 1\}$ (recommend / skip). The reward is the positive-interview indicator $r(s, a) = a \cdot \mathbb{1}[\text{positive interview}]$. The cost is the *group-level* demographic-parity gap measured over a sliding window of recent actions:

$$c_t = \left| \widehat{p}_t(a = 1 \mid g = 0) - \widehat{p}_t(a = 1 \mid g = 1) \right|,$$

where $\widehat{p}_t$ is the empirical recommend rate over the last W decisions. The budget is d, the maximum tolerated parity gap.

The CMDP optimisation is

$$\max_{\pi} \ \mathbb{E}_\pi \left[\sum_t r(s_t, a_t) \right] \ \text{ s.t. } \ \mathbb{E}_\pi[c_t] \ \leq \ d.$$

Note: cost is a population statistic. Unlike the lava-gridworld cost (per-step physical hazard), the fairness cost *depends on the action distribution* rather than individual actions. This is a policy-level constraint. For fixed exogenous group frequencies, the population DP constraint can be expressed as two linear inequalities in expected group-conditional action rates. A sliding-window statistic, however, depends on history: the displayed context alone is not a Markov state for this cost. The toy trainer uses the same differentiable batch gap in predicted recommendation probabilities for its actor penalty and multiplier update. Realised window gaps are diagnostics. This is a finite-batch surrogate, not an exact CMDP policy-gradient or a population strong-duality guarantee. A faithful sequential formulation would include window history in state and account for how an action changes future windows.

2.2 Off-policy evaluation: SNIPS

Definition 2.2.1 (Self-Normalised Inverse Propensity Score (SNIPS))**.** For a logged dataset $\{(s_i, a_i, r_i, \mu_i)\}_{i=1}^N$ with logging propensities $\mu_i = \mu(a_i \mid s_i)$ and a target policy π,

$$\hat{V}_{\text{SNIPS}}(\pi) = \frac{\sum_i \frac{\pi(a_i|s_i)}{\mu_i} r_i}{\sum_i \frac{\pi(a_i|s_i)}{\mu_i}}.$$

SNIPS is generally biased in finite samples because its denominator is random. It is consistent under correct logged propensities, target support contained in logger support, a suitable sampling law, and integrable weights/rewards. It can reduce variance relative to IPS, but this is not a universal bound. We use it to compare *the value of the trained policy against the logging policy* without rolling out a single new trajectory.

2.3 Fairness metrics

Definition 2.3.1 (Demographic parity gap)**.** $\text{DP}(\pi) = |P_\pi(a = 1 \mid g = 0) - P_\pi(a = 1 \mid g = 1)|$.

Definition 2.3.2 (Equal opportunity gap)**.** $\text{EO}(\pi) = |P_\pi(a = 1 \mid g = 0, y = 1) - P_\pi(a = 1 \mid g = 1, y = 1)|$, where y is the ground-truth positive-outcome label.

Calibration. Outcome calibration compares a prediction of $P(y = 1 \mid s)$ to observed outcomes in probability bins. The policy probability $\pi(a = 1 \mid s)$ is a decision frequency, not necessarily an outcome prediction. The toy audit plots the latter against relevance labels; treat it as a descriptive relationship, not evidence of outcome calibration or safe thresholding.

2.4 IQL in the one-step contextual setting

Theorem 2.4.1 (IQL collapse to AWR in 1-step bandits)**.** *For a contextual bandit (episodes of length 1), the IQL value/policy update reduces to advantage-weighted regression (AWR) with a single Q-network:*

$$\mathcal{L}_Q = \mathbb{E}_{(s,a,r)\sim D}\big[(Q(s,a) - r)^2\big], \qquad \mathcal{L}_V = \mathbb{E}_{(s,a)\sim D}\big[\rho_\tau(Q(s,a) - V(s))\big],$$

$$\mathcal{L}_\pi = -\mathbb{E}_{(s,a)\sim D}\big[\exp(\beta(Q(s,a) - V(s)))\, \log \pi(a \mid s)\big],$$

where ρ_τ is the expectile loss $\rho_\tau(x) = |\tau - \mathbb{1}[x < 0]| \cdot x^2$.

Sketch. The IQL update is $Q(s,a) \leftarrow r + \gamma V(s')$, which in the 1-step case reduces to $Q(s,a) \leftarrow r$ (since s' is terminal and $V(s') = 0$). The V expectile regression is then the same as in multi-step IQL. The policy step (AWR) is unchanged. □

This is exactly the implementation in `project/offline_iql.py`.

3 Algorithms

3.1 The three phases

Algorithm: Capstone pipeline

1. **Synthesise data.** Sample jobs, candidates, and 4000 logged ϵ-greedy interactions under a biased logger.
2. **IQL pretrain.** Run 30 epochs of expectile-Q + AWR over the dataset. Output: an initial policy π_0.
3. **PPO-Lagrangian fine-tune.** 25 dual-loop iterations of 512 rollout steps each. Differentiate the empirical gap in policy recommendation probabilities; update λ using that same gap.
4. **Audit.** On an independently held-out interaction set, compute DP, EO, SNIPS, reliability, and a counterfactual red-team probe.

3.2 Worked numerical example: the bias path

For relevance 0.3 and default group bias 0.6, the logger adds or subtracts 0.1: group 0 scores 0.4 and group 1 scores 0.2. Both are below the 0.5 threshold. With two actions and $\epsilon = 0.1$, each candidate is recommended with probability $\epsilon/2 = 0.05$, and skipped with probability 0.95. These particular contexts have equal logging recommendation probabilities, despite different scores.

At relevance 0.5, group 0 scores 0.6 and is recommended with probability $0.9 + 0.05 = 0.95$; group 1 scores 0.4 and is recommended with probability 0.05. This pair demonstrates the actual support imbalance. With correct contextual coverage, a biased action frequency does not by itself imply downward-biased conditional Q estimates. It reduces coverage and can distort the learned policy through finite data and approximation. A parity penalty can reduce either group's recommendation rate; it need not correct disparity by raising the disadvantaged group's rate.

3.3 The sliding-window cost estimator

The cost is computed over a sliding window of length $W = 256$. At each step we append (g, a) to the deque and compute

$$\hat{c} = \left| \frac{\sum_{(g_i,a_i)\in W,\, g_i=0} a_i}{N_0} - \frac{\sum_{(g_i,a_i)\in W,\, g_i=1} a_i}{N_1} \right|.$$

The moving-window quantity is a diagnostic. The actor instead differentiates

$$\hat{g}(\theta) = \left| \frac{1}{N_0} \sum_{i:g_i=0} \pi_\theta(1 \mid x_i) - \frac{1}{N_1} \sum_{i:g_i=1} \pi_\theta(1 \mid x_i) \right|.$$

Both groups must appear. The actor adds a scaled $\lambda\hat{g}(\theta)$ penalty to its PPO loss; the dual update uses $\hat{g}(\theta) - d$. This empirical surrogate supplies no population fairness guarantee.

Common pitfall

A population gap is not an immediate bandit cost. Treating the moving-window gap as an independent one-step cost omits how each action changes later windows. A cost critic does not repair that missing gradient. The explicit probability-gap penalty makes the implemented surrogate visible; its behaviour still depends on sampling, optimisation, and scale.

4 Implementation walkthrough

4.1 Data synthesis

```
def _logging_policy_score(job, cand, group_bias=0.6):
    rel = _true_relevance(job, cand)
    bias = group_bias - 0.5
    return rel + (bias if cand.group == 0 else -bias)

def generate_dataset(n_candidates=1000, n_jobs=50, n_interactions=4000, eps=0.1,
↪   seed=0):
    ...
```

The true relevance is a clean cosine-similarity scalar; the logging policy adds a group-dependent distortion to the logger's score.

4.2 IQL training (one-step)

```
# Q step (regression to r, since s' is terminal).
q_pred = model.q(o).gather(1, a.unsqueeze(-1)).squeeze(-1)
q_loss = F.mse_loss(q_pred, r)
# V step (expectile regression).
v_loss = expectile_loss(q_target - v_pred, tau)
# Pi step (AWR).
adv = q_target - v_pred
w = torch.clamp(torch.exp(beta * adv), max=100.0)
pi_loss = -(w * logp).mean()
```

We chose $\tau = 0.7$ (mild upper-expectile bias) and $\beta = 3$ (moderate sharpening). These are standard IQL hyperparameters.

4.3 PPO-Lagrangian online

The implementation reuses the week-22 PPO-Lagrangian almost verbatim, with two additions:

1. Initial weights come from the IQL pretrain (warm start).
2. The differentiable fairness penalty is the absolute gap in mean recommendation probability between groups in the rollout batch. Sliding-window sampled parity is reported as a diagnostic.

4.4 Audit module

```
def full_audit(net, data, n_episodes=500):
    ...
    return {
        "demographic_parity_gap": dp,
        "equal_opportunity_gap": eo,
        "snips_value": snips,
        "calibration": cal,
        "red_team": {"noise": ..., "group_flip_disagreement": ...},
        "mean_rec_rate": float(actions.mean()),
    }
```

4.5 The CLI

```
python -m project.cli rank \
    --job '{"title": "Senior SDE", "skills": [...16 floats...]}' \
    --candidates candidates.json
```

Evaluation scope. The trainer uses an independent synthetic population and logged sample for the before/after audits. Fine-tuning copies the offline policy so the before audit retains its original weights. These audits assess the simulator and do not establish performance on live outcomes.

The CLI runs the whole pipeline end-to-end (30 s on CPU) and emits both a ranked list and an audit summary. In a real deployment the pipeline would be triggered by a nightly retrain; the audit summary lands in a dashboard and an alerting channel.

5 Empirical results

5.1 Statistics bridge: A small subgroup can dominate uncertainty in a safety audit

Example 5.1.1 (Original statistical teaching fixture)**.** Two subgroups show zero failures in 100 and 10 independent Bernoulli evaluations respectively. Assume a stable failure probability within each subgroup for this interval illustration.

With zero failures, the exact one-sided 95% upper bound is $1 - 0.05^{1/n}$. At $n = 100$ it is about 0.02951; at $n = 10$ it is about 0.25887. Identical observed rates of zero therefore leave very different subgroup uncertainty.

Neither subgroup has established a failure probability below a one-percent budget. Pooling can obscure weak subgroup evidence, and searching many subgroup definitions on the same data introduces selection. The Bernoulli bound also requires the stated independent-unit assumptions.

Check a changed assumption. What bound results at 1,000 independent zero-failure trials? Would repeated decisions from ten customers justify treating the trial count as 1,000?

Check. The bound becomes $1 - 0.05^{1/1000} \approx 0.002991$. Repeated customer decisions may be dependent; preserve customer clustering and state the population to which the bound applies.

Statistical foundation. Siegrist § 8.1, PDF p.960; Ross § 7.3, PDF p.309. Section source: https://stats.libretexts.org/@go/page/10200. The course statistics companion records the supplied editions and one-based PDF pages. This fixture is not a newly measured project result.




Figure 5.1: Left: IQL pretrain losses on the synthetic dataset. Centre: online return during PPO-Lagrangian fine-tune. Right: sampled parity diagnostic tracked against the budget d, alongside the Lagrange multiplier λ. The update uses a probability-gap surrogate.

5.2 Reading the audit

For a representative run (seed 0, cost limit $d = 0.10$):




Figure 5.2: Online return, sampled parity diagnostic and multiplier during fine-tuning. A finite simulation curve does not establish fairness feasibility on a new population.




Figure 5.3: Observed trade-off between fairness (lower DP gap) and value (higher SNIPS). Each point is a separate training run at the indicated cost budget d. This finite sweep need not be a monotone frontier.

- DP gap before fine-tune ~ 0.05, after ~ 0.03 — the Lagrangian closes the gap without crashing reward.
- SNIPS value before ~ 0.10, after ~ 0.25 — the re-weighted off-policy estimate of *achievable reward* more than doubles, even with a tighter fairness budget.
- Counterfactual group-flip disagreement: ~ 0.10 before, ~ 0.05 after — the policy becomes more attribute-invariant.

This is the audit page you would present to compliance, with seeds, code hashes, and dataset SHAs attached.

Safety angle

This week's safety analysis is the entire lecture. A condensed lessons-list:

- **Logging bias is the default.** Any RL trained on observational human data inherits a bias structure unless explicitly counteracted.




Figure 5.4: Reliability diagram before vs. after Lagrangian fine-tune. The plot compares action probabilities with synthetic relevance labels. This does not establish calibrated outcome predictions or safe decisions.

- **Population-level constraints are tractable.** Demographic-parity constraints fit straight into the CMDP framework; the dual variable is the price of fairness.
- **Audits must be multi-metric.** DP and EO disagree on which policies satisfy a chosen definition; calibration asks another question. SNIPS is a value point estimate, not a bound. Report the metric definitions, appropriate uncertainty and their limitations together.
- **Counterfactual probes catch attribute leakage.** If flipping g changes the top-1 decision rate above your tolerance, you have a problem regardless of what DP says.
- **Offline-first matters.** A randomly initialised online policy interacting with real users (candidates) is unacceptable. IQL gives a data-informed warm start, not a safety certificate.

References: Kostrikov et al. 2021, arXiv:2110.06169, "Offline RL with Implicit Q-Learning"; Ray, Achiam, Amodei 2019, author-published Safety Gym report; Hardt, Price, Srebro 2016, arXiv:1610.02413, "Equality of opportunity". For additional offline-safe-RL datasets and algorithms, require a verified primary source and a matching cost definition before extending the exercise.

Matching application

This entire lecture is the matching application. Two more concrete connections:
To synthetic ATS. This synthetic pipeline is a design exercise, not a drop-in validated production replacement. A real integration needs its own action space, reward definition, logging support, held-out evaluation, and review of which fairness estimands fit the decision. Use documented, appropriately collected audit attributes; do not infer sensitive identities from names or pronouns as a substitute for validated group information.
To synthetic insurance lead routing. Same skeleton, different cost: instead of demographic parity, the cost is broker-saturation variance, and the "protected attribute" is the broker's tier. The Lagrangian prices broker fairness; the audit reports broker-level

conversion ratios and an OPE estimate of the revenue under the live policy without rolling it out.

General template. Any two-sided market re-ranking problem: (i) train offline; (ii) fine-tune online with PPO-Lagrangian on population-level constraints; (iii) audit before deploy; (iv) ship behind a CLI / dashboard with the audit row attached to every recommendation batch.

6 Exercises

- **Ex. 1 ($\star$):** dataset synthesis and shape verification.
- **Ex. 2 ($\star$):** measure the logger's demographic parity gap.
- **Ex. 3 ($\star\star$):** IQL pretrain and inspect losses.
- **Ex. 4 ($\star\star$):** SNIPS off-policy evaluation of a uniformly random target.
- **Ex. 5 ($\star\star$):** PPO-Lagrangian fine-tune; record the final parity gap.
- **Ex. 6 ($\star\star\star$, meaningful objective):** end-to-end pipeline; before/after audit; tie the result to a synthetic insurance or ATS deployment.
- **Ex. 7 ($\star\star\star$):** counterfactual red-team probe.
- **Ex. 8 ($\star\star\star$, open-ended):** sketch the Pareto frontier between fairness budget and SNIPS value.

7 Further reading

See `extended_reading.pdf` for the full annotated bibliography. Sourced from `research/safety_rl_sota.md` (sections 1, 5, 6, 8), `research/bandits_matching_sota.md` (off-policy evaluation, fairness), and `research/llm_rl_sota.md` (audits and alignment).