Action API

class **mini.apis.api_action.PlayAction**(*is_serial: bool = True, action_name: Optional[str] = None*) [source]

Bases: `mini.apis.base_api.BaseApi`

Execute built-in action API

The robot performs a built-in action with a specified name The action name can be obtained with GetActionList APi

Parameters:
- **is_serial** (*bool*) – Whether to wait for a reply, the default is True
- **action_name** (*str*) – Action name, cannot be none or empty string

#PlayActionResponse.isSuccess : True or False

#PlayActionResponse.resultCode : Result Code

async **execute**() [source]

Send instructions to execute actions

Returns: PlayActionResponse

class **mini.apis.api_action.StopAllAction**(*is_serial: bool = True*) [source]

Bases: `mini.apis.base_api.BaseApi`

Stop all action API

Stop all actions being performed, stop the specified custom action.

if the action is an uninterruptible action, StopCustomActionResponse.resultCode = 403

Args

is_serial (bool): Whether to wait for a reply, the default is True

async **execute**() [source]

Send command to stop all actions

Returns: StopActionResponse

class **mini.apis.api_action.MoveRobotDirection**(*value*) [source]

Bases: `enum.Enum`

Robot moving direction

FORWARD : move forward

BACKWARD : move backward

LEFTWARD : move leftward

RIGHTWARD : move rightward

> **FORWARD**= *3*

> **BACKWARD**= *4*

> **LEFTWARD**= *1*

> **RIGHTWARD**= *2*

---

class **mini.apis.api_action.MoveRobot**(*is_serial: bool = True, direction: mini.apis.api_action.MoveRobotDirection = MoveRobotDirection.FORWARD, step: int = 1*) [source]

Bases: `mini.apis.base_api.BaseApi`

Control robot moving-API

Control the robot to move n steps in a certain direction (MoveRobotDirection)

Parameters:
- **is_serial** (*bool*) – Whether to wait for a reply, the default is True
- **direction** (*MoveRobotDirection*) – Robot movement direction, default FORWARD, move forward
- **step** (*int*) – Number of steps, default 1 step

#MoveRobotResponse.isSuccess : True or False

#MoveRobotResponse.code : Result Code

> *async* **execute**() [source]

Send robot movement instructions

Returns: MoveRobotResponse

---

class **mini.apis.api_action.RobotActionType**(*value*) [source]

Bases: `enum.Enum`

Robot action resource type

INNER (built-in): the unmodifiable motion file built into the robot

CUSTOM (custom): Action files that can be modified by the developer placed in the sdcard/customize/actions directory

> **INNER**= *0*

> **CUSTOM**= *1*

---

class **mini.apis.api_action.GetActionList**(*is_serial: bool = True, action_type: mini.apis.api_action.RobotActionType = RobotActionType.INNER*) [source]

Bases: `mini.apis.base_api.BaseApi`

Get robot action resource list API

Get a list of action files stored in the robot's local (built-in/custom)

Parameters:
- **is_serial** (*bool*) – Whether to wait for a reply, the default is True
- **action_type** (*RobotActionType*) – Action type, default is INNER, built-in action

#GetActionListResponse.actionList ([str]): Action list, str array

#GetActionListResponse.isSuccess: Is it successful, True Or False

#GetActionListResponse.resultCode: Result Code

> *async* **execute**() [source]

Send command to get list of robot actions

Returns: GetActionListResponse

---

class **mini.apis.api_action.PlayCustomAction**(*is_serial: bool = True, action_name: Optional[str] = None*) [source]

Bases: `mini.apis.base_api.BaseApi`

xecute custom action api

Let the robot perform a custom action with a specified name.

Action name can be obtained with GetActionList.

Parameters:
- **is_serial** (*bool*) – Whether to wait for a reply, the default is True
- **action_name** (*str*) – custom action name, cannot be empty or None

#PlayCustomActionResponse.isSuccess: Is it successful

#PlayCustomActionResponse.resultCode: Return code

> *async* **execute**() [source]

execute custom action instructions

Returns: PlayCustomActionResponse

---

class **mini.apis.api_action.StopCustomAction**(*is_serial: bool = True, action_name: Optional[str] = None*) [source]

Bases: `mini.apis.base_api.BaseApi`

Stop custom action API

Stop the specified custom action, if the action is an uninterruptible action, StopCustomActionResponse.resultCode = 403

Parameters:
- **is_serial** (*bool*) – Whether to wait for a reply, the default is True
- **action_name** (*str*) – custom action name, cannot be empty or None

#StopCustomActionResponse.isSuccess: Is it successful

#StopCustomActionResponse.resultCode: Return code

async **execute**() [source]

Execute stop custom action command

Returns: StopCustomActionResponse