Common API

mini.mini_sdk.set_log_level(*level: int, save_file: Optional[str] = None*) [source]

Set the sdk log level

Parameters:
- **level** – logging.DEBUG, logging.INFO, logging.WARNING, logging.ERROR
- **save_file** – Need to save to a file, fill in the log file path

class **mini.mini_sdk.RobotType**(*value*) [source]

Bases: `enum.Enum`

Robot Product Type

DEDU = *1*

AlphaMini China Education Edition

MINI = *2*

AlphaMini China Standard Edition

EDU = *3*

AlphaMini Oversea Education Edition

KOR = *4*

AlphaMini Korea Edition

OTOC = *5*

AlphaMini Oversea ToC Edition

mini.mini_sdk.set_robot_type(*robot: mini.mini_sdk.RobotType*) [source]

Set the robot product type to be linked

Parameters: **robot** – Value is: RobotType.EDU, RobotType.KOR, RobotType.MINI or RobotType.DEDU

async **mini.mini_sdk.get_device_by_name**(*name: str, timeout: int*) → Optional[mini.dns.dns_browser.WiFiDevice] [source]

Get the robot device information with the specified name in the current LAN

Parameters:
- **name** – device serial number
- **timeout** – scan timeout

Returns: Optional[WiFiDevice]

async **mini.mini_sdk.get_device_list**(*timeout: int*) → tuple [source]

Get all the robot device information in the current LAN

Parameters: **timeout** – timeout

Returns: Optional[WiFiDevice]

---

async **mini.mini_sdk.connect**(*device: mini.dns.dns_browser.WiFiDevice*)→ bool [source]

Connect robot equipment

Parameters: **device** (*WiFiDevice*) – Specify the robot device object

Returns: Whether the device is connected successfully

Return type: bool

---

async **mini.mini_sdk.release**() [source]

Disconnect the link and release resources

---

async **mini.mini_sdk.enter_program**()→ bool [source]

Enter programming mode api

Robot enters programming mode

Returns: bool

---

async **mini.mini_sdk.quit_program**()→ bool [source]

Exit programming mode api

Robot exits programming mode

Returns: bool

---

async **mini.mini_sdk.play_action**(*action_name: Optional[str] = None*)→ bool [source]

Execute built-in action api

The robot performs a built-in action with a specified name

The action name can be obtained with get_action_list

Parameters: **action_name** (*str*) – action name

Returns: bool

---

async **mini.mini_sdk.stop_action**()→ bool [source]

Stop action

If the action is an uninterruptible action, stop_action returns False

Returns: bool

---

async **mini.mini_sdk.play_custom_action**(*action_name: Optional[str] = None*)→ bool [source]

Execute custom action api

Let the robot perform a custom action with a specified name and wait for the result

The action name can be obtained by get_custom_action_list

Parameters: **action_name** (*str*) – custom action name

Returns: bool

---

async **mini.mini_sdk.stop_custom_action**()→ bool [source]

Stop custom action

If the action is an uninterruptible action, stop_action returns False

Returns: bool

---

async **mini.mini_sdk.move**(*direction: mini.apis.api_action.MoveRobotDirection = MoveRobotDirection.FORWARD, step: int = 1*)→ bool [source]

Control robot movement

Control the robot to move 10 steps to the left (LEFTWARD) and wait for the execution result

Parameters:
- **direction** (*MoveRobotDirection*) – direction
- **step** (*int*) – number of steps

Returns: bool

---

async **mini.mini_sdk.get_action_list**()→ list [source]

Get action list

Get the list of actions built into the robot system, and wait for the reply result

Returns: Action list

Return type: []

---

async **mini.mini_sdk.get_custom_action_list**()→ list [source]

Get a list of custom actions

Get the action list under the robot/sdcard/customize/actions and wait for the reply result

Returns: Custom action list

Return type: []

---

async **mini.mini_sdk.wiki**(*query: str*)→ bool [source]

Query encyclopedia demo

Query encyclopedia, for example: query content “you must choose”, and wait for the result, the robot broadcasts the

query result

Parameters: **query** (*str*) – query keyword

Returns: bool

---

async **mini.mini_sdk.translate**(*query: str, from_lan: Optional[mini.apis.api_config.LanType] = None, to_lan: Optional[mini.apis.api_config.LanType] = None, platform: mini.apis.api_config.ServicePlatform = ServicePlatform.BAIDU*)→ bool [source]

translation

For example: Use Baidu Translate to translate “张学友” from Chinese to English, and wait for the result,

the robot broadcasts the translation result:

translate(query=”张学友”,from_lan=CN,to_lan=EN,platform=GOOGLE)

Args:

query (str): keyword from_lan (LanType): source language to_lan (LanType): target language platform (ServicePlatform): GOOGLE, Only Support Google

Returns: bool

---

async **mini.mini_sdk.play_expression**(*express_name: str*)→ **bool** [source]

Do an Expression

Let the robot play a built-in expression of express_name and wait for the reply result

Parameters: **express_name** (*str*) – emoticon file name, such as: “codemao1”

Returns: bool

---

async **mini.mini_sdk.play_behavior**(*behavior_name: str*)→ **bool** [source]

Do a dance

Let the robot start to dance a dance named behavior_name and wait for the response result

Parameters: **behavior_name** (*str*) – e.g. “dance_0004”

Returns: bool

---

async **mini.mini_sdk.stop_behavior**()→ **bool** [source]

stop dance

Returns: bool

---

async **mini.mini_sdk.set_MouthLamp_NormalMode**(*color: mini.apis.api_expression.MouthLampColor = MouthLampColor.RED, duration: int = 1000*)→ **bool** [source]

Set mouth light always on mode and wait for the result

Parameters:
- **color** (*MouthLampColor*) – Mouth lamp color, default RED
- **duration** (*int*) – unit ms, duration

Returns: bool

---

async **mini.mini_sdk.set_MouthLamp_BreathMode**(*breath_duration: int = 1000, color: mini.apis.api_expression.MouthLampColor = MouthLampColor.RED, duration: int = 1000*)→ **bool** [source]

Set mouth light breathing mode and wait for the result

Parameters:
- **breath_duration** (*int*) – unit ms, the duration of one breath
- **color** (*MouthLampColor*) – Mouth lamp color, default RED
- **duration** (*int*) – unit ms, duration

Returns: bool

---

async **mini.mini_sdk.switch_MouthLamp**(*is_open: bool = True*)→ bool [source]

Switch mouth light

Turn on and off the robot's mouth light and wait for the result

Parameters: **is_open** – bool

Returns: bool

async **mini.mini_sdk.play_tts**(*text: str*)→ bool [source]

Play tts

Make the robot start playing a period of tts and wait for the result

Parameters: **text** – str, for example: "Hello, I am Wukong, la la la",

Returns: bool

async **mini.mini_sdk.stop_tts**()→ bool [source]

Stop speech synthesis broadcast, and wait for the result

Returns: bool

async **mini.mini_sdk.play_online_audio**(*url: str*)→ bool [source]

Play online sound effects

Make the robot play an online sound effect,

And wait for the result

Parameters: **url** – str, for example:
http://yun.lnpan.com/music/download/ring/000/075/5653bae83917a892589b372782175d
Supported formats are mp3, amr, wav, etc.

Returns: bool

async **mini.mini_sdk.play_local_audio**(*local_file: str*)→ bool [source]

Play local sound effects

Make the robot play a local built-in sound effect, the sound effect name is "read_016", and wait for the result

Parameters: **local_file** –

Returns: bool

async **mini.mini_sdk.stop_audio**()→ bool [source]

Stop all audio that is playing

Stop all sound effects and wait for the result

Returns: bool

async **mini.mini_sdk.get_system_audio_list**()→ codemao_getaudiolist_pb2.GetAudioListResponse [source]

Get a list of sound effects

Get the list of sound effects built into the robot and wait for the result

#GetAudioListResponse.audio ([Audio]): audio effect list

#Audio.name: Audio effect name

#Audio.suffix: audio suffix

#GetAudioListResponse.isSuccess: Is it successful, True or False

#GetAudioListResponse.resultCode: Result code

Returns: GetAudioListResponse

---

async **mini.mini_sdk.get_custom_audio_list**()→ codemao_getaudiolist_pb2.GetAudioListResponse [source]

Get a list of sound effects

Get the list of sound effects placed by the robot developer under /sdcard/customize/music/, and wait for the result

#GetAudioListResponse.audio ([Audio]): Audio effect list

#Audio.name: Audio effect name

#Audio.suffix: audio suffix

#GetAudioListResponse.isSuccess: Is it successful, True or False

#GetAudioListResponse.resultCode: Result code

Returns: GetAudioListResponse

---

async **mini.mini_sdk.change_volume**(*volume: float = 0.5*)→ bool [source]

Adjust the robot volume demo

Set the robot volume to 0~1 and wait for the reply result

Parameters: **volume** – float default 0.5

Returns: bool

---

async **mini.mini_sdk.face_detect**()→ codemao_facedetect_pb2.FaceDetectResponse [source]

Face count detection

Do a face count detection and wait for the reply result

#FaceDetectResponse.count: the number of faces

#FaceDetectResponse.isSuccess: Is it successful, True or False

#FaceDetectResponse.resultCode: Return code

Returns: FaceDetectResponse

---

async **mini.mini_sdk.face_analysis**()→ codemao_faceanalyze_pb2.FaceAnalyzeResponse [source]

Face analysis (gender)

Do a face information (gender, age) detection, and wait for the reply result

When multiple people are in front of the camera, return the face information that accounts for the

largest proportion of the screen.

Return value: Example {“age”: 24, “gender”: 99, “height”: 238, “width”: 238}

age: age

gender: [1, 100], females less than 50 are females, males greater than 50

height: the height of the face in the camera image

width: the width of the face in the camera image

#FaceAnalyzeResponse.faceInfos: face information array [FaceInfoResponse]

#FaceInfoResponse.gender (int) :[1,100], females less than 50, males greater than 50

#FaceInfoResponse.age: age

#FaceInfoResponse.width: The width of the face in the camera screen

#FaceInfoResponse.height: The height of the face in the camera screen

#FaceAnalyzeResponse.isSuccess: Is it successful, True or False

#FaceAnalyzeResponse.resultCode: Return code

Returns: FaceAnalyzeResponse

---

async **mini.mini_sdk.face_recognise**()→ codemao_facerecognise_pb2.FaceRecogniseResponse
[source]

Face recognition

Do a face recognition test and wait for the result

#FaceRecogniseResponse.faceInfos: [FaceInfoResponse] face information array

#FaceInfoResponse.id: face id

#FaceInfoResponse.name: name, if it is a stranger, the default name is “stranger”

#FaceInfoResponse.gender: gender

#FaceInfoResponse.age: age

#FaceRecogniseResponse.isSuccess: Is it successful, True or False

#FaceRecogniseResponse.resultCode: Return code

Returns: RecogniseObjectResponse

---

async **mini.mini_sdk.flower_recognise**()→ codemao_recogniseobject_pb2.RecogniseObjectResponse
[source]

Flower and grass recognition

Let the robot do a flower and grass recognition (you need to manually place the flower or flower photo in front of the robot),

and wait for the result.

#RecogniseObjectResponse.objects: Recognition result array [str]

#RecogniseObjectResponse.isSuccess: Is it successful, True or False

#RecogniseObjectResponse.resultCode: Return code

Returns: RecogniseObjectResponse

---

async **mini.mini_sdk.fruit_recognise**()→ codemao_recogniseobject_pb2.RecogniseObjectResponse [source]

Fruit recognition

Let the robot do a fruit recognition (you need to manually put the fruit or fruit photo in front of the robot),

and wait for the result.

#RecogniseObjectResponse.objects: Recognition result array [str]

#RecogniseObjectResponse.isSuccess: Is it successful

#RecogniseObjectResponse.resultCode: Return code

Returns: RecogniseObjectResponse

---

async **mini.mini_sdk.gesture_recognise**()→ codemao_recogniseobject_pb2.RecogniseObjectResponse [source]

Gesture Recognition

Let the robot do a user gesture recognition, (need to make a gesture in front of the robot), and wait for the result

#RecogniseObjectResponse.objects: Recognition result array [str]

#RecogniseObjectResponse.isSuccess: Is it successful

#RecogniseObjectResponse.resultCode: Return code

Returns: RecogniseObjectResponse

---

async **mini.mini_sdk.take_picture_immediately**()→ codemao_takepicture_pb2.TakePictureResponse [source]

Take pictures

Let the robot take a photo immediately and wait for the result

#TakePictureResponse.isSuccess: Is it successful, True or False

#TakePictureResponse.code: Return code

#TakePictureResponse.picPath: The storage path of the photo in the robot

Returns: TakePictureResponse

---

async **mini.mini_sdk.take_picture**()→ codemao_takepicture_pb2.TakePictureResponse [source]

Take pictures

Let the robot find the face before taking a picture and wait for the result

#TakePictureResponse.isSuccess: Is it successful, True or False

#TakePictureResponse.code: Return code

#TakePictureResponse.picPath: The storage path of the photo in the robot

Returns: TakePictureResponse

---

async **mini.mini_sdk.get_register_faces()→ codemao_getregisterfaces_pb2.GetRegisterFacesResponse** [source]

Get registered face information

Get all the face information registered in the robot and wait for the result

#GetRegisterFacesResponse.faceInfos: [FaceInfoResponse] face information array

#FaceInfoResponse.id: face id

#FaceInfoResponse.name: name

#FaceInfoResponse.gender: gender

#FaceInfoResponse.age: age

#GetRegisterFacesResponse.isSuccess: Is it successful, True or False

#GetRegisterFacesResponse.resultCode: Return code

Returns: GetRegisterFacesResponse

---

async **mini.mini_sdk.get_infrared_distance()→ codemao_getinfrareddistance_pb2.GetInfraredDistanceResponse** [source]

Infrared distance detection

Get the infrared distance detected by the current robot and wait for the result

#GetInfraredDistanceResponse.distance: Infrared distance

Returns: GetInfraredDistanceResponse