Tools API

mini.pkg_tool.setup_py_pkg(*project_dir: str*)→ str [source]

Package a py project into a .whl file.

Parameters: **project_dir** – project file root directory

Returns: the absolute path of the generated .whl file

Return type: str

mini.pkg_tool.install_py_pkg(*package_path: str, robot_id: str, debug: bool = False*) [source]

Install a py program installation package on the robot with the specified serial number.

Parameters:
- **package_path** – the absolute path of the installation package
- **robot_id** – robot serial number
- **debug** – Whether to print the log when pkg is uninstalled on the robot side

Returns: None

mini.pkg_tool.uninstall_py_pkg(*pkg_name: str, robot_id: str, debug: bool = False*) [source]

Uninstall an installed py program from the robot with the specified serial number. For example, there is a py program whose setup.py file is configured as follows:

setuptools.setup(

name=”tts_demo”,

...#Omitted

),

Then, its pkg_name is “tts_demo”.

Parameters:
- **pkg_name** – program name
- **robot_id** – robot serial number
- **debug** – Whether to print the log when pkg is uninstalled on the robot side

Returns: None

mini.pkg_tool.query_py_pkg(*pkg_name: str, robot_id: str*)→ str [source]

Query the py program specified by pkg_name on the robot, and its detailed information, for example, there is a py program, and its setup.py file is configured as follows:

```
setuptools.setup(
    name="tts_demo",
    version="0.0.2",
    author='Gino Deng',
    author_email='jingjing.deng@ubtrobot.com',
    description="demo with mini_sdk",
    long_description='demo with mini_sdk,xxxxxxx',
    long_description_content_type="text/markdown",
    license="GPLv3",
    packages=setuptools.find_packages(),
    classifiers=[
        "Programming Language :: Python :: 3",
        "Programming Language :: Python :: 3.6",
        "Programming Language :: Python :: 3.7",
        "Programming Language :: Python :: 3.8",
        "License :: OSI Approved :: MIT License",
        "Operating System :: OS Independent",
    ],
    install_requires=[
        'alphamini',
    ],
),
```

When querying, specify pkg_name="tts_demo", and the returned information is as follows:

Name: tts-demo

Version: 0.0.2

Summary: demo with mini_sdk

Home-page: UNKNOWN

Author: Gino Deng

Author-email: jingjing.deng@ubtrobot.com

License: GPLv3

Location: /data/data/com.termux/files/usr/lib/python3.8/site-packages

Requires: alphamini

Required-by:

Parameters:
- **pkg_name** – py program name,
- **robot_id** – robot serial number

Returns: install package trust information

Return type: str

---

mini.pkg_tool.list_py_pkg(*robot_id: str*)→ **str** [source]

List the py programs installed on the robot, for example:

Package Version

———- ——-

alphamini 0.1.0

ifaddr 0.1.7

pip 20.1.1

protobuf 3.12.2

setuptools 47.3.1

six 1.15.0

tts-demo 0.0.2

websockets 8.1

wheel 0.34.2

Parameters: **robot_id** – robot serial number

Returns: name of all py programs-version number

Return type: str

---

mini.pkg_tool.run_py_pkg(*entry_point: str, robot_id: str, debug: bool = False*) [source]

Trigger a specified py program to run on the specified robot. :

Parameters:

- **entry_point** – The name of the console scripts of the py program, for example, in the setup.py file,
- **entry_points=(** (*such as configuration*) –
  'console_scripts': [

  'XXX = Packages.Modules:XXX'

  ],
  }, the program entry name is xxx
- **robot_id** – robot serial number
- **debug** – Whether to return the log when the program is executed

Returns: None

---

mini.pkg_tool.switch_adb(*robot_id: str, switch: bool = True*) [source]

Turn on the robot ADB debugging switch :param switch: bool, True or False :param robot_id: robot serial number

Returns: None

---

mini.pkg_tool.upload_script(*cmd_id: int, robot_id: str, file_name: Optional[str] = None, content: Optional[bytes] = None*) [source]