

Javascript Notes: Concepts, Algorithms, and Data Structures

Samuel Duval

July 26, 2022

Welcome to my notes on coding. In this document I'll keep track of basic Javascript concepts, algorithms, and perhaps some data structures as well. These notes are to help me formalize this information in my own brain. Pretty much everything is from the internet, attribution will be given in some cases, but generally for the sake of brevity and since all concepts are basic it will be omitted.

Contents

1 Basic Javascript Concepts	5
1.1 Array.prototype.slice()	5
1.2 Array.prototype.sort()	6
1.3 Array.prototype.join()	7
1.4 Array.prototype.indexOf()	8
1.5 Array.prototype.reduce()	9
1.6 String.prototype.split()	10
1.7 Array.prototype.fill()	11
1.8 map()	12
1.9 Array.prototype.push()	14
1.10 Array.prototype.splice()	15
1.11 Bitwise XOR (^)	16
1.12 String.prototype.charCodeAt()	17
1.13 String.fromCharCode()	18
1.14 Array.prototype.some()	19
1.15 Array.prototype.every()	20
1.16 Array.prototype.includes()	21
1.17 Array.prototype.find()	22
1.18 Math.max(), Math.min(), Math.abs()	23
1.19 parseInt() & parseFloat()	24
1.20 Logical (and &&) and (or)	25
1.21 Set() constructor	27
1.22 String.prototype.charAt()	28
1.23 for...of	29
1.24 for...in	30
1.25 Conditional (ternary) operator	31
1.26 Map.prototype.get()	32
1.27 Map.prototype.has()	33
1.28 Set	34
1.29 Object.prototype.toString()	36
1.30 String.prototype.replace()	37
1.31 Set.prototype.add()	38
1.32 Array.prototype.unshift()	39
1.33 Set.prototype.size	40
1.34 Set.prototype.delete()	41
1.35 delete operator	42

1.36	Array.prototype.reverse()	43
1.37	Array() constructor	45
1.38	Math.trunc()	46
1.39	continue	47
1.40	Map.prototype.set()	49
1.41	String.prototype.substring()	50
1.42	String.prototype.toLowerCase() String.prototype.toUpperCase()	51
1.43	this	52
1.44	Object.values()	53
1.45	constructor	55
1.46	Classes	56
1.47	Array.from()	57
1.48	Array.prototype.forEach()	58
1.49	Map() constructor	59
2	Array Algorithm Problems	60
2.1	Build Array from Permutation	60
2.2	Count Items Matching a Rule	61
2.3	Create Target Array in the Given Order	62
2.4	Decode XORed Array	63
2.5	Decompress Run-Length Encoded List	64
2.6	Final Value of Variable After Performing Operations	65
2.7	Concatenation of Array	66
2.8	Kids With the Greatest Number of Candies	67
2.9	Maximum Number of Words Found in Sentences	69
2.10	Number of Good Pairs	70
2.11	Shuffle String	71
2.12	Richest Customer Wealth	72
2.13	Running Sum of 1d Array	73
2.14	Shuffle the Array	74
2.15	How Many Numbers Are Smaller Than the Current Number	75
2.16	Sum of All Odd Length Subarrays	76
2.17	Count Number of Pairs With Absolute Difference K	78
2.18	Minimum Number of Moves to Seat Everyone	79
2.19	Minimum Amount of Time to Fill Cups	80
2.20	Assign Cookies	81
3	String Algorithm Problems	82
3.1	Defanging an IP Address	82
3.2	Jewels and Stones	83
3.3	Goal Parser Interpretation	84
3.4	Cells in a Range on an Excel Sheet	85
3.5	Split a String in Balanced Strings	86
3.6	Sorting the Sentence	88
3.7	Decode the Message	89
3.8	Maximum Nesting Depth of the Parentheses	90

3.9	Fizz Buzz	91
3.10	Check If Two String Arrays are Equivalent	92
3.11	Count the Number of Consistent Strings	93
3.12	To Lower Case	95
3.13	Rings and Rods	96
3.14	Truncate Sentence	98
3.15	Check if the Sentence Is Pangram	99
3.16	Count Asterisks	100
3.17	Unique Morse Code Words	102
3.18	Number of Strings That Appear as Substrings in Word	104
3.19	Remove Outermost Parentheses	105
3.20	Replace All Digits with Characters	106
4	Hash Tables	107
4.1	Destination City	107
4.2	Maximum Number of Pairs in Array	108
4.3	Design an Ordered Stream	109
4.4	Increasing Decreasing String	110
4.5	Check if All Characters Have Equal Number of Occurrences	111
4.6	Divide Array Into Equal Pairs	112
4.7	N-Repeated Element in Size 2N Array	113
4.8	Sum of Unique Elements	114
4.9	Maximum Number of Balls in a Box	115
4.10	Check if Number Has Equal Digit Count and Digit Value	116
4.11	Keep Multiplying Found Values by Two	117
4.12	Two Out of Three	118
4.13	Kth Distinct String in an Array	120
4.14	Maximum Number of Words You Can Type	121
4.15	Substrings of Size Three with Distinct Characters	122
4.16	Find the Difference of Two Arrays	123
4.17	Isomorphic Strings	124
4.18	Word Pattern	125
4.19	Longest Harmonious Subsequence	126
4.20	Next Greater Element I	127
5	Dynamic Programming	128
5.1	Counting Bits	128
5.2	Fibonacci Number	129
5.3	Pascal's Triangle	130
5.4	Divisor Game	132
5.5	N-th Tribonacci Number	133
5.6	Min Cost Climbing Stairs	134
5.7	Pascal's Triangle II	135
5.8	Best Time to Buy and Sell Stock	136

1 Basic Javascript Concepts

1.1 Array.prototype.slice()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/slice

- slice() returns a shallow copy of a portion of an array
- array.slice(startIndex, endIndex)
- slice() does not modify the array
- without arguments slice() will automatically be slice(0, endIndex)

Example slice()

```
1 let fruits = ['Banana', 'Orange', 'Lemon', 'Apple',  
2             , 'Mango']  
3 let citrus = fruits.slice(1, 3)  
4 // citrus contains ['Orange','Lemon']  
5  
6 // fruits STILL contains ['Banana', 'Orange', '  
    Lemon', 'Apple', 'Mango']
```

1.2 `Array.prototype.sort()`

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/sort

- `sort()` returns the same array in sorted order
- default order is ascending, done by converting everything to a string then comparing the UTF-16 code unit values. So it does not naturally work for numbers as expected.
- `sort()` modifies the array

Example `sort()` for integers

```
1 const numbers = [4, 2, 5, 1, 3];  
2  
3 numbers.sort((a, b) => a - b);  
4  
5 console.log(numbers);  
6 // [1, 2, 3, 4, 5]
```

1.3 Array.prototype.join()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/join

- join() returns a new STRING by concatenating all elements in an ARRAY
- items should be separated by commas (,) (or specified separator string), if only one item then that item will be returned without using the separator.

Example join()

```
1  const elements = ['Fire', 'Air', 'Water'];
2
3  console.log(elements.join());
4  // expected output: "Fire,Air,Water"
5
6  console.log(elements.join(' '));
7  // expected output: "FireAirWater"
8
9  console.log(elements.join('-'));
10 // expected output: "Fire-Air-Water"
```

1.4 Array.prototype.indexOf()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/indexOf

- `indexOf()` returns the first index at which a given element can be found in an array or -1 if not found
- good for finding the index of first appearance of something. If you want last use `lastIndexOf()`

Example `indexOf()`

```
1 const names = ['sam', 'bill', 'steve', 'matt']
2
3 const idx = names.indexOf('sam')
4 names[idx] = 'replaced-sam'
5
6 console.log(names)
7 //['replaced-sam', 'bill', 'steve', 'matt']
```


1.5 `Array.prototype.reduce()`

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/reduce

- `reduce()` passes a callback function on each item in the array and has a second parameter for storing current value
- `reduce((callback, currentValue) → callback, currentValue)`

Example `reduce()`

```
1  const array = [1,2,3,4,5]
2
3  let reduceExample = array.reduce((callback,
4      currentValue) => callback + currentValue)
5  console.log(reduceExample)
6  //output: 15
```

1.6 String.prototype.split()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/String/split

- takes a string and splits it into parts and returns it as an array
- split(), split(separator), split(separator, limit)
- can pass in a value(separator) and it will decide where the string will be split
- can also take regular expressions ex. too many commas split(/,+/) may help resolve

Example split()

```
1 const splitString = 'Hello,my,name,is,Sam'
2
3 let split = splitString.split(',')
4
5 console.log(split)
6 //[ 'Hello', 'my', 'name', 'is', 'Sam' ]
```

1.7 `Array.prototype.fill()`

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/fill

- Modifies an array with the value given in `fill()`
- `fill(0)` by default, `fill(value, start, end)`
- useful for filling an array with numbers (0 seems common followed by other operations)

Example `fill()`

```
1  const fillArray = [0,1,2,3,4,5]
2  const fillArray2 = [0,1,2,3,4,5]
3
4  fillArray.fill(0)
5  //[ 0, 0, 0, 0, 0, 0 ]
6
7  fillArray2.fill(0,3,5)
8  //[ 0, 1, 2, 0, 0, 5 ]
```

1.8 map()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Map

- Executes a function on all elements of an array and returns a new array
- Does not change original array
- map(callback)
- Can even return new array of objects
- Useful for pulling specific parts out of an array or for manipulating an entire array (ex. to find total value of objects within)

Example simple map() multiplying all elements by two

```
1 const numbers = [1,2,3,4,5];
2
3 let mapNumbers = numbers.map(nums => (nums * 2))
4 // [ 2, 4, 6, 8, 10 ]
```

Example map() Number constructor turning string numbers into regular integers

```
1 const stringNumbers = ['1', '2', '3', '4', '5']
2
3 const regNumbers = stringNumbers.map(Number)
4 // [ 1, 2, 3, 4, 5 ]
```

Example simple map() to manipulate objects within array

```
1 const products = [
2   {
3     name: 'laptop',
4     price: 1500,
5     count: 5
6   },
7   {
8     name: 'desktop',
9     price: 2000,
10    count: 10
11  },
12  {
13    name: 'phone',
14    price: 1000,
15    count: 100
16  }
17 ]
```

```
16     }
17 ];
18
19 const totalProductValue = products.map(item => item.
    price * item.count);
20 // [ 7500, 20000, 100000 ]
21
22 const totalProductValueObject = products.map(item =>
    ({
23     name: item.name,
24     totalValue: item.price * item.count
25 }));
26 // [
27 //     { name: 'laptop', totalValue: 7500 },
28 //     { name: 'desktop', totalValue: 20000 },
29 //     { name: 'phone', totalValue: 100000 }
30 // ]
```

1.9 Array.prototype.push()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/push

- push() add ones or more elements to the end of an array
- push(x,y,z,1,2,3,etc.) can have as many parameters as desired
- push returns the new array length (for updated original array simply return that itself)

Example push()

```
1  const numbers = [1,2,3,4,5]
2
3  numbers.push(6)
4  //[ 1, 2, 3, 4, 5, 6 ]
5
6  numbers.push(6,7,8,9,10)
7  //[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
8
9  //note: if done in order above it would be
10 //[1, 2, 3, 4, 5, 6, 6, 7, 8, 9, 10]
11
12 const total = numbers.push(6,7,8,9,10)
13 //10
14 //note: would be 16 if done as above
```

1.10 Array.prototype.splice()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/splice

- splice() modifies an array by removing and/or replacing existing elements from it
- splice(startIndex, removalCount, newElementsAdded)

Example splice()

```
1  const numbers = [1,2,3,4,5];
2
3  numbers.splice(2,3)
4  //[ 1, 2 ]
5
6  let deleted = numbers.splice(2,3)
7  //[ 3, 4, 5 ]
8
9  numbers.splice(2,3,6,9)
10 //[ 1, 2, 6, 9 ]
11
12 numbers.splice(2,0,6,9)
13 //[ 1, 2, 6, 9, 3, 4, 5 ]
```

1.11 Bitwise XOR (^)

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Operators/Bitwise_XOR

- XOR (^) returns a 1 if the other corresponding bit is different

XOR (^) rules

1	// 0 & 0 = 0
2	// 0 & 1 = 1
3	// 1 & 1 = 0

Example XOR (^)

[illegible]

1.12 String.prototype.charCodeAt()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/String/charCodeAt

- Returns the unicode integer of the character in a string representing the UTF-16 code unit of the given index.

Example charCodeAt()

```
1  const sentence = 'My name is Sam';
2
3  const index = 4;
4  const otherLocation = 1;
5
6  console.log('The character code ${sentence.charCodeAt(
   index)} is equal to ${sentence.charAt(index)}');
7  // "The character code 97 is equal to a"
8
9  console.log('The character code ${sentence.charCodeAt(
   otherLocation)} is equal to ${sentence.charAt(
   otherLocation)}');
10 // "The character code 121 is equal to y"
```

1.13 String.fromCharCode()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/String/fromCharCode

- The static String.fromCharCode() method returns a string created from the specified sequence of UTF-16 code units.

Example fromCharCode()

```
1 String.fromCharCode(65, 66, 67);  
2 // returns "ABC"
```

1.14 Array.prototype.some()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/some

- Executes a given function and returns true if at least one element in array provides a truthy value.
- If no item in array is true, it will provide false

Example some()

```
1  const numbers = [1,2,3,4,5]
2
3  const res = numbers.some(greaterThanThree)
4  //true
5
6  function greaterThanThree(num) {
7      return num > 3;
8  }
```

1.15 Array.prototype.every()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/every

- Executes a given function on all items in an array and return true only if ALL items are truthy
- If any item in the array returns a falsy value, it will automatically return false

Example every()

```
1 const numbers = [1,2,3,4,5,-1]
2
3 const res = numbers.every(isPositive)
4 //false
5
6 function isPositive(num) {
7     return num > 0;
8 }
```

1.16 Array.prototype.includes()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/includes

- Checks if an element is included in an array
- If the item is included it will return true
- If the item is not included it will return false

Example includes()

```
1  const names = ['Sam', 'Gabe', 'Troy']
2
3  const res = names.includes('Sam')
4  // true
5  const res = names.includes('Bill')
6  // false
```

1.17 Array.prototype.find()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/find

- Returns the first element in an array for which the callback has a truthy value
- If object will return the whole object (or you can return a part of an object)
- if nothing is found it will return undefined

Example find()

```
1 const names = ['Sam', 'Gabe', 'Troy']
2
3 const namedPerson = names.find(findName)
4 //Gabe
5
6 function findName(name) {
7     return name === 'Gabe'
8 }
```

Example find() with objects

```
1 const inventory = [
2     {name: 'apples', quantity: 2},
3     {name: 'bananas', quantity: 0},
4     {name: 'cherries', quantity: 5}
5 ];
6
7 const result = inventory.find( ({ name }) => name
8     === 'cherries' );
9 //{ name: 'cherries', quantity: 5 }
10 const result = inventory.find( ({ name }) => name
    === 'cherries' ).quantity;
//5
```

1.18 Math.max(), Math.min(), Math.abs()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Math/max

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Math/min

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Math/abs

- Math.max()
- Returns highest value in list
- Math.min()
- Returns lowest value in list
- Math.abs()
- Returns absolute value of a number (distance from zero)

Example Math.max()

```
1 console.log(Math.max(1, 3, 2));
2 // expected output: 3
3
4 console.log(Math.max(-1, -3, -2));
5 // expected output: -1
```

Example Math.min()

```
1 console.log(Math.min(2, 3, 1));
2 // expected output: 1
3
4 console.log(Math.min(-2, -3, -1));
5 // expected output: -3
```

Example Math.abs()

```
1 function difference(a, b) {
2   return Math.abs(a - b);
3 }
4
5 console.log(difference(3, 5));
6 // expected output: 2
7
8 console.log(difference(5, 3));
9 // expected output: 2
```

1.19 parseInt() & parseFloat()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/parseInt

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/parseFloat

- parseInt() take a float or string and parses the integer out of it
- Will go from start to end of the first integer it sees (if it sees words, space, or any non-number it will stop)
- parseFloat() will do the same except it will run through the first period (.) and stop at the next period / non-number
- These don't work if the int / float isn't at the start of the string
- Note: parseInt(string, radix) careful of radix when passing values to parseInt

Example parseInt()

```
1 let testString = '1337demo'
2 let parseIntDemo = parseInt(testString)
3 //1337
```

Example parseFloat()

```
1 let testStringTwo = '1337.37.37demo'
2 let parseFloatDemo = parseFloat(testStringTwo)
3 //1337.37
```

Example parseInt() without numbers at start

```
1 let testString = 'doesnotwork1337.37.37demo'
2 let parseIntDemo = parseInt(testString)
3 //NaN
```

Example parseInt() with radix 16

```
1 console.log(roughScale('0xF', 16));
2 // expected output: 1500
```


1.20 Logical (and &&) and (or ||)

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Operators/Logical_OR

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Operators/Logical_AND

- The logical AND (&&) operator (logical conjunction) for a set of boolean operands will be true if and only if all the operands are true. Otherwise it will be false.
- More generally, the operator returns the value of the first falsy operand encountered when evaluating from left to right, or the value of the last operand if they are all truthy.
- The logical OR (||) operator (logical disjunction) for a set of operands is true if and only if one or more of its operands is true.
- the || operator actually returns the value of one of the specified operands, so if this operator is used with non-Boolean values, it will return a non-Boolean value.

Example Logical AND &&

```
1 const a = 3;  
2 const b = -2;  
3  
4 console.log(a > 0 && b > 0);  
5 // expected output: false
```

Example Logical AND &&

```
1 result = 2 && 0;  
2 // result is assigned 0  
3 result = 'foo' && 4;  
4 // result is assigned 4
```

Example Logical OR ||

```
1 const a = 3;  
2 const b = -2;  
3  
4 console.log(a > 0 || b > 0);  
5 // expected output: true
```

Example Logical OR ||

```
1 o3 = true  || false
2 // t || f returns true
3 o4 = false || (3 == 4)
4 // f || f returns false
5 o5 = 'Cat' || 'Dog'
6 // t || t returns "Cat"
```

1.21 Set() constructor

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Set/Set

- The Set constructor lets you create Set objects that store unique values of any type, whether primitive values or object references.

Example set1

```
1 const set1 = new Set([1, 2, 3, 4, 5]);
2
3 console.log(set1.has(1));
4 // expected output: true
5
6 console.log(set1.has(5));
7 // expected output: true
8
9 console.log(set1.has(6));
10 // expected output: false
```

Example using Set() object

```
1 let mySet = new Set()
2
3 mySet.add(1)
4 // Set [ 1 ]
5 mySet.add(5)
6 // Set [ 1, 5 ]
7 mySet.add(5)
8 // Set [ 1, 5 ]
9 mySet.add('some text') // Set [ 1, 5, 'some text' ]
10 let o = {a: 1, b: 2}
11 mySet.add(o)
```

1.22 String.prototype.charAt()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/String/charAt

- The String object's `charAt()` method returns a new string consisting of the single UTF-16 code unit located at the specified offset into the string.
- `charAt(index)`

Example charAt()

```
1 const sentence = 'The quick brown fox jumps over the  
  lazy dog.';  
2  
3 const index = 4;  
4  
5 console.log('The character at index ${index} is ${  
  sentence.charAt(index)}');  
6 // expected output: "The character at index 4 is q"
```

1.23 for...of

<https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Statements/for...of>

- The for...of statement creates a loop iterating over iterable objects, including: built-in String, Array, array-like objects (e.g., arguments or NodeList), TypedArray, Map, Set, and user-defined iterables. It invokes a custom iteration hook with statements to be executed for the value of each distinct property of the object.

Example for...of

```
1 const array1 = ['a', 'b', 'c'];
2
3 for (const element of array1) {
4   console.log(element);
5 }
6
7 // expected output: "a"
8 // expected output: "b"
9 // expected output: "c"
```

Example for...of

```
1 for (variable of iterable) {
2   statement
3 }
```

1.24 for...in

<https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Statements/for...in>

- The for...in statement iterates over all enumerable properties of an object that are keyed by strings (ignoring ones keyed by Symbols), including inherited enumerable properties.

Example for...in

```
1  const object = { a: 1, b: 2, c: 3 };
2
3  for (const property in object) {
4      console.log(`${property}: ${object[property]}`);
5  }
6
7  // expected output:
8  // "a: 1"
9  // "b: 2"
10 // "c: 3"
```

Example for...in

```
1  for (const variable in object) {
2      statement
3  }
```

1.25 Conditional (ternary) operator

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Operators/Conditional_Operator

- The conditional (ternary) operator is the only JavaScript operator that takes three operands
- A condition followed by a question mark (?), then an expression to execute if the condition is truthy followed by a colon (:), and finally the expression to execute if the condition is falsy.
- This operator is frequently used as an alternative to an if...else statement.
- `condition ? exprIfTrue : exprIfFalse`

Example ternary operator

```
1 function getFee(isMember) {  
2   return (isMember ? '$2.00' : '$10.00');  
3 }  
4  
5 console.log(getFee(true));  
6 // expected output: "$2.00"  
7  
8 console.log(getFee(false));  
9 // expected output: "$10.00"  
10  
11 console.log(getFee(null));  
12 // expected output: "$10.00"
```

Example ternary operator

```
1 const age = 26;  
2 const beverage = age >= 21 ? "Beer" : "Juice";  
3 console.log(beverage); // "Beer"
```

1.26 Map.prototype.get()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Map/get

- The `get()` method returns a specified element from a Map object.
- If the value that is associated to the provided key is an object, then you will get a reference to that object and any change made to that object will effectively modify it inside the Map object.
- `get(key)`

Example Map.prototype.get()

```
1 const map1 = new Map();
2 map1.set('bar', 'foo');
3
4 console.log(map1.get('bar'));
5 // expected output: "foo"
6
7 console.log(map1.get('baz'));
8 // expected output: undefined
```

Example get()

```
1 const arr = [];
2 const myMap = new Map();
3
4 myMap.set('bar', arr);
5 myMap.get('bar').push('foo');
6
7 console.log(arr);
8 // ["foo"]
9 console.log(myMap.get('bar'));
10 // ["foo"]
```


1.27 Map.prototype.has()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Map/has

- The `has()` method returns a boolean indicating whether an element with the specified key exists or not.
- `has(key)`

Example Map.prototype.has()

```
1 const map1 = new Map();
2 map1.set('bar', 'foo');
3
4 console.log(map1.has('bar'));
5 // expected output: true
6
7 console.log(map1.has('baz'));
8 // expected output: false
```

Example has()

```
1 let myMap = new Map()
2 myMap.set('bar', "foo")
3
4 myMap.has('bar')
5 // returns true
6 myMap.has('baz')
7 // returns false
```

1.28 Set

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Set

- The Set object lets you store unique values of any type, whether primitive values or object references.
- Set objects are collections of values. A value in the Set may only occur once; it is unique in the Set's collection.
- You can iterate through the elements of a set in insertion order. The insertion order corresponds to the order in which each element was inserted into the set by the add()

Example Set Object

```
1  const mySet1 = new Set()
2
3  mySet1.add(1)           // Set [ 1 ]
4  mySet1.add(5)           // Set [ 1, 5 ]
5  mySet1.add(5)           // Set [ 1, 5 ]
6  mySet1.add('some text') // Set [ 1, 5, 'some text' ]
7  const o = {a: 1, b: 2}
8  mySet1.add(o)
9
10 mySet1.add({a: 1, b: 2}) // o is referencing a
    different object, so this is okay
11
12 mySet1.has(1)            // true
13 mySet1.has(3)            // false, since 3 has not
    been added to the set
14 mySet1.has(5)            // true
15 mySet1.has(Math.sqrt(25)) // true
16 mySet1.has('Some Text'.toLowerCase()) // true
17 mySet1.has(o)            // true
18
19 mySet1.size              // 5
20
21 mySet1.delete(5)         // removes 5 from the set
22 mySet1.has(5)            // false, 5 has been removed
23
24 mySet1.size              // 4, since we just removed one
    value
25
26 mySet1.add(5)            // Set [1, 'some text', {...},
    {...}, 5] - a previously deleted item will be added
```

```

    as a new item, it will not retain its original
    position before deletion
27
28 console.log(mySet1)

```

Example remove duplicate elements from array

```

1 // Use to remove duplicate elements from the array
2
3 const numbers =
  [2,3,4,4,2,3,3,4,4,5,5,6,6,7,5,32,3,4,5]
4
5 console.log([...new Set(numbers)])
6
7 // [2, 3, 4, 5, 6, 7, 32]

```

Example relationship with array

```

1 const myArray = ['value1', 'value2', 'value3'];
2
3 // Use the regular Set constructor to transform an
  Array into a Set
4 const mySet = new Set(myArray);
5
6 mySet.has('value1') // returns true
7
8 // Use the spread operator to transform a set into an
  Array.
9 console.log([...mySet]); // Will show you exactly the
  same Array as myArray

```

Example relationship with string

```

1 const text = 'India';
2
3 const mySet = new Set(text); // Set(5) {'I', 'n', 'd',
  ', 'i', 'a'}
4 mySet.size // 5
5
6 //case sensitive & duplicate omission
7 new Set("Firefox") // Set(7) { "F", "i", "r", "e", "f",
  ", "o", "x" }
8 new Set("firefox") // Set(6) { "f", "i", "r", "e", "o",
  ", "x" }

```

1.29 Object.prototype.toString()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Object/toString

- The `toString()` method returns a string representing the object.
- `toString()`

Example toString()

```
1 function Dog(name) {  
2   this.name = name;  
3 }  
4  
5 const dog1 = new Dog('Gabby');  
6  
7 Dog.prototype.toString = function dogToString() {  
8   return `${this.name}`;  
9 };  
10  
11 console.log(dog1.toString());  
12 // expected output: "Gabby"
```

Example toString()

```
1 const arr = [1, 2, 3];  
2  
3 arr.toString()  
4 // "1,2,3"  
5 Object.prototype.toString.call(arr)  
6 // "[object Array]"
```

1.30 String.prototype.replace()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/String/replace

- The `replace()` method returns a new string with some or all matches of a pattern replaced by a replacement.
- The pattern can be a string or a `RegExp`, and the replacement can be a string or a function called for each match.
- If pattern is a string, only the first occurrence will be replaced.
- The original string is left unchanged.
- `replace(substr, newSubstr)`

Example `replace()`

```
1  const p = 'The quick brown fox jumps over the lazy dog
   . If the dog reacted, was it really lazy?';
2
3  console.log(p.replace('dog', 'monkey'));
4  // expected output: "The quick brown fox jumps over
   the lazy monkey. If the dog reacted, was it really
   lazy?"
5
6  const regex = /Dog/gi;
7  console.log(p.replace(regex, 'ferret'));
8  // expected output: "The quick brown fox jumps over
   the lazy ferret. If the ferret reacted, was it
   really lazy?"
9
10 const regex = /Dog/i;
11 console.log(p.replace(regex, 'ferret'));
12 // expected output: "The quick brown fox jumps over
   the lazy ferret. If the dog reacted, was it really
   lazy?"
```

1.31 Set.prototype.add()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Set/add

- The add() method inserts a new element with a specified value in to a Set object
- Only works if there isn't an element with the same value already in the Set.
- add(value)

Example add()

```
1  const set1 = new Set();
2
3  set1.add(42);
4  set1.add(42);
5  set1.add(13);
6
7  for (const item of set1) {
8    console.log(item);
9    // expected output: 42
10   // expected output: 13
11 }
```

Example add()

```
1  const mySet = new Set();
2
3  mySet.add(1);
4  mySet.add(5).add('some text'); // chainable
5
6  console.log(mySet);
7  // Set [1, 5, "some text"]
```

1.32 Array.prototype.unshift()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/unshift

- The `unshift()` method adds one or more elements to the beginning of an array and returns the new length of the array.
- `unshift(element0)`
- `unshift(element0, element1)`

Examples using `unshift()`

```
1  const arr = [1, 2]
2
3  arr.unshift(0)
4  // result of the call is 3, which is the new array
   // length
5  // arr is [0, 1, 2]
6
7  arr.unshift(-2, -1)
8  // the new array length is 5
9  // arr is [-2, -1, 0, 1, 2]
10
11 arr.unshift([-4, -3])
12 // the new array length is 6
13 // arr is [[-4, -3], -2, -1, 0, 1, 2]
14
15 arr.unshift([-7, -6], [-5])
16 // the new array length is 8
17 // arr is [ [-7, -6], [-5], [-4, -3], -2, -1, 0, 1, 2
   ]
```

1.33 Set.prototype.size

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Set/size

- The size accessor property returns the number of (unique) elements in a Set object.
- The value of size is an integer representing how many entries the Set object has.
- A set accessor function for size is undefined; you cannot change this property.
- `set.size()`

Examples using `size()`

```
1  const mySet = new Set();
2  mySet.add(1);
3  mySet.add(5);
4  mySet.add('some text')
5
6  mySet.size;
7  // 3
```


1.34 Set.prototype.delete()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Set/delete

- The delete() method removes a specified value from a Set object, if it is in the set.
- delete(value)
- Returns true if value was already in Set; otherwise false.

Examples using delete()

```
1  const mySet = new Set();
2  mySet.add('foo');
3
4  mySet.delete('bar');
5  // Returns false. No "bar" element found to be deleted
6
7  mySet.delete('foo');
8  // Returns true. Successfully removed.
9
10 mySet.has('foo');
    // Returns false. The "foo" element is no longer
    present.
```

Examples using delete()

```
1  const setObj = new Set();
2  // Create a new set.
3
4  setObj.add({x: 10, y: 20});
5  // Add object in the set.
6
7  setObj.add({x: 20, y: 30});
8  // Add object in the set.
9
10 // Delete any point with 'x > 10'.
11 setObj.forEach(function(point){
12     if (point.x > 10){
13         setObj.delete(point)
14     }
15 })
```

1.35 delete operator

<https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Operators/delete>

- The JavaScript delete operator removes a property from an object; if no more references to the same property are held, it is eventually released automatically.
- delete expression
- true for all cases except when the property is an Object.hasOwn non-configurable property, in which case, false is returned in non-strict mode.

Example using delete operator

```
1  const Employee = {  
2    firstname: 'John',  
3    lastname: 'Doe'  
4  };  
5  
6  console.log(Employee.firstname);  
7  // expected output: "John"  
8  
9  delete Employee.firstname;  
10  
11 console.log(Employee.firstname);  
12 // expected output: undefined
```

Example using delete operator

```
1  const trees = ['redwood', 'bay', 'cedar', 'oak', 'maple'];  
2  delete trees[3];  
3  console.log(3 in trees); // false
```

1.36 Array.prototype.reverse()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/reverse

- The reverse() method reverses an array in place. The first array element becomes the last, and the last array element becomes the first.
- reverse()
- return the reversed array

Example using reverse()

```
1 const array1 = ['one', 'two', 'three'];
2 console.log('array1:', array1);
3 // expected output: "array1:" Array ["one", "two", "
  three"]
4
5 const reversed = array1.reverse();
6 console.log('reversed:', reversed);
7 // expected output: "reversed:" Array ["three", "two",
  "one"]
8
9 // Careful: reverse is destructive -- it changes the
  original array.
10 console.log('array1:', array1);
11 // expected output: "array1:" Array ["three", "two", "
  one"]
```

Example using reverse() with array

```
1 const items = [1, 2, 3];
2 console.log(items);
3 // [1, 2, 3]
4
5 items.reverse();
6 console.log(items); ]
7 // [3, 2, 1]
```

Example using reverse() in array like object

```
1 const obj = {0: 1, 1: 2, 2: 3, length: 3};
2 console.log(obj);
3 // {0: 1, 1: 2, 2: 3, length: 3}
4
5 Array.prototype.reverse.call(obj);
6 //same syntax for using apply()
```

```
7 console.log(obj);  
8 // {0: 3, 1: 2, 2: 1, length: 3}
```

1.37 Array() constructor

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/Array

- The Array() constructor is used to create Array objects.

Example Array() constructor

```
1 // literal constructor
2 [element0, element1, ..., elementN]
3
4 // construct from elements
5 new Array(element0, element1, ..., elementN)
6
7 // construct from array length
8 new Array(arrayLength)
```

Example using literal notation

```
1 let fruits = ['Apple', 'Banana'];
2
3 console.log(fruits.length);
4 // 2
5 console.log(fruits[0]);
6 // "Apple"
```

1.38 Math.trunc()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/Array

- The Math.trunc() function returns the integer part of a number by removing any fractional digits.
- Math.trunc(x)

Example Math.trunc()

```
1 console.log(Math.trunc(13.37));  
2 // expected output: 13  
3  
4 console.log(Math.trunc(42.84));  
5 // expected output: 42  
6  
7 console.log(Math.trunc(0.123));  
8 // expected output: 0  
9  
10 console.log(Math.trunc(-0.123));  
11 // expected output: -0
```

Example Math.trunc()

```
1 Math.trunc(13.37);    // 13  
2 Math.trunc(42.84);    // 42  
3 Math.trunc(0.123);    // 0  
4 Math.trunc(-0.123);   // -0  
5 Math.trunc('-1.123'); // -1  
6 Math.trunc(NaN);      // NaN  
7 Math.trunc('foo');    // NaN  
8 Math.trunc();         // NaN
```

1.39 continue

<https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Statements/continue>

- The continue statement terminates execution of the statements in the current iteration of the current or labeled loop, and continues execution of the loop with the next iteration.
- continue [label];
- In a while loop, it jumps back to the condition.
- In a for loop, it jumps to the update expression.

Example continue

```
1 let text = '';  
2  
3 for (let i = 0; i < 10; i++) {  
4   if (i === 3) {  
5     continue;  
6   }  
7   text = text + i;  
8 }  
9  
10 console.log(text);  
11 // expected output: "012456789"
```

Example continue and label

```
1 let i = 0;  
2 let j = 8;  
3  
4 checkiandj: while (i < 4) {  
5   console.log('i: ' + i);  
6   i += 1;  
7  
8   checkj: while (j > 4) {  
9     console.log('j: ' + j);  
10    j -= 1;  
11  
12    if ((j % 2) == 0)  
13      continue checkj;  
14    console.log(j + ' is odd.');15  }  
16  console.log('i = ' + i);  
17  console.log('j = ' + j);  
18 }
```

Example output continue and label

```
1 i: 0
2
3 // start checkj
4 j: 8
5 7 is odd.
6 j: 7
7 j: 6
8 5 is odd.
9 j: 5
10 // end checkj
11
12 i = 1
13 j = 4
14
15 i: 1
16 i = 2
17 j = 4
18
19 i: 2
20 i = 3
21 j = 4
22
23 i: 3
24 i = 4
25 j = 4
```


1.40 Map.prototype.set()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Map/set

- The `set()` method adds or updates an entry in a Map object with a specified key and a value.
- `set(key, value)`
- The key of the element to add to the Map object. The key may be any JavaScript type (any primitive value or any type of JavaScript object).
- The value of the element to add to the Map object. The value may be any JavaScript type (any primitive value or any type of JavaScript object).
- The Map object.

Example `map.set()`

```
1  const map1 = new Map();
2  map1.set('bar', 'foo');
3
4  console.log(map1.get('bar'));
5  // expected output: "foo"
6
7  console.log(map1.get('baz'));
8  // expected output: undefined
```

1.41 String.prototype.substring()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/String/substring

- The `substring()` method returns the part of the string between the start and end indexes, or to the end of the string.
- `substring(indexStart)`
- `substring(indexStart, indexEnd)`

Example substring()

```
1  const str = 'Mozilla';
2
3  console.log(str.substring(1, 3));
4  // expected output: "oz"
5
6  console.log(str.substring(2));
7  // expected output: "zilla"
```

Example substring()

```
1  const anyString = 'Mozilla';
2
3  // Displays 'M'
4  console.log(anyString.substring(0, 1));
5  console.log(anyString.substring(1, 0));
6
7  // Displays 'Mozill'
8  console.log(anyString.substring(0, 6));
9
10 // Displays 'lla'
11 console.log(anyString.substring(4));
12 console.log(anyString.substring(4, 7));
13 console.log(anyString.substring(7, 4));
14
15 // Displays 'Mozilla'
16 console.log(anyString.substring(0, 7));
17 console.log(anyString.substring(0, 10));
```

1.42 String.prototype.toLowerCase() String.prototype.toUpperCase()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/String/toLowerCase https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/String/toUpperCase

- The toLowerCase() method returns the calling string value converted to lower case.
- toLowerCase()
- The toUpperCase() method returns the calling string value converted to uppercase (the value will be converted to a string if it isn't one).
- toUpperCase()

Example toLowerCase()

```
1 const sentence = 'The quick brown fox jumps over the  
  lazy dog.';  
2  
3 console.log(sentence.toLowerCase());  
4 // expected output: "the quick brown fox jumps over  
  the lazy dog."
```

Example toUpperCase()

```
1 const sentence = 'The quick brown fox jumps over the  
  lazy dog.';  
2  
3 console.log(sentence.toUpperCase());  
4 // expected output: "THE QUICK BROWN FOX JUMPS OVER  
  THE LAZY DOG."
```

1.43 this

<https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Operators/this>

- In most cases, the value of `this` is determined by how a function is called (runtime binding). It can't be set by assignment during execution, and it may be different each time the function is called

Example this

```
1 const test = {  
2   prop: 42,  
3   func: function() {  
4     return this.prop;  
5   },  
6 };  
7  
8 console.log(test.func());  
9 // expected output: 42
```

1.44 Object.values()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_objects/Object/values

- The `Object.values()` method returns an array of a given object's own enumerable property values, in the same order as that provided by a `for...in` loop.
- (The only difference is that a `for...in` loop enumerates properties in the prototype chain as well.)
- `Object.values(obj)`

Example `Object.values()`

```
1 const object1 = {  
2   a: 'somestring',  
3   b: 42,  
4   c: false  
5 };  
6  
7 console.log(Object.values(object1));  
8 // expected output: Array ["somestring", 42, false]
```

Example `values()`

```
1 const obj = { foo: 'bar', baz: 42 };  
2 console.log(Object.values(obj)); // ['bar', 42]  
3  
4 // Array-like object  
5 const arrayLikeObj1 = { 0: 'a', 1: 'b', 2: 'c' };  
6 console.log(Object.values(arrayLikeObj1 )); // ['a', 'b', 'c']  
7  
8 // Array-like object with random key ordering  
9 // When using numeric keys, the values are returned in  
10 // the keys' numerical order  
10 const arrayLikeObj2 = { 100: 'a', 2: 'b', 7: 'c' };  
11 console.log(Object.values(arrayLikeObj2 )); // ['b', 'c', 'a']  
12  
13 // getFoo is property which isn't enumerable  
14 const my_obj = Object.create({}, { getFoo: { value() {  
15   return this.foo; } } });  
15 my_obj.foo = 'bar';  
16 console.log(Object.values(my_obj)); // ['bar']  
17
```

```
18 // non-object argument will be coerced to an object
19 console.log(Object.values('foo')); // ['f', 'o', 'o']
```

1.45 constructor

<https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Classes/constructor>

- The constructor method is a special method of a class for creating and initializing an object instance of that class.
- `constructor() /* ... */`
- `constructor(argument0, argument1, /* ... */ argumentN) /* ... */`

Example Classes Constructor

```
1 class Polygon {  
2   constructor() {  
3     this.name = 'Polygon';  
4   }  
5 }  
6  
7 const poly1 = new Polygon();  
8  
9 console.log(poly1.name);  
10 // expected output: "Polygon"
```

1.46 Classes

<https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Classes>

- Classes are a template for creating objects. They encapsulate data with code to work on that data.
- Classes in JS are built on prototypes but also have some syntax and semantics that are not shared with ES5 class-like semantics.

Example Classes

```
1 class Rectangle {
2   constructor(height, width) {
3     this.height = height;
4     this.width = width;
5   }
6   // Getter
7   get area() {
8     return this.calcArea();
9   }
10  // Method
11  calcArea() {
12    return this.height * this.width;
13  }
14 }
15
16 const square = new Rectangle(10, 10);
17
18 console.log(square.area); // 100
```


1.47 Array.from()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/from

- The `Array.from()` static method creates a new, shallow-copied `Array` instance from an iterable or array-like object.

Example from()

```
1 console.log(Array.from('foo'));
2 // expected output: Array ["f", "o", "o"]
3
4 console.log(Array.from([1, 2, 3], x => x + x));
5 // expected output: Array [2, 4, 6]
```

Examples from()

```
1 // Arrow function
2 Array.from(arrayLike, (element) => {stuff})
3 Array.from(arrayLike, (element, index) => {stuff})
4
5 // Mapping function
6 Array.from(arrayLike, mapFn)
7 Array.from(arrayLike, mapFn, thisArg)
8
9 // Inline mapping function
10 Array.from(arrayLike, function mapFn(element) {stuff})
11 Array.from(arrayLike, function mapFn(element, index) {
12   stuff})
12 Array.from(arrayLike, function mapFn(element) {stuff},
13   thisArg)
13 Array.from(arrayLike, function mapFn(element, index) {
14   stuff}, thisArg)
```

1.48 Array.prototype.forEach()

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array/forEach

- The `forEach()` method executes a provided function once for each array element.

Example `forEach()`

```
1 const array1 = ['a', 'b', 'c'];
2
3 array1.forEach(element => console.log(element));
4
5 // expected output: "a"
6 // expected output: "b"
7 // expected output: "c"
```

Examples `forEach()`

```
1 const words = ['one', 'two', 'three', 'four'];
2 words.forEach((word) => {
3   console.log(word);
4   if (word === 'two') {
5     words.shift(); // 'one' will delete from array
6   }
7 }); // one // two // four
8
9 console.log(words); // ['two', 'three', 'four']
```

1.49 Map() constructor

https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Map/Map

- The Map() constructor creates Map objects.
- new Map()
- new Map(iterable)

Example new Map()

```
1 let myMap = new Map([
2   [1, 'one'],
3   [2, 'two'],
4   [3, 'three'],
5 ])
```

2 Array Algorithm Problems

2.1 Build Array from Permutation

<https://leetcode.com/problems/build-array-from-permutation/>

1. initialize result array
2. loop through nums
3. push nums at each i to the answer
4. return result

Solution with for loop

```
1 var buildArray = function(nums) {  
2  
3   let result = []  
4  
5   for (let i = 0; i<nums.length; i++){  
6     result.push(nums[nums[i]])  
7   }  
8  
9   return result  
10 };
```

Solution with map()

```
1 const buildArray = (nums) => {  
2   return nums.map(result => nums[result])  
3 };
```

2.2 Count Items Matching a Rule

<https://leetcode.com/problems/count-items-matching-a-rule/>

1. create rule index object
2. reduce(ans, items) so that ruleIndex[ruleKey] is equal to ruleValue
3. if equal increase ans by 1
4. if not equal answer is 0

Solution countMatches

```
1  const countMatches = (items, ruleKey, ruleValue) => {  
2  
3      const ruleIndex = {  
4          'type': 0,  
5          'color': 1,  
6          'name': 2  
7      }  
8  
9      return items.reduce((ans, item) =>  
10         item[ruleIndex[ruleKey]] === ruleValue ? ans + 1 :  
11         ans, 0);  
};
```

2.3 Create Target Array in the Given Order

<https://leetcode.com/problems/create-target-array-in-the-given-order/>

1. initialize empty target array
2. loop through array
3. loop through each index of the previous loop
4. if array[i] is less than or equal to inner loop, increment inner loop
5. loop in the nums array giving target the value: target[array[j]] = nums[i]
6. return target

Solution createTargetArray

```
1  const createTargetArray = (nums, array) => {
2
3      let target = [];
4
5      for( let i=0; i<array.length; i++){
6          for(let j=0; j<i; j++){
7              if(array[i] <= array[j]){
8                  array[j]++
9              }
10         }
11     }
12
13     for(const i in nums){
14         target[array[i]] = nums[i]
15     }
16
17     return target;
18 };
```

Solution createTargetArray with splice()

```
1  const createTargetArray = (nums, index) => {
2
3      let target = []
4
5      for(let i in nums){
6          target.splice(index[i], 0, nums[i])
7      }
8
9      return target
10 };
```

2.4 Decode XORed Array

<https://leetcode.com/problems/decode-xored-array/>

1. initialize result with first in array
2. for loop through encoded
3. push result through $\text{result}[i] \oplus \text{encoded}[i]$
4. return result

Solution decode

```
1  const decode = (encoded, first) => {  
2  
3      let result = [first];  
4  
5      for(let i = 0; i<encoded.length; i++){  
6          result.push(result[i] ^ encoded[i])  
7      }  
8  
9      return result;  
10 };
```

2.5 Decompress Run-Length Encoded List

<https://leetcode.com/problems/decompress-run-length-encoded-list/>

1. initialize empty result array
2. loop through nums, starting from 1, increasing by 2 each time
3. push result into a new array nums[i-1]
4. fill new array with nums[i]
5. return result

Solution decompressRLEList

```
1  const decompressRLEList = (nums) => {  
2  
3      let result = [];  
4  
5      for (let i=1; i< nums.length; i+=2){  
6          result.push(...new Array(nums[i-1]).fill(nums[  
7              i]));  
8      }  
9      return result;  
10 };
```


2.6 Final Value of Variable After Performing Operations

<https://leetcode.com/problems/final-value-of-variable-after-performing-operations/>

1. initialize count at 0
2. loop through the values of operations (not the index)
3. if i is equal to 'X++' or '++X' increment
4. else decrement
5. return final count

Solution finalValueAfterOperations

```
1  const finalValueAfterOperations = (operations) => {  
2  
3      let count = 0;  
4  
5      for (let i of operations) {  
6          if (i === 'X++' || i === '++X') {  
7              count++  
8          } else count --;  
9      }  
10  
11     return count;  
12 };
```

2.7 Concatenation of Array

<https://leetcode.com/problems/concatenation-of-array/>

1. take nums and split it using ... operator
2. return nums twice in a single []

Solution getConcatenation

```
1 var getConcatenation = function (nums) {  
2   return [...nums, ...nums]  
3 }
```

2.8 Kids With the Greatest Number of Candies

<https://leetcode.com/problems/kids-with-the-greatest-number-of-candies/>

1. initialize results array
2. initialize max value tracker
3. loop through candies array
4. create logic for max value
5. loop through candies[i]
6. test each candies with extraCandies to see if value is true
7. return result

Solution kidsWithCandies with for-of loop

```
1 var kidsWithCandies = function(candies, extraCandies)
  {
2   const ret = []
3   let max = 0
4
5   for (const val of candies) {
6     val > max && (max = val)
7   }
8
9   for (let i = 0; i < candies.length; ++i){
10    ret.push(candies[i] + extraCandies >= max);
11  }
12
13  return ret;
14 }
```

Solution kidsWithCandies with for loop

```
1 var kidsWithCandies = function(candies, extraCandies)
  {
2
3   let answer = []
4   let max = 0
5
6   for(let i=0; i<candies.length; i++){
7     candies[i] > max && (max = candies[i])
8   }
9
10  for(let j=0; j<candies.length; j++){
```

```
11         answer.push(candies[j] + extraCandies >= max)
12     }
13     return answer
14 };
```

2.9 Maximum Number of Words Found in Sentences

<https://leetcode.com/problems/maximum-number-of-words-found-in-sentences/>

1. Initialize max and temp variables at zero
2. Loop through sentence.length
3. Split sentences based on parentheses and add the length of each to temp variable
4. Find which value of temp or max is biggest and pass to max
5. Return max

Solution mostWordsFound

```
1  const mostWordsFound = (sentence) => {
2
3      let max = 0;
4      let temp = 0;
5
6      for(let i=0; i < sentence.length; i++){
7          temp = sentence[i].split(" ").length;
8          if(temp>max){
9              max = temp;
10         }
11     }
12
13     return max;
14 }
```

Solution mostWordsFound with for-in loop and Math.max

```
1  const mostWordsFound = (sentence) => {
2
3      let max = 0
4      let temp = 0
5
6      for(let i in sentence){
7          temp = sentence[i].split(" ").length;
8      }
9
10     return Math.max(max, temp)
11 }
```

2.10 Number of Good Pairs

<https://leetcode.com/problems/number-of-good-pairs/>

1. initialize counter
2. loop through nums array
3. loop again starting at i+1
4. logic if(nums[i] === nums[j]) increase count
5. return count

Solution numIdenticalPairs

```
1 var numIdenticalPairs = function (nums) {  
2  
3   let count = 0;  
4  
5   for (let i=0; i<nums.length; i++){  
6     for(let j=i+1; j<nums.length; j++){  
7       if(nums[i] === nums[j]){  
8         count++  
9       }  
10    }  
11  }  
12  
13  return count;  
14 }
```

2.11 Shuffle String

<https://leetcode.com/problems/shuffle-string/>

1. initialize empty results array
2. loop through indices array
3. tie the indices to the s parameter
4. return the result and join() it together since we are looking for a string

Solution restoreString

```
1  const restoreString = (s, indices) => {  
2  
3      const result = [];  
4  
5      for(let i = 0; i<indices.length; i++){  
6          result[indices[i]] = s[i]  
7      }  
8  
9      return result.join('');  
10 }
```

2.12 Richest Customer Wealth

<https://leetcode.com/problems/richest-customer-wealth/>

1. initialize an answer
2. loop through the people, accounts
3. initialize temp variable
4. loop through the banks accounts[i]
5. add all their wealth to temp
6. use `math.max` to find the highest number
7. return the account with most wealth

Solution maximumWealth

```
1  const maximumWealth = (accounts) => {  
2      let res = 0;  
3  
4      for(let i=0; i<accounts.length; i++){  
5          let temp = 0;  
6          for(let j = 0; j< accounts[i].length; j++){  
7              temp += accounts[i][j];  
8          }  
9          res = Math.max(res, temp);  
10     }  
11  
12     return res;  
13 }
```


2.13 Running Sum of 1d Array

<https://leetcode.com/problems/running-sum-of-1d-array/>

1. create loop from 1(i) to end of array
2. add `nums[i]` and `nums[i-1]` to array
3. return `nums` array

Solution `runningSum`

```
1  const runningSum = (nums) => {  
2  
3      for (let i = 1; i < nums.length; i++){  
4          nums[i] += nums[i-1]  
5      }  
6  
7      return nums  
8  }
```

2.14 Shuffle the Array

<https://leetcode.com/problems/shuffle-the-array/>

1. create empty result array
2. loop through n with i; n
3. push into nums[i]
4. push into nums[i+n]
5. return result

Solution shuffle

```
1 var shuffle = function (nums, n) {  
2  
3     let res = [];  
4  
5     for(let i = 0; i < n; i++){  
6         res.push(nums[i])  
7         res.push(nums[i+n])  
8     }  
9  
10    return res  
11 };
```

2.15 How Many Numbers Are Smaller Than the Current Number

leetcode.com/problems/how-many-numbers-are-smaller-than-the-current-number/

1. Initialize empty results array
2. Initialize sorted array
3. Slice() sorted array to duplicated
4. Sort() sorted array using $((a, b) \rightarrow a - b)$ so it works for numbers
5. For loop through nums
6. Compare the value of sorted array with nums array and push into results the index of at which sorted is in `nums[i]`
7. Return results

Solution smallerNumbersThanCurrent

```
1  const smallerNumbersThanCurrent = (nums) => {  
2  
3      let answer = []  
4      let sorted = nums.slice().sort((a,b)=>a-b)  
5  
6      for(let i = 0; i<nums.length; i++){  
7          answer.push(sorted.indexOf(nums[i]))  
8      }  
9  
10     return answer  
11 }
```

2.16 Sum of All Odd Length Subarrays

<https://leetcode.com/problems/sum-of-all-odd-length-subarrays/>

1. Initialize result at 0
2. For loop through arr starting at 1
3. Start from second element and add to itself the first element and so on.
So each index has the value of all previous indexes added to it
4. loop through all start indices
5. End is initially start and look for all odd ($+=2$) subarrays
6. Sum up $+=$ the query in result
7. Return result
8. Setup helper sumBetween function that takes sum from start to end

Solution sumOddLengthSubarrays with helper function

```
1  const sumOddLengthSubarrays = (arr) => {
2
3      let result = 0;
4
5      for(let i = 1; i<arr.length; i++){
6          arr[i] += arr[i - 1]
7      }
8
9      for(let start = 0; start<arr.length; start++){
10         for(let end = start; end<arr.length; end +=2){
11             result += sumBetween(start, end)
12         }
13     }
14
15     return result
16
17     function sumBetween(start, end){
18         return arr[end] - (arr[start -1] || 0)
19     }
20 }
```

Solution sumOddLengthSubarrays with parseInt

```
1  var sumOddLengthSubarrays = function(arr) {
2
3      let res = 0, n = arr.length
```

```

4
5     for(let i = 0; i < n; ++i) {
6         res += parseInt(((i + 1) * (n - i) + 1) / 2) *
7         arr[i];
8     }
9     return res
10 };

```

Solution sumOddLengthSubarrays with for loops and modulo

```

1  const sumOddLengthSubarrays = (arr) => {
2
3      let count = 0;
4
5      for(let i=0; i<arr.length; i++){
6          for(let j=i; j<arr.length; j++){
7              if((i-j)%2==0){
8                  for(let k=i;k<=j;k++){
9                      count+=arr[k]
10                 }
11             }
12         }
13     }
14
15     return count;
16 }

```

Solution sumOddLengthSubarrays with while loop

```

1  var sumOddLengthSubarrays = function(arr) {
2
3      let i=1;
4      let sum=0;
5
6      while(i<=arr.length){
7          for(let j=0;j<=arr.length-i;j++){
8              for(let k=j;k<i+j;k++){
9                  sum+=arr[k]
10             }
11         }
12         i+=2
13     }
14
15     return sum
16 };

```

2.17 Count Number of Pairs With Absolute Difference K

<https://leetcode.com/problems/count-number-of-pairs-with-absolute-difference-k/>

1. Create empty object
2. Initialize answer at zero
3. Loop through nums giving values to the object
4. Loop through nums if `obj[nums[i]-k] += that value` to answer
5. Return Answer

Solution countKDifference

```
1  const countKDifference = (nums, k) => {
2
3      let obj = {}
4      let answer = 0
5
6      for(let i of nums){
7          obj[i] ? obj[i]++ : obj[i] = 1
8      }
9
10     for (let i=0; i<nums.length; i++) {
11         if(obj[nums[i] -k]){
12             answer += obj[nums[i] - k]
13         }
14     }
15
16     return answer
17 }
```

2.18 Minimum Number of Moves to Seat Everyone

<https://leetcode.com/problems/minimum-number-of-moves-to-seat-everyone/>

1. Initialize answer variable
2. Sort seats
3. Sort students
4. Loop through arrays finding the absolute value of the number and += to answer
5. Return answer

Solution minMovesToSeat

```
1  const minMovesToSeat = (seats, students) => {  
2  
3      let answer = 0  
4  
5      seats = seats.sort((a,b) => a-b)  
6      students = students.sort((a,b) => a-b)  
7  
8      for(let i in seats){  
9          answer += Math.abs(seats[i] - students[i])  
10     }  
11  
12     return answer  
13 };
```

2.19 Minimum Amount of Time to Fill Cups

<https://leetcode.com/problems/minimum-amount-of-time-to-fill-cups/>

1. Initialize answer to zero
2. Sort the amount array
3. While loop amount 1 and 2 decrement them until zero while increasing answer
4. Sort in the while loop to keep the biggest amounts furthest away
5. Add the remaining amount to the answer in second (only 1 amount so will always be 1 per second)
6. Return answer

Solution fillCups

```
1  const fillCups = (amount) => {  
2  
3      let answer = 0;  
4  
5      amount.sort((a, b) => a - b);  
6  
7      while (amount[1] && amount[2]) {  
8          answer++;  
9          amount[1]--;  
10         amount[2]--;  
11         amount.sort((a, b) => a - b);  
12     }  
13  
14     answer += amount[2];  
15     return answer;  
16 };
```


2.20 Assign Cookies

<https://leetcode.com/problems/assign-cookies/>

1. Initialize empty answer
2. Sort (g) children and (s) cookies
3. While loop amount 1 and 2 decrement them until zero while increasing answer
4. Loop with forEach through (s) and if child is greater than g[answer] increment answer (this needs work not sure exactly what is happening here)
5. Return answer

Solution findContentChildren

```
1  const findContentChildren = (g,s) => {  
2  
3      let answer = 0  
4  
5      g.sort((a,b) => a-b)  
6      s.sort((a,b) => a-b)  
7  
8      s.forEach((child) => {  
9          if(child >= g[answer]){  
10             answer++  
11         }  
12     })  
13  
14     return answer  
15 }
```

3 String Algorithm Problems

3.1 Defanging an IP Address

<https://leetcode.com/problems/defanging-an-ip-address/>

1. split and join the address
2. return return address

Solution defangIPAddr

```
1 const defangIPAddr = (address) => {  
2   return address.split('.').join('[' + ']' + ' ')  
3 }
```

3.2 Jewels and Stones

<https://leetcode.com/problems/jewels-and-stones/>

1. Initialize count to zero
2. Loop through jewels string
3. Loop through stones string
4. Logic to check if each part of stones is equal to jewels
5. If equal add to count
6. Return count

Solution numJewelsInStones

```
1  const numJewelsInStones = (jewels, stones) => {  
2  
3      let count = 0  
4  
5      for(let i = 0; i<jewels.length; i++){  
6          for(let j=0; j<stones.length; j++){  
7              if(stones[j] === jewels[i]){  
8                  count ++  
9              }  
10         }  
11     }  
12  
13     return count  
14 };
```

3.3 Goal Parser Interpretation

<https://leetcode.com/problems/goal-parser-interpretation/>

1. Split command by () join o in place
2. Split command by (al) join al in place
3. Return command

Solution interpret

```
1  const interpret = (command) => {  
2      return command.split('(').join('o').split('(al)')  
        .join('al')  
3  };
```

3.4 Cells in a Range on an Excel Sheet

<https://leetcode.com/problems/cells-in-a-range-on-an-excel-sheet/>

1. Initialize empty answer array
2. Initialize array with string s [col1, row1, EMPTY SPACE, col2, row2] = s
3. Loop through columns - c with charCodeAt
4. Loop through rows - r with +row
5. Push answer to a string using fromCharCode(c) + r
6. Return answer

Solution cellsInRange

```
1  const cellsInRange = (s) => {  
2  
3      let answer = []  
4      let [col1, row1, , col2, row2] = s  
5  
6      for(let c = col1.charCodeAt(0), ce = col2.  
charCodeAt(0); c<= ce; c++){  
7          for(let r = +row1, re = +row2; r<=re; r++){  
8              answer.push(String.fromCharCode(c) + r)  
9          }  
10     }  
11  
12     return answer  
13 };
```

3.5 Split a String in Balanced Strings

<https://leetcode.com/problems/split-a-string-in-balanced-strings/>

1. Initialize empty matches variable
2. Initialize empty balance variable
3. Loop through s.length
4. If each S[i] is equal to L add +1 to balance, else reduce it by one
5. If balance is equal to zero add +1 to matches
6. Return matches

Solution balancedStringSplit with balance counter

```
1  const balancedStringSplit = (s) => {
2
3      let matches = 0;
4      let balance = 0;
5
6      for (let i = 0; i < s.length; i++) {
7          s[i] === 'L' ? balance++ : balance--
8          if (balance === 0) {
9              matches++;
10         }
11     }
12
13     return matches;
14 };
```

Solution balancedStringSplit with stack

```
1  var balancedStringSplitStack = function(s) {
2
3      let matches = 0
4      const stack = []
5
6      stack.push(s[0])
7
8      for (let i = 1; i < s.length; i++) {
9          const top = stack[stack.length - 1];
10         if (top !== undefined && top !== s[i]) {
11             stack.pop()
12         } else {
13             stack.push(s[i]);
14         }
15     }
16     return matches;
17 }
```

```
14         }
15         if (stack.length === 0) {
16             matches += 1;
17         }
18     }
19
20     return matches;
21 }
```

3.6 Sorting the Sentence

<https://leetcode.com/problems/sorting-the-sentence/>

1. Return s.split to put into parts
2. Sort by number orders and use x[x.length-1] to find last item (the number)
3. Map to remove the last item (the number) from the words
4. Join(' ') to turn it back into a string as opposed to array

Solution sortSentence

```
1 const sortSentence = function(s) {  
2   return s.split(' ').  
3     .sort((a,b) => a[a.length-1] - b[b.length-1])  
4     .map((word) => word.slice(0, word.length-1))  
5     .join(' ');  
6 }
```


3.7 Decode the Message

<https://leetcode.com/problems/decode-the-message/>

1. Create map variable of empty map()
2. Set start at 97
3. Initialize empty result string
4. For of loop through key if map has i or is empty continue
5. If not set i as a string fromCharCode(start++)
6. map.set(' ', ' ')
7. For of loop through message and add map.get(m) to result
8. Return result

Solution decodeMessage

```
1  const decodeMessage = (key, message) => {
2
3      let map = new Map();
4      let start=97;
5      let result="";
6
7      for(let i=0; i<key.length;i++){
8          if(map.has(key[i])||key[i]===" "){
9              continue
10         } else {
11             map.set(key[i],String.fromCharCode(start++))
12         }
13     }
14
15     map.set(" ", " ");
16
17     for(let m of message){
18         result+=map.get(m)
19     }
20
21     return result
22 };
```

3.8 Maximum Nesting Depth of the Parentheses

<https://leetcode.com/problems/maximum-nesting-depth-of-the-parentheses/>

1. Initialize answer int at zero
2. Initialize counter int at zero
3. For loop through s
4. If s[i] is equal to (answer.math.max(answer, ++counter)
5. Else decrement counter
6. Return answer

Solution maxDepth

```
1  const maxDepth = (s) => {
2
3      let answer = 0
4      let count = 0
5
6      for(let i = 0; i < s.length; i++){
7          if(s[i] === '('){
8              answer = Math.max(answer, ++count)
9          }else if(s[i] === ')'){
10             count--
11         }
12     }
13
14     return answer
15 };
```

Solution maxDepth with split() and reduce()

```
1  const maxDepth = (s) => {
2
3      let l = 0
4      let r = 0
5
6      return s.split('').reduce((depth, c) => {
7          if (c === '(') l++
8          if (c === ')') r++
9          return Math.max(l - r, depth)
10     }, 0)
11 }
```

3.9 Fizz Buzz

<https://leetcode.com/problems/fizz-buzz/>

1. Initialize empty answer array
2. Loop through n starting at 1 and ending when $j = n$
3. If i modulo 15 is equal to zero push string 'FizzBuzz'
4. Else if i modulo 5 is equal to zero push string 'Buzz'
5. Else if i modulo 3 is equal to zero push string 'Fizz'
6. Else push string i
7. Return answer

Solution fizzBuzz with for loop

```
1  const fizzBuzz = (n) => {  
2  
3      const result = []  
4  
5      for(let i=1; i<=n; i++) {  
6          if(i % 15 === 0) {  
7              result.push('FizzBuzz')  
8          } else if(i % 3 === 0) {  
9              result.push('Fizz')  
10         } else if(i % 5 === 0) {  
11             result.push('Buzz')  
12         } else {  
13             result.push(i.toString())  
14         }  
15     }  
16  
17     return result  
18 };
```

Solution fizzBuzz ES6

```
1  var fizzBuzz = function(n) {  
2      return new Array(n).fill(0).map((a, i) => (++i % 3  
3      ? '' : 'Fizz') + (i % 5 ? '' : 'Buzz') || '' + i)  
};
```

3.10 Check If Two String Arrays are Equivalent

<https://leetcode.com/problems/check-if-two-string-arrays-are-equivalent/>

1. Join("") word1 and word2 so they become strings
2. Compare the two strings so they are equal
3. Return true if equal
4. Return false if not equal

Solution arrayStringsAreEqual

```
1 var arrayStringsAreEqual = function(word1, word2) {  
2  
3     let w1 = word1.join('')  
4     let w2 = word2.join('')  
5  
6     if(w1 === w2){  
7         return true  
8     } else {  
9         return false  
10    }  
11 };
```

Solution arrayStringsAreEqual ES6

```
1 var arrayStringsAreEqual = function(word1, word2) {  
2     return word1.join('') === word2.join('')  
3 };
```

3.11 Count the Number of Consistent Strings

<https://leetcode.com/problems/count-the-number-of-consistent-strings/>

1. Initialize empty answer array
2. For of loop through i of words
3. Set word equals to i
4. Loop through word.length and set wordChar as word[j]
5. If !allowed includes wordChar break
6. Else if j===word.length -1 push word.length to answer
7. Return answer.length

Solution countConsistentStrings with loops

```
1  const countConsistentStrings = (allowed, words) => {
2
3      let answer = []
4
5      for(let i of words){
6          let word = i
7          for(let j = 0; j<word.length; j++){
8              let wordChar = word[j]
9              if(!allowed.includes(wordChar)){
10                 break
11             } else if(j === word.length-1){
12                 answer.push(word.length)
13             }
14         }
15     }
16
17     return answer.length
18 }
```

Solution countConsistentStrings ES6

```
1  const countConsistentStrings = (allowed, words) => {
2
3      let set = new Set(allowed)
4
5      return words.reduce((a, w) => {
6          return w.split('').every(l => set.has(l)) ? ++a
7      }, 0)
```

8	}
9	

3.12 To Lower Case

<https://leetcode.com/problems/to-lower-case/>

1. Return s.toLowerCase()

Solution toLowerCase

```
1 var toLowerCase = function(s) {  
2   return s.toLowerCase()  
3 };
```

Solution toLowerCase with hex code

```
1 //hex code for letter 'A' is 0x41 and for letter 'a'  
  is 0x61. That's a diff of 0x20.  
2 var toLowerCase = function(str) {  
3   let i = 0;  
4   let lowerCase = "";  
5  
6   while (i < str.length) {  
7     lowerCase += String.fromCharCode(str.  
charCodeAt(i) | 0x20);  
8     i++;  
9   }  
10  
11   return lowerCase;  
12 };
```

3.13 Rings and Rods

<https://leetcode.com/problems/rings-and-rods/>

1. Initialize new Map() called map
2. Initialize answer int to zero
3. Loop through rings.length
4. Set color to rings[i]
5. Set rod to +rings[i+1]
6. If !map has rod Map.set rod, new Set()
7. Map.get rod.add(color)
8. Loop through map with [rod, setColors]
9. If set color size is equal to 3 answer ++
10. Return answer

Solution countPoints

```
1  const countPoints = (rings) => {
2
3      let map = new Map()
4      let answer = 0
5
6      for(let i = 0; i<rings.length; i += 2){
7          let color = rings[i]
8          let rod = +rings[i + 1]
9          if(!map.has(rod))
10             map.set(rod, new Set())
11             map.get(rod).add(color)
12      }
13
14      for(let [rod, setColors] of map){
15          if(setColors.size === 3){
16              answer++
17          }
18      }
19
20      return answer
21  }
```


Solution countPoints is this slower?

```
1 var countPoints = function(rings) {  
2  
3   let rods = Array(10).fill("");  
4  
5   for(let i = 0; i < rings.length; i += 2){  
6     if(!(rods[rings[i+1]].includes(rings[i])))  
rods[rings[i+1]] += rings[i]  
7   }  
8  
9   return rods.filter(rod => rod.length > 2).length  
10 };
```

3.14 Truncate Sentence

<https://leetcode.com/problems/truncate-sentence/>

1. Split string so that it becomes array
2. Slice the array from index 0 to index k (desired length)
3. Join the array into a string (' ') removing commas
4. Return the string

Solution truncateSentence

```
1 var truncateSentence = function(s, k) {  
2  
3     return s.split(' ').slice(0,k).join(' ')  
4  
5 };
```

3.15 Check if the Sentence Is Pangram

<https://leetcode.com/problems/check-if-the-sentence-is-pangram/>

1. Make new Set (what does this mean?)
2. Split(" ") the sentence
3. Set size to equal 26
4. Return

Solution checkIfPangram

```
1 var checkIfPangram = function(sentence) {  
2  
3     return new Set(sentence.split(" ")).size === 26;  
4  
5 }
```

3.16 Count Asterisks

<https://leetcode.com/problems/count-asterisks/>

1. Set count and result counters
2. For loop through s.length
3. If s[i] === — increment count
4. If count is multiple of two and s[i] = * then increment result
5. Return result

Solution countAsterisks

```
1 var countAsterisks = function(s) {
2
3   let count = 0;
4   let res = 0;
5
6   for(let i = 0; i < s.length; i++){
7     if(s[i] === '|'){
8       count ++
9     }
10    if(count % 2 === 0 && s[i] === '*'){
11      res ++
12    }
13  }
14
15  return res;
16 };
```

My messy solution while learning

```
1 var countAsterisks = function(s) {
2
3   let count = 0
4   let s2 = s.split('|')
5   let temp = []
6
7   for(let i=0; i<s2.length; i+=2){
8     temp = s2[i].split('').join(',')
9     for(let j=0; j<temp.length;j++){
10      if(temp[j] === '*'){
11        count++
12      }
13    }
14  }
```

```
14     }  
15  
16     return count  
17 };
```

3.17 Unique Morse Code Words

<https://leetcode.com/problems/unique-morse-code-words/>

1. Set const morse to morse code from questions
2. Initialize answer to new Set
3. For of loop through words with word
4. Initialize transform as empty string
5. For loop through word to separate each character
6. Set i equal to char.charCodeAt(0) - 97
7. Add morse[i] to transform
8. Add transform to answer Set
9. Return size of answer set

Solution uniqueMorseRepresentations

```
1  const morse = [".-","-...","-.-.","-..",".","..-.",
2  "-.-.","...",".", "-.--","-.","-..","--","-.-.",
3  "-.-.", "-.-.", "-.", "...", "-", ".-.", "...-",
4  "-.-.", "-.-.", "-.-."]
5
6  const uniqueMorseRepresentations = (words) => {
7
8      let answer = new Set
9
10     for (let word of words){
11         let transform = ''
12         for(let char of word){
13             let i = char.charCodeAt(0) - 97
14             transform += morse[i]
15         }
16         answer.add(transform)
17     }
18
19     return answer.size
20 };
```

Solution uniqueMorseRepresentations with object

```
1  const alphabet = {
```

```

2 |     a: '.-', b: '-...', c: '-.-.', d: '-..', e: '.',
   |     f: '..-', g: '--.', h: '....', i: '...', j: '.---
   |     ', k: '-.-', l: '.-..', m: '--',
3 |     n: '-.', o: '---', p: '-.-.', q: '--.-', r: '
   |     .-', s: '...', t: '-', u: '..-', v: '...-', w: '
   |     .--', x: '-.-.', y: '-.-.-', z: '--..'
4 | }
5 |
6 | const uniqueMorseRepresentations = words => {
7 |
8 |     return new Set(words.map(word => word.split('').
   |     map(letter => alphabet[letter]).join('')).size
9 | }

```

3.18 Number of Strings That Appear as Substrings in Word

leetcode.com/problems/number-of-strings-that-appear-as-substrings-in-word/

1. Initialize answer to zero
2. Loop through patterns
3. If word includes(patter[i]) increment answer
4. Return answer

Solution numOfStrings

```
1 var numOfStrings = function(patterns, word) {  
2  
3   let answer = 0  
4  
5   for (let i = 0; i < patterns.length ; i++){  
6     if(word.includes(patterns[i])){  
7       answer++  
8     }  
9   }  
10  
11 return answer  
12 };
```


3.19 Remove Outermost Parentheses

<https://leetcode.com/problems/remove-outermost-parentheses/>

1. Initialize empty answer string
2. Initialize counter to zero
3. Loop through s
4. If s[i] is equal to (if counter is greater than zero add (to answer string and increment counter
5. Else if s[i] is equal to) and counter greater than one add) to answer string and decrement counter
6. Return answer

Solution removeOuterParentheses

```
1  const removeOuterParentheses = (s) => {
2
3      let answer = ''
4      let counter = 0
5
6      for(let i = 0; i<s.length; i++){
7          if(s[i] === '('){
8              if(counter > 0){
9                  answer += '('
10             }
11             counter++
12         } else if(s[i] === ')'){
13             if(counter > 1){
14                 answer += ')'
15             }
16             counter--
17         }
18     }
19
20     return answer
21 };
```

3.20 Replace All Digits with Characters

<https://leetcode.com/problems/replace-all-digits-with-characters/>

1. loop through s starting at 1 += 2
2. Initialize value to String.fromCharCode(s[i-1].charCodeAt()+Number(s[i]))
3. Update s to equal s.replace(s[i], value)
4. Return s

Solution replaceDigits

```
1  const replaceDigits = (s) => {  
2  
3      for(let i = 1; i<s.length; i+=2){  
4          let value = String.fromCharCode(s[i-1].  
charCodeAt()+Number(s[i]))  
5          s = s.replace(s[i], value)  
6      }  
7  
8      return s  
9  }
```

4 Hash Tables

4.1 Destination City

<https://leetcode.com/problems/destination-city/>

1. Create new set named departure
2. Loop through paths and add path[0] to departure
3. Loop through paths again and check if subarray has second index value (if it does not it is unique)
4. If no second index value, return that value (should be destination)

Solution destCity

```
1  const destCity = (paths) => {  
2  
3      let set = new Set()  
4  
5      for(let path of paths){  
6          set.add(path[0])  
7      }  
8  
9      for(let path of paths){  
10         if(!set.has(path[1])){  
11             return path[1]  
12         }  
13     }  
14 }
```

4.2 Maximum Number of Pairs in Array

<https://leetcode.com/problems/maximum-number-of-pairs-in-array/>

1. Initialize new map and count
2. Loop through nums
3. If map[nums[i]] then go ahead and delete map[nums[i]] and increment count
4. Else replace map[nums[i]] with one
5. Return [count, Object.values(map).length]

Solution numberOfPairs

```
1  const numberOfPairs = (nums) => {
2
3      let map = new Map()
4      let count = 0
5
6
7      for(let i=0;i<nums.length;i++){
8          if(map[nums[i]]){
9              delete(map[nums[i]])
10             count++
11         } else {
12             map[nums[i]] = 1
13         }
14     }
15
16     return [count, Object.values(map).length]
17 }
```

4.3 Design an Ordered Stream

<https://leetcode.com/problems/design-an-ordered-stream/>

1. Created class OrderedStream
2. Setup constructor
3. Set pointer to zero and initialize empty list
4. Insert (id, value)
5. Initialize empty chunk array
6. Set this.list[id-1] to value
7. While loop through (this.list[this.pointer])
8. Push (this.list[this.pointer]) into chunk
9. Increment this.pointer
10. Return chunk

Solution orderedStream

```
1 class OrderedStream {
2     constructor(n) {
3         this.pointer = 0
4         this.list = []
5     }
6
7     insert(id, value) {
8         let chunk = []
9         this.list[id - 1] = value
10        while(this.list[this.pointer]) {
11            chunk.push(this.list[this.pointer])
12            this.pointer++
13        }
14
15        return chunk
16    }
17 }
```

4.4 Increasing Decreasing String

<https://leetcode.com/problems/increasing-decreasing-string/>

1. Initialize arr with Array.from(s) (splitting s into an array of its parts)
2. Initialize empty answer string
3. Sort arr
4. While loop through arr.length
5. Filter arr so that if i === 0 or x !== answer.length-1 increase answer by x and return false
6. Else return true
7. Reverse arr
8. Return answer

Solution sortString

```
1  const sortString = (s) => {
2
3      let arr = Array.from(s)
4      let answer = '';
5
6      arr.sort();
7
8      while (arr.length) {
9          arr = arr.filter((x, i) => {
10             if (i === 0 || x !== answer[answer.length -
11                1]) {
12                 answer += x;
13                 return false;
14             }
15             return true;
16         });
17         arr.reverse();
18     }
19     return answer;
20 };
```

4.5 Check if All Characters Have Equal Number of Occurrences

<https://leetcode.com/problems/check-if-all-characters-have-equal-number-of-occurrences/>

1. Initialize empty Map
2. Loop through letters of s
3. Map[letter] is equal to itself or zero + 1 (setup count of each letter)
4. Initialize occurrences equal to the set of Object.values(map)
5. If occurrences.size === 1 (all letter groups are equal) return true
6. Else return false

Solution areOccurrencesEqual with Map

```
1 const areOccurrencesEqual = (s) => {
2
3   let map = new Map()
4
5   for(let letter of s){
6     map[letter] = (map[letter] || 0) + 1
7   }
8
9   let count = new Set(Object.values(map))
10  if(count.size === 1) return true
11  return false
12 }
```

Solution areOccurrencesEqual with reduce()

```
1 const areOccurrencesEqualReduce = (s) => {
2
3   let count = s.split('').reduce((obj, cur)=>{
4     obj.hasOwnProperty(cur) ? obj[cur] += 1 : obj[
5     cur] = 1
6     return obj
7   },{})
8
9   return new Set(Object.values(count)).size === 1
10  };
11 }
```

4.6 Divide Array Into Equal Pairs

<https://leetcode.com/problems/divide-array-into-equal-pairs/>

1. Create empty map ()
2. Loop through nums and if map has number delete it else set the number true
3. Return true if map size is empty else return false

Solution divideArray

```
1  const divideArray = (nums) => {  
2  
3      let map = new Map();  
4  
5      for (const number of nums) {  
6          map.has(number) ? map.delete(number) : map.set(  
7              number, true);  
8      }  
9      return map.size === 0;  
10 };
```


4.7 N-Repeated Element in Size 2N Array

<https://leetcode.com/problems/n-repeated-element-in-size-2n-array/>

1. Initialize empty Map()
2. Loop through values of nums
3. If value is in map return value
4. Else return zero

Solution repeatedNTimes with Map()

```
1 const repeatedNTimes = (nums) => {  
2  
3   let map = new Map()  
4  
5   for ( let num of nums) {  
6     if (num in map) {  
7       return num;  
8     } else {  
9       map[num] = 0;  
10    }  
11  }  
12 };
```

Solution repeatedNTimes with ES6

```
1 var repeatedNTimes = function(nums) {  
2   return nums.find((a, index, array) => array.  
3     indexOf(a) !== index)  
};
```

Solution repeatedNTimes with Set()

```
1 var repeatedNTimes = function(A) {  
2   let set = new Set();  
3  
4   for(let a of A) {  
5     if(set.has(a))  
6       return a;  
7  
8     set.add(a);  
9   }  
10 };
```

4.8 Sum of Unique Elements

<https://leetcode.com/problems/sum-of-unique-elements/>

1. Create empty Map()
2. Initialize sum at zero
3. Loop through nums if map[n] is undefined increase sum by n and set map[n] to true
4. Else if decrement n from sum and set map[n] to false
5. Return sum

Solution sumOfUnique with Map()

```
1  const sumOfUnique = (nums) => {
2
3      let map = new Map()
4      let sum = 0
5
6      for(let n of nums){
7          if(map[n] === undefined){
8              sum += n
9              map[n] = true
10         } else if(map[n]){
11             sum -= n
12             map[n] = false
13         }
14     }
15
16     return sum
17 }
```

Solution sumOfUnique with forEach

```
1  var sumOfUnique = function(nums) {
2      let result = []
3      nums.forEach(function(e){
4          if(nums.indexOf(e) === nums.lastIndexOf(e)){
5              result.push(e)
6          }
7      })
8      return result.reduce((a,b) => a + b , 0)
9  }
```

4.9 Maximum Number of Balls in a Box

<https://leetcode.com/problems/maximum-number-of-balls-in-a-box/>

1. Create empty Map()
2. Loop from low to high limit incrementing i and setting sum to zero
3. Loop through i with j using Math.trunc for the numbers that are more digits
4. Map.set the numbers so the map is counting the values
5. Return with math.max the map of split map with the highest values

Solution countBalls

```
1  const countBalls = (lowLimit, highLimit) => {
2
3      let map = new Map();
4
5      for (let i = lowLimit, sum = 0; i <= highLimit; i
6      ++, sum = 0) {
7          for (let j = i; j; j = Math.trunc(j / 10)) {
8              sum += j % 10;
9              map.set(sum, (map.get(sum) || 0) + 1);
10         }
11
12         return Math.max(...map.values());
13     };
```

4.10 Check if Number Has Equal Digit Count and Digit Value

<https://leetcode.com/problems/check-if-number-has-equal-digit-count-and-digit-value/>

1. Create array with num length and fill it with zero
2. For of Loop through num and increase arr[Number(i)++]
3. return arr.join("") if it is equal to num

Solution digitCount

```
1 const digitCount = (num) => {  
2  
3   let arr= Array(num.length).fill(0);  
4  
5   for(let i of num){  
6     arr[Number(i)]++;  
7   }  
8  
9   return arr.join(',') === num;d  
10 };
```

4.11 Keep Multiplying Found Values by Two

<https://leetcode.com/problems/keep-multiplying-found-values-by-two/submissions/>

1. Loop through nums
2. If nums includes original value multiply original by two
3. Return original

Solution findFinalValue with while loop

```
1  const findFinalValue = (nums, original) => {  
2  
3      while(nums.includes(original)){  
4          original = original * 2  
5      }  
6  
7      return original  
8  };
```

Solution findFinalValue with for loop

```
1  const findFinalValue = (nums, original) => {  
2  
3      for(let i = 0; i<nums.length; i++){  
4          if(nums.includes(original)){  
5              original = original * 2  
6          }  
7      }  
8  
9      return original  
10 };
```

Solution findFinalValue with set

```
1  var findFinalValueSet = function(nums, original) {  
2  
3      const set = new Set(nums)  
4      let result = original  
5  
6      while (set.has(result))  
7          result *= 2  
8  
9      return result  
10 };
```

4.12 Two Out of Three

<https://leetcode.com/problems/two-out-of-three/>

1. Initialize arr with three split... Set() for nums1,2,3
2. Initialize map object
3. Initialize empty results array
4. For of loop through arr and build map to have count of each value
5. For in loop through map and push any values ≥ 2 into the results array
6. Return results

Solution twoOutOfThree O(n) time/space

```
1  const twoOutOfThree = (nums1, nums2, nums3) => {
2
3      let arr = [...new Set(nums1), ...new Set(nums2),
4      ...new Set(nums3)]
5      let map = {}
6      let result = []
7
8      for(let n of arr) {
9          if(map[n]) {
10             map[n] += 1
11          } else {
12             map[n] = 1
13          }
14      }
15
16      for(let i in map) {
17          if(map[i] >= 2) {
18             result.push(i)
19          }
20      }
21
22      return result
23  };
```

Solution twoOutOfThree - clunky first answer

```
1  var twoOutOfThree = function(nums1, nums2, nums3) {
2
3      let answer = []
4  }
```

```

5      for(let n of nums1){
6          for(let n2 of nums2){
7              if(n === n2){
8                  answer.push(n)
9              }
10             for(let n3 of nums3){
11                 if (n2 === n3){
12                     answer.push(n2)
13                 }
14                 if (n === n3){
15                     answer.push(n3)
16                 }
17             }
18         }
19     }
20
21     let finalAnswer = [...new Set(answer)];
22     return finalAnswer
23 };

```

4.13 Kth Distinct String in an Array

<https://leetcode.com/problems/kth-distinct-string-in-an-array/>

1. Initialize empty map
2. Initialize answer array
3. For each through the array to build the map
4. For loop through [key, val] of map Object
5. Return the values === 1 and push their key to the answer
6. Return answer [k-1] since it starts at zero index — empty string if nothing

Solution kthDistinct

```
1  const kthDistinct = (arr, k) => {  
2  
3      let map = {}  
4      let answer = []  
5  
6      arr.forEach(i => map[i] = map[i] + 1 || 1)  
7  
8      for (let [key, val] of Object.entries(map))  
9          if (val === 1) answer.push(key)  
10  
11     return answer[k-1] || ""  
12 };
```


4.14 Maximum Number of Words You Can Type

<https://leetcode.com/problems/maximum-number-of-words-you-can-type/>

1. Initialize empty answer variable
2. Set `t = true`
3. Create new Set with `brokenLetter` split into characters
4. Loop through text and set letter to `charAt(i)`
5. If set has letter set `t` to false
6. If letter is empty or letter is there increase by one, set `t` to true again
7. If `t` is there, increase answer by 1
8. Return answer

Solution `canBeTypedWords`

```
1  const canBeTypedWords = (text, brokenLetters) => {  
2  
3      let answer = 0;  
4      let t = true;  
5      let set = new Set(brokenLetters.split(''));  
6  
7      for(let i=0;i<text.length;i++){  
8          let letter = text.charAt(i);  
9          if(set.has(letter)) t = false;  
10         if(letter==' ') {  
11             if(t) answer += 1;  
12             t = true;  
13         }  
14     }  
15  
16     if(t) answer += 1;  
17  
18     return answer;  
19 }
```

4.15 Substrings of Size Three with Distinct Characters

<https://leetcode.com/problems/substrings-of-size-three-with-distinct-characters/>

1. Initialize answer at zero
2. For loop through s.length - 1
3. Set str to a slice of s that starts at i and goes till i+3
4. Make a new Set(str)
5. If the size of the set is === 3, += 1 to answer
6. Return answer

Solution countGoodSubstrings

```
1  const countGoodSubstrings = (s) => {
2
3      let answer = 0
4
5      for (let i = 0; i < s.length - 2; i++) {
6          let str = s.slice(i, i + 3)
7          let set = new Set(str)
8          if (set.size === 3) answer += 1
9      }
10
11     return answer
12 };
```

4.16 Find the Difference of Two Arrays

<https://leetcode.com/problems/find-the-difference-of-two-arrays/submissions/>

1. Set set1 to a new Set of nums1
2. Set set2 to a new Set of nums2
3. ForEach loop through nums2 where it will delete any values that are also in set1
4. ForEach loop through nums1 where it will delete any values that are also in set2
5. Return an array of split arrays set1 and set2

Solution findDifference

```
1  const findDifference = (nums1, nums2) => {  
2  
3      let set1 = new Set(nums1)  
4      let set2 = new Set(nums2)  
5  
6      nums2.forEach(i => {set1.delete(i)})  
7      nums1.forEach(i => {set2.delete(i)})  
8  
9      return ([...set1], [...set2])  
10 };
```

4.17 Isomorphic Strings

<https://leetcode.com/problems/isomorphic-strings/>

1. Initialize new Map()
2. Loop through s.length
3. If there is no map['s' +s[i]] then add it and set to t[i]
4. If there is no map['t' +t[i]] then add it and set to s[i]
5. If t[i] is not equal to the s map or if s[i] is not equal to the t map return false
6. Return true

Solution isIsomorphic

```
1  const isIsomorphic = (s, t) => {
2
3      let map = new Map()
4
5      for (let i = 0; i<s.length; i++){
6          if(!map['s' + s[i]]) {
7              map['s' + s[i]] = t[i]
8          }
9          if(!map['t' + t[i]]) {
10             map['t' + t[i]] = s[i]
11         }
12         if(t[i] !== map['s' + s[i]] || s[i] !== map['t'
+ t[i]]){
13             return false
14         }
15     }
16
17     return true;
18 };
```

4.18 Word Pattern

<https://leetcode.com/problems/word-pattern/>

1. Set words to s.split(' ')
2. Set map to new Map()
3. If words.length is not equal to pattern return false (catches diff length)
4. If words.size is not equal to set(patter).size return false (catches equal word)
5. For loop through pattern length
6. If map pattern has pattern [i] and it is not equal to words[i] return false
7. Map.set pattern[i] and words[i]
8. Return true

Solution wordPattern

```
1  const wordPattern = (pattern, s) => {
2
3      let words = s.split(' ')
4      let map = new Map()
5
6      if(words.length !== pattern.length){
7          return false
8      }
9      if(new Set(words).size !== new Set(pattern).size){
10         return false
11     }
12
13     for(let i = 0; i < pattern.length; i++) {
14         if(map.has(pattern[i]) &&
15             map.get(pattern[i]) !== words[i]) {
16             return false
17         }
18         map.set(pattern[i], words[i])
19     }
20
21     return true
22 };
```

4.19 Longest Harmonious Subsequence

<https://leetcode.com/problems/longest-harmonious-subsequence/>

1. Initialize new Map()
2. Set result at zero
3. For of loop through nums $\text{map}[v] = \text{map}[v] + 1$ or 1 (build map)
4. Loop through the key of map and parse int $\text{key} + 1$
5. Set result to math max result, $\text{map}[\text{key}] + \text{map}[\text{parseInt}(\text{key}) + 1]$
6. Return result

Solution findLHS

```
1  const findLHS = (nums) => {
2
3      let map = new Map()
4      let result = 0
5
6      for(let v of nums) {
7          map[v] = map[v] + 1 || 1
8      }
9
10     for (let key in map) {
11         if(map[parseInt(key) + 1]) {
12             result = Math.max(result, map[key] + map[
13                 parseInt(key) + 1])
14         }
15     }
16     return result
17 };
```

4.20 Next Greater Element I

<https://leetcode.com/problems/next-greater-element-i/>

1. Initialize new Map()
2. Initialize empty array called stack
3. Loop through nums2 with forEach and nest a while loop
4. While stack.length 0 && it is within stack push stack n
5. Return nums1.map(n map[n] or -1)

Solution nextGreaterElement

```
1  const nextGreaterElement = (nums1, nums2) => {  
2  
3      let map = {}  
4      let stack = []  
5  
6      nums2.forEach(n => {  
7          while (stack.length > 0 && stack[stack.length -  
8              1] < n) {  
9              map[stack.pop()] = n  
10             }  
11             stack.push(n)  
12         })  
13         return nums1.map(n => map[n] || -1)  
14     };
```

5 Dynamic Programming

5.1 Counting Bits

<https://leetcode.com/problems/counting-bits/>

1. Initialize result array at [0]
2. Initialize offset at 1
3. For loop through n starting at 1, going till n+1
4. If $\text{offset} * 2 === i$ then set offset to i
5. $\text{result}[i]$ is equal to $1 + \text{result}[i - \text{offset}]$
6. Return result

Solution countBits

```
1  const countBits = (n) => {  
2  
3      let result = [0]  
4      let offset = 1  
5  
6      for (let i = 1; i < n + 1; i++) {  
7          if (offset * 2 === i) {  
8              offset = i  
9          }  
10         result[i] = 1 + result[i - offset]  
11     }  
12  
13     return result  
14 };  
15
```


5.2 Fibonacci Number

<https://leetcode.com/problems/fibonacci-number/>

1. Initialize result to [0,1]
2. For loop starting from 2 till i := n
3. Result push result[i-2] plus result[i-1]
4. Return result[n]

Solution fib

```
1  const fib = (n) => {  
2  
3      let result = [0,1]  
4  
5      for(let i = 2; i<= n; i++){  
6          result.push(result[i-1] + result[i-2])  
7      }  
8  
9      return result[n]  
10 };
```

5.3 Pascal's Triangle

<https://leetcode.com/problems/pascals-triangle/>

1. Initialize empty results array
2. For loop through n
3. Set result[i] to empty array
4. Set result[i][0] equal to result[i][i] = 1
5. For loop through i starting at 1
6. Set result[i][j] equal to result[i-1][j] + result[i-1][j-1]
7. Return result

Solution generate

```
1  const generate = (n) => {
2
3      let result = []
4
5      for(let i = 0; i<n; i++){
6          result[i] = []
7          result[i][0] = result[i][i] = 1
8          for(let j = 1; j < i; j++){
9              result[i][j] = result[i-1][j] + result[i
10             -1][j-1]
11         }
12     }
13     return result
14 };
```

Solution generate with less mess

```
1  const generate = (n) => {
2
3      let r = []
4
5      for(let i =0;i<n; i++){
6          r[i] = []
7          r[i][0] = r[i][i] = 1
8          for(let j = 1; j<i; j++){
9              r[i][j] = r[i-1][j]+r[i-1][j-1]
10         }
11     }
```

```
12     return r
13 };
```

5.4 Divisor Game

<https://leetcode.com/problems/divisor-game/>

1. return $n \% 2 === 0$

Solution divisorGame

```
1 const divisorGame = (n) => {  
2   return n % 2 === 0  
3 };
```

Solution divisorGame

```
1 const divisorGame = (n) => {  
2  
3   let result = Array(n + 1).fill(false)  
4  
5   for (let i = 2; i <= n; ++i){  
6     for (let j = Math.floor(Math.sqrt(i)); 1 <= j;  
7       --j){  
8       if (!(i % j) && !result[i - j]){  
9         result[i] = true  
10      }  
11    }  
12  
13    return result[n]  
14 };
```

5.5 N-th Tribonacci Number

<https://leetcode.com/problems/n-th-tribonacci-number/>

1. return Initialize result array to 0,1,1
2. For loop through n starting from 3
3. Set result to result -1,-2-3 for initial values
4. Return result[n]

Solution tribonacci

```
1  const tribonacci = (n) => {  
2  
3      let result = [0,1,1]  
4  
5      for(let i = 3; i<=n; i++) {  
6          result[i] = result[i-1] + result[i-2] + result  
7          [i-3]  
8      }  
9      return result[n]  
10 };
```

5.6 Min Cost Climbing Stairs

<https://leetcode.com/problems/min-cost-climbing-stairs/>

1. Initialize L array at cost[0]
2. Initialize R array at cost[1]
3. Initialize current as empty array
4. if cost.length === 1 return zero
5. If cost.length === 2 return math.min(L, R)
6. Loop through cost starting from 2
7. Set current to cost[i] + math.min(L, R)
8. Set L to R
9. Set R to current
10. Return Math.min(L, R)

Solution minCostClimbingStairs

```
1  const minCostClimbingStairs = (cost) => {  
2  
3      let L = cost[0]  
4      let R = cost[1]  
5      let current = []  
6  
7      if (cost.length === 1) return 0  
8      if (cost.length === 2) return Math.min(L, R)  
9  
10     for (let i = 2; i < cost.length; i++) {  
11         current = cost[i] + Math.min(L, R)  
12         L = R  
13         R = current  
14     }  
15  
16     return Math.min(L, R)  
17 };
```

5.7 Pascal's Triangle II

<https://leetcode.com/problems/pascals-triangle-ii/>

1. Initialize result as empty array
2. Loop through row index + 1
3. Set result[i] to empty array
4. Result [i][0] = result [i][i] = 1
5. Loop through i starting from 1
6. Set result [i][j] to result[i-1][j] + result[i-1][j-1]
7. Return result[rowIndex]

Solution getRow

```
1  const getRow = (rowIndex) => {
2
3      let result = []
4
5      for(let i = 0; i<rowIndex+1; i++){
6          result[i] = []
7          result[i][0] = result[i][i] = 1
8          for(let j = 1; j < i; j++){
9              result[i][j] = result[i-1][j] + result[i
10         -1][j-1]
11         }
12     }
13     return result[rowIndex]
14 };
```

5.8 Best Time to Buy and Sell Stock

<https://leetcode.com/problems/best-time-to-buy-and-sell-stock/>

1. Initialize profits at zero
2. Initialize min at prices[0]
3. Loop through prices starting from index 1
4. If min greater than prices[i] set min=prices[i]
5. Else if prices[i] - min greater than profit set profit = prices[i] - min
6. Return profit

Solution maxProfit

```
1  const maxProfit = (prices) => {  
2  
3      let profit = 0  
4      let min = prices[0]  
5  
6      for(let i = 1; i < prices.length; i++) {  
7          if(min > prices[i]) {  
8              min = prices[i]  
9          } else if(prices[i] - min > profit) {  
10             profit = prices[i] - min  
11         }  
12     }  
13  
14     return profit  
15 };
```