

Brine Dispersion Modelling Case Study

Universal Brine Dispersion Solver (UBDS): Near-, Medium- and Far-Field Assessment of the Bahia Azul Seawater Desalination & Brine Outfall

Author: Akosa Samuel Onyejekwe (Independent Researcher)

Solver: UBDS v1.0.0 | Document: case.docx

Executive Summary

This study presents a holistic near-, medium- and far-field assessment of the brine discharge from the proposed Bahia Azul seawater desalination and brine outfall, performed entirely with the Universal Brine Dispersion Solver (UBDS) - a novel, open, physics-based solver developed by the author. UBDS unifies, in a single dynamically-coupled and mass-conserving framework, the near-field integral jet/plume modelling and the far-field hydrodynamic transport modelling that conventionally require two separate, proprietary codes. Its sign-agnostic buoyancy treatment and dense-water gravity-current closure make it universal across negatively buoyant (brine), positively buoyant (thermal) and neutral discharges.

For the proposed inclined 4-port diffuser, the near-field initial dilution of the reverse-osmosis (RO) concentrate at first seabed contact ranges between x58 and x186 across the flow and tidal range, corresponding to seabed salinities of 36.7-37.0 psu against a background of 36.5 psu.

The medium- and far-field assessment confirms that, for the phase-1 RO concentrate at the maximum discharge of 1200 m³/hr, the salinity increment of 0.5 psu above background is confined to an area of 0.0544 km² on the 25 m assessment grid (the 60 m regional grid cannot resolve a footprint this small and reports 0.000 km²; see section 6), with the 38.5 psu threshold not exceeded beyond 0 m from the diffuser - well within the 100 m regulatory mixing zone. All trace impurities remain below their Environmental Quality Standards after dilution. That compliance result does NOT extend to the phase-2 saturated cavern brine. At full flow the 250 psu cavern source exceeds the 38.5 psu seabed threshold to at least 1213 m from the diffuser on the 2.5 km assessment domain, and to at least 3530 m - 35 times the 100 m regulatory mixing zone - on the 7.2 km regional domain (section 5). Both are lower bounds: the model holds each domain edge at the background salinity and this plume reaches both edges, so neither domain contains it and the true extent is larger than either figure. That uncertainty is in the SIZE of the breach, not in whether there is one. Phase 2 is not permissible on this diffuser as modelled. Every near-field run lies inside the Froude range over which the entrainment closure is validated (see section 4); the saturated-cavern-brine worst case governs the seabed-salinity assessment.

The solver was tested against canonical self-similar jet and plume dilution laws, published inclined dense-jet experimental data, and reference seawater/brine densities. The equation of state, the

dense-jet return distance and the dense-jet return-point dilution fall inside their reference ranges; the round-jet dilution slope, the pure-plume exponent and the dense-jet terminal rise fall a few per cent outside theirs. Each deviation is quantified in the Validation section rather than asserted away. Data sources are recorded there also. The hydrodynamic skill scores in section 3 are not part of this evidence: the ADCP series they score against is synthetic, derived from the model solution itself.

1 Introduction and the UBDS Solver

Brine discharges from desalination plants and solution-mined storage caverns are negatively buoyant and sink towards the seabed, where elevated salinity can affect benthic ecology. Their assessment requires resolving both the small-scale turbulent jet/plume mixing in the immediate vicinity of the diffuser (the near field) and the tidally-driven transport and dilution over the wider water body (the medium and far field). Conventionally these two regimes are handled by separate, proprietary software, with manual transfer of results between them.

1.1 Novelty and gaps bridged

- Unified near-to-far field coupling in a single open framework, removing the manual hand-off and the associated mass-conservation errors between separate codes.
- Sign-agnostic buoyancy: the same governing equations describe dense (brine), buoyant (thermal/freshwater) and neutral discharges - a genuinely universal solver.
- A dense-water gravity-current closure in the sigma-layer transport engine that reproduces the strong bottom-trapping of brine that 2-D depth-averaged models cannot capture and that 3-D models obtain only at large computational cost.
- Built-in regulatory-metric engine: mixing-zone radius, salinity-increment areas, diffusion distances and EQS compliance computed automatically from the solution.
- Fully open and reproducible: physically-standard, documented entrainment and turbulence closures, with all inputs and outputs exposed as data.

1.2 Governing equations

Near field - steady Eulerian flux-integral equations (top-hat) integrated along the jet arclength s , with combined shear + cross-flow entrainment and a sign-agnostic buoyancy body force:

$$d(\rho_e Q)/ds = \rho_a E ; \quad d(\rho_e Q V)/ds = \rho_a E V_a + (0,0,(\rho_a - \rho_e) g \pi b^2)$$

$$d(\rho_e Q S)/ds = \rho_a E S_a ; \quad E = 2 \pi b \alpha_s |V - V_a| + 2 b \alpha_f |V_a_{\text{perp}}|$$

Far field - depth-averaged shallow-water hydrodynamics (mass + momentum with Manning friction, Coriolis and turbulent mixing) driving a sigma-layer advection-dispersion equation augmented with the buoyancy-scaled inter-layer gravity-current flux:

$$d(\eta)/dt + d(Hu)/dx + d(Hv)/dy = 0$$

$$d(hs)/dt + d(uhs)/dx + d(vhs)/dy = d/dx(hDx ds/dx) + d/dy(hDy ds/dy) + \text{sources}$$

2 Case Study Site and Input Data

Site: Bahia Azul Seawater Desalination & Brine Outfall (Bahia Azul (fictional), open Mediterranean-type coast). A mid-size seawater reverse-osmosis desalination plant (product capacity 60,000 m³/d) discharging hypersaline concentrate through an offshore inclined multiport diffuser, with provision for later receipt of saturated leaching brine from an adjacent salt-cavern energy-storage scheme. Latitude 36.5 N.

2.1 Discharge and ambient inputs

Product (freshwater) capacity	60,000 m ³ /d
Recovery ratio	0.45
Brine (concentrate) flow - full	1200 m ³ /hr (28,800 m ³ /d)
RO brine salinity / excess temp	68.0 psu / +0.3 C
Cavern brine salinity / excess temp	250.0 psu / +2.0 C
Background salinity / temperature	36.5 psu / 18.0 C
Outfall depth / offshore distance	18.0 m / 850.0 m
Diffuser	4 x 6" ports @ 20.0 m, 60.0 deg, 0.8 m above bed
Mixing-zone radius / threshold	100.0 m / 38.5 psu

2.2 Flow scenarios

Table. Hydrodynamic and transport model parameters used in the simulations.

Parameter	Value
Minimum time step	0.4 s
CFL number	0.85
Manning coefficient n	0.025 (0.022-0.04)
Horizontal eddy viscosity	10.0 m ² /s
Smagorinsky constant	0.2
Horizontal dispersion	1.0 m ² /s
Vertical diffusivity	0.0005 m ² /s
Gravity-current coefficient	12.0
Background salinity	36.5 psu
Background temperature	18.0 C
RO brine salinity	68.0 psu
Cavern brine salinity	250.0 psu
Outfall depth	18.0 m
Shear entrainment coefficient (jet)	0.057
Shear entrainment coefficient (plume)	0.083
Forced entrainment coefficient	0.9
Ports installed	4
Port diameter	0.1524 m (6 inch)
Port discharge angle	60.0 deg
Port spacing	20.0 m
Port height above bed	0.8 m

3 Model Geometry, Mesh and Setup

Two nested structured-grid domains were configured: a high-resolution medium-field domain (2500 x 2500 m at 25 m, 9 sigma layers) and a regional far-field domain (7200 x 7200 m at 60 m, 4 layers).

The bathymetry deepens offshore and includes a southern headland whose lee generates a tidal eddy.

The two domains are windows onto one site, defined on a single set of absolute coordinates: the same coastline, the same headland, island and shallow bank, and the same diffuser at 850 m offshore in about 18 m of water. The regional domain therefore contains the medium-field one and can be used as a check on it, rather than being a second, differently-shaped site that happens to carry the same name.

One consequence of the domain sizes has to be stated because it bounds a headline number. The transport model holds every domain edge at the ambient background salinity - an open, flushing boundary. For a plume that decays well inside the domain, which is the case for the phase-1 RO concentrate at every flow and tide, this is exactly the right condition and has no influence on the result. The phase-2 saturated cavern plume is different: its 38.5 psu contour runs out to within a few cells of the medium-field boundary, so that boundary is actively holding the contour in. Every phase-2 threshold radius and area measured on the 2.5 km assessment domain is therefore a LOWER BOUND set by the domain, not a converged result, and it is reported as such throughout. The 7.2 km regional domain has room for the plume to close and is reported alongside it as the upper end of the range.




Figure. Medium-field mesh & bathymetry (Bahia Azul)




Figure. Far-field (regional) domain & bathymetry




Figure. Diffuser location & ADCP current-meter stations




Figure. Modelled current speed & direction at station A0 (neap & spring), against a synthetic ADCP reference generated from the model solution with a 3 percent bias and random noise. Not an independent measurement.




Figure. Modelled current speed & direction at station A1 (neap & spring), against a synthetic ADCP reference generated from the model solution with a 3 percent bias and random noise. Not an independent measurement.




Figure. Modelled current speed & direction at station A2 (neap & spring), against a synthetic ADCP reference generated from the model solution with a 3 percent bias and random noise. Not an independent measurement.




Figure. Modelled current speed & direction at station A3 (neap & spring), against a synthetic ADCP reference generated from the model solution with a 3 percent bias and random noise. Not an independent measurement.




Figure. Modelled current speed & direction at station A4 (neap & spring), against a synthetic ADCP reference generated from the model solution with a 3 percent bias and random noise. Not an independent measurement.




Figure. Modelled tidal level (spring tide) against a synthetic reference series derived from the model solution with an imposed bias and noise. Not an independent measurement.




Figure. Depth-averaged tidal flow field at flood (spring tide).




Figure. Depth-averaged tidal flow field at ebb (spring tide).

Table. Sigma-layer schemes (% of water-column depth per layer).

layer	pct_14	pct_9	pct_4
L1 (bed)	0.1	1.0	15.0
L2	0.5	1.2	15.0
L3	0.6	1.5	35.0
L4	0.8	2.5	35.0
L5	1.0	4.5	-
L6	1.5	9.3	-
L7	2.0	15.0	-
L8	3.0	25.0	-
L9	4.5	40.0	-
L10	6.5	-	-
L11	8.5	-	-
L12	11.0	-	-
L13	20.0	-	-
L14	40.0	-	-

A note on what the skill scores below do and do not show. Bahia Azul is a fictitious site, so no measured currents exist for it. The 'ADCP' series is the model solution itself, perturbed by a 3 per cent proportional bias and random noise scaled to the local signal amplitude. The Willmott index and

Nash-Sutcliffe efficiency reported here therefore quantify that imposed perturbation and confirm that the skill-metric pipeline behaves correctly. They are NOT evidence that the hydrodynamic engine reproduces field measurements, and they must not be read as calibration against observations. The independent evidence for the solver is in the Validation section, which compares it against published experimental data and analytical laws.

Table. Model skill against the synthetic ADCP reference series. The reference is the model solution plus an imposed bias and noise, so near-unity scores are expected by construction and are not a field validation.

station	tide	peak_speed_ms	rmse_speed_ms	willmott_d	nse
A0	neap	0.541	0.011	0.999	0.996
A0	spring	0.844	0.02	0.998	0.993
A1	neap	0.578	0.013	0.999	0.995
A1	spring	0.946	0.024	0.998	0.994
A2	neap	0.056	0.002	0.997	0.987
A2	spring	0.108	0.002	0.999	0.994
A3	neap	0.271	0.006	0.998	0.994
A3	spring	0.43	0.01	0.999	0.995
A4	neap	0.297	0.007	0.999	0.996
A4	spring	0.543	0.014	0.999	0.995

4 Near-Field Initial Dilution

The near-field initial dilution was computed with the UBDS integral jet/plume engine for both brine types, all flow scenarios and a range of tidal velocities (slack, neap and spring). Dilution is the bulk (flux-averaged, top-hat) dilution, and salinity is reported at first contact with the seabed; every run in the table below is verified to terminate on seabed contact.

Validity of the near-field results. The inclined dense-jet benchmark spans $9.0 \leq Fr \leq 33.3$ (7 cases), which was chosen to cover the Froude numbers this study actually runs at rather than a convenient band above them. All 18 runs below lie inside that span: the RO concentrate at Fr 24.0-27.9 and the denser saturated-cavern brine, which governs the seabed assessment, at Fr 9.2-10.7. The diffuser stages ports in with flow, holding the per-port exit velocity between 4.57 and 5.33 m/s. Coverage is not the same as agreement: across the benchmark the return distance is inside its published band in 7/7 cases and the return-point dilution in 6/7, but the terminal rise is inside its band in only 1/7, and the shortfall grows as Fr falls - that is, it is largest at the cavern-brine Froude numbers. Section 9 quantifies it. The greatest predicted plume rise is 6.4 m in 18 m of water (36% of the water column), so the free surface, which the model does not impose, is not approached.

Table. Near-field initial-dilution results. Every run terminates on seabed contact; the termination check is retained in the CSV.

brine	scenario	flow_m_3hr	n_ports	tide	velocity_ms	exit_velocity_ms	dilution	seabed_salinity_psu	rise_height_m	impact_distance_m
RO concentrate	S1	300	1	slack	0.08	4.57	58.2	37.04	5.51	8.6
RO concentrate	S1	300	1	neap	0.28	4.57	122.1	36.76	4.31	19.75

RO concentrate	S1	300	1	spring	0.55	4.57	161.6	36.69	3.58	39.24
RO concentrate	S2	700	2	slack	0.08	5.33	67.4	36.97	6.39	10.08
RO concentrate	S2	700	2	neap	0.28	5.33	140.5	36.72	4.97	22.95
RO concentrate	S2	700	2	spring	0.55	5.33	185.9	36.67	4.11	45.51
RO concentrate	S3	1200	4	slack	0.08	4.57	58.2	37.04	5.51	8.6
RO concentrate	S3	1200	4	neap	0.28	4.57	122.1	36.76	4.31	19.75
RO concentrate	S3	1200	4	spring	0.55	4.57	161.6	36.69	3.58	39.24
Saturated cavern brine	S1	300	1	slack	0.08	4.57	14.3	51.4	2.65	3.35
Saturated cavern brine	S1	300	1	neap	0.28	4.57	28.7	43.95	2.36	3.58
Saturated cavern brine	S1	300	1	spring	0.55	4.57	44.3	41.32	2.11	5.95
Saturated cavern brine	S2	700	2	slack	0.08	5.33	16.5	49.48	3.03	3.95
Saturated cavern brine	S2	700	2	neap	0.28	5.33	32.8	43.0	2.69	4.21
Saturated cavern brine	S2	700	2	spring	0.55	5.33	50.1	40.76	2.39	6.89
Saturated cavern brine	S3	1200	4	slack	0.08	4.57	14.3	51.4	2.65	3.35
Saturated cavern brine	S3	1200	4	neap	0.28	4.57	28.7	43.95	2.36	3.58
Saturated cavern brine	S3	1200	4	spring	0.55	4.57	44.3	41.32	2.11	5.95

Near-field behaviour - RO concentrate | 300 m3/hr, 1 port = 300 m3/hr/port - identical to S3 (same flow per port)




Figure. Near-field trajectory, dilution and salinity - RO concentrate, 300 m³/hr (300 m³/hr per port).




Figure. Near-field trajectory, dilution and salinity - RO concentrate, 700 m³/hr (350 m³/hr per port).




Figure. Near-field trajectory, dilution and salinity - RO concentrate, 1200 m³/hr (300 m³/hr per port).




Figure. Near-field trajectory, dilution and salinity - Saturated cavern brine, 300 m³/hr (300 m³/hr per port).




Figure. Near-field trajectory, dilution and salinity - Saturated cavern brine, 700 m³/hr (350 m³/hr per port).




Figure. Near-field trajectory, dilution and salinity - Saturated cavern brine, 1200 m³/hr (300 m³/hr per port).




Figure. Seabed initial dilution by flow scenario and tidal state.

5 Medium-Field Dispersion

The medium-field dispersion was simulated with the sigma-layer transport engine driven by the calibrated tidal currents, including a layer-resolution sensitivity test and the near-field-coupled brine source. Maximum-salinity envelopes, tidal-phase snapshots with current vectors, and vertical profiles through the diffuser are presented. Every medium-field run in this section uses the SATURATED CAVERN BRINE source at full flow - the phase-2 worst case, not the RO concentrate of the base case. The medium-field seabed salinities are therefore not comparable with the far-field values of section 6, which are computed for RO concentrate unless a figure states otherwise.

Layer-resolution sensitivity (maximum seabed salinity, psu): 4-layer = 44.3, 9-layer = 44.3, 14-layer = 44.7. The 9-layer scheme was adopted for the production runs. The peak is grid-converged in the vertical.

The peak is not the whole story, and the area is the metric that matters. The seabed area above the 38.5 psu threshold is 4-layer = 1.191 km², 9-layer = 0.484 km², 14-layer = 0.323 km². That is a factor of 3.7 between the coarsest and the finest scheme, against under 1% variation in the peak - so the AREA is roughly two orders of magnitude more sensitive to layer count than the peak is, not less. It is not converged in the vertical, and it decreases as the vertical resolution improves, which means the adopted 9-layer scheme over-predicts the exceedance area relative to the 14-layer solution. The conclusion that phase 2 breaches the mixing zone is nevertheless robust to this: the 38.5 psu radius is 4-layer = 1280 m, 9-layer = 1213 m, 14-layer = 813 m, so every vertical resolution tested puts it far outside the 100 m allowance. The magnitude of the exceedance is resolution-dependent; its existence is not.

Phase-2 mixing-zone compliance: the threshold IS exceeded. The 38.5 psu seabed threshold is a regulatory limit, and the mixing-zone radius reported for the base case in section 6 is 0 m. That figure is computed on the RO concentrate, whose seabed increment never approaches the threshold. It is not a statement about the phase-2 source. Evaluated on the saturated-cavern envelope modelled in this section, the same metric gives a radius of at least 1213 m on the spring-neap envelope, with at least 0.484 km² of seabed above 38.5 psu. The cavern brine lands on the bed at 41-51 psu in the near field (section 4), so this outcome is consistent with the near-field solution rather than a surprise from it.

That medium-field figure is a lower bound, and the reason matters. The transport model holds every domain edge at the ambient background salinity, and this plume reaches to within 3 cells of the 2.5 km assessment-domain edge - so the boundary is clipping the contour rather than the physics closing it. Re-run on the 7.2 km regional domain, which is the same site with nearly three times the room, the same metric gives 3530 m and 2.498 km² - and reaches that domain's edge as well (1 cell of margin). Neither domain contains this plume. The honest statement is therefore a floor rather than a range: the 38.5 psu contour extends AT LEAST 3530 m from the diffuser, at least 35 times the 100 m mixing zone, and where it finally closes is not resolved by this study. What is not in doubt is the breach: the tightest bound available already exceeds the mixing zone by 12 times, so no plausible refinement of the extent makes phase 2 compliant. Bounding it properly needs a purpose-sized domain (section 10), and that should be done before any phase-2 design is fixed - not to decide compliance, which is already decided, but to size the impact.

Consequence. The phase-1 RO discharge, which is the discharge the plant is being built for, complies comfortably: the threshold is not exceeded anywhere and the mixing-zone radius is 0 m. The phase-2 saturated cavern brine, discharged through the same diffuser, does not comply and cannot be permitted on this design as modelled. The flow sensitivity below shows that it cannot be operated into compliance either. Accommodating it would require a fundamentally higher-dilution discharge - a much higher exit velocity through smaller or more numerous ports, or pre-dilution of the cavern stream with seawater - and that redesign is outside the scope of this study. The statement that the diffuser accommodates the future cavern stream 'without redesign' applies to near-field dilution and water quality, not to mixing-zone compliance.

Table. Phase-2 saturated cavern brine at full flow: extent of the 38.5 psu seabed exceedance against the 100 m regulatory mixing zone.

tide	peak_seabed_salinity_psu	mixing_zone_radius_m	area_above_threshold_km2	edge_margin_cells	domain_limited	regulatory_radius_m	compliant
neap	44.27	1213.0	0.4844	3	Yes (lower bound)	100.0	No
spring	42.48	738.0	0.2575	21	No	100.0	No
spring-neap envelope	44.27	1213.0	0.4844	3	Yes (lower bound)	100.0	No
regional mode	43.97	3530.0	2.4984	1	Yes (lower bound)	100.0	No

l (60 m, 7.2 km domain)							
-------------------------	--	--	--	--	--	--	--

Can the cavern stream simply be throttled? No, and the reason matters. Reducing the discharge is the obvious mitigation, so it was tested across flows from 1200 down to 75 m³/hr and across port counts. Every case exceeds the threshold, and the low-flow cases are WORSE, not better: cutting the per-port flow from 300 to 75 m³/hr raises the peak seabed salinity from 43.95 to 52.42 psu. Near-field dilution is driven by the exit momentum of the jet, so a lower per-port flow means a lower exit velocity, a lower Froude number and less entrainment. Throttling attacks the wrong variable.

The binding constraint is dilution, not load, and it can be stated in one line. To land a 250 psu source on the seabed below the 38.5 psu threshold requires a near-field dilution of at least $(250 - 36.5) / (38.5 - 36.5)$ = about 107:1. The diffuser achieves 14-50:1 for the cavern brine at every flow and tidal state assessed - short by a factor of two to seven. For comparison the RO concentrate needs only about 16:1 and receives 58-186:1, which is why phase 1 passes with so much room. No operating point of this diffuser closes that gap: phase 2 needs a fundamentally higher-dilution discharge (much higher exit velocity through smaller or more numerous ports, or pre-dilution of the cavern stream with seawater), or it needs a different outfall.

Table. Phase-2 cavern brine: seabed compliance against discharge flow and port count. No flow complies, and lower per-port flows are worse.

case	flow_m 3hr	n_ports	per_port_ m3hr	peak_seabed_salinity_psu	mixing_zone_radius_m	area_above_threshold_km2	domain_limited	compliant
S3 (full flow)	1200	4	300.0	44.27	1213.0	0.4844	Yes (lower bound)	No
S2	700	2	350.0	43.85	489.0	0.1469	No	No
S1	300	1	300.0	43.95	363.0	0.0813	No	No
half S1	150	1	150.0	48.76	340.0	0.07	No	No
quarter S1	75	1	75.0	52.42	438.0	0.11	No	No
S1 flow, 4 ports	300	4	75.0	52.42	1241.0	0.5194	Yes (lower bound)	No




Figure. Terrain-following sigma layers versus water depth (9-layer scheme). Layers are numbered from the seabed upward, so L1 is the thin bed cell that resolves the dense bottom plume and L9 is the thick surface cell.

Maximum seabed salinity - 4-layer model (full flow, neap, saturated cavern brine)




Figure. Maximum seabed salinity - 4-layer model (full flow, neap, saturated cavern brine)

Maximum seabed salinity - 9-layer model (full flow, neap, saturated cavern brine)




Figure. Maximum seabed salinity - 9-layer model (full flow, neap, saturated cavern brine)

Maximum seabed salinity - 14-layer model (full flow, neap, saturated cavern brine)




Figure. Maximum seabed salinity - 14-layer model (full flow, neap, saturated cavern brine)

Maximum salinity vs height above the seabed - neap, full flow, saturated cavern brine (dense plume is bottom-trapped and decays upward)




Figure. Maximum salinity vs height above the seabed - neap, full flow, saturated cavern brine (dense plume is bottom-trapped and decays upward)




Figure. Seabed salinity & current vectors at high water - neap (saturated cavern brine)




Figure. Seabed salinity & current vectors at mid ebb - neap (saturated cavern brine)




Figure. Seabed salinity & current vectors at low water - neap (saturated cavern brine)




Figure. Seabed salinity & current vectors at mid flood - neap (saturated cavern brine)

Vertical salinity profile at high water - neap (saturated cavern brine)




Figure. Vertical salinity profile at high water - neap (saturated cavern brine)

Vertical salinity profile at mid ebb - neap (saturated cavern brine)




Figure. Vertical salinity profile at mid ebb - neap (saturated cavern brine)

Vertical salinity profile at low water - neap (saturated cavern brine)




Figure. Vertical salinity profile at low water - neap (saturated cavern brine)

Vertical salinity profile at mid flood - neap (saturated cavern brine)




Figure. Vertical salinity profile at mid flood - neap (saturated cavern brine)




Figure. Vertical salinity profiles at the diffuser column - all tidal phases (neap, saturated cavern brine)




Figure. Seabed salinity & current vectors at high water - spring (saturated cavern brine)




Figure. Seabed salinity & current vectors at mid ebb - spring (saturated cavern brine)




Figure. Seabed salinity & current vectors at low water - spring (saturated cavern brine)




Figure. Seabed salinity & current vectors at mid flood - spring (saturated cavern brine)

Maximum seabed salinity over a full spring-neap cycle (full flow, saturated cavern brine)




Figure. Maximum seabed salinity over a full spring-neap cycle (full flow, saturated cavern brine)





Figure. Phase-2 cavern brine: peak seabed salinity and 38.5 psu mixing-zone radius against discharge flow and port count. Every case exceeds the threshold, and reducing the per-port flow makes the peak worse because near-field dilution is driven by exit momentum. The constraint is dilution, not load: a 250 psu source needs ~107:1 to reach 38.5 psu and the diffuser delivers 14-50:1.



Both domains hold their edge at ambient salinity, and this plume reaches both edges - so every hatched bar is a floor, not a measurement. The contour reaches AT LEAST the largest of them. Where it actually stops is not bounded by this study; the breach is not in doubt.

Figure. Phase-2 saturated cavern brine at full flow: the 38.5 psu seabed threshold is exceeded to at least 1213 m from the diffuser on the 25 m assessment domain and to at least 3530 m on the 7.2 km regional domain - at least 35 times the 100 m regulatory mixing zone. Both domains hold their boundary at ambient salinity and this plume reaches both, so both figures are lower bounds and the true extent is larger than either. The RO concentrate of phase 1 does not exceed the threshold anywhere.

6 Far-Field Dispersion




Figure. Far-field maximum seabed salinity by discharge scenario - neap tide (RO brine)

Far-field maximum seabed salinity - spring, full flow (RO brine)




Figure. Far-field maximum seabed salinity - spring, full flow (RO brine)

Far-field maximum seabed salinity - spring-neap envelope (full flow, RO brine)




Figure. Far-field maximum seabed salinity - spring-neap envelope (full flow, RO brine)

Far-field maximum seabed salinity - phase-2 saturated cavern brine (worst case)




Figure. Far-field maximum seabed salinity - phase-2 saturated cavern brine (worst case)

Which grid the metrics come from, and why it matters. The influence areas, diffusion distances and mixing-zone radius below are resolved on the 25 m assessment grid, not on the 60 m regional grid. The reason is a detection limit: one regional cell covers 0.0036 km², so the smallest footprint in the table (S1, 0.0056 km²) spans only about 1.6 regional cells - far too few to form a contour. Averaging the plume over cells that coarse drags the increment peak down from 0.87 psu to 0.37 psu, below the lowest 0.5 psu contour, so every area on the regional grid collapses to exactly 0.000 km². Those zeros are the resolution of the grid, not a property of the plume. On the 25 m grid the 0.5 psu contour resolves cleanly and the areas are 0.0056-0.0544 km². Both are reported: the assessment grid gives the footprint, and the regional column shows what the coarser grid sees.

The 1.0 and 1.5 psu influence areas are 0.000 km² for a different and genuine reason: the seabed increment peaks at 0.87 psu on the assessment grid and so never reaches either contour. Those zeros are physical. The mixing-zone radius is 0 m on both grids, and that result is robust - the 38.5 psu threshold requires an increment of 2.0 psu, against a resolved peak of 0.87 psu.

Table. Salinity-increment influence areas, diffusion distances and mixing-zone radius per scenario, resolved on the 25 m assessment grid. The final column is the peak on the 60 m regional grid, which cannot resolve the footprint; see the note above.

scenario	flow_m3hr	area_0p5_psu_km2	area_1p0_psu_km2	area_1p5_psu_km2	diff_dist_parallel_m	diff_dist_transverse_m	mixing_zone_radius_m	max_seabed_salinity_psu	regional_max_seabed_salinity_psu
S1	300	0.0056	0.0	0.0	79.0	56.0	0.0	37.11	36.78
S2	700	0.0244	0.0	0.0	200.0	150.0	0.0	37.37	36.84
S3	1200	0.0544	0.0	0.0	334.0	200.0	0.0	37.33	36.87

7 Diffuser Design Optimisation and Layout

The effect of diffuser port discharge angle on near-field dilution was assessed, and a recommended layout selected. Cross-shore salinity and current-speed transects and the marine-constraints overlay support the siting decision.




Figure. Diffuser port-angle optimisation: seabed dilution vs port discharge angle. The right-hand axis re-labels the same curve as seabed salinity, which is a fixed function of dilution, not an independent measurement.




Figure. Maximum seabed salinity along a transect through the diffuser (neap, full flow, saturated cavern brine).




Figure. Maximum current speed along the outfall corridor (spring tide).




Figure. Distribution of marine development and environmental constraints relative to the mixing zone.




Figure. Recommended optimised diffuser/intake layout (inclined 4-port diffuser).

8 Outfall Siting and Intake Recirculation

Following the desalination-siting methodology, the salinity rise at the plant intake was assessed as a function of outfall distance from shore under steady northward, southward and weak-southward currents, for both discharges. The criterion is a salinity rise at the intake of no more than 0.1 ppt above ambient, applied to the peak cell in the intake window. The weak southward current is the critical (least-flushing) condition.

The two brines behave very differently, and the distinction matters. The intake signal scales with the excess salinity the plume delivers to the bed: the RO concentrate lands at 37.04 psu, an excess of 0.54 psu over the 36.5 psu background, whereas the saturated cavern brine lands at 51.40 psu, an excess of 14.90 psu - about 28 times larger.

Table. Rise in salinity at intake above ambient - southward current 0.25 m/s, both brines.

brine	outfall_dist_m	rise_min_ppt	rise_max_ppt	rise_avg_ppt	recirc_risk
RO concentrate	600	0.002	0.044	0.016	No
RO concentrate	800	0.0	0.006	0.002	No

RO concentrate	1000	0.0	0.001	0.0	No
RO concentrate	1200	0.0	0.0	0.0	No
RO concentrate	1400	0.0	0.0	0.0	No
Saturated cavern brine	600	0.032	0.664	0.237	Yes
Saturated cavern brine	800	0.004	0.102	0.031	Yes
Saturated cavern brine	1000	0.001	0.017	0.005	No
Saturated cavern brine	1200	0.0	0.003	0.001	No
Saturated cavern brine	1400	0.0	0.001	0.0	No

Table. Rise in salinity at intake above ambient - weak southward current 0.05 m/s, both brines.

brine	outfall_dist_m	rise_min_ppt	rise_max_ppt	rise_avg_ppt	recirc_risk
RO concentrate	600	0.022	0.096	0.052	No
RO concentrate	800	0.009	0.033	0.019	No
RO concentrate	1000	0.004	0.015	0.008	No
RO concentrate	1200	0.002	0.007	0.004	No
RO concentrate	1400	0.001	0.004	0.002	No
Saturated cavern brine	600	0.515	2.233	1.207	Yes
Saturated cavern brine	800	0.209	0.759	0.437	Yes
Saturated cavern brine	1000	0.1	0.342	0.198	Yes
Saturated cavern brine	1200	0.053	0.173	0.101	Yes
Saturated cavern brine	1400	0.029	0.092	0.054	No

Table. Rise in salinity at intake above ambient - northward current 0.25 m/s, both brines.

brine	outfall_dist_m	rise_min_ppt	rise_max_ppt	rise_avg_ppt	recirc_risk
RO concentrate	600	0.001	0.036	0.009	No
RO concentrate	800	0.0	0.004	0.001	No
RO concentrate	1000	0.0	0.001	0.0	No
RO concentrate	1200	0.0	0.0	0.0	No
RO concentrate	1400	0.0	0.0	0.0	No
Saturated cavern brine	600	0.016	0.559	0.147	Yes
Saturated cavern brine	800	0.002	0.062	0.018	No
Saturated cavern brine	1000	0.0	0.009	0.003	No
Saturated cavern brine	1200	0.0	0.002	0.0	No
Saturated cavern brine	1400	0.0	0.0	0.0	No

Result. For the RO concentrate the criterion is met at every distance tested: the worst cell over all currents and distances is 0.096 ppt, at the closest 600 m siting under the weak southward current. The 850 m siting modelled in this study therefore clears the criterion, as does every distance from 600 to 1400 m. For the phase-2 saturated cavern brine the criterion is NOT met at any distance below 1400 m (worst case 2.233 ppt at the closest siting under the weak southward current). It is first met at 1400 m offshore (0.092 ppt).

Consequence for the design. The 850 m outfall modelled in this study satisfies the recirculation criterion for the phase-1 RO discharge, which is the discharge the plant is being built for; so does every distance tested, so recirculation does not constrain the phase-1 siting. It does not satisfy it for the phase-2 cavern brine. If the cavern stream is committed, the outfall must be moved to at least 1400 m, or the recirculation criterion re-examined against the intermittency of that stream. This is a screening result on a 50 m grid under a steady current and is adequate to rank distances and to test the threshold; it is not a basis for fixing a siting distance to the nearest 200 m without a tidally-resolved run.




Figure. Variation of the maximum salinity rise at the intake with outfall distance from shore, for the RO concentrate and the phase-2 saturated cavern brine (log scale; 0.1 ppt recirculation criterion). Values of zero are plotted at the axis floor.

Contours of salinity rise - outfall 600 m from shore (weak southward, RO brine)




Figure. Salinity-rise contours, outfall 600 m from shore, weak southward current (RO concentrate).

Contours of salinity rise - outfall 1200 m from shore (weak southward, RO brine)




Figure. Salinity-rise contours, outfall 1200 m from shore, weak southward current (RO concentrate).

Time history of salinity rise - outfall 600 m from shore (weak current, RO brine)




Figure. Time history of salinity rise at intake and outfall, outfall 600 m from shore (weak southward current, RO concentrate).




Figure. Time history of salinity rise at intake and outfall, outfall 1200 m from shore (weak southward current, RO concentrate).

9 Other Impurities and Water-Quality Compliance

Table. Trace-impurity concentrations vs Environmental Quality Standards after dilution.

parameter	brine_ugL	seawater_ugL	eqs_ugL	dilution	predicted_ugL	margin_x	compliant
Arsenic	3.2	0.9	25.0	14.3	1.061	23.6	Yes
Boron	3450.0	4300.0	7000.0	14.3	4240.559	1.7	Yes
Cadmium	0.3	0.04	2.5	14.3	0.058	43.0	Yes
Chromium	1.1	0.8	15.0	14.3	0.821	18.3	Yes
Copper	1.8	1.1	5.0	14.3	1.149	4.4	Yes
Lead	2.0	0.1	25.0	14.3	0.233	107.4	Yes
Mercury	0.02	0.015	0.3	14.3	0.015	19.5	Yes
Nickel	2.9	0.3	30.0	14.3	0.482	62.3	Yes
Zinc	4.0	1.2	40.0	14.3	1.396	28.7	Yes




Figure. Predicted receiving-water trace-impurity concentrations vs EQS thresholds.

10 Validation and Data Sources

UBDS was tested against the following independent benchmarks. Where the model and the reference quantity are defined differently, the model value is converted before comparison and the conversion is stated; agreement is reported as measured, including where the model falls outside the published band.

- Equation of state: maximum error 0.402% vs reference seawater/brine densities (UNESCO EOS-80; CRC Handbook). Within tolerance.
- Momentum jet: volume-flux dilution slope 0.228 per z/D and spread 0.114 vs canonical 0.25-0.32 and ~ 0.11 (Fischer, List, Koh, Imberger & Brooks, 1979). The spread is reproduced; the dilution slope sits about 9% below the lower end of the canonical range, i.e. the model entrains slightly less than the canonical round jet.
- Pure plume: volume-flux exponent 1.596 vs the $5/3 = 1.667$ power law (Morton, Taylor & Turner, 1956); about 4% below the analytical exponent.
- Inclined 60 deg dense jet (Papakonstantis, Christodoulou & Papanicolaou, 2011), benchmarked over Fr 9.0-33.3 (7 cases), the span the case study runs at: $x_r/(D.Fr) = 2.522$ (mean) vs the published 2.2-3.3 band - in band in 7/7 cases. Return-point dilution, converted from the model's bulk (top-hat) value to the centreline minimum that the published band refers to (divide by 1.694, Gaussian profile, $\lambda = 1.2$): $S_r(\min)/Fr = 0.581$ vs the published 0.4-0.6 band - in band in 6/7 cases. The uncorrected bulk value is 0.985 and is not directly comparable.
- Terminal rise of the same dense jet: $z_t/(D.Fr) = 1.49$ (mean) against the published 1.6-2.2 band - about 7% BELOW the lower bound, and inside the band in only 1 of the 7 cases. The shortfall is not uniform: it grows as the Froude number falls, so it is worst at the Fr 9-11 of the saturated-cavern brine, which is the case that governs the seabed assessment. UBDS therefore under-predicts the terminal rise height of an inclined dense jet. Because a lower rise gives a shorter

trajectory and less entrainment before the plume returns to the bed, this bias is conservative for seabed salinity - it over-states, not under-states, the salinity reaching the bed. It is not corrected by tuning, since raising the rise height would require reducing entrainment and would degrade the jet-dilution and return-point dilution agreement above.

- Domain sufficiency for phase 2 (a stated limitation, not a validated result). The transport model holds each domain edge at the background salinity. The phase-1 RO plume decays hundreds of metres inside the domain, so that boundary never touches it and every phase-1 number in this report is domain-independent. The phase-2 cavern plume is not: it reaches to within 3 cells of the 2.5 km assessment-domain edge (1213 m radius, 0.484 km²) AND to within 1 cell of the 7.2 km regional-domain edge (3530 m, 2.498 km²). Neither domain contains it, so both sets of figures are lower bounds and the phase-2 extent is NOT bounded above by this study. It is reported as a floor - at least 3530 m, at least 35 times the mixing zone - and a purpose-sized domain, fine enough to resolve the plume over its whole footprint, is required to size the impact. That study would refine the number; it cannot rescue compliance, since even the tightest bound exceeds the mixing zone by 12 times.




Figure. Momentum-jet dilution: UBDS vs the canonical self-similar law (Fischer et al. 1979).




Figure. Pure-plume dilution: UBDS vs the 5/3 power law (Morton, Taylor & Turner 1956).




Figure. Inclined 60 deg dense-jet dimensionless rise and dilution vs published experimental bands.

Table. Equation-of-state validation.

salinity_psu	temp_C	ref_density	model_density	error_pct	source
0.0	25.0	997.05	997.05	-0.0	Pure water (CRC)
35.0	15.0	1025.97	1025.97	0.0	EOS-80 (Millero & Poisson 1981)
35.0	25.0	1023.34	1023.34	0.0	EOS-80
38.0	20.0	1026.95	1027.05	0.01	EOS-80
260.0	20.0	1200.0	1204.82	0.402	Saturated NaCl brine (CRC Handbook)

Table. Inclined dense-jet dimensionless validation.

Fr	zt_over_DFr	xr_over_DFr	Sr_bulk_over_Fr	Sr_min_over_Fr	termination
9.0	1.349	2.375	0.955	0.564	seabed
11.0	1.41	2.416	0.963	0.568	seabed
12.8	1.441	2.449	0.967	0.57	seabed
17.9	1.5	2.538	0.981	0.579	seabed
23.0	1.546	2.597	0.999	0.59	seabed
28.2	1.579	2.627	1.008	0.595	seabed
33.3	1.602	2.651	1.019	0.601	seabed

10.1 Data sources

- Fischer, H.B., List, E.J., Koh, R.C.Y., Imberger, J. & Brooks, N.H. (1979). Mixing in Inland and Coastal Waters. Academic Press. [jet/plume dilution laws]
- Morton, B.R., Taylor, G.I. & Turner, J.S. (1956). Turbulent gravitational convection from maintained and instantaneous sources. Proc. R. Soc. Lond. A 234, 1-23. [plume 5/3 law]
- Papakonstantis, I.G., Christodoulou, G.C. & Papanicolaou, P.N. (2011). Inclined negatively buoyant jets 1 & 2. J. Hydraulic Research 49(1), 3-22. [inclined dense-jet data]
- Roberts, P.J.W., Ferrier, A. & Daviero, G. (1997). Mixing in inclined dense jets. J. Hydraulic Engineering 123(8), 693-699. [dense-jet dilution]
- Millero, F.J. & Poisson, A. (1981). International one-atmosphere equation of state of seawater. Deep-Sea Research 28A, 625-629; UNESCO (1981) Tech. Papers Mar. Sci. 36. [EOS-80]
- Jirka, G.H. (2004). Integral model for turbulent buoyant jets in unbounded stratified flows. Part 1. Environmental Fluid Mechanics 4, 1-56. [integral jet model]
- Lee, J.H.W. & Chu, V.H. (2003). Turbulent Jets and Plumes - A Lagrangian Approach. Kluwer. [entrainment closure]
- CRC Handbook of Chemistry and Physics. [saturated NaCl brine density]
- Synthetic site-specific data (bathymetry, tides, ADCP currents, CTD salinity/temperature, brine chemistry) generated by the author for this case study; all values are documented and engineering-credible, and none are taken from any real consent.

10.2 Supporting data plots

Derived plots summarising the tabulated results above: seabed dilution against tidal velocity, salinity-increment area against discharge flow, and the per-station index-of-agreement against the synthetic current reference.




Figure. Seabed dilution as a function of tidal velocity for each brine type and scenario. S1 and S3 coincide because dilution is set by the per-port flow (300 m3/hr in both), not the total.




Figure. Left: the 0.5 psu influence area by discharge scenario, resolved on the 25 m assessment grid, against the 60 m regional grid's 0.0036 km2 detection floor - the S1 footprint is smaller than one regional cell, which is why that grid reports 0.000 km2. Right: the peak seabed increment reaches 0.87 psu on the assessment grid but only 0.37 psu once averaged onto the regional grid; it never reaches the 1.0 or 1.5 psu contour, so those areas are genuinely zero.




Figure. Index-of-agreement between the model and the synthetic current reference by station (spring). The reference is derived from the model solution, so this is not a field comparison.

11 Conclusions

The UBDS solver provides a single, open, physically-validated framework spanning the near-, medium- and far-field dispersion of brine and other buoyant effluents. Applied to the Bahia Azul case study with fully documented, credible site-specific inputs, it demonstrates that the proposed inclined 4-port diffuser achieves effective initial dilution and, FOR THE PHASE-1 RO CONCENTRATE, confines significant salinity increments and all trace impurities to within the regulatory mixing zone across all simulated discharge flows and tidal states. The phase-1 discharge is the discharge the plant is being built for, and it complies on every metric assessed.

The phase-2 saturated cavern brine does not. Two independent regulatory criteria fail for it, and they must not be read as caveats to a passing result:

(1) Mixing zone. Discharged at full flow through the same diffuser, the 250 psu cavern source exceeds the 38.5 psu seabed threshold to at least 1213 m from the diffuser on the 2.5 km assessment domain and to at least 3530 m on the 7.2 km regional domain - at least 35 times the 100 m regulatory mixing zone (section 5). Both figures are lower bounds, because the plume reaches the edge of both domains and the model holds those edges at background salinity; the true extent is larger than either. The 0 m mixing-zone radius reported for the base case is an RO-concentrate result and does not apply to this source.

(2) Intake recirculation. The 850 m outfall meets the 0.1 ppt criterion for the phase-1 RO concentrate at every distance screened (worst cell 0.096 ppt), but no siting inside 1400 m meets it for the cavern brine (section 8).

Recommendation. Proceed with the inclined 4-port 60 degree diffuser for the phase-1 RO discharge. Do NOT commit the phase-2 saturated-cavern stream to this diffuser: as modelled it breaches the mixing zone by an order of magnitude and fails the recirculation criterion, and neither can be operated away. Throttling the cavern flow was tested and makes the seabed salinity worse, because near-field dilution is set by exit momentum and a lower per-port flow entrains less. The constraint is dilution: a 250 psu source needs about 107:1 near-field dilution to reach the 38.5 psu threshold, and this diffuser delivers 14-50:1 at every operating point assessed. Accommodating phase 2 therefore requires a fundamentally higher-dilution discharge - much higher exit velocity through smaller or more numerous ports, or pre-dilution of the cavern stream with seawater - together with an outfall at least 1400 m offshore for recirculation. That redesign is outside the scope of this study and should be assessed on its own terms.

12 Animated Outputs

The following animated outputs (GIF files in outputs/animations/) show the time-evolving brine dispersion and tidal current field over a tidal cycle. A static filmstrip of the dispersion animation is embedded below; the full animations are in outputs/animations/.

- ANIM_brine_dispersion_spring.gif - Brine dispersion over a tidal cycle (full flow, spring, saturated cavern brine)
- ANIM_brine_dispersion_neap.gif - Brine dispersion over a tidal cycle (full flow, neap, saturated cavern brine)
- ANIM_current_field_spring.gif - Tidal current field over a cycle (spring)




Figure. Brine dispersion over a tidal cycle (full flow, spring, saturated cavern brine) (filmstrip of the animation).

Appendix A Representative Output Figures from the Reference Studies

For methodological comparison, representative output figures from the three reference studies that guided this work are reproduced below (author's reference materials, attributed). They illustrate the output categories - mesh/bathymetry, current calibration, near-field trajectories/dilution, salinity envelopes and snapshots, and intake/outfall time histories - that the UBDS outputs reproduce for the Bahia Azul case.




Figure 1-1 – Mesh and Bathymetry of the Islandmagee Medium Field Tidal Model

3 INITIAL DILUTION MODELLING

The initial dilution study examines the dispersion of the brine discharged from the outfall diffuser jets in the immediate area around the diffuser. For this study the initial dilution achieved by the brine discharge from the proposed outfall was modelled using the US EPA "Plumes" software utilising the UM3 routine. The Visual Plumes programme simulates the flow of the outlet jets under the influence of density, temperature and velocity. The programme is primarily a near-field model and a mid- and far-field model is therefore also required to simulate the plume dispersion over the wider area.

UM3 is an acronym for the three-dimensional Updated Merge (UM) model. UM3 simulates single and multi-port submerged discharges. UM3 is a Lagrangian model that assumes that the plume is in a steady state. However, ambient and discharge conditions can change as long as they do so over time scales which are long compared to the time in which a discharged element reaches the end of the initial dilution phase. To make UM three-dimensional, the model includes an entrainment term corresponding to the third-dimension i.e. a cross-current term. As a result, single-port plumes are simulated as truly three-dimensional entities. Merged plumes are simulated by distributing the cross-current entrainment over all plumes. Dilution from diffusers oriented parallel to the current is estimated by limiting the effective spacing to correspond to a cross-diffuser flow angle of 20 degrees.

3.1 Initial Dilution Model Results

The initial dilution modelling was undertaken using a diffuser with either 1 or 2 ports depending on the flow range as stated in Section 2.2. The diffuser ports were at 20m centres with the port exits discharging vertically upwards at approximately 0.75m above the seabed. Following discharge it is expected that the brine will sink down towards the seabed due to the density of the brine solution, with the initial trajectory depending on the tidal velocity. Consequently the UM3 model was run for a variety of spring and neap flow conditions to simulate the initial dilution achieved at various stages of the tidal cycle.

3.1.1 Scenario 1: 250m³/hr via a Single Port

This scenario represents the early stages of project development when the leaching of the caverns is just commencing and the full flow of leaching water is not required. For this stage of the process it was assumed that one port on the diffuser would be blanked off and hence the 250m³/h would be discharged via one diffuser port.

The trajectories for the discharge from a 6" Tideflex port across the range of tidal velocities are presented in Figure 3-1. The trajectory in red relates to low tidal velocity of <0.1m/s which would be experienced during the turning tide, the trajectory in blue relates to tidal velocity of 0.3 m/s which would represent peak velocities during neap tide. The trajectory in green relates to a typical spring tidal velocity of 0.6 m/s.

Table 4-1: Table showing Water Column division into Layers within the Models in terms of % of overall water depth assigned to each layer.

	14 Layer	9 Layer	4 Layer
Layer 14	40	-	-
Layer 13	20	-	-
Layer 12	11	-	-
Layer 11	8.5	-	-
Layer 10	6.5	-	-
Layer 9	4.5	40	-
Layer 8	3	25	-
Layer 7	2	15	-
Layer 6	1.5	9.3	-
Layer 5	1	4.5	-
Layer 4	0.8	2.5	35
Layer 3	0.6	1.5	35
Layer 2	0.5	1.2	15
Bottom Layer 1	0.1	1	15




Figure 4-1: Variation of sigma layers with water depth (9 layers)

For the sensitivity testing the 1,000m³/hr scenario was selected as this represents the maximum input of salt and hence density effects will be more prevalent than with lower salt inputs. The results of the sensitivity testing in terms of maximum seabed salinity levels are presented in Figure 4-2 to Figure 4-4 for the 4 layer, 9 layer and 14 layer models respectively. It should be noted in all figures presented the colour contour bands are not linear with smaller intervals at the lower salinity values in order to fully illustrate the range




Figure 4-8: Maximum Salinity at Bed – Neap Tide

Figure 5-4 respectively. In all figures presented the colour contour bands are not linear with smaller intervals used at the lower salinity and the 36 psu threshold is shown in yellow.

The salinity increases predicted beyond the initial mixing zone in all cases are relatively small; the contour intervals plotted representing very small increases of 0.25-0.50 psu. A maximum far field increase in salinity of less than 4 psu i.e. total salinity <38 psu, was recorded throughout all the simulations which is commensurate with the levels predicted for the concept design considered at planning stage.

The baseline salinity data obtained from AFB1 and NIEA at the initial project development stage indicated that background salinities in this part of the North Channel off Islandmagee can range between circa 30.5 psu and 34.8 psu. Even with an assumed background salinity of 34.2 any salinity increase in excess of the range normally experienced in seasonal variations (34.8 psu) is expected to be restricted to an area less than 300 metres from the outfall.




Figure 5-2: Maximum Seabed Salinity during a Neap Tidal Cycle – 250m³/hour Discharge




Figure 2. Grid distribution in the computational domain, and color-shaded bathymetry. A, B, C, and D are control points for open water boundaries. T1 is a tidal level monitoring point.




Figure 3. Local grid refinement in the engineered area, and locations of verification points. C1 and C2 are current monitoring points.

Figure. Reference Study 2 (Laoshan Bay desalination): computational mesh and bathymetry of the bay.




Figure 4. Comparison of the simulated and measured values of the tidal level at the Qingdao Port (a) and Station T1 (b).

The tidal flow field simulation results were verified by continuous 25 h measured current data and model calculation results from two stations in Laoshan Bay in April 2018. The positions of the tidal flow verification points are shown in Figure 3, and the tidal flow verification curves of the two stations are shown in Figures 5 and 6, respectively.




Figure 5. Comparison between the simulated and measured values of the flow velocity and direction at Station C1.




Figure 6. Comparison between the simulated and measured values of the flow velocity and direction at Station C2.

The calculated results of the model were found to be in good agreement with the measured tidal level data and ocean current data, properly reflecting the tidal level and ocean current characteristics in Laoshan Bay and its surrounding waters and meeting the simulation accuracy requirements of the hydrodynamic model and advection-diffusion model in this paper.

4. Results and Discussion

4.1. Simulation Results of Tidal Flow Field in Laoshan Bay

The simulation results of the tidal flow field in Laoshan Bay calculated using the model are shown in Figure 7. During the flood tide, the flow velocity in Laoshan Bay is generally 30–55 cm/s, and outside the bay the flow velocity is 60–70 cm/s. The flood current flows from NE to SW from the eastern sea area of Tianheng Town, then turns to NW after passing the headland and flows into Aoshan Bay on the north side. The flow velocity of the flood current in Aoshan Bay is typically 10–42 cm/s, and the flow velocity on the shore is relatively small, generally less than 10 cm/s. Near Nvdiao Island, the flow velocity of the flood current is relatively high, between 54 cm/s and 78 cm/s. The flood current in the area where the project is located flows from NNW to SSE, with a velocity between

10 cm/s and 36 cm/s. After passing the project area, the flood current along the coast passes around the Aoshantou headland and then turns west to Xiaodao Bay. The flow velocity in the Aoshantou sea area is relatively high, with a maximum of 72 cm/s. The flood current in the Xiaodao Bay generally flows from NE to SW at a velocity of 10–42 cm/s, while the velocity near the shore is low, generally less than 10 cm/s. Then the tidal current flows from N to S along the shore to the outside of the bay, and the velocity increases accordingly.




Figure 7. Hydrodynamic flow field simulation results.

During the ebb tide, the velocity in Laoshan Bay is generally 25–50 cm/s, and the velocity outside the bay is 55–65 cm/s. The northern ebb current flows from NW to SE, bypasses Nvdao Island, then turns to the NE and flows to the sea on the east side of Tianheng Town. The flow velocity in Aoshan Bay is 10–48 cm/s, and the velocity on the shore is low, generally less than 10 cm/s. The ebb tide velocity on the south side of Nvdao Island is relatively high, between 54 cm/s and 72 cm/s. Along the south side of the sea, the ebb tide flows from S to N outside the bay, and then from SW to NE inside Xiaodao Bay, and the flow velocity decreases accordingly. The flow velocity of the ebb tide in Xiaodao Bay is 10–36 cm/s, and the flow velocity on the shore is relatively low, generally less than 10 cm/s. After bypassing Aoshantou Headland, the ebb tidal current passes through the sea area of the project area, flowing from SSE to NNW at a flow velocity of 10–30 cm/s. The sea area south of Aoshantou has a high flow velocity of up to 68 cm/s.

The calculation results of the tidal flow field and the conclusions of historical research results are consistent [22,23], and the numerical simulation results properly reflect the distribution law of the tidal flow field in Laoshan Bay.

4.2. Simulation Results of Salinity Field after Brine Discharge

The diffusion process of brine in Laoshan Bay is mainly affected by tidal currents. The calculated results of salinity field distribution of brine discharged by different water intake-outlet schemes of seawater desalination projects are shown in Figure 8. It can be seen that the impact of the brine discharge under different schemes on the increase of salinity in the nearby sea area is less than 0.6 units in most sea areas, although the impact of the increase of salinity in a small area near the discharge outlet is more than 2.3 units. With the continuous discharge of brine, the salinity of the sea area near the discharge outlet obviously increases. However, due to the water exchange between Aoshan Bay and the

where A = horizontal eddy viscosity.

MIKE21-AD/Transport module is based on the following non-linear vertically integrated 2-D equations of conservation of salinity which takes into account advection, dispersion, source and sink.

$$\frac{\partial h\bar{s}}{\partial t} + \frac{\partial h\bar{u}\bar{s}}{\partial x} + \frac{\partial h\bar{v}\bar{s}}{\partial y} = hF_s + h\bar{s}_s S \quad (6)$$

where, $\bar{s}$ = Depth average salinity, F_s = the horizontal diffusion term defined by

$$F_s = \left[\frac{\partial}{\partial x} \left(D_h \frac{\partial \bar{s}}{\partial x} \right) + \frac{\partial}{\partial y} \left(D_h \frac{\partial \bar{s}}{\partial y} \right) \right] \quad (7)$$

and D_h = horizontal diffusion coefficient.

In the 2D transport equations, the low order approximation uses simple first order upwinding, i.e., element average values in the upwinding direction are used as values at the boundaries. The higher order version approximates gradients to obtain second order accurate values at the boundaries. Values in the upwinding direction are used. To provide stability and minimize oscillatory effects, a TVD-MUSCL limiter is applied [5].

4. MODEL SIMULATION

4.1. Model Region

The region considered for the model is about 9 km X 12 km covering about 6 km on the either side of the proposed port and extending up to about -30 m contour as shown in Fig. 1. The western side of the model region consists the shoreline while the remaining sides are open to sea. The region is discretised by 11947 triangular elements and 6241 nodes (Fig.2). It is observed in the open sea at the site that the flow is unidirectional (either northerly or southerly). Hence to get the northerly flow, a tidal variation at southern boundary and velocities at northern boundary were considered. To get southern flow, the boundary conditions are reversed. At the seaward boundary, no flow was assumed.

4.2. Model Calibration

Before using the model for predictive purpose, it is calibrated. The Fig. 3A and 3B show calibration of the hydrodynamic model, particularly the observed and computed variation of




Figure 1 Bathymetry in the model region




Figure 2 Flexible computational mesh

4.4. Model Operation

The ambient temperature of sea water is assumed to be 27°C. Ambient salinity of sea water is assumed to be 32 ppt. The rise in salinity of brine water to be discharged at the outfall is given to be 31 ppt above ambient.

For the salinity model, as the open boundaries have been taken sufficiently away from the outfall locations, zero rise in salinity is assumed at the open boundaries. It is observed that in the open sea at the site, the flow is unidirectional, either northerly or southerly generally parallel to the coastline. During the period February-September the flow is northward, while during the period October-January the flow is southward. The model is operated for different current conditions namely northward 0.25 m/s, southward 0.25 m/s and weak current i.e. 0.05 m/s towards. The direction of the weak current is considered to be northward or southward depending on the locations of intake and outfall to simulate the critical condition.

4.5. Model Operating Cases

The following cases of the intake and outfall were considered for the numerical model simulations.

Intake and outfall locations on south of south breakwater of L & T port as shown in Fig.1 are considered. Intake is taken at 550 m from shore. The outfall distance from shore is varied from 1000 m to 1300 m. Discharge of 1.25 m³/s (100 MLD) is considered at outfall while inflow at intake is taken twice that of outfall.. The following alternatives of outfall locations are considered.

1. With outfall at 1000 m from shore
2. With outfall at 1100 m from shore
3. With outfall at 1200 m from shore
4. With outfall at 1300 m from shore

4.6. Results and Discussion

The model is operated under northward, southward and weak current conditions in each of the above cases of outfall location. Typical results, namely, contour plots and time histories of rise in salinity are shown in Figs. 4A, 4B, 5A and 5B. The salinity rise at the intake is nearly zero in case of average northward current of 0.25 for all the outfall lengths. The salinity rise obtained at the intake for different outfall lengths and for the remaining two current conditions (namely, southward and weak current) are tabulated in Table 1A and 1B. It is seen that for the average northward current of 0.25 m/s the rise in salinity above ambient at the intake is well below 0.1 ppt. The salinity rise results from the tables are also plotted in the Fig. 6. From the tables and the Fig. 6 it is seen that it is also less than 0.1 ppt for average southward current of 0.25 m/s for the outfall distance greater than 1000 m and it is more than 0.1 ppt for outfall distance less than about 975 m.

Appendix B Complete Output Inventory

All figures and datasets generated by the UBDS solver for this case study:

B.1 Figures

- 01. [Near-field initial dilution] A_nearfield_RO_S1.png - Near-field trajectory, dilution and salinity - RO concentrate, 300 m³/hr (300 m³/hr per port).
- 02. [Near-field initial dilution] A_nearfield_RO_S2.png - Near-field trajectory, dilution and salinity - RO concentrate, 700 m³/hr (350 m³/hr per port).
- 03. [Near-field initial dilution] A_nearfield_RO_S3.png - Near-field trajectory, dilution and salinity - RO concentrate, 1200 m³/hr (300 m³/hr per port).
- 04. [Near-field initial dilution] A_nearfield_Sa_S1.png - Near-field trajectory, dilution and salinity - Saturated cavern brine, 300 m³/hr (300 m³/hr per port).
- 05. [Near-field initial dilution] A_nearfield_Sa_S2.png - Near-field trajectory, dilution and salinity - Saturated cavern brine, 700 m³/hr (350 m³/hr per port).
- 06. [Near-field initial dilution] A_nearfield_Sa_S3.png - Near-field trajectory, dilution and salinity - Saturated cavern brine, 1200 m³/hr (300 m³/hr per port).
- 07. [Near-field initial dilution] A_scenario_comparison.png - Seabed initial dilution by flow scenario and tidal state.
- 08. [Diffuser design optimisation] A2_angle_opt.png - Diffuser port-angle optimisation: seabed dilution vs port discharge angle. The right-hand axis re-labels the same curve as seabed salinity, which is a fixed function of dilution, not an independent measurement.
- 09. [Hydrodynamics, mesh & calibration] B_mesh_medium.png - Medium-field mesh & bathymetry (Bahia Azul)
- 10. [Hydrodynamics, mesh & calibration] B_mesh_far.png - Far-field (regional) domain & bathymetry
- 11. [Hydrodynamics, mesh & calibration] B_stations.png - Diffuser location & ADCP current-meter stations
- 12. [Hydrodynamics, mesh & calibration] B_adcp_A0.png - Modelled current speed & direction at station A0 (neap & spring), against a synthetic ADCP reference generated from the model solution with a 3 percent bias and random noise. Not an independent measurement.
- 13. [Hydrodynamics, mesh & calibration] B_adcp_A1.png - Modelled current speed & direction at station A1 (neap & spring), against a synthetic ADCP reference generated from the model solution with a 3 percent bias and random noise. Not an independent measurement.
- 14. [Hydrodynamics, mesh & calibration] B_adcp_A2.png - Modelled current speed & direction at station A2 (neap & spring), against a synthetic ADCP reference generated from the model solution with a 3 percent bias and random noise. Not an independent measurement.
- 15. [Hydrodynamics, mesh & calibration] B_adcp_A3.png - Modelled current speed & direction at station A3 (neap & spring), against a synthetic ADCP reference generated from the model solution with a 3 percent bias and random noise. Not an independent measurement.
- 16. [Hydrodynamics, mesh & calibration] B_adcp_A4.png - Modelled current speed & direction at station A4 (neap & spring), against a synthetic ADCP reference generated from the model solution with a 3 percent bias and random noise. Not an independent measurement.

- 17. [Hydrodynamics, mesh & calibration] B_tidal_level.png - Modelled tidal level (spring tide) against a synthetic reference series derived from the model solution with an imposed bias and noise. Not an independent measurement.
- 18. [Hydrodynamics, mesh & calibration] B_flowfield_flood.png - Depth-averaged tidal flow field at flood (spring tide).
- 19. [Hydrodynamics, mesh & calibration] B_flowfield_ebb.png - Depth-averaged tidal flow field at ebb (spring tide).
- 20. [Medium-field dispersion] C_sigma_layers.png - Terrain-following sigma layers versus water depth (9-layer scheme). Layers are numbered from the seabed upward, so L1 is the thin bed cell that resolves the dense bottom plume and L9 is the thick surface cell.
- 21. [Medium-field dispersion] C_layersens_4.png - Maximum seabed salinity - 4-layer model (full flow, neap, saturated cavern brine)
- 22. [Medium-field dispersion] C_layersens_9.png - Maximum seabed salinity - 9-layer model (full flow, neap, saturated cavern brine)
- 23. [Medium-field dispersion] C_layersens_14.png - Maximum seabed salinity - 14-layer model (full flow, neap, saturated cavern brine)
- 24. [Medium-field dispersion] C_env_heights_panel.png - Maximum salinity vs height above the seabed - neap, full flow, saturated cavern brine (dense plume is bottom-trapped and decays upward)
- 25. [Medium-field dispersion] C_snap_neap_high_water.png - Seabed salinity & current vectors at high water - neap (saturated cavern brine)
- 26. [Medium-field dispersion] C_snap_neap_mid_ebb.png - Seabed salinity & current vectors at mid ebb - neap (saturated cavern brine)
- 27. [Medium-field dispersion] C_snap_neap_low_water.png - Seabed salinity & current vectors at low water - neap (saturated cavern brine)
- 28. [Medium-field dispersion] C_snap_neap_mid_flood.png - Seabed salinity & current vectors at mid flood - neap (saturated cavern brine)
- 29. [Medium-field dispersion] C_vprof_neap_high_water.png - Vertical salinity profile at high water - neap (saturated cavern brine)
- 30. [Medium-field dispersion] C_vprof_neap_mid_ebb.png - Vertical salinity profile at mid ebb - neap (saturated cavern brine)
- 31. [Medium-field dispersion] C_vprof_neap_low_water.png - Vertical salinity profile at low water - neap (saturated cavern brine)
- 32. [Medium-field dispersion] C_vprof_neap_mid_flood.png - Vertical salinity profile at mid flood - neap (saturated cavern brine)
- 33. [Medium-field dispersion] C_vprof_neap.png - Vertical salinity profiles at the diffuser column - all tidal phases (neap, saturated cavern brine)
- 34. [Medium-field dispersion] C_snap_spring_high_water.png - Seabed salinity & current vectors at high water - spring (saturated cavern brine)
- 35. [Medium-field dispersion] C_snap_spring_mid_ebb.png - Seabed salinity & current vectors at mid ebb - spring (saturated cavern brine)
- 36. [Medium-field dispersion] C_snap_spring_low_water.png - Seabed salinity & current vectors at low water - spring (saturated cavern brine)

- 37. [Medium-field dispersion] C_snap_spring_mid_flood.png - Seabed salinity & current vectors at mid flood - spring (saturated cavern brine)
- 38. [Medium-field dispersion] C_env_springneap.png - Maximum seabed salinity over a full spring-neap cycle (full flow, saturated cavern brine)
- 39. [Medium-field dispersion] C_phase2_flow_sensitivity.png - Phase-2 cavern brine: peak seabed salinity and 38.5 psu mixing-zone radius against discharge flow and port count. Every case exceeds the threshold, and reducing the per-port flow makes the peak worse because near-field dilution is driven by exit momentum. The constraint is dilution, not load: a 250 psu source needs ~107:1 to reach 38.5 psu and the diffuser delivers 14-50:1.
- 40. [Medium-field dispersion] C_phase2_mixing_zone.png - Phase-2 saturated cavern brine at full flow: the 38.5 psu seabed threshold is exceeded to at least 1213 m from the diffuser on the 25 m assessment domain and to at least 3530 m on the 7.2 km regional domain - at least 35 times the 100 m regulatory mixing zone. Both domains hold their boundary at ambient salinity and this plume reaches both, so both figures are lower bounds and the true extent is larger than either. The RO concentrate of phase 1 does not exceed the threshold anywhere.
- 41. [Far-field dispersion] D_far_neap_scenarios.png - Far-field maximum seabed salinity by discharge scenario - neap tide (RO brine)
- 42. [Far-field dispersion] D_far_spring_S3.png - Far-field maximum seabed salinity - spring, full flow (RO brine)
- 43. [Far-field dispersion] D_far_springneap.png - Far-field maximum seabed salinity - spring-neap envelope (full flow, RO brine)
- 44. [Far-field dispersion] D_far_cavern.png - Far-field maximum seabed salinity - phase-2 saturated cavern brine (worst case)
- 45. [Design comparison & optimisation] E_salinity_transect.png - Maximum seabed salinity along a transect through the diffuser (neap, full flow, saturated cavern brine).
- 46. [Design comparison & optimisation] E_current_curve.png - Maximum current speed along the outfall corridor (spring tide).
- 47. [Design comparison & optimisation] E_constraints.png - Distribution of marine development and environmental constraints relative to the mixing zone.
- 48. [Design comparison & optimisation] E_optimised_layout.png - Recommended optimised diffuser/intake layout (inclined 4-port diffuser).
- 49. [Outfall siting & recirculation] H_intake_rise_curve.png - Variation of the maximum salinity rise at the intake with outfall distance from shore, for the RO concentrate and the phase-2 saturated cavern brine (log scale; 0.1 ppt recirculation criterion). Values of zero are plotted at the axis floor.
- 50. [Outfall siting & recirculation] H_rise_contour_near.png - Salinity-rise contours, outfall 600 m from shore, weak southward current (RO concentrate).
- 51. [Outfall siting & recirculation] H_rise_contour_far.png - Salinity-rise contours, outfall 1200 m from shore, weak southward current (RO concentrate).
- 52. [Outfall siting & recirculation] H_timehist_near.png - Time history of salinity rise at intake and outfall, outfall 600 m from shore (weak southward current, RO concentrate).
- 53. [Outfall siting & recirculation] H_timehist_far.png - Time history of salinity rise at intake and outfall, outfall 1200 m from shore (weak southward current, RO concentrate).

- 54. [Inputs, parameters & water quality] F_impurities.png - Predicted receiving-water trace-impurity concentrations vs EQS thresholds.
- 55. [Data plots] G_dilution_vs_velocity.png - Seabed dilution as a function of tidal velocity for each brine type and scenario. S1 and S3 coincide because dilution is set by the per-port flow (300 m³/hr in both), not the total.
- 56. [Data plots] G_area_vs_flow.png - Left: the 0.5 psu influence area by discharge scenario, resolved on the 25 m assessment grid, against the 60 m regional grid's 0.0036 km² detection floor - the S1 footprint is smaller than one regional cell, which is why that grid reports 0.000 km². Right: the peak seabed increment reaches 0.87 psu on the assessment grid but only 0.37 psu once averaged onto the regional grid; it never reaches the 1.0 or 1.5 psu contour, so those areas are genuinely zero.
- 57. [Data plots] G_skill.png - Index-of-agreement between the model and the synthetic current reference by station (spring). The reference is derived from the model solution, so this is not a field comparison.
- 58. [Validation] V_jet.png - Momentum-jet dilution: UBDS vs the canonical self-similar law (Fischer et al. 1979).
- 59. [Validation] V_plume.png - Pure-plume dilution: UBDS vs the 5/3 power law (Morton, Taylor & Turner 1956).
- 60. [Validation] V_dense_jet.png - Inclined 60 deg dense-jet dimensionless rise and dilution vs published experimental bands.
- 61. [Animations] ANIM_brine_dispersion_filmstrip.png - Brine dispersion over a tidal cycle (full flow, spring, saturated cavern brine) (filmstrip of the animation).
- 62. [Reference output figures (source studies)] appendix_b_fig_p8.png - Reference Study 1 (salt-cavern brine outfall): model mesh, bathymetry and current-meter comparison.
- 63. [Reference output figures (source studies)] appendix_b_fig_p25.png - Reference Study 1: near-field brine-plume trajectory and initial-dilution prediction.
- 64. [Reference output figures (source studies)] appendix_b_fig_p33.png - Reference Study 1: sigma-layer scheme and layer-resolution sensitivity.
- 65. [Reference output figures (source studies)] appendix_b_fig_p39.png - Reference Study 1: maximum seabed-salinity envelope and salinity/current snapshots.
- 66. [Reference output figures (source studies)] appendix_b_fig_p55.png - Reference Study 1: far-field maximum seabed-salinity envelopes.
- 67. [Reference output figures (source studies)] water_15_02402_fig_p4.png - Reference Study 2 (Laoshan Bay desalination): computational mesh and bathymetry of the bay.
- 68. [Reference output figures (source studies)] water_15_02402_fig_p6.png - Reference Study 2: tidal flow-field simulation results.
- 69. [Reference output figures (source studies)] water_15_02402_fig_p7.png - Reference Study 2: salinity-field results and salinity profile for the layout plans.
- 70. [Reference output figures (source studies)] ijciat_fig_p4.png - Reference Study 3 (Chennai desalination): bathymetry and flexible computational mesh.
- 71. [Reference output figures (source studies)] ijciat_fig_p5.png - Reference Study 3: hydrodynamic calibration (observed vs computed tidal level and current).

- 72. [Reference output figures (source studies)] ijciет_fig_p7.png - Reference Study 3: contours of salinity rise and time history at intake/outfall.

B.2 Animations

- 01. ANIM_brine_dispersion_spring.gif - Brine dispersion over a tidal cycle (full flow, spring, saturated cavern brine)
- 02. ANIM_brine_dispersion_neap.gif - Brine dispersion over a tidal cycle (full flow, neap, saturated cavern brine)
- 03. ANIM_current_field_spring.gif - Tidal current field over a cycle (spring)

B.3 Datasets (CSV)

- 01. A_nearfield_initial_dilution.csv - Near-field initial-dilution results (bulk top-hat dilution and salinity at first seabed contact) for all brine types, flow scenarios and tidal states.
- 02. A2_port_angle_optimisation.csv - Effect of diffuser port discharge angle on near-field dilution (300 m³/hr, neap).
- 03. B_current_validation_skill.csv - Skill of the model against the synthetic ADCP reference series (RMSE, Willmott index, Nash-Sutcliffe). The reference is the model solution plus an imposed bias and noise, so these scores measure that perturbation, not agreement with field data.
- 04. B_tidal_level.csv - Tidal-level validation time series.
- 05. C_vertical_profiles.csv - Vertical salinity profile at the diffuser column for each neap tidal phase (the data behind the mean-and-spread figure).
- 06. C_phase2_mixing_zone.csv - Phase-2 saturated cavern brine at full flow: extent of the 38.5 psu threshold exceedance on the seabed, against the 100 m regulatory mixing zone. The transport model holds the domain edge at ambient salinity, so where the contour approaches that edge (edge_margin_cells) the radius and area are lower bounds set by the domain. The 2.5 km assessment domain truncates this plume; the 7.2 km regional domain does not.
- 07. C_phase2_flow_sensitivity.csv - Phase-2 cavern brine: seabed compliance vs discharge flow and port count. No flow complies; reducing the per-port flow lowers the exit momentum and therefore the near-field dilution, so the peak seabed salinity rises. Landing a 250 psu source below 38.5 psu requires a near-field dilution of about 107:1; the diffuser achieves 14-50:1.
- 08. D_influence_area_diffusion.csv - Influence areas of salinity increments, diffusion distances and mixing-zone radius per flow scenario, resolved on the 25 m assessment grid. The final column is the peak on the coarser 60 m regional grid, whose cell (0.0036 km²) is too large to resolve the footprint.
- 09. E_salinity_transect.csv - Seabed salinity transect data.
- 10. H_intake_recirculation.csv - Salinity rise above ambient at the intake vs outfall distance from shore, by brine and current condition (0.1 ppt recirculation criterion, applied to the peak cell).
- 11. H_table1A_southward.csv - Rise in salinity at intake above ambient - southward 0.25 m/s, both brines.
- 12. H_table1B_weak.csv - Rise in salinity at intake above ambient - weak southward 0.05 m/s, both brines.
- 13. H_table1C_northward.csv - Rise in salinity at intake above ambient - northward 0.25 m/s, both brines.

- 14. H_timehist_near.csv - Time-history data, outfall 600 m from shore (RO concentrate).
- 15. H_timehist_far.csv - Time-history data, outfall 1200 m from shore (RO concentrate).
- 16. F_layer_scheme.csv - Sigma-layer schemes: percentage of water-column depth per layer, indexed from the seabed (L1 is the bed cell in every scheme; each scheme's surface cell is its last numbered entry - L14, L9 and L4 respectively). A dash means the scheme has no such layer. The bed cell is 0.1% of depth with 14 layers, 1.0% with 9 and 15% with 4.
- 17. F_model_parameters.csv - Hydrodynamic and transport model parameters.
- 18. F_impurities_eqs.csv - Trace-impurity concentrations in the brine vs EQS after near-field dilution.
- 19. V_eos_validation.csv - Equation-of-state validation against reference seawater/brine densities.
- 20. V_jet.csv - Round-jet dilution validation data.
- 21. V_dense_jet.csv - Inclined (60 deg) dense-jet dimensionless geometry/dilution vs published ranges. S_r is reported both as the model's bulk (top-hat) dilution and converted to the centreline minimum dilution, which is what the published band refers to.