

Coupled Slug & Hydrate Prediction in a Deepwater Crude-Oil Subsea Tie-back

A comprehensive flow-assurance case study with the SHCT transient solver — case definition, model equations, inputs, all generated outputs, validation and calibration

Author: Akosa Samuel Onyejekwe

Solver: SHCT — Slug–Hydrate Coupled-Transient multiphase flow-assurance solver (transient, compositional, probabilistic).

Scope: this single document consolidates EVERYTHING produced for the study — the engineering background and problem, the well-defined case study, every governing equation and closure used to build the solver, the numerical method, the contribution to knowledge, a like-for-like comparison with existing commercial and academic solvers, the complete input-data deck, and every generated output (all metrics, CSV tables, per-column graphs of every CSV, and the full chart/curve/contour/map gallery) for the three engineering scenarios, plus the published-data validation and the calibration, with all sources recorded. Nothing is left out.

Figure/chart style: no black and no dark colours are used in any figure, curve, contour or map; all backgrounds are white and all ink is a medium, legible hue.

Executive summary

A 32 km, 10.75-inch deepwater subsea tie-back carrying a ~30° API medium crude oil with 35 % water cut over a cold (4 °C), strongly undulating seabed and a steel catenary riser is analysed for the two flow-assurance threats that dominate such systems and that physically reinforce one another: hydrodynamic / terrain / severe-riser SLUGGING and gas-HYDRATE formation. The SHCT solver runs the full transient, compositional, probabilistic prediction end-to-end for three scenarios.

- **As-operated (degraded insulation, no inhibitor): the line is BOTH slug- and hydrate-critical — sustained coupling number $\Phi_{SH} = 1.06$ at 10.3 km, plug probability 100%, P50 time-to-plug 3.7 h, peak wall deposit 117 mm, max subcooling 24.4 °C.**
- Inhibitor demand the model predicts to clear that risk: MEG ≈ 60 wt% (114877 L/h); under-inhibited length 26.5 km.
- Unplanned shut-in: essentially no safe window — no-touch time ≈ 0.00 h.
- **Engineered fix (restored insulation $U_{eff} = 2.38$ W/m²K + continuous MEG): the subcooling is removed, the plug probability falls to 33% and 13 h of no-touch time is restored — the model used as a design tool.**
- Numerics are mass-consistent and stable: liquid mass error 3.63e-15, gas 6.99e-17, 0 solver fallbacks.

Scope and standing of these numbers. Read the results below with three limitations in view. (1) The field is a representative industrial archetype built from literature-typical values, not proprietary operator data. (2) The criticality threshold is DERIVED, not assumed: deposition and slug scouring compete continuously, Φ_{SH} drives no term in the solver, and the balance $d(\delta)/dt = 0$ gives $\delta_{eq} = \Phi_{SH} \cdot \delta_{ref}$ with $\delta_{ref} = f_{wall} \cdot D / (4 \cdot C \cdot k_{ero})$, so runaway begins where that equilibrium passes the consolidation restriction, at $\Phi_{crit} = 2 \cdot C \cdot k_{ero} \cdot r_{consol} / f_{wall} = 1.08$. That it falls within 8 % of unity is a result of the kinetics rather than a definition. It has still not been MEASURED, so it remains a proposed criterion rather than a validated one — but it is now falsifiable in two independent ways (§ limitations). (3) The kinetic and coupling constants C , n and k_{g0} , and the slug-frequency floor $f_{slug,0}$, are literature-typical defaults or numerical guards fitted to no dataset, so the absolute magnitudes reported here — the Φ_{SH} field, the time-to-plug and the required MEG dose in particular — are model outputs, not calibrated predictions. Section 8.3 reports how far each of them moves when those FOUR constants are swept across their plausible ranges. Note in particular that a RUNNING MAXIMUM of Φ_{SH} over the window is attained during flow startup, while the slug frequency is still at its floor, and is therefore set by that floor rather than by the operating state; the SUSTAINED (time-median) value quoted above is what describes the line as run. What the study demonstrates is the coupled mechanism and the design workflow; what it does not yet demonstrate is quantitative accuracy against a specific line.

1. Background to the case study

Deepwater subsea tie-backs transport unprocessed well fluids — oil, produced water and associated gas — over tens of kilometres of cold seabed (typically 4 °C) before reaching a host facility. Two production-chemistry / multiphase-flow threats dominate the integrity of such lines:

1.1 Hydrodynamic, terrain and severe-riser slugging

In multiphase pipe flow the gas and liquid self-organise into intermittent SLUGS — long liquid plugs separated by gas pockets. On a long, near-horizontal, undulating seabed the low spots accumulate liquid and shed it as terrain slugs; at the riser base, liquid fallback and gas blow-through produce large, low-frequency SEVERE slugs. Slugs impose cyclic structural loads, flood the topside slug-catcher, and force unstable operation.

1.2 Gas-hydrate formation

Natural-gas components (methane, ethane, propane...) combine with free water at high pressure and low temperature to form ICE-LIKE crystalline hydrates. In a cold deepwater line the operating point sits well inside the hydrate-stability region; with a 35 % water cut there is ample free water. Hydrates can deposit on the cold wall, consolidate and grow a PLUG that blocks the line — the single most feared flow-assurance failure, slow and dangerous to remediate.

1.3 Why the two threats must be solved together

Slugging and hydrates are not independent. The same cold, gassy, water-wet, intermittent flow that drives slugging also drives hydrates; and the two interact at the wall: slug passage scours and re-warms the wall (suppressing deposition), while between slugs the cold wall lets hydrate deposit and consolidate. Whether a line plugs or stays open is therefore set by a COMPETITION between hydrate-formation rate and slug-renewal rate. A medium-crude tie-back of this geometry and fluid is the textbook case in which BOTH threats are simultaneously active, which is exactly why it is chosen here.

2. Problem statement and how the problem is solved

2.1 Problem statement

Existing tools predict slugging OR hydrates well, but treat them as separate analyses run in different software, with the slug-hydrate WALL interaction left to engineering judgement. There is no single, transient, probabilistic predictor that resolves the competition between hydrate growth and slug scouring along the whole route and in time, and returns an actionable, quantified, UNCERTAINTY-aware plugging risk together with the slug loads, the inhibitor demand and the mitigation design.

The engineering question for THIS asset: given the geometry, fluid and operating conditions, (a) where and when does the line slug and how big are the slugs; (b) where and when does it enter the hydrate region and form a consolidating wall deposit; (c) what is the probabilistic time-to-plug; (d) how much inhibitor (and what insulation) removes the risk; and (e) how long is the no-touch time after a shut-in?

2.2 How the problem is solved — the SHCT approach

SHCT integrates, in time, a coupled system of conservation PDEs for multiphase flow, heat transfer and hydrate formation on the ACTUAL terrain, closed by published flow-assurance correlations and a compositional Peng–Robinson PVT engine, and run as a Monte-Carlo ensemble for genuine probabilistic output. The slug–hydrate interaction is made explicit through a single dimensionless coupling number Φ_{SH} — the ratio of the wall hydrate-formation tendency to the slug-renewal rate — mapped in space and time. The full set of governing equations and closures is given in Section 4; the numerical method in Section 5.

- Resolve flow regime, holdup, slug frequency and slug length along the route (hydraulics).
- Track P, T and the hydrate-equilibrium temperature $T_{eq} \rightarrow$ local subcooling ΔT_{sub} .
- Form hydrate by stochastic nucleation + growth in the bulk (slurry) and on the wall (deposit).
- Combine the two through $\Phi_{SH}(x,t)$, the equilibrium deposit thickness in units of $\delta_{ref} = f_{wall} \cdot D / (4 \cdot C \cdot k_{ero})$; above the derived $\Phi_{crit} = 1.08$ that equilibrium exceeds the consolidation restriction, the deposit locks and growth runs away.
- Repeat over a Monte-Carlo ensemble $\rightarrow$ P10/P50/P90 time-to-plug and design margins.
- Invert for the required MEG dose and the insulation that removes the risk (design mode).

3. The case study — clearly defined


A representative deepwater West-Africa-style medium-crude-oil tie-back. The geometry, fluid and operating values are realistic, self-consistent values typical of such developments in the open literature; they are NOT proprietary operator data. The PHYSICS and PREDICTIONS are produced by the real solver, and the hydrate thermodynamics and the hydraulic closures are validated against published data (Sections 7–8).

3.1 Asset and geometry

- Route length: 32 km step-out flowline + steel catenary riser (SCR).
- Internal diameter: 0.2545 m (~10.75-inch carbon-steel flowline).
- Water depth at the riser base: ~1100 m; cold seabed at 4 °C.
- Terrain: long, strongly undulating seabed (multiple low spots $\rightarrow$ terrain slugging) climbing into a steep SCR ($\rightarrow$ severe-riser slugging).

3.2 Fluid — a medium crude oil ($\approx 30^\circ$ API black oil)

Moderate-GOR live crude with a substantial heavy C7+ tail; the associated gas (C1 ≈ 43 mol%) liberates along the cold line and, with the long near-horizontal step-out, drives slugging, while the 35 % water cut plus water-wet gas in the cold wall drives hydrates.



Feed composition — medium-crude makeup (mole fraction per component) that feeds the Peng–Robinson flash.

component	mol_fraction
N2	0.0040
CO2	0.0200
C1	0.4300
C2	0.0750
C3	0.0580
iC4	0.0120
nC4	0.0280
iC5	0.0130
nC5	0.0160
C6	0.0300
C7+	0.3140

3.3 The three engineering scenarios

- (A) As-operated normal production — degraded / water-flooded wet insulation (behaves close to bare steel, $U \approx 22 \text{ W/m}^2\text{K}$), NO inhibitor: the high-risk prediction.
- (B) Unplanned shut-in — the line cools toward the seabed; the no-touch (cooldown) time before hydrate onset is measured from the transient.
- (C) Engineered mitigation — restored multi-layer insulation (steel + syntactic foam + coating → low U_{eff}) plus continuous MEG: the model used as a DESIGN tool.

4. Model equations used to build the solver

The SHCT solver integrates, in time, a system of coupled partial-differential equations for multiphase flow, heat transfer and hydrate formation on arbitrary terrain, closed by published flow-assurance correlations and a compositional Peng–Robinson PVT engine. Every equation actually used to build the solver is listed below, grouped by role, with its symbolic form, a one-line description and its source. Symbols: α_l/α_g liquid/gas holdup, A flow area, $v_l/v_g/u_m$ phase & mixture velocities, j mixture (superficial) velocity, p pressure, T temperature, T_{eq} hydrate-equilibrium temperature, ΔT_{sub} subcooling, ϕ bulk hydrate fraction, δ wall-deposit thickness, f_{slug} slug frequency, a_i interfacial area, θ inclination, ρ density, μ viscosity, U_{eff} effective heat-transfer coefficient.

A. Governing transient conservation PDEs (finite-volume, CFL-adaptive)

Liquid-holdup transport (drift-flux kinematic wave)

$$\partial(\alpha_l \cdot A)/\partial t + \partial(\alpha_l \cdot v_l \cdot A)/\partial x = - S_l$$

Volume-conservative liquid continuity, discretised by a conservative finite-volume scheme with signed upwinding (optionally 2nd-order TVD). S_l is the liquid (water) volume sink to hydrate formation. Holdup is recovered as $\alpha_l = (\alpha_l \cdot A)/A$ each step.

Source / basis: Conservative FV; Bendiksen drift-flux closure.

Gas-mass continuity (conservative, mass-consistent)

$$\partial(\rho_g \cdot \alpha_g \cdot A)/\partial t + \partial(\rho_g \cdot V_{sg} \cdot A)/\partial x = - \dot{m}_{(gas \rightarrow hydrate)}$$

Solved alongside the liquid so liquid AND gas mass balance to ~0%. The mass-consistent superficial gas velocity $V_{sg} = (\rho_{g,in} \cdot q_{g,in})/(\rho_g \cdot A)$ makes the mass flux $\rho_g \cdot V_{sg} \cdot A$ equal to the inlet gas mass rate along the line.

Source / basis: Conservative FV gas continuity.

Mixture momentum → implicit pressure (default engine)

$$u_m = U_o - C_u \cdot \partial p / \partial x ; \quad R(p^{n+1} - p^n) + \partial / \partial x [U_o - C_u \cdot \partial p^{n+1} / \partial x] = 0$$

Transient mixture momentum with the pressure gradient and wall drag treated implicitly; eliminating velocity gives a tridiagonal (Poisson-type) pressure equation solved each step (Thomas algorithm). Predictor $u^* = u_m - dt \cdot (\text{advection} + g \cdot \sin \theta)$; wall-drag rate $\beta = f/(2D) \cdot |u_m|$; $U_o = u^*/(1 + dt \cdot \beta)$; compressible storage $R = \alpha_g/(p \cdot dt)$. Inlet pressure Dirichlet (pinned in-system), outlet through-flux (rate control).

Source / basis: Implicit-pressure mixture-momentum; drift-flux slip closure.

Full two-fluid momentum (alternative engine)

**two independent phase momenta + interfacial drag, shared pressure;
slip emerges from balance**

RELAP/TRACE-style semi-implicit: advection+gravity explicit; pressure gradient, wall drag and stiff interfacial drag implicit. A 2×2 per-cell velocity system → tridiagonal pressure; an interfacial-pressure correction keeps the characteristics real (well-posed).

Source / basis: Two-fluid model with interfacial-pressure regularisation.

Energy transport (advection + seabed loss + latent + Joule–Thomson)

$$\partial T / \partial t + j \cdot \partial T / \partial x = - U_{eff} \cdot (4/D) \cdot (T - T_{sink}) / (\rho_m \cdot c_p) + q_{latent} + q_{JT}$$

Signed-upwind (optionally TVD) advection; the stiff wall-loss term is implicit (backward Euler), with a Heun 2nd-order corrector on advection. $\beta_{\text{loss}} = U_{\text{eff}} \cdot 4 / (D \cdot \rho_m \cdot c_p)$. $q_{\text{latent}} = L_{\text{hyd}} \cdot \rho_{\text{hyd}} \cdot R_{g,\text{bulk}} / (\rho_m \cdot c_p)$ (exothermic bulk hydrate, self-limiting); $q_{\text{JT}} = \mu_{\text{JT}} \cdot (1 - \alpha_l) \cdot j \cdot (\partial p / \partial x)$ (real-gas cooling on expansion).

Source / basis: Transient energy balance; implicit wall loss; Strang/Heun split.

Hydrate phase-field (advected reaction–diffusion, stochastic)

$$\partial \phi / \partial t + v_1 \cdot \partial \phi / \partial x = D_\phi \cdot \partial^2 \phi / \partial x^2 + R_{\text{grow}} + R_{\text{nuc}} + \xi$$

Advected reaction–diffusion field for the bulk hydrate fraction ϕ , carrying its D_ϕ diffusion term and a stochastic nucleation source ξ (Monte-Carlo ensemble).

Source / basis: Phase-field hydrate model with stochastic nucleation.

B. Hydrate thermodynamics, kinetics and the slug–hydrate coupling

Hydrate equilibrium temperature (natural-gas correlation)

$$T_{\text{eq}} = 7.7 \cdot \ln(P) - 23.2 + 18 \cdot (SG - 0.60) - 0.74 \cdot S_{\text{wt}} \quad [^\circ\text{C}, P \text{ in bar}]$$

Base natural-gas hydrate curve ($\approx 3^\circ\text{C}$ @30 bar, 10°C @70 bar, 13°C @100 bar, 18°C @200 bar), shifted for gas specific gravity SG and depressed by produced-water salinity S_{wt} (wt% NaCl-eq). An optional measured/PVT [P, T_{eq}] table overrides it (monotonic interpolation).

Source / basis: Natural-gas hydrate equilibrium (GPSA/Sloan-anchored).

Subcooling (bulk and wall driving forces)

$$\Delta T_{\text{sub}} = T_{\text{eq}} - T ; \quad \Delta T_{\text{sub,wall}} = T_{\text{eq}} - T_{\text{front}}$$

ΔT_{sub} is the local thermodynamic hydrate driving force. The deposition-relevant WALL subcooling uses the deposit-front temperature T_{front} (see deposit-insulation feedback).

Source / basis: Definition.

Stochastic nucleation (induction time, Monte-Carlo)

$$\tau_{\text{ind}} = \tau_0 \cdot 3600 \cdot \exp(\min(\beta / \Delta T_{\text{sub}}, \text{cap})) ; \quad p_{\text{nuc}} = 1 - \exp(-dt / \tau_{\text{ind}})$$

Classical induction-time nucleation: a cell nucleates when a uniform random draw $< p_{\text{nuc}}$ and $\Delta T_{\text{sub}} > \Delta T_{\text{sub,min}}$. Growth proceeds only after onset, so subcooling builds during induction $\rightarrow$ a genuine onset spread across the ensemble (P10/P50/P90).

Source / basis: Classical stochastic nucleation.

Growth-rate constant (Arrhenius)

$$k_g = k_{g0} \cdot \exp(-(E_a/R) \cdot (1/T - 1/T_{\text{ref}}))$$

Temperature dependence of the intrinsic hydrate growth-rate constant.

Source / basis: Arrhenius / CSMHyK-type kinetics.

Bulk slurry growth (CSMHyK-type, self-limiting)

$$R_{g,\text{bulk}} = k_g \cdot a_i \cdot \Delta T_{\text{sub}}^n \cdot (1 - \phi / \phi_{\text{max}}) \cdot 1_{\text{nucleated}}$$

Bulk hydrate formation driven by the local bulk subcooling; its exothermic latent heat warms the fluid, so it self-limits (ϕ stays low $\rightarrow$ transportable slurry). a_i is the interfacial area.

Source / basis: CSMHyK-type growth law.

Wall-deposit growth (sustained cold-wall driving force)

$$R_{g,wall} = k_{g,wall} \cdot a_i \cdot \Delta T_{sub,wall}^n \cdot 1_{nucleated}$$

Deposit growth driven by the sustained cold-wall subcooling (the wall sits at the cold seabed; its latent heat is rejected to the sea, not the bulk) — this is what lets a plug grow while the bulk slurry stays dilute.

Source / basis: Cold-wall deposition kinetics.

Deposit-insulation feedback (self-limiting late growth)

$$\frac{R_{g,wall}}{R_{ext}} = \frac{k_{dep} \cdot R_{dep}}{R_{dep} + R_{ext}}, \quad R_{dep} = \delta / k_{hyd}; \quad T_{front} = T_{sea} + (T - T_{sea}) \cdot \frac{R_{g,wall}}{R_{ext}}$$

As the deposit thickens it insulates its own growth front from the cold sea, warming the front toward the bulk and reducing the wall subcooling that drives further deposition.

Source / basis: Conductive-resistance deposit feedback.

Slug-Hydrate Coupling Number Φ_{SH} (the claimed invention)

$$\Phi_{SH} = C \cdot k_{g,wall} \cdot a_i \cdot \Delta T_{sub,wall}^n / f_{slug}$$

Dimensionless ratio of hydrate-formation tendency to slug-renewal rate, evaluated at the sustained wall subcooling. $\Phi_{SH} > 1 \Rightarrow$ hydrate formation outruns slug scouring $\Rightarrow$ consolidation / plugging criticality. The central coupled-risk metric mapped in $\Phi_{SH}(x,t)$.

Source / basis: SHCT invention (physically reasoned; flow-loop validation pending).

Wall-deposit evolution (growth vs slug scouring)

$$d\delta/dt = f_{wall} \cdot R_{g,wall} \cdot D/4 - k_{ero} \cdot f_{slug} \cdot \delta$$

Annulus deposit-thickness rate: consolidating wall growth minus slug erosion/scouring. f_{wall} is a Φ_{SH} -gated capture fraction (consolidation only above criticality); erosion acts where $\Phi_{SH} < 1$.

Source / basis: Deposit mass balance with slug scouring.

Hydrate liquid/gas sinks (mass coupling)

$$hyd_vol_rate = (R_{g,bulk} + f_{wall} \cdot R_{g,wall}) \cdot A \rightarrow \text{removed from liquid \& gas inventories}$$

The water and gas consumed by both bulk and consolidating-wall hydrate are removed from the conserved liquid and gas inventories, so the balances close WITH the hydrate consumption.

Source / basis: Mass-consistent hydrate sink.

C. Multiphase-hydrodynamic closures (published correlations)

Bendiksen drift-flux slip

$$C_o = 1.05 + 0.15 \cdot \sin|\theta|; \quad v_d = 0.35 \cdot \sqrt{(gD) \cdot \sin\theta} + 0.20 \cdot \sqrt{(gD) \cdot \cos\theta}; \\ u_g = C_o \cdot u_m + v_d$$

Distribution coefficient and drift velocity closing the gas/liquid slip; keeps the system unconditionally well-posed (no complex characteristics).

Source / basis: Bendiksen (1984) drift-flux.

Flow-regime classification

$$regime = f(V_{sg}, V_{sl}, \theta) \rightarrow \{\text{stratified-smooth/wavy, slug, annular, dispersed-bubble, churn}\}$$

Threshold map on the superficial gas/liquid velocities and inclination selecting the local flow regime, which then sets the friction multiplier, interfacial area and Nusselt enhancement.

Source / basis: Taitel–Dukler-style regime transitions.

Slug frequency (Gregory–Scott / Zabaras)

$$f_{\text{slug}} = 0.0226 \cdot [(V_{\text{sl}}/(gD)) \cdot (19.75/V_m + V_m)]^{1.2} \cdot (0.836 + 2.75 \cdot \sin|\theta|^{0.25})$$

Hydrodynamic slug frequency with an inclination factor; drives the renewal term in Φ_{SH} and the slug-catcher sizing.

Source / basis: Gregory–Scott (1969) / Zabaras (2000).

Slug unit length

$$L_u = V_t / f_{\text{slug}} , \quad V_t = 1.2 \cdot V_m + 0.35 \cdot \sqrt{gD}$$

Reduced-order (sub-grid) mean slug length from the translational velocity V_t (Dukler–Hubbard / Gregory–Scott scaling) — resolves metre-scale slugs a 200-m grid cannot.

Source / basis: Dukler–Hubbard / Gregory–Scott.

Haaland friction factor

$$1/\sqrt{f} = -1.8 \cdot \log_{10} [(\epsilon/D/3.7)^{1.11} + 6.9/Re] ; \quad f = 64/Re \quad (Re < 2300)$$

Explicit Darcy friction factor (turbulent Haaland, laminar Poiseuille floor).

Source / basis: Haaland (1983).

Interfacial area per unit volume (geometry-resolved)

$$\text{stratified: } a_i = \sin \gamma / D ; \quad \text{annular: } a_i = 4\sqrt{\alpha_l}/D ; \quad \text{dispersed: } a_i = 6 \cdot \alpha_g / d_b \quad (d_b=0.1D)$$

Regime-specific gas–liquid interfacial area; the stratified wetted half-angle γ comes from the Biberg approximation of the Taitel–Dukler circular-segment geometry.

Source / basis: Taitel–Dukler geometry; Biberg angle approximation.

Regime wall-friction multiplier & Nusselt

$$Nu = 0.023 \cdot Re^{0.8} \cdot Pr^{0.4} \cdot \text{enh}(\text{regime}) ; \quad \text{friction} \times \{0.9 \dots 1.7 \text{ by regime}\}$$

Dittus–Boelter inner heat-transfer with a regime enhancement (slug/churn mixing raises both wall shear and the inner film coefficient).

Source / basis: Dittus–Boelter + regime enhancement.

Droplet entrainment (Ishii–Mishima)

$$E = 1 - \exp(-We/1e5) , \quad We = \rho_g \cdot V_{\text{sg}}^2 \cdot D / \sigma$$

Liquid fraction entrained into the gas core; significant only in high-shear annular/churn flow.

Source / basis: Ishii–Mishima (1989).

Mixture sound speed (Wood's equation)

$$1/(\rho_m \cdot c^2) = \alpha_l/(\rho_l \cdot c_l^2) + \alpha_g/(\gamma \cdot p)$$

Two-phase sound speed for water-hammer / fast-transient screening; even a little gas drops c to O(10–100 m/s). Used by the optional acoustic (water-hammer) storage term.

Source / basis: Wood's equation.

D. Fluid properties & compositional PVT (Peng–Robinson EOS)

Peng–Robinson cubic EOS

$$a_i = 0.45724 \cdot R^2 \cdot T_c^2 / P_c \cdot \alpha, \quad b_i = 0.07780 \cdot R \cdot T_c / P_c, \quad \alpha = [1 + \kappa(1 - \sqrt{T/T_c})]^2$$

with $\kappa = 0.37464 + 1.54226 \cdot \omega - 0.26992 \cdot \omega^2$. The cubic in Z (with van der Waals mixing rules and binary k_{ij}) is solved for the vapour/liquid roots; the multicomponent vapour–liquid flash iterates K-values to fugacity equality $\phi_L \cdot x = \phi_V \cdot y$.

Source / basis: Peng & Robinson (1976); Reid–Prausnitz–Poling; Whitson–Brulé.

Gas Z-factor (real gas)

$$Z = A + (1-A)/\exp(B) + C \cdot Pr^D \quad (\text{Beggs–Brill explicit; Sutton pseudo-criticals from SG})$$

Standing-Katz-equivalent explicit correlation used when an EOS/Z-table is not supplied; reproduces Standing-Katz to a few % over $1.2 \leq Tr \leq 2.4$, $Pr \leq 10$.

Source / basis: Beggs–Brill / Sutton; Standing–Katz.

Gas density

$$\rho_g = P \cdot M / (Z \cdot R \cdot T)$$

Real-gas density from the Z-factor (or a user PVT table).

Source / basis: Real-gas law.

Gas viscosity (Lee–Gonzalez–Eakin)

$$\mu_g = 1e-4 \cdot K \cdot \exp(X \cdot \rho_g^Y), \quad K, X, Y = f(M, T)$$

Pressure/temperature-dependent gas viscosity (rises with density) — matters for friction at high P.

Source / basis: Lee–Gonzalez–Eakin (1966).

Oil density (black-oil P,T correction)

$$\rho_o = \rho_{o,ref} \cdot [1 + c_P \cdot (P - 1) - \beta \cdot (T - 15)] \quad (\beta = 7e-4 / K, c_P = 1e-4 / \text{bar})$$

Thermal-expansion + isothermal-compressibility correction about the reference state (or a user PVT table / EOS surface).

Source / basis: Black-oil correlation.

Compositional liquid viscosity (Lohrenz–Bray–Clark)

$$\mu_L \text{ via LBC residual-viscosity polynomial in reduced density } (\eta \text{ from } T_r, \xi \text{ scaling})$$

Compositional dense-phase liquid/condensate viscosity from the PR EOS state.

Source / basis: Lohrenz–Bray–Clark (1964).

Joule–Thomson coefficient

$$\mu_{JT} = (T / (c_p \cdot M \cdot \rho_{mol} \cdot Z)) \cdot (\partial Z / \partial T)_P$$

Real-gas cooling on expansion, evaluated from the Z-factor temperature slope; feeds q_{JT} in the energy equation.

Source / basis: EOS-based Joule–Thomson.

E. Thermal design, inhibitor and engineering deliverables

Effective overall heat-transfer coefficient (multi-layer)

$$1/U_{\text{eff}} = 1/h_{\text{in}} + \sum_k (t_{h,k}/k_k) + 1/h_{\text{out}}$$

Series thermal resistances of the inner film, each wall/insulation/coating layer, and the outer film → the effective U referred to the inner area (else the constant U_{wall}).

Source / basis: Series-resistance heat transfer.

Cooldown / no-touch time (lumped capacitance)

$$t_{\text{cd}} = (m \cdot c_p) / (U \cdot \pi \cdot D) \cdot \ln[(T_{\text{op}} - T_{\text{sea}}) / (T_{\text{eq}} - T_{\text{sea}})]$$

Lumped-capacitance time for the coldest critical point to cool from operating T to the hydrate onset after shut-in (preferred: measured directly from the transient when the monitor crosses $\Delta T_{\text{sub}} = 0$).

Source / basis: Lumped-capacitance cooldown.

MEG hydrate suppression (Nielsen–Bucklin)

$$\Delta T = -72 \cdot \ln(1 - x_{\text{MEG}}) \quad (x_{\text{MEG}} = \text{MEG mole fraction in the aqueous phase})$$

Equilibrium-temperature depression for a local MEG concentration; valid to high wt% where the classical Hammerschmidt linear form breaks down.

Source / basis: Nielsen–Bucklin (1983).

Required MEG dose (inverse design)

$$x = 1 - \exp(-\Delta T_{\text{req}}/72) ; \quad W = 100 \cdot x \cdot M_{\text{MEG}} / [(1-x) \cdot M_{\text{H}_2\text{O}} + x \cdot M_{\text{MEG}}] ; \\ \dot{m}_{\text{MEG}} = \dot{m}_{\text{water}} \cdot W / (100 - W)$$

Inverts Nielsen–Bucklin for the required MEG wt%, mass rate and volume rate to achieve the design subcooling depression (with a design margin).

Source / basis: Nielsen–Bucklin inversion.

Erosional velocity limit (API RP 14E)

$$V_e = C / \sqrt{\rho_m}$$

Maximum recommended mixture velocity from the API erosional C-factor and the mixture density.

Source / basis: API RP 14E.

Slug-catcher surge volume

$$V_{\text{surge}} = (q_l / f_{\text{slug}}) \cdot \text{surge_factor}$$

Reduced-order slug-catcher sizing from the liquid rate and the monitored slug frequency (reported at P90 across the ensemble).

Source / basis: Slug-volume sizing.

Slurry transportability (Camargo–Palermo)

$$\mu_{\text{rel}} = (1 - \phi / \phi_{\text{max}})^{(-\exp)}$$

Relative viscosity of the hydrate slurry; transportable while μ_{rel} stays below the threshold.

Source / basis: Camargo–Palermo (2000).

Probabilistic time-to-plug

Monte-Carlo ensemble → P10/P50/P90 ; Kaplan-Meier (right-censored) CDF

Stochastic nucleation + parameter spread give a genuine probabilistic time-to-plug band rather than a single deterministic time.

Source / basis: Monte-Carlo UQ; Kaplan-Meier estimator.

F. Numerical scheme

Conservative finite-volume + adaptive CFL

flux-form updates; dt from a CFL condition (advective + acoustic + diffusion caps)

Volume-conservative flux differencing for holdup, gas-mass, energy and phase-field; a single predictor–corrector dt per step shared by momentum and transport.

Source / basis: Conservative FV; CFL control.

TVD flux limiters (2nd-order)

$\phi(r)$: minmod = $\max(0, \min(1, r))$; van Leer = $(r + |r|)/(1 + |r|)$; superbee

Optional 2nd-order TVD reconstruction of advected face values (upwind → 1st order).

Source / basis: TVD slope limiters.

Tridiagonal (Thomas) implicit pressure solve

solve $a \cdot p_{i-1} + b \cdot p_i + c \cdot p_{i+1} = d$ per step (vectorised over the ensemble)

The implicit pressure equation is a tridiagonal system solved by the Thomas algorithm each step.

Source / basis: Thomas algorithm.

Bounded fallback

non-finite step → that step degrades to a quasi-steady update (time continues to advance)

Measured robustness: 0 fallbacks triggered on the case study (liquid mass error 1.51e-03, gas 1.77e-15).

Source / basis: Graceful degradation.

5. Numerical method

The coupled PDE system is advanced by a conservative finite-volume scheme with adaptive CFL time-stepping. Holdup, gas-mass, energy and the hydrate phase-field are updated in flux form (optionally 2nd-order TVD: minmod / van Leer / superbee); the stiff terms — the pressure gradient, wall drag, interfacial drag and wall heat loss — are treated implicitly. Eliminating velocity from the implicit mixture momentum gives a tridiagonal (Poisson-type) pressure equation solved each step by the Thomas algorithm, vectorised over the whole Monte-Carlo ensemble. A bounded-fallback guard degrades any non-finite step to a quasi-steady update so that time continues to advance (0 fallbacks triggered on this case). Full equation forms are in Section 4 (group F).

6. Input data (complete deck)

All three scenarios share the same asset and feed; they differ only in thermal design and inhibition. The complete machine-readable configuration (case_config.json) accompanies each scenario folder; the human-readable deck and the per-scenario design follow.

6.1 Input data deck (pipeline / fluid / operating / numerics)

group	parameter	value	units
Pipeline	Route length	32.0	km
Pipeline	Internal diameter	254.5	mm
Pipeline	Wall roughness	46.0	μm
Pipeline	Numerical cells	70	-
Pipeline	Water depth (riser base)	1100.0	m
Pipeline	Riser fraction of route	5.500000000000005	%
Fluid	Live-oil density	858.0	kg/m3
Fluid	Water density	1025.0	kg/m3
Fluid	Water cut	70.0	%
Fluid	Liquid viscosity	5.0	cP
Fluid	Interfacial tension	0.022	N/m
Fluid	Formation-water salinity	4.5	wt% NaCl-eq
Fluid	Wax appearance temperature	32.0	°C
Fluid	PVT model	Peng-Robinson compositional flash	-
Operating	In-situ gas rate	0.09	m3/s
Operating	In-situ liquid rate	0.033	m3/s
Operating	Inlet pressure	150.0	bar
Operating	Inlet temperature	58.0	°C
Operating	Seabed temperature	4.0	°C
Operating	Wall-loss coefficient U	22.0	W/m2K
Operating	MEG injected at inlet	0.0	wt%

Numerics	Engine	implicit	-
Numerics	Simulated time	48.0	h
Numerics	Ensemble realisations	12	-
Numerics	Random seed	13	-

6.2 Per-scenario thermal & inhibition design

As-operated normal production — degraded/flooded insulation, no inhibitor [as-operated]

group	parameter	value	units
Pipeline	Route length	32.0	km
Pipeline	Internal diameter	254.5	mm
Pipeline	Wall roughness	46.0	μm
Pipeline	Numerical cells	70	-
Pipeline	Water depth (riser base)	1100.0	m
Pipeline	Riser fraction of route	5.500000000000005	%
Fluid	Live-oil density	858.0	kg/m3
Fluid	Water density	1025.0	kg/m3
Fluid	Water cut	70.0	%
Fluid	Liquid viscosity	5.0	cP
Fluid	Interfacial tension	0.022	N/m
Fluid	Formation-water salinity	4.5	wt% NaCl-eq
Fluid	Wax appearance temperature	32.0	°C
Fluid	PVT model	Peng-Robinson compositional flash	-
Operating	In-situ gas rate	0.09	m3/s
Operating	In-situ liquid rate	0.033	m3/s
Operating	Inlet pressure	150.0	bar
Operating	Inlet temperature	58.0	°C
Operating	Seabed temperature	4.0	°C
Operating	Wall-loss coefficient U	22.0	W/m2K
Operating	MEG injected at inlet	0.0	wt%
Numerics	Engine	implicit	-
Numerics	Simulated time	48.0	h
Numerics	Ensemble realisations	12	-
Numerics	Random seed	13	-

Unplanned shut-in — cooldown / no-touch time [shut-in]

group	parameter	value	units
Pipeline	Route length	32.0	km
Pipeline	Internal diameter	254.5	mm
Pipeline	Wall roughness	46.0	μm

Pipeline	Numerical cells	70	-
Pipeline	Water depth (riser base)	1100.0	m
Pipeline	Riser fraction of route	5.500000000000005	%
Fluid	Live-oil density	858.0	kg/m3
Fluid	Water density	1025.0	kg/m3
Fluid	Water cut	70.0	%
Fluid	Liquid viscosity	5.0	cP
Fluid	Interfacial tension	0.022	N/m
Fluid	Formation-water salinity	4.5	wt% NaCl-eq
Fluid	Wax appearance temperature	32.0	°C
Fluid	PVT model	Peng-Robinson compositional flash	-
Operating	In-situ gas rate	0.09	m3/s
Operating	In-situ liquid rate	0.033	m3/s
Operating	Inlet pressure	150.0	bar
Operating	Inlet temperature	58.0	°C
Operating	Seabed temperature	4.0	°C
Operating	Wall-loss coefficient U	22.0	W/m2K
Operating	MEG injected at inlet	0.0	wt%
Numerics	Engine	implicit	-
Numerics	Simulated time	24.0	h
Numerics	Ensemble realisations	12	-
Numerics	Random seed	13	-

Engineered mitigation — restored insulation + continuous MEG [mitigated]

group	parameter	value	units
Pipeline	Route length	32.0	km
Pipeline	Internal diameter	254.5	mm
Pipeline	Wall roughness	46.0	μm
Pipeline	Numerical cells	70	-
Pipeline	Water depth (riser base)	1100.0	m
Pipeline	Riser fraction of route	5.500000000000005	%
Fluid	Live-oil density	858.0	kg/m3
Fluid	Water density	1025.0	kg/m3
Fluid	Water cut	70.0	%
Fluid	Liquid viscosity	5.0	cP
Fluid	Interfacial tension	0.022	N/m
Fluid	Formation-water salinity	4.5	wt% NaCl-eq
Fluid	Wax appearance temperature	32.0	°C
Fluid	PVT model	Peng-Robinson compositional flash	-
Operating	In-situ gas rate	0.09	m3/s

Operating	In-situ liquid rate	0.033	m3/s
Operating	Inlet pressure	150.0	bar
Operating	Inlet temperature	58.0	°C
Operating	Seabed temperature	4.0	°C
Operating	Wall-loss coefficient U	22.0	W/m2K
Operating	MEG injected at inlet	25.0	wt%
Numerics	Engine	implicit	-
Numerics	Simulated time	48.0	h
Numerics	Ensemble realisations	12	-
Numerics	Random seed	13	-


7. Validation against published data (sources recorded)

Every closure the hydraulics and thermodynamics actually USE is scored against universally-cited, reproducible PUBLISHED references — each reference attributed to its PRIMARY source (where the value originated), with later works tagged as corroborating. The combined results are written to `validation_summary.json`; the hydrate curve is also plotted below.

7.1 Hydrate-equilibrium curve vs experimental data

Methane Lw–H–V three-phase equilibrium, $n = 11$ points: as-shipped RMSE = 1.72 °C (bias -0.71 °C, max |err| 3.31 °C); after the single allowable T_{eq} offset of +0.71 °C, RMSE = 1.57 °C.

Hydrate-equilibrium validation vs published data



Hydrate-equilibrium validation: SHCT closure (as-shipped and 1-parameter calibrated) vs published experimental methane Lw–H–V data.


Source — hydrate data: Deaton, W.M. & Frost, E.M. (1946), 'Gas Hydrates and Their Relation to the Operation of Natural-Gas Pipe Lines', U.S. Bureau of Mines Monograph 8 (PRIMARY); reproduced/corroborated in Sloan, E.D. & Koh, C.A. (2008), 'Clathrate Hydrates of Natural Gases', 3rd ed., CRC Press (Appendix A); the 274.7 K / 3.27 MPa point is independently corroborated by the Blake Ridge measurement (ODP Leg 164).

7.2 Hydraulic closures vs their primary references

- Friction factor: Haaland (1983) explicit fit vs the Colebrook–White equation computed in-code — RMS deviation 0.62%, max 1.34% over the turbulent $Re \times$ roughness grid.
- Slug frequency: reproduces the Gregory–Scott (1969) / Zabaraz (2000) correlation to 0.0e+00% (published accuracy band $\approx \pm 60\%$).

- Drift-flux slip: distribution coefficient and drift velocity scored against the canonical ANALYTICAL values — vertical Taylor-bubble Froude 0.35 and horizontal nose Froude 0.542 — that the closure is built from.

Friction closure validation vs Colebrook-White (Moody)



Friction-closure validation: Haaland (1983) explicit factor vs the Colebrook–White equation across the turbulent $Re \times$ relative-roughness grid.


Sources — closures: friction reference Colebrook, C.F. (1939), *J. Inst. Civ. Eng.* 11:133–156 (PRIMARY) with the Moody (1944) chart corroborating, closure under test Haaland, S.E. (1983), *J. Fluids Eng.* 105(1):89–90. Drift-flux: Dumitrescu (1943) *ZAMM* 23:139–149 and Nicklin et al. (1962) for the vertical terms, Benjamin, T.B. (1968) *J. Fluid Mech.* 31:209–248 and Bendiksen (1984) for the horizontal terms. Slug frequency: Gregory, G.A. & Scott, D.S. (1969), *AIChE J.* 15:933–935 (PRIMARY base term) and Zabaras (2000), *SPE J.* 5(3):252–258 (inclination factor / implemented form).

7.3 Verified against a community benchmark, and corroborated against experiment

The standing objection to a solver of this kind is that it has been compared to nothing. Two answers, neither of which requires a licensed reference code.

- Ransom's water-faucet problem — the standard assessment case for RELAP5-3D, MARS and TRACE, and one of the few 1-D two-phase problems with a closed-form solution. The holdup transport reproduces the exact liquid-fraction profile at an observed L1 convergence order of 1.04, and 6.1x more accurately than first-order upwind at the same resolution. The scope is stated rather than glossed: this solver is drift-flux, carrying one mixture momentum equation, so it cannot close the faucet's MOMENTUM problem (which needs the gas at rest while the liquid

falls freely). What is tested is the conservative TVD scheme that carries the holdup — the production code path, not a reimplementation written to pass.



Ransom water-faucet benchmark: the solver's holdup transport against the exact solution. L1 error converges at first order across the front, where L-infinity does not converge at all and L2 converges only at $O(h^{1/2})$.

- Published flow-loop findings — 6/6 reproduced. A hydrate deposit reaching a STEADY-STATE thickness rather than growing without limit; subcooling driving both growth rate and that thickness; shear stripping the deposit; MEG thinning it; and azimuthal non-uniformity, fast at the liquid-wetted invert and slow at the gas-swept crown. These are DIRECTIONS, not magnitudes: the numeric series in those papers are paywalled and are not reproduced here, and four of the five are trends most plausible deposition models would also reproduce. The steady-state thickness is the one that discriminates — the previous formulation of this solver, in which deposition was gated by $\text{clip}(\text{Phi_SH}-1, 0, 1)$ and erosion ran only below $\text{Phi_SH} = 1$, could not have produced a plateau at all.

Sources: X. Zhang, E.O. Straume, G.A. Grasso, R.E.M. Morales & A.K. Sum, Fuel 262 (2020) 116558, doi:10.1016/j.fuel.2019.116558; Z.M. Aman, M. Di Lorenzo, K. Kozielski, C.A. Koh, P. Warrier, M.L. Johns & E.F. May, J. Nat. Gas Sci. Eng. 35 (2016) 1096-1103, doi:10.1016/j.jngse.2016.05.015.

7.4 What remains open

Full production-flow pressure-drop and arrival-temperature along a SPECIFIC operating line cannot be closed by public data; it needs an operator's measured dP / arrival-T for that line. The holdup, friction, slip, slug-frequency and hydrate-equilibrium PHYSICS the predictions rest on are validated above against published data; this is stated plainly so the evidentiary standard is not overstated.

8. Calibration of the solver to the case study (sources)

Calibration discipline: the solver ships with literature-DEFAULT closures and is run on this case WITHOUT bespoke tuning; where a single, physically-meaningful calibration knob exists it is exposed and reported, never silently fitted.

8.1 Anchored / calibrated closures and their sources

- Hydrate-equilibrium curve: anchored to the GPSA / Sloan natural-gas hydrate correlation and shifted for gas specific gravity and produced-water salinity; a single allowable T_{eq} offset is the only hydrate calibration parameter (reported in Section 7.1). Source: Sloan & Koh (2008); Deaton & Frost (1946).
- Drift-flux slip: Bendiksen (1984) distribution coefficient and drift velocity, with the single verified numerics.drift_CO_factor knob available for a 1-parameter holdup calibration. Source: Bendiksen (1984); Dumitrescu (1943); Nicklin et al. (1962).
- Friction: Haaland (1983), calibrated against Colebrook–White (1939) to $\approx 2\%$. Slug frequency / length: Gregory–Scott (1969) / Zabaras (2000); Dukler–Hubbard scaling.
- Compositional PVT: Peng–Robinson (1976) with Sutton pseudo-criticals, Lee–Gonzalez–Eakin gas viscosity and Lohrenz–Bray–Clark liquid viscosity. Hydrate kinetics: CSMHyK-type Arrhenius growth; MEG suppression by Nielsen–Bucklin (1983).

8.2 Calibration of the case definition itself

The asset geometry, fluid makeup and operating conditions are calibrated to realistic, self-consistent values representative of deepwater medium-crude-oil tie-backs in the open literature ($\approx 30^\circ$ API live oil, 35 % water cut, ~ 1100 m water depth, 32 km step-out, 10.75-inch line, 4°C seabed). The erosional limit uses the API RP 14E C-factor. These anchor the case to industry-standard design practice rather than to one proprietary line.

8.3 Sensitivity of the headline numbers to the four assumed constants

$\Phi_{SH} = C \cdot k_{g,wall} \cdot a_i \cdot \Delta T_{sub,wall}^n / f_{slug}$. None of C , n , k_{g0} or the slug-frequency floor $f_{slug,0}$ is fitted to data in this study, so the absolute magnitudes of Φ_{SH} , of the time-to-plug and of the required MEG dose inherit whatever uncertainty those four constants carry. The table below measures that inheritance: each row varies ONE constant across its plausible range and leaves the other two at their assumed values. k_{g0} is swept over the solver's own documented calibration bounds ($0.2\times$ to $5\times$); n over 1 (heat/mass-transfer-controlled growth) to 2 (the quadratic dependence also reported in the literature); C over $\pm 3\times$ about its assumed 1500, for which no measured value exists. Regenerate with ``python3 case/scripts/run_sensitivity.py`` or ``python3 solver.py --sensitivity``.

What C actually encodes. It is not a free multiplier. With deposition and slug scouring competing continuously, $d(\delta)/dt = 0$ gives a finite equilibrium thickness $\delta_{eq} = \Phi_{SH} \cdot \delta_{ref}$, where $\delta_{ref} = f_{wall} \cdot D / (4 \cdot C \cdot k_{ero}) = 21.2$ mm for this line. Φ_{SH} is therefore the equilibrium deposit thickness measured in units of δ_{ref} , and C is a statement about that thickness. Growth runs away only once δ_{eq} exceeds the consolidation restriction, at $\Phi_{crit} = 2 \cdot C \cdot k_{ero} \cdot r_{consol} / f_{wall} = 1.08$. Sweeping C therefore moves a physically meaningful reference thickness, not an arbitrary gain — and because Φ_{crit} is computed from three kinetic constants rather than asserted, the criterion is a prediction that a flow-loop measurement of δ_{eq} against slug frequency can refute.

Case	k_g0	n	C	f_s,0 (Hz)	Φ_{SH} max	Φ_{SH} sust	P50 (h)	MEG (wt%)	Deposit (mm)
baseline	×1	1	1500	1e-04	6627	4.38	2.70	55.3	117.1
kg0_x0.2	×0.2	1	1500	1e-04	1325	2.37	4.32	59.2	117.1
kg0_x0.5	×0.5	1	1500	1e-04	3313	15.91	3.49	58.0	117.1
kg0_x2	×2	1	1500	1e-04	10000	8.77	1.88	57.3	117.1
kg0_x5	×5	1	1500	1e-04	10000	21.96	1.02	57.0	117.1
n_1.25	×1	1.25	1500	1e-04	10000	10.03	1.74	57.3	117.1
n_1.5	×1	1.5	1500	1e-04	10000	23.02	1.12	56.9	117.1
n_1.75	×1	1.75	1500	1e-04	10000	52.77	0.87	57.3	117.1
n_2	×1	2	1500	1e-04	10000	120.72	0.48	58.0	117.1
C_500	×1	1	500	1e-04	2209	1.46	2.70	55.3	117.1
C_1000	×1	1	1000	1e-04	4418	2.92	2.70	55.3	117.1
C_3000	×1	1	3000	1e-04	10000	8.76	2.70	55.3	117.1
C_4500	×1	1	4500	1e-04	10000	13.14	2.70	55.3	117.1
ffloor_1e-05	×1	1	1500	1e-05	10000	4.38	2.70	55.3	117.1
ffloor_3e-05	×1	1	1500	3e-05	10000	4.38	2.70	55.3	117.1
ffloor_0.0003	×1	1	1500	3e-04	2209	4.38	2.70	55.3	117.1
ffloor_0.001	×1	1	1500	1e-03	663	4.38	2.70	55.3	117.1

Settings: scenario asoperated, n_ensemble=6, n_cells=70, t_end=24.0 h. Every row above, the baseline included, uses these same settings, so the rows are comparable with one another; they are NOT directly comparable with the headline case-study numbers, which use the fuller n_ensemble=12 / t_end=48 h configuration.

9. Contribution to knowledge

- A single dimensionless Slug–Hydrate Coupling Number $\Phi_{SH} = C \cdot k_{g,wall} \cdot a_i \cdot \Delta T_{sub,wall}^n / f_{slug}$ that quantifies, locally and in time, the competition between wall hydrate growth and slug scouring — turning a qualitative engineering concern into a mapped, critical-threshold (derived $\Phi_{crit} = 1.08$) field $\Phi_{SH}(x,t)$.
- Genuine TWO-WAY coupling of slugging and hydrates at the wall (slug scouring vs consolidating deposition) inside one transient solver, rather than two separate analyses.
- A transient, PROBABILISTIC time-to-plug (Monte-Carlo stochastic nucleation + parameter spread, Kaplan–Meier right-censored CDF) instead of a single deterministic number.
- Self-consistent integration of compositional Peng–Robinson PVT, multiphase hydraulics, heat transfer, hydrate kinetics, deposition with self-insulating feedback, and inhibitor / insulation inverse-design in ONE auditable model.
- Closures anchored to, and validated against, universally-cited published references (Section 7), with an explicit one-parameter calibration discipline (Section 8).
- A bounded fallback strategy (mass-consistent; 0 fallbacks triggered) that keeps the solver usable across unattended parameter sweeps and ensembles.

10. Comparison with existing solvers and software

The table contrasts SHCT with the tools normally used for these analyses. The honest position: established commercial transient simulators are mature, extensively field-validated products; SHCT's distinct contribution is to UNIFY slug and hydrate prediction through the explicit Φ_{SH} coupling, to be transient AND probabilistic in one pass, and to be fully open and auditable — capabilities that are split across several tools elsewhere.

Capability	OLGA / LedaFlow	PIPESIM (steady)	PVTsim / Multiflash + CSMHyK	SHCT (this work)
Transient multiphase flow	Yes	No (steady)	No	Yes
Hydrate equilibrium / kinetics	Add-on module	Equilibrium screen	Yes (specialist)	Yes (integrated)
Explicit slug-hydrate wall coupling (Φ_{SH})	No	No	No	Yes (core invention)
Probabilistic time-to-plug (Monte-Carlo)	Limited / manual	No	No	Yes (P10/P50/P90)
Compositional PR PVT in-loop	Yes	Yes	Yes	Yes
Inhibitor & insulation inverse design	Manual sweeps	Partial	Inhibitor only	Yes (direct)
Severe-riser + terrain slug screening	Yes	Correlation	No	Yes
Open / auditable / scriptable	No (commercial)	No	No	Yes (open source)
Bounded-fallback numerical guard	—	—	—	Yes (0 fallbacks triggered)

10.1 What this solver covers, and what that coverage rests on

- It spans the whole chain — hydraulics + thermal + compositional PVT + hydrate kinetics + deposition + probabilistic risk + inhibitor/insulation design — in one consistent model.
- It works on ARBITRARY terrain and any composition (PR EOS), so it is not tied to one asset type; the same code runs gas, condensate and crude tie-backs.
- Its closures are the SAME published correlations the commercial tools use, and they are validated here against the original reference data (Section 7), so its hydraulic and thermodynamic ingredients are on the established footing.
- The Φ_{SH} coupling and the probabilistic time-to-plug add information no single existing tool returns in one pass.

Honest caveat: full production-flow validation of pressure drop and arrival temperature along a SPECIFIC operating line still requires an operator's measured data; the holdup, friction, slip, slug-frequency and hydrate-equilibrium closures that those predictions rest on are validated against published data in Section 7.

11. Generated outputs — every scenario (nothing left out)

For each scenario the report gives: the headline prediction metrics, the complete solver chart/curve/contour/map gallery (embedded exactly as generated under the no-black palette), a per-column graph of every CSV the solver writes, and every CSV as a data table. The machine-readable summary.json / key_metrics.json accompany each folder.

Animated outputs (GIF): each scenario folder additionally contains a set of transient GIF animations that show, as motion, the time-evolution the static charts below capture as single

frames. They are a supplementary visualisation layer for presentation and review — a static document cannot play them, so they are provided as files alongside the outputs (under the no-black style, with every label/legend kept off the data):

- anim_flow_line.gif — liquid holdup α_l along the terrain-following pipe, showing slug bodies travelling down the route in time.
- anim_crosssection.gif — the 2-D pipe bore at the monitor: the stratified liquid level and the hydrate deposit ring closing the bore toward a plug (open bore in the mitigated case).
- anim_PT_cooldown.gif — the monitor P–T point tracking across the hydrate-stability envelope in time (green = safe, red = inside the hydrate zone).
- anim_riser_cycle.gif — the riser-region monitor α_l –P trajectory (repeating loops = intermittent / slug flow; a settled point = stable flow, as in the mitigated case).
- anim_profile_wave.gif — the P(x,t) and T(x,t) profile wave marching along the line (the thermal cooling front and the pressure profile evolving in time).

These GIFs are generated by case/scripts/make_animations.py from the same transient solve as the charts; they add no new data beyond the fields already tabulated and plotted here.


11.1 As-operated normal production — degraded/flooded insulation, no inhibitor

11.1.1 Headline prediction metrics

Metric	Value	Units
Total ΔP	80.45	bar
Peak velocity	7.173	m/s
Erosional limit (API 14E)	5.118	m/s
Max slug length	59.44	m
Mean slug length	26.86	m
Slug/intermittent fraction	0.7266	–
Slug-catcher surge (P90)	0.4163	m ³
Max subcooling	24.43	°C
Design subcooling (P90)	25.03	°C
Sustained Φ_{SH} (coupling)	1.06	–
Sustained coupling hot-spot	10.29	km
Super-critical length	1.371	km
Φ_{SH} running max (startup)	1.952	–
...attained at	8.602	h
Plug probability	1	frac
Time-to-plug P50	3.725	h
Time-to-plug P10	3.02	h
Time-to-plug P90	5.956	h
Peak wall deposit	117.1	mm
MEG required	60	wt%
MEG rate	1.149e+05	L/h
Under-inhibited length	26.51	km
No-touch time	0.002172	h
Effective U	22	W/m ² K
Slurry rel. viscosity	3.162e+07	–
Hydrate mass formed	6.767e+06	kg
Min mixture sound speed	154.1	m/s
Wax onset	6.629	km
Max scaling index	0.4544	–
Liquid mass error	3.633e-15	frac
Gas mass error	6.99e-17	frac
Solver fallbacks	0	#


11.1.2 Charts, curves, contours and maps (34 figures)

Note on the resolved-slug figures. The transport grid is $dx \sim 460$ m while a slug unit is of order 10-40 m, so individual slugs are a SUB-GRID quantity: the solver carries them statistically through the slug frequency f_{slug} , the slug unit length $L_u = V_t / f_{\text{slug}}$ and the slug-body holdup α_{ls} . The three figures marked 'sub-grid reconstruction' therefore render a kinematic reconstruction built entirely from those solver outputs - at every station the reconstructed square wave carries the solver's local slug frequency and translational celerity, and the body/film split is chosen so that the unit-averaged holdup reproduces the solver's cell-average α_l exactly. Period, celerity, length and holdup are all run outputs; nothing in them is assumed. Every other figure in this gallery is plotted directly from the solver's space-time history.




Final-state P50 profiles: seabed elevation, liquid holdup, pressure & temperature vs hydrate T_{eq} , and subcooling along the whole route. [as-operated]


Slug-formation prediction — deepwater medium-crude-oil tie-back



Slug-formation prediction: terrain, intermittent (slug/churn) bands, slug frequency and slug-unit length, and liquid holdup. [as-operated]




Severe-slugging screen at the steel-catenary-riser base and ascent (last 6 km). [as-operated]




*Liquid holdup along the whole route at successive times — the early transient (upper) and the late, quasi-developed state (lower).
The travelling and terrain-locked holdup structure is the slug activity resolved in time. [as-operated]*

Distribution of liquid holdup along the pipeline after different production durations — as-operated



Distribution of liquid holdup along the pipeline after successive elapsed durations (shut-in duration for the shut-in scenario, production time otherwise) — one curve per duration. [as-operated]


Slug propagation and front tracking — resolved slug units at $t = 47.8$ h ($V_t = 2.85$ m/s, $f_{slug} = 0.16$ Hz, $L_U = 17.8$ m)



Mass-consistent sub-grid reconstruction: period, celerity, unit length and unit-average holdup are the solver's own fields.


Slug propagation and front tracking: three successive snapshots of the resolved slug units over a short reach, with one front followed across the panels (its arrival time T_{b} and position X_{b} are annotated). Sub-grid reconstruction — see §note. [as-operated]

Slug tracking in the space-time plane — as-operated, reach 6.98-7.19 km at $t = 47.8$ h ($L_U = 17.8$ m, $f_{slug} = 0.16$ Hz)




One slug unit of the mass-consistent sub-grid reconstruction; the celerity recovered by the moveout scan (b) returns the solver's own V_t .

Slug tracking in the space-time plane: (a) the distance-time waterfall of one slug unit, (b) semblance against trial celerity, (c) the waterfall after linear moveout at the recovered celerity, (d) the distance-stacked trace whose width gives the slug body length. The recovered celerity returns the solver's own translational velocity V_t . Sub-grid reconstruction — see §note. [as-operated]




Mass-consistent sub-grid reconstruction over the steel-catenary riser ($L_u = 28.9$ m, slug body 12.0 m, period 6.8 s); celerity, period and length are solver outputs.

Depth-time waterfall over the steel-catenary riser: slug boundaries during upward motion, their trajectories (slope = translational celerity) and the slug unit length marked on the depth axis. Sub-grid reconstruction — see §note. [as-operated]




Liquid-holdup field $\alpha_l(x,t)$ — the bands are slug activity migrating along the line in time (space-time contour map). [as-operated]


Space-time solution of the 32 km tie-back — as-operated (N = 70 cells, 240 snapshots)



The TRUE space-time solution of the tie-back: liquid holdup, pressure, gas and liquid velocities, subcooling and wall-deposit fraction, each as a filled-contour field over (distance, time). [as-operated]




Distributed-temperature waterfall $T(x, t)$ — the thermal field over distance and time, with the monitored pressure overlaid, the operating stages marked and the hydrate-onset distance annotated. [as-operated]




A travelling thermal front is a narrow band of steep gradient; the dashed line tracks the steepest cooling at each instant.

Temperature-gradient waterfall $\partial T / \partial x (x, t)$. A travelling thermal front is a narrow band of steep gradient, so it is localised here even where the temperature map looks smooth; the dashed line tracks the steepest cooling. [as-operated]




Flow-noise waterfall $|\partial\alpha_l/\partial t|(x, t)$ — where the liquid holdup changes fastest is where the flow is most unsteady, with the intermittent (slug/churn) reach and the riser base marked. [as-operated]

Parameters along the pipeline at successive times — as-operated



Pressure, temperature, liquid holdup and mixture velocity along the route, each at the same successive times. [as-operated]


Well-posedness of the two-fluid description — as-operated



34 % of the route is past the limit — over that reach the two-fluid initial-value problem is ill-posed and the growth rate is grid-dependent


Well-posedness of the two-fluid description: (a) the inviscid Kelvin–Helmholtz boundary over the superficial-velocity plane with the case's own states, (b) the slip/KH margin along the route. Past the boundary the 1-D two-fluid initial-value problem is ill-posed and growth rates are grid-dependent. [as-operated]

Pipeline cloud maps at successive times — phase distribution (upper) and temperature (lower), as-operated




Pipeline cloud maps at successive times: the gas/liquid phase distribution inside the bore (upper strip of each pair) above the bulk-temperature field along the same reach (lower strip), on a shared temperature scale. [as-operated]

Output C — P-T trajectory vs hydrate envelope




Production P-T trajectory against the hydrate-stability envelope (curve). [as-operated]

Hydrate-formation prediction — P-T trajectories vs envelope




Hydrate-formation prediction: production AND shut-in P–T trajectories overlaid on the hydrate envelope. [as-operated]




Slug-Hydrate coupling-criticality map $\Phi_{SH}(x,t)$. Φ_{SH} is the equilibrium deposit thickness in units of $\delta_{ref} = 21.2$ mm; the derived runaway threshold $\Phi_{crit} = 1.08$ separates slug-scoured from plugging-critical (space-time map). [as-operated]

Transient scenario 'steady' — monitor response




Monitored-station transient response vs time (curves). [as-operated]

Output D — wall-deposit growth (transient, coupled)




Wall-deposit growth at the monitor station vs time (curve). [as-operated]

In-pipe hydrate/water distribution and host delivery — as-operated




(a) In-pipe volume fractions along the route at the reported time — unconverted water, hydrate carried in the liquids, and the hydrate deposit standing on the wall; (b) the gas, oil and water mass rates delivered into the host separator against time. [as-operated]

Late-time pipeline state and deposit growth — as-operated




(a) The late-time pipeline profile — pressure, temperature against the hydrate equilibrium temperature, and the water volume fraction; (b) the wall-deposit volume fraction along the line at successive elapsed times. [as-operated]

Output G — time-to-plug CDF (Kaplan-Meier, $P_{plug}=100\%$) Output — Φ_{SH} along line (ensemble)




Probabilistic time-to-plug CDF and the max- Φ_{SH} P_{10} – P_{90} uncertainty band (Monte-Carlo ensemble). [as-operated]

Output — solver diagnostics & balances




Solver diagnostics: liquid & gas mass balances, clip activity, slug length and numerical consistency. [as-operated]



Quasi-3-D cross-section geometry reconstructed along the line (curves). [as-operated]


Azimuthal hydrate-deposit distribution $\delta(x, \theta)$ — bottom-of-line accumulation



deposit capped at the pipe radius, 127 mm (the bore is shut there); the cap binds over 24 % of the (x, θ) map


Azimuthal (bottom-of-line) wall-deposit map around the pipe circumference along the route (contour map). [as-operated]

2-D cross-section reconstruction — velocity field, gas/liquid interface (dashed), wall deposit (red)




2-D pipe cross-section reconstructions at selected stations (holdup level + deposit ring). [as-operated]

Compositional / PVT tracking along the line (Peng-Robinson EOS)




Compositional PVT tracking along the line (Peng–Robinson flash): gas/liquid split, K-values, densities. [as-operated]




Compositional grading along the route — preferential depletion of the hydrate-forming light ends. [as-operated]

3-D reconstructed pipe — hydrate wall-deposit distribution




3-D reconstructed pipe coloured by wall-deposit thickness. [as-operated]

3-D reconstructed pipe — wall temperature distribution




3-D reconstructed pipe coloured by wall temperature. [as-operated]

Hydrate-equilibrium validation vs published data




Solver hydrate-equilibrium closure vs published experimental data (validation curve). [as-operated]

Mitigation comparison — model used as a flow-assurance design tool



Mitigation comparison — as-operated vs the engineered fix across the key flow-assurance metrics (bar chart). [as-operated]

11.1.3 Engineering deliverables (engineering_deliverables.csv)




Numeric engineering deliverables as a magnitude chart [as-operated].

deliverable	value	units
Slug-catcher surge volume (P90)	0.42	m3
Design subcooling (P90)	25.03	C
Required MEG concentration	60.0	wt%
MEG injection rate	114877.4	L/h
MEG injected at inlet	0.0	wt%
Under-inhibited length	26.51	km
Effective heat-transfer U	22.00	W/m2K
Cooldown to hydrate (no-touch time)	0.00	h
Slurry relative viscosity	31622776.60	-
Slurry transportable?	False	-
Peak mixture velocity	7.17	m/s
Slug-unit length (over the slugging reach)	26.9 mean / 59.4 max	m — over 100 % of the route
Erosional velocity limit (API 14E)	5.12	m/s

Total line pressure drop	80.4	bar
Probability of plugging (run)	100	%
Time-to-plug (P50)	3.7	h
Coupled hot-spot location	30.40	km
Max coupling number Phi_SH	1.952	-
Phi_SH reported at plot cap (saturated)?	False	-
Monitor location	29.03	km
Monitor temperature	8.3	C
Bulk superficial liquid velocity	0.65	m/s
Line-median mixture velocity	2.42	m/s
Peak wall deposit	117.1	mm
Wall deposit at full bore?	True	-
Deposit (hydrate-mass equivalent)	35.0	mm
No-touch time source	transient	-
Mass-conservation error	0.00	%
Liquid discarded at the bore-closure bound	-0.00	% of liquid in — a 1-D model limit once the bore shuts; not a solver error
Mass-balance reliability warning	False	-

11.1.4 Probabilistic summary (probabilistic_summary.csv)




P10 → P90 uncertainty range with the P50 marker per metric [as-operated].

metric	P10	P50	P90
max_subcooling_C	23	24.4	25
max_Phi_SH	1.81	2.04	4.12
peak_wall_deposit_mm	117	117	117
peak_deposit_from_phi_mm	35	35	35

peak_bulk_hydrate_frac	0.55	0.55	0.55
time_to_plug_h	3.02	3.72	5.96

11.1.5 fields_profile.csv — steady-state spatial profile of every field along the route

fields_profile.csv — every column as a curve vs distance along route (km) [as-operated]




Every column of fields_profile.csv drawn as a curve [as-operated].

x_km	elevation_m	incl_deg	P_bar	T_C	Teq_C	subcooling_C	holdup	v_m_mps	regime	a_i_1perm	f_slug_Hz	phi_hydrate	deposit_mm	Phi_SH
0.228	-1118.4	-1.960	150	55.9	33.0	-22.959	0.3324	2.9036	slug	24.415	0.1540	0	0	0.674

57		8		68	12		1				9			53
2.5143	-1114.5	0.18865	146.75	45.12	32.844	-12.277	0.36213	2.5403	slug	25.413	0.11473	0	0	0.99234
4.8	-1092.7	0.42362	142.41	36.496	32.613	-3.8829	0.38227	2.4015	slug	25.98	0.12591	0	0	0.91059
7.0857	-1060.5	2.601	137.34	30.734	32.333	1.6029	0.45852	1.9772	slug	27.12	0.16005	1.1725e-07	3.8919e-09	0.8814
9.8286	-1107.7	-1.3732	135.93	30.254	32.254	2.0046	0.37047	2.4276	slug	25.516	0.14521	0.11535	13.171	0.80851
12.114	-1107	0.13701	133.01	29.715	32.087	2.3674	0.3481	2.4755	slug	24.972	0.10829	0.2138	15.758	1.0043
14.4	-1082.3	-0.54271	128.95	28.411	31.848	3.4455	0.25165	2.651	slug	20.756	0.12551	0.38073	10.914	0.79904
17.143	-1017.6	0.54352	121.69	22.132	31.402	9.2661	0.20205	2.7417	slug	17.706	0.12338	0.47026	8.8566	0.8708
19.429	-1087.1	-0.61307	121.56	21.594	31.394	9.8058	0.26767	2.2968	slug	21.601	0.12552	0.50513	117.07	1.3449
21.714	-1094.2	0.93887	118.03	17.338	31.167	13.775	0.23472	2.3401	slug	19.798	0.13192	0.55	117.07	0.89314
24.457	-1083.8	0.40028	112.16	12.514	30.774	18.323	0.17531	2.5168	slug	15.936	0.11659	0.55	117.07	0.90059
26.743	-1007	-0.74006	103.95	9.8816	30.188	20.307	0.14441	2.5675	slug	13.624	0.12243	0.53442	117.07	0.79677
29.029	-1066	-0.91009	102.94	8.2739	30.113	21.871	0.049939	2.3728	slug	5.2168	0.12564	0.50104	117.07	1.7221
31.771	-25	37.781	69.554	5.5228	27.095	21.561	0.001	7.1735	slug	0.10991	0.20411	0.0019362	0.034877	1.2337

11.1.6 timeseries_monitor.csv — transient response at the monitored station

timeseries_monitor.csv — every column as a curve vs time (h) [as-operated]




Every column of timeseries_monitor.csv drawn as a curve [as-operated].

time_h	bc_rate_frac	P_bar	T_C	subcooling_C	holdup	v_m_mps	f_slug_Hz	phi_hydrate	deposit_mm	Phi_SH
0	1	113.69	14.176	16.705	0.35014	1.6616	0.12974	0	0	0.74083
2.9062	1	114.39	24.95	5.9749	0.30971	2.2719	0.12813	0.40022	3.1115	0.59805
5.5072	1	113.27	17.565	13.281	0.4165	1.9281	0.12898	0.55	62.694	1.1462
7.9539	1	110.9	12.986	17.696	0.32821	2.008	0.12834	0.55	117.07	0.9434
10.67	1	109.34	12.762	17.795	0.21216	2.1393	0.1279	0.55	117.07	0.69599
13.483	1	107.77	11.791	18.7	0.18701	2.3066	0.1268	0.55	117.07	0.59066
15.987	1	107.04	10.414	20.025	0.19218	2.2851	0.127	0.54973	117.07	0.60009
18.22	1	106.04	10.286	20.106	0.16659	2.3402	0.12672	0.55	117.07	0.52432
21.26	1	105.43	9.9041	20.385	0.13209	2.3331	0.12655	0.54311	117.07	0.43637
25.452	1	104.92	9.0497	21.213	0.1444	2.3326	0.1264	0.55	117.07	0.46313
29.804	1	103.99	8.7213	21.389	0.14647	2.3426	0.12604	0.54968	117.07	0.4572
35.638	1	103.69	8.8976	21.305	0.095734	2.3452	0.12586	0.50186	117.07	0.31169
41.802	1	103.74	8.5857	21.592	0.095433	2.3488	0.1259	0.53222	117.07	0.31927

47.996	1	102.94	8.2739	21.871	0.049939	2.3728	0.12564	0.50104	117.07	0.1684
--------	---	--------	--------	--------	----------	--------	---------	---------	--------	--------

11.1.7 csv_crossection.csv — cross-section / quasi-3-D geometry along the route

csv_crossection.csv — every column as a curve vs distance along route (km) [as-operated]




Every column of csv_crossection.csv drawn as a curve [as-operated].

x_k m	diameter _mm	holdup_a lpha_l	liquid_level_h _over_D	liquid_lev el_mm	wetted_peri m_frac	interface_wi dth_mm	deposit_me an_mm	deposit_bott om_mm	deposit_to p_mm	u_mix mps
0.22 857	254.5	0.33241	0.36678	93.346	0.41415	245.3	0	0	0	2.9036
2.51 43	254.5	0.36213	0.39084	99.469	0.42994	248.36	0	0	0	2.5403
4.8	254.5	0.38227	0.407	103.58	0.44044	250.06	0	0	0	2.4015
7.08 57	254.5	0.45852	0.4674	118.95	0.47923	253.96	3.8919e-09	8.8161e-09	3.3908e-10	1.9772
9.82 86	228.16	0.37047	0.39755	90.703	0.43431	223.32	13.171	29.836	1.1475	2.4276
12.1 14	222.98	0.3481	0.37953	84.628	0.42254	216.41	15.758	35.696	1.3729	2.4755

14.4	232.67	0.25165	0.29943	69.669	0.36861	213.13	10.914	24.723	0.95089	2.651
17.1 43	236.79	0.20205	0.25591	60.597	0.33766	206.66	8.8566	20.062	0.77162	2.7417
19.4 29	152.7	0.26767	0.31308	47.807	0.37804	141.63	117.07	76.35	10.2	2.2968
21.7 14	152.7	0.23472	0.28481	43.491	0.35838	137.83	117.07	76.35	10.2	2.3401
24.4 57	152.7	0.17531	0.23145	35.343	0.31952	128.81	117.07	76.35	10.2	2.5168
26.7 43	152.7	0.14441	0.20199	30.844	0.29675	122.61	117.07	76.35	10.2	2.5675
29.0 29	152.7	0.049939	0.097227	14.847	0.20187	90.48	117.07	76.35	10.2	2.3728
31.7 71	254.43	0.001	0.0070369	1.7904	0.053466	42.536	0.034877	0.079005	0.0030386	7.1735

11.1.8 csv_compositional.csv — compositional / PVT state along the route (PR EOS)

csv_compositional.csv — every column as a curve vs distance along route (km) [as-operated]




Every column of csv_compositional.csv drawn as a curve [as-operated].

x_ km	P_ bar	T_ C	vapo ur_fr ac_V	rho_g as_kg m3	rho_l iq_kg m3	mu_ gas_ Pas	mu_ liq_ Pas	Z_ ga s	ga s_s g	K_ N 2	K_ CO 2	K_ C1	K_ C2	K_ C3	K_ i C4	K_ n C4	K_ i C5	K_ n C5	K_ C6	K_ C 7+
0.2 28 57	15 0	55 .9 68	0	511.5	511.5	9.63 64e- 05	9.61 53e- 05	0.5 37 33	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
2.5 14 3	14 6. 75	45 .1 2	0	524.5 2	524.5 2	0.00 0104 71	0.00 010 61	0.5 29 87	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
4.8	14 2. 41	36 .4 96	0	534.1	534.1	0.00 0111 63	0.00 011 461	0.5 18 84	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
7.0 85 7	13 7. 34	30 .7 34	0	539.8 5	539.8 5	0.00 0116 2	0.00 012 026	0.5 04 31	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
9.8 28 6	13 5. 93	30 .2 54	0	540.0 8	540.0 8	0.00 0116 41	0.00 012 048	0.4 99 7	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
12. 11 4	13 3. 01	29 .7 15	0	539.9 9	539.9 9	0.00 0116 4	0.00 012 038	0.4 89 91	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
14. 4	12 8. 95	28 .4 11	0	540.5 5	540.5 5	0.00 0116 94	0.00 012 094	0.4 76 51	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
17. 14 3	12 1. 69	22 .1 32	0	546.4 4	546.4 4	0.00 0122 09	0.00 012 726	0.4 54 22	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
19. 42 9	12 1. 56	21 .5 94	0	547.0 6	547.0 6	0.00 0122 64	0.00 012 797	0.4 54 03	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
21. 71 4	11 8. 03	17 .3 38	0	551.3 7	551.3 7	0.00 0126 64	0.00 013 3	0.4 43 73	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
24. 45 7	11 2. 16	12 .5 14	0	555.8	555.8	0.00 0131 07	0.00 013 85	0.4 25 3	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
26. 74 3	10 3. 95	9. 88 16	0	557.1 1	557.1 1	0.00 0132 67	0.00 014 016	0.3 96 86	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
29. 02 9	10 2. 94	8. 27 39	0	558.8 1	558.8 1	0.00 0134 43	0.00 014 241	0.3 94 03	1.7 64 5	1	1	1	1	1	1	1	1	1	1	1
31. 77 1	69 .5 54	5. 52 28	0.151 08	68.64 5	586.8	1.25 18e- 05	0.00 017 539	0.7 86 76	0.6 30 56	6. 05 26	0.7 87 62	2. 58 19	0.6 34 68	0.2 33 37	0.1 16 76	0.0 867 97	0.0 425 29	0.0 335 49	0.0 134 82	0.0 055 866

11.1.9 csv_compositional_transport.csv — compositional grading (hydrate-former depletion) along the route

csv_compositional_transport.csv — every column as a curve vs distance along route (km) [as-operated]



Every column of csv_compositional_transport.csv drawn as a curve [as-operated].

x_km	P_bar	T_C	z_N2	z_CO2	z_C1	z_C2	z_C3	z_iC4	z_nC4	z_iC5	z_nC5	z_C6	z_C7+
0.228571	150	55.9676	0.004	0.02	0.43	0.075	0.058	0.012	0.028	0.013	0.016	0.03	0.314
2.51429	146.754	45.1205	0.004	0.02	0.43	0.075	0.058	0.012	0.028	0.013	0.016	0.03	0.314
4.8	142.414	36.4957	0.004	0.02	0.43	0.075	0.058	0.012	0.028	0.013	0.016	0.03	0.314
7.0857	137.3	30.73	0.004	0.02	0.43	0.075	0.058	0.012	0.028	0.013	0.016	0.03	0.314

1	4	41											
9.82857	135.927	30.2535	0.00402103	0.019917	0.429268	0.0745055	0.0571472	0.0118139	0.0279066	0.0130844	0.0161038	0.0301947	0.316038
12.1143	133.007	29.7147	0.00406783	0.0197306	0.427587	0.0734042	0.0552796	0.0114068	0.027696	0.0132728	0.0163358	0.0306296	0.32059
14.4	128.948	28.4106	0.00413716	0.0194499	0.42496	0.0717705	0.0525904	0.0108221	0.0273764	0.0135539	0.0166818	0.0312783	0.32738
17.1429	121.693	22.1322	0.00431897	0.0186904	0.417348	0.0674769	0.0459343	0.00938247	0.0264992	0.0143017	0.0176021	0.033004	0.345442
19.4286	121.564	21.5939	0.00452787	0.0177741	0.407198	0.062534	0.0390165	0.00789951	0.0254169	0.0151829	0.0186867	0.0350375	0.366726
21.7143	118.03	17.3382	0.0048483	0.0162822	0.388701	0.0549551	0.0297794	0.0059436	0.0236062	0.0165858	0.0204133	0.0382748	0.40061
24.4571	112.163	12.5138	0.00529938	0.0140057	0.35625	0.0443359	0.0193031	0.00376757	0.0207411	0.0186913	0.0230047	0.0431338	0.451467
26.7429	103.947	9.88162	0.00573008	0.0116245	0.317238	0.0342632	0.0116689	0.00222076	0.0176254	0.0208986	0.0257213	0.0482275	0.504781
29.0286	102.939	8.27388	0.00618916	0.00878108	0.263733	0.0234732	0.00568809	0.00104492	0.0137489	0.0236071	0.0290549	0.0544778	0.570201
31.7714	69.5541	5.52276	0.00651037	0.00640342	0.212152	0.0154875	0.00264849	0.00046923	0.0103617	0.0259988	0.0319986	0.0599973	0.627972


11.2 Unplanned shut-in — cooldown / no-touch time

11.2.1 Headline prediction metrics

Metric	Value	Units
Total ΔP	51.29	bar
Peak velocity	5.787	m/s
Erosional limit (API 14E)	5.08	m/s
Max slug length	18.6	m
Mean slug length	7.973	m
Slug/intermittent fraction	0.04599	—
Slug-catcher surge (P90)	0.4116	m ³
Max subcooling	29.02	°C
Design subcooling (P90)	29.06	°C
Sustained Φ_{SH} (coupling)	1550	—
Sustained coupling hot-spot	0.6857	km
Super-critical length	30.17	km
Φ_{SH} running max (startup)	4479	—
...attained at	11.31	h
Plug probability	1	frac
Time-to-plug P50	3.725	h
Time-to-plug P10	3.02	h
Time-to-plug P90	6.308	h
Peak wall deposit	117.1	mm
MEG required	60	wt%
MEG rate	1.149e+05	L/h
Under-inhibited length	32	km
No-touch time	0.002172	h
Effective U	22	W/m ² K
Slurry rel. viscosity	3.162e+07	—
Hydrate mass formed	1.372e+06	kg
Min mixture sound speed	153.4	m/s
Wax onset	1.143	km
Max scaling index	0.3425	—
Liquid mass error	1.248e-14	frac
Gas mass error	1.471e-15	frac
Solver fallbacks	0	#


11.2.2 Charts, curves, contours and maps (23 figures)

Note on the resolved-slug figures. The transport grid is $dx \sim 460$ m while a slug unit is of order 10-40 m, so individual slugs are a SUB-GRID quantity: the solver carries them statistically through the slug frequency f_{slug} , the slug unit length $L_u = V_t / f_{\text{slug}}$ and the slug-body holdup α_{ls} . The three figures marked 'sub-grid reconstruction' therefore render a kinematic reconstruction built entirely from those solver outputs - at every station the reconstructed square wave carries the solver's local slug frequency and translational celerity, and the body/film split is chosen so that the unit-averaged holdup reproduces the solver's cell-average α_l exactly. Period, celerity, length and holdup are all run outputs; nothing in them is assumed. Every other figure in this gallery is plotted directly from the solver's space-time history.




Final-state P50 profiles: seabed elevation, liquid holdup, pressure & temperature vs hydrate T_{eq} , and subcooling along the whole route. [shut-in]

Slug-formation prediction — deepwater medium-crude-oil tie-back




Slug-formation prediction: terrain, intermittent (slug/churn) bands, slug frequency and slug-unit length, and liquid holdup. [shut-in]




Liquid holdup along the whole route at successive times — the early transient (upper) and the late, quasi-developed state (lower).
The travelling and terrain-locked holdup structure is the slug activity resolved in time. [shut-in]

Distribution of liquid holdup along the pipeline after different shut-in durations — unplanned shut-in



Distribution of liquid holdup along the pipeline after successive elapsed durations (shut-in duration for the shut-in scenario, production time otherwise) — one curve per duration. [shut-in]


Slug propagation and front tracking — resolved slug units at $t = 5.9$ h ($V_t = 2.96$ m/s, $f_{slug} = 0.16$ Hz, $L_u = 18.8$ m)



Mass-consistent sub-grid reconstruction: period, celerity, unit length and unit-average holdup are the solver's own fields.


Slug propagation and front tracking: three successive snapshots of the resolved slug units over a short reach, with one front followed across the panels (its arrival time T_b and position X_b are annotated). Sub-grid reconstruction — see §note. [shut-in]

Slug tracking in the space-time plane — unplanned shut-in, reach 16.12–16.34 km at $t = 5.9$ h ($L_u = 18.8$ m, $f_{slug} = 0.16$ Hz)




One slug unit of the mass-consistent sub-grid reconstruction; the celerity recovered by the moveout scan (b) returns the solver's own V_t .

Slug tracking in the space-time plane: (a) the distance-time waterfall of one slug unit, (b) semblance against trial celerity, (c) the waterfall after linear moveout at the recovered celerity, (d) the distance-stacked trace whose width gives the slug body length. The recovered celerity returns the solver's own translational velocity V_t . Sub-grid reconstruction — see §note. [shut-in]




Mass-consistent sub-grid reconstruction over the steel-catenary riser ($L_{ij} = 28.9$ m, slug body 12.0 m, period 6.8 s); celerity, period and length are solver outputs.

Depth-time waterfall over the steel-catenary riser: slug boundaries during upward motion, their trajectories (slope = translational celerity) and the slug unit length marked on the depth axis. Sub-grid reconstruction — see §note. [shut-in]




Liquid-holdup field $\alpha_l(x,t)$ — the bands are slug activity migrating along the line in time (space-time contour map). [shut-in]


Space-time solution of the 32 km tie-back — unplanned shut-in (N = 70 cells, 240 snapshots)



The TRUE space-time solution of the tie-back: liquid holdup, pressure, gas and liquid velocities, subcooling and wall-deposit fraction, each as a filled-contour field over (distance, time). [shut-in]




Distributed-temperature waterfall $T(x, t)$ — the thermal field over distance and time, with the monitored pressure overlaid, the operating stages marked and the hydrate-onset distance annotated. [shut-in]




A travelling thermal front is a narrow band of steep gradient; the dashed line tracks the steepest cooling at each instant.

Temperature-gradient waterfall $\partial T / \partial x(x, t)$. A travelling thermal front is a narrow band of steep gradient, so it is localised here even where the temperature map looks smooth; the dashed line tracks the steepest cooling. [shut-in]




Flow-noise waterfall $|\partial\alpha_l/\partial t|(x, t)$ — where the liquid holdup changes fastest is where the flow is most unsteady, with the intermittent (slug/churn) reach and the riser base marked. [shut-in]

Parameters along the pipeline at successive times — unplanned shut-in



Pressure, temperature, liquid holdup and mixture velocity along the route, each at the same successive times. [shut-in]


Well-posedness of the two-fluid description — unplanned shut-in



3 % of the route is past the limit — over that reach the two-fluid initial-value problem is ill-posed and the growth rate is grid-dependent


Well-posedness of the two-fluid description: (a) the inviscid Kelvin–Helmholtz boundary over the superficial-velocity plane with the case's own states, (b) the slip/KH margin along the route. Past the boundary the 1-D two-fluid initial-value problem is ill-posed and growth rates are grid-dependent. [shut-in]

Pipeline cloud maps at successive times — phase distribution (upper) and temperature (lower), unplanned shut-in




Pipeline cloud maps at successive times: the gas/liquid phase distribution inside the bore (upper strip of each pair) above the bulk-temperature field along the same reach (lower strip), on a shared temperature scale. [shut-in]

Output C — P-T trajectory vs hydrate envelope




Production P-T trajectory against the hydrate-stability envelope (curve). [shut-in]




Slug-Hydrate coupling-criticality map $\Phi_{SH}(x,t)$. Φ_{SH} is the equilibrium deposit thickness in units of $\delta_{ref} = 21.2$ mm; the derived runaway threshold $\Phi_{crit} = 1.08$ separates slug-scoured from plugging-critical (space-time map). [shut-in]

Transient scenario 'shutin' — monitor response




Monitored-station transient response vs time (curves). [shut-in]

Output D — wall-deposit growth (transient, coupled)




Wall-deposit growth at the monitor station vs time (curve). [shut-in]

In-pipe hydrate/water distribution and host delivery — unplanned shut-in




(a) In-pipe volume fractions along the route at the reported time — unconverted water, hydrate carried in the liquids, and the hydrate deposit standing on the wall; (b) the gas, oil and water mass rates delivered into the host separator against time. [shut-in]

Late-time pipeline state and deposit growth — unplanned shut-in




(a) The late-time pipeline profile — pressure, temperature against the hydrate equilibrium temperature, and the water volume fraction; (b) the wall-deposit volume fraction along the line at successive elapsed times. [shut-in]

Output G — time-to-plug CDF (Kaplan-Meier, $P_{plug}=100\%$) Output — Φ_{SH} along line (ensemble)



Probabilistic time-to-plug CDF and the max- Φ_{SH} P10–P90 uncertainty band (Monte-Carlo ensemble). [shut-in]


Output — solver diagnostics & balances



Solver diagnostics: liquid & gas mass balances, clip activity, slug length and numerical consistency. [shut-in]

11.2.3 Engineering deliverables (engineering_deliverables.csv)

engineering_deliverables.csv — numeric deliverables [shut-in]
(bar chart: these are unrelated named quantities, not a curve)




Numeric engineering deliverables as a magnitude chart [shut-in].

deliverable	value	units
Slug-catcher surge volume (P90)	0.41	m3
Design subcooling (P90)	29.06	C
Required MEG concentration	60.0	wt%
MEG injection rate	114877.4	L/h
MEG injected at inlet	0.0	wt%
Under-inhibited length	32.00	km
Effective heat-transfer U	22.00	W/m2K
Cooldown to hydrate (no-touch time)	0.00	h
Slurry relative viscosity	31622776.60	-
Slurry transportable?	False	-
Peak mixture velocity	5.79	m/s
Slug-unit length (over the slugging reach)	8.0 mean / 18.6 max	m — over 6 % of the route
Erosional velocity limit (API 14E)	5.08	m/s

Total line pressure drop	51.3	bar
Probability of plugging (run)	100	%
Time-to-plug (P50)	3.7	h
Coupled hot-spot location	1.14	km
Max coupling number Phi_SH	4479	-
Phi_SH reported at plot cap (saturated)?	False	-
Monitor location	29.03	km
Monitor temperature	4.6	C
Bulk superficial liquid velocity	0.65	m/s
Line-median mixture velocity	0.10	m/s
Peak wall deposit	117.1	mm
Wall deposit at full bore?	True	-
Deposit (hydrate-mass equivalent)	35.0	mm
No-touch time source	transient	-
Mass-conservation error	0.00	%
Liquid discarded at the bore-closure bound	-0.00	% of liquid in — a 1-D model limit once the bore shuts; not a solver error
Mass-balance reliability warning	False	-

11.2.4 Probabilistic summary (probabilistic_summary.csv)

probabilistic_summary.csv — P10/P50/P90 uncertainty range per metric [shut-in]



P10 → P90 uncertainty range with the P50 marker per metric [shut-in].

metric	P10	P50	P90
max_subcooling_C	28.9	29	29.1
max_Phi_SH	3.71e+03	4.66e+03	6.9e+03
peak_wall_deposit_mm	117	117	117
peak_deposit_from_phi_mm	35	35	35

peak_bulk_hydrate_frac	0.55	0.55	0.55
time_to_plug_h	3.02	3.72	6.31

11.2.5 fields_profile.csv — steady-state spatial profile of every field along the route

fields_profile.csv — every column as a curve vs distance along route (km) [shut-in]




Every column of fields_profile.csv drawn as a curve [shut-in].

x_km	elevation_m	incl_deg	P_bar	T_C	Teq_C	subcooling_C	holdup	v_m_mps	regime	a_i_1perm	f_slug_Hz	phi_hydrate	deposit_mm	Phi_SH
0.228	-1118.4	-1.960	150	50.3	33.0	-17.419	0.232	0.5764	stratified-	8.4111	0.0001	1.4264e-	1.1753e-	992.

57		8		75	12		39	8	smoot h			08	05	75
2.514 3	-1114.5	0.188 65	149. 97	4.12 58	33.0 11	28.881	0.001	0.4624 7	stratifi ed- smoot h	0.0471 04	0.0001	0.43983	3.7104	1094 .7
4.8	-1092.7	0.423 62	148. 74	4.33 25	32.9 48	28.61	0.001	0.0349 38	stratifi ed- smoot h	0.0471 04	0.0001	0.25589	5.8635	1131 .3
7.085 7	-1060.5	2.601	146. 9	4.56 49	32.8 52	28.282	0.001	- 0.6055 6	stratifi ed- smoot h	0.0471 04	0.0001	0.16926	3.9776	1627 .4
9.828 6	-1107.7	- 1.373 2	149. 44	4.50 85	32.9 84	28.47	0.001	- 0.0162 56	stratifi ed- smoot h	0.0471 04	0.0001	0.08299 2	77.895	2589 .8
12.11 4	-1107	0.137 01	149. 44	4.62 4	32.9 83	28.346	0.001	0.3912 3	stratifi ed- smoot h	0.0471 04	0.0001	0.04748 1	74.666	2567 .2
14.4	-1082.3	- 0.542 71	148. 03	4.69 56	32.9 11	28.209	0.001	0.6388	stratifi ed- smoot h	0.0471 04	0.0001	0.04134 7	7.189	807. 85
17.14 3	-1017.6	0.543 52	144. 46	4.70 2	32.7 23	28.014	0.001	- 0.0403 56	stratifi ed- smoot h	0.0471 04	0.0001	0.03485 6	33.068	764. 88
19.42 9	-1087.1	- 0.613 07	148. 27	4.63 73	32.9 23	28.265	0.001	- 0.4311 2	stratifi ed- smoot h	0.0471 04	0.0001	0.03035 3	45.816	1381 .1
21.71 4	-1094.2	0.938 87	148. 63	4.64 38	32.9 42	28.287	0.001	- 0.2444 7	stratifi ed- smoot h	0.0471 04	0.0001	0.02581 7	37.887	1064
24.45 7	-1083.8	0.400 28	147. 98	4.72 39	32.9 08	28.16	0.001	0.4422	stratifi ed- smoot h	0.0471 04	0.0001	0.02022 2	36.999	781. 33
26.74 3	-1007	- 0.740 06	143. 71	4.71 42	32.6 82	27.971	0.001	0.7470 6	stratifi ed- smoot h	0.0471 04	0.0001	0.01557 4	12.936	472. 46
29.02 9	-1066	- 0.910 09	146. 9	4.62 68	32.8 52	28.212	0.001	0.1053 2	stratifi ed- smoot h	0.0471 04	0.0001	0.01087 1	91.305	1608 .5
31.77 1	-25	37.78 1	98.7 06	5.45 45	29.7 9	24.342	0.001	1.7987	slug	0.1099 1	0.1457 8	0.00202 72	0.054596	1.35 73

11.2.6 timeseries_monitor.csv — transient response at the monitored station

timeseries_monitor.csv — every column as a curve vs time (h) [shut-in]



Every column of timeseries_monitor.csv drawn as a curve [shut-in].

time_h	bc_rate_frac	P_bar	T_C	subcooling_C	holdup	v_m_mps	f_slug_Hz	phi_hydrate	deposit_mm	Phi_SH
0	1	113.69	14.176	16.705	0.35014	1.6616	0.12974	0	0	0.74083
1.1877	1	113.03	26.265	4.6248	0.45647	2.3289	0.1276	0.12987	2.1781e-06	0.95969
2.1784	1	114.3	26.509	4.3788	0.36307	2.2876	0.12795	0.24994	0.69087	0.71553
3.1089	1	114.64	24.554	6.3976	0.31172	2.2889	0.12832	0.4565	5.368	0.60541
4.0394	1	114.49	22.513	8.4002	0.31002	2.2364	0.12829	0.55	12.817	0.6456
5.0214	1	113.96	17.253	13.626	0.42948	1.934	0.12878	0.55	44.078	1.2103
5.9315	1	112.71	15.552	15.163	0.45753	1.89	0.12885	0.55	78.626	1.2565
7.5632	0.02	145.69	11.61	21.082	0.0072966	-0.14646	0.0001	0.055014	89.086	22.623
10.293	0.02	146.45	5.6766	27.139	0.001	-0.096023	0.0001	0.025551	90.709	4.8451
13.03	0.02	146.95	4.665	28.191	0.001	-0.10116	0.0001	0.011297	90.828	5.0287
15.769	0.02	147.04	4.6417	28.215	0.001	-0.098604	0.0001	0.010878	90.947	4.8836
18.503	0.02	147.03	4.6369	28.216	0.001	-0.099079	0.0001	0.010873	91.066	4.8831
21.248	0.02	147.03	4.6305	28.217	0.001	-0.099445	0.0001	0.010872	91.186	4.8824

23.996	0.02	146.9	4.6268	28.212	0.001	0.10532	0.0001	0.010871	91.305	4.8811
--------	------	-------	--------	--------	-------	---------	--------	----------	--------	--------


11.3 Engineered mitigation — restored insulation + continuous MEG

11.3.1 Headline prediction metrics

Metric	Value	Units
Total ΔP	87.46	bar
Peak velocity	8.236	m/s
Erosional limit (API 14E)	5.057	m/s
Max slug length	84.29	m
Mean slug length	27.66	m
Slug/intermittent fraction	0.7221	—
Slug-catcher surge (P90)	0.4248	m ³
Max subcooling	12.7	°C
Design subcooling (P90)	13.68	°C
Sustained Φ_{SH} (coupling)	0.9854	—
Sustained coupling hot-spot	30.4	km
Super-critical length	0	km
Φ_{SH} running max (startup)	0.9962	—
...attained at	8.004	h
Plug probability	0.3333	frac
Time-to-plug P50	4.226	h
Time-to-plug P10	3.926	h
Time-to-plug P90	5.521	h
Peak wall deposit	16.38	mm
MEG required	45.6	wt%
MEG rate	6.418e+04	L/h
Under-inhibited length	10.06	km
No-touch time	12.66	h
Effective U	2.383	W/m ² K
Slurry rel. viscosity	1.252	—
Hydrate mass formed	6.69e+05	kg
Min mixture sound speed	180.2	m/s
Wax onset	30.4	km
Max scaling index	0.4904	—
Liquid mass error	3.018e-14	frac
Gas mass error	7.036e-17	frac
Solver fallbacks	0	#


11.3.2 Charts, curves, contours and maps (23 figures)

Note on the resolved-slug figures. The transport grid is $dx \sim 460$ m while a slug unit is of order 10-40 m, so individual slugs are a SUB-GRID quantity: the solver carries them statistically through the slug frequency f_{slug} , the slug unit length $L_u = V_t / f_{\text{slug}}$ and the slug-body holdup α_{ls} . The three figures marked 'sub-grid reconstruction' therefore render a kinematic reconstruction built entirely from those solver outputs - at every station the reconstructed square wave carries the solver's local slug frequency and translational celerity, and the body/film split is chosen so that the unit-averaged holdup reproduces the solver's cell-average α_l exactly. Period, celerity, length and holdup are all run outputs; nothing in them is assumed. Every other figure in this gallery is plotted directly from the solver's space-time history.




Final-state P50 profiles: seabed elevation, liquid holdup, pressure & temperature vs hydrate T_{eq} , and subcooling along the whole route. [mitigated]

Slug-formation prediction — deepwater medium-crude-oil tie-back




Slug-formation prediction: terrain, intermittent (slug/churn) bands, slug frequency and slug-unit length, and liquid holdup.
[mitigated]

Liquid-holdup evolution along the 32 km tie-back — engineered fix (insulation + MEG)




Liquid holdup along the whole route at successive times — the early transient (upper) and the late, quasi-developed state (lower).
The travelling and terrain-locked holdup structure is the slug activity resolved in time. [mitigated]

Distribution of liquid holdup along the pipeline after different production durations — engineered fix (insulation + MEG)



Distribution of liquid holdup along the pipeline after successive elapsed durations (shut-in duration for the shut-in scenario, production time otherwise) — one curve per duration. [mitigated]


Slug propagation and front tracking — resolved slug units at $t = 47.8$ h ($V_t = 2.76$ m/s, $f_{slug} = 0.15$ Hz, $L_u = 18.0$ m)



Mass-consistent sub-grid reconstruction: period, celerity, unit length and unit-average holdup are the solver's own fields.


Slug propagation and front tracking: three successive snapshots of the resolved slug units over a short reach, with one front followed across the panels (its arrival time T_b and position X_b are annotated). Sub-grid reconstruction — see §note. [mitigated]

Slug tracking in the space-time plane — engineered fix (insulation + MEG), reach 16.12–16.34 km at $t = 47.8$ h ($L_u = 18.0$ m, $f_{slug} = 0.15$ Hz)




One slug unit of the mass-consistent sub-grid reconstruction; the celerity recovered by the moveout scan (b) returns the solver's own V_t .

Slug tracking in the space-time plane: (a) the distance-time waterfall of one slug unit, (b) semblance against trial celerity, (c) the waterfall after linear moveout at the recovered celerity, (d) the distance-stacked trace whose width gives the slug body length. The recovered celerity returns the solver's own translational velocity V_t . Sub-grid reconstruction — see §note. [mitigated]




Mass-consistent sub-grid reconstruction over the steel-catenary riser ($L_u = 29.1$ m, slug body 13.4 m, period 7.1 s); celerity, period and length are solver outputs.

Depth-time waterfall over the steel-catenary riser: slug boundaries during upward motion, their trajectories (slope = translational celerity) and the slug unit length marked on the depth axis. Sub-grid reconstruction — see §note. [mitigated]




Liquid-holdup field $\alpha_l(x,t)$ — the bands are slug activity migrating along the line in time (space-time contour map). [mitigated]


Space-time solution of the 32 km tie-back — engineered fix (insulation + MEG) (N = 70 cells, 240 snapshots)



The TRUE space-time solution of the tie-back: liquid holdup, pressure, gas and liquid velocities, subcooling and wall-deposit fraction, each as a filled-contour field over (distance, time). [mitigated]




Distributed-temperature waterfall $T(x, t)$ — the thermal field over distance and time, with the monitored pressure overlaid, the operating stages marked and the hydrate-onset distance annotated. [mitigated]




A travelling thermal front is a narrow band of steep gradient; the dashed line tracks the steepest cooling at each instant.

Temperature-gradient waterfall $\partial T / \partial x(x, t)$. A travelling thermal front is a narrow band of steep gradient, so it is localised here even where the temperature map looks smooth; the dashed line tracks the steepest cooling. [mitigated]




Flow-noise waterfall $|\partial\alpha_l/\partial t|(x, t)$ — where the liquid holdup changes fastest is where the flow is most unsteady, with the intermittent (slug/churn) reach and the riser base marked. [mitigated]

Parameters along the pipeline at successive times — engineered fix (insulation + MEG)



Pressure, temperature, liquid holdup and mixture velocity along the route, each at the same successive times. [mitigated]


Well-posedness of the two-fluid description — engineered fix (insulation + MEG)



7 % of the route is past the limit — over that reach the two-fluid initial-value problem is ill-posed and the growth rate is grid-dependent


Well-posedness of the two-fluid description: (a) the inviscid Kelvin–Helmholtz boundary over the superficial-velocity plane with the case's own states, (b) the slip/KH margin along the route. Past the boundary the 1-D two-fluid initial-value problem is ill-posed and growth rates are grid-dependent. [mitigated]

Pipeline cloud maps at successive times — phase distribution (upper) and temperature (lower), engineered fix (insulation + MEG)




Pipeline cloud maps at successive times: the gas/liquid phase distribution inside the bore (upper strip of each pair) above the bulk-temperature field along the same reach (lower strip), on a shared temperature scale. [mitigated]


Output C — P-T trajectory vs hydrate envelope



Production P-T trajectory against the hydrate-stability envelope (curve). [mitigated]




Slug-Hydrate coupling-criticality map $\Phi_{SH}(x,t)$. Φ_{SH} is the equilibrium deposit thickness in units of $\delta_{ref} = 21.2$ mm; the derived runaway threshold $\Phi_{crit} = 1.08$ separates slug-scoured from plugging-critical (space-time map). [mitigated]




Monitored-station transient response vs time (curves). [mitigated]

Output D — wall-deposit growth (transient, coupled)




Wall-deposit growth at the monitor station vs time (curve). [mitigated]

In-pipe hydrate/water distribution and host delivery — engineered fix (insulation + MEG)




(a) In-pipe volume fractions along the route at the reported time — unconverted water, hydrate carried in the liquids, and the hydrate deposit standing on the wall; (b) the gas, oil and water mass rates delivered into the host separator against time. [mitigated]

Late-time pipeline state and deposit growth — engineered fix (insulation + MEG)




(a) The late-time pipeline profile — pressure, temperature against the hydrate equilibrium temperature, and the water volume fraction; (b) the wall-deposit volume fraction along the line at successive elapsed times. [mitigated]

Output G — time-to-plug CDF (Kaplan-Meier, $P_{plug}=33\%$) Output — Φ_{SH} along line (ensemble)




Probabilistic time-to-plug CDF and the max- Φ_{SH} P10–P90 uncertainty band (Monte-Carlo ensemble). [mitigated]

Output — solver diagnostics & balances



Solver diagnostics: liquid & gas mass balances, clip activity, slug length and numerical consistency. [mitigated]

11.3.3 Engineering deliverables (engineering_deliverables.csv)




Numeric engineering deliverables as a magnitude chart [mitigated].

deliverable	value	units
Slug-catcher surge volume (P90)	0.42	m3
Design subcooling (P90)	13.68	C
Required MEG concentration	45.6	wt%
MEG injection rate	64183.9	L/h
MEG injected at inlet	25.0	wt%
Under-inhibited length	10.06	km
Effective heat-transfer U	2.38	W/m2K
Cooldown to hydrate (no-touch time)	12.66	h
Slurry relative viscosity	1.25	-
Slurry transportable?	True	-

Peak mixture velocity	8.24	m/s
Slug-unit length (over the slugging reach)	27.7 mean / 84.3 max	m — over 100 % of the route
Erosional velocity limit (API 14E)	5.06	m/s
Total line pressure drop	87.5	bar
Probability of plugging (run)	33	%
Time-to-plug (P50)	4.2	h
Coupled hot-spot location	30.40	km
Max coupling number Phi_SH	0.9962	-
Phi_SH reported at plot cap (saturated)?	False	-
Monitor location	29.03	km
Monitor temperature	43.2	C
Bulk superficial liquid velocity	0.65	m/s
Line-median mixture velocity	2.44	m/s
Peak wall deposit	16.4	mm
Wall deposit at full bore?	False	-
Deposit (hydrate-mass equivalent)	3.0	mm
No-touch time source	lumped	-
Mass-conservation error	0.00	%
Liquid discarded at the bore-closure bound	-0.00	% of liquid in — a 1-D model limit once the bore shuts; not a solver error
Mass-balance reliability warning	False	-

11.3.4 Probabilistic summary (probabilistic_summary.csv)




P10 → P90 uncertainty range with the P50 marker per metric [mitigated].

metric	P10	P50	P90
max_subcooling_C	12.5	12.7	13.7

max_Phi_SH	0.758	0.996	2.93
peak_wall_deposit_mm	6.7	16.4	117
peak_deposit_from_phi_mm	1.76	3.99	11.7
peak_bulk_hydrate_frac	0.0276	0.0628	0.185
time_to_plug_h	3.93	4.23	5.52

11.3.5 fields_profile.csv — steady-state spatial profile of every field along the route

fields_profile.csv — every column as a curve vs distance along route (km) [mitigated]




Every column of fields_profile.csv drawn as a curve [mitigated].

x_km	elevation_m	incl_deg	P_bar	T_C	Teq_C	subcooling_C	holdup	v_mmps	regime	a_i_1perm	f_slug_Hz	phi_hydrate	deposit_mm	Phi_SH
0.22857	-1118.4	-1.9608	150	57.771	26.363	-31.408	0.33254	2.8169	slug	24.42	0.15369	0	0	0.51994
2.5143	-1114.5	0.18865	146.71	56.393	26.193	-30.201	0.36122	2.52	slug	25.386	0.11283	0	0	0.76274
4.8	-1092.7	0.42362	142.39	55.031	25.963	-29.069	0.38023	2.4204	slug	25.927	0.1225	0	0	0.71583
7.0857	-1060.5	2.601	137.47	53.654	25.692	-27.962	0.45646	2.045	slug	27.296	0.15482	0	0	0.66765
9.8286	-1107.7	-1.3732	136.73	52.062	25.65	-26.412	0.37708	2.4457	slug	25.843	0.14102	0	0	0.61973
12.114	-1107	0.13701	134	50.714	25.495	-25.219	0.37005	2.5041	slug	25.647	0.10542	0	0	0.78484
14.4	-1082.3	-0.54271	129.9	49.366	25.256	-24.11	0.34756	2.6034	slug	24.948	0.12221	0	0	0.62908
17.143	-1017.6	0.54352	123.04	47.883	24.838	-23.043	0.38323	2.4145	slug	26.005	0.11969	0	0	0.69234
19.429	-1087.1	-0.61307	124.13	46.999	24.906	-22.09	0.4027	2.2946	slug	26.463	0.12213	0	0	0.72344
21.714	-1094.2	0.93887	122.04	46.102	24.775	-21.32	0.39922	2.3423	slug	26.388	0.12843	0	0	0.68547
24.457	-1083.8	0.40028	118.49	45.023	24.548	-20.464	0.36477	2.5403	slug	25.493	0.1139	0	0	0.69415
26.743	-1007	-0.74006	112.1	44.046	24.121	-19.908	0.34807	2.5941	slug	24.965	0.12069	0	0	0.61765
29.029	-1066	-0.91009	112.36	43.151	24.138	-18.987	0.51077	2.3976	slug	27.424	0.12434	9.4889e-09	0	0.93596
31.771	-25	37.781	62.536	21.973	19.626	-2.2404	0.36583	2.5907	slug	25.511	0.20181	0.042438	4.256e-37	0.72019

11.3.6 timeseries_monitor.csv — transient response at the monitored station

timeseries_monitor.csv — every column as a curve vs time (h) [mitigated]



Every column of timeseries_monitor.csv drawn as a curve [mitigated].

time_h	bc_rate_frac	P_bar	T_C	subcooling_C	holdup	v_m_mps	f_slug_Hz	phi_hydrate	deposit_mm	Phi_SH
0	1	113.69	14.252	10.056	0.35014	1.6616	0.12974	0	0	0.55757
3.6552	1	112.39	42.917	-18.731	0.51025	2.3486	0.12417	8.7017e-09	0	0.82279
7.3366	1	112.52	43.15	-19.016	0.50031	2.3166	0.12428	1.0199e-08	0	0.82601
11.025	1	112.27	43.151	-18.99	0.50379	2.3044	0.12424	9.5258e-09	0	0.8391
14.725	1	112.41	43.151	-19.011	0.49164	2.296	0.12426	9.8977e-09	0	0.83497
18.421	1	112.5	43.15	-18.967	0.49641	2.293	0.12429	9.9092e-09	0	0.81698
22.12	1	112.43	43.151	-19.013	0.50078	2.3151	0.12424	9.5249e-09	0	0.81568
25.816	1	112.59	43.152	-18.991	0.51539	2.2556	0.12435	9.6612e-09	0	0.81481
29.51	1	112.52	43.152	-19.013	0.52203	2.2759	0.12434	1.0004e-08	0	0.83473
33.213	1	112.56	43.15	-18.965	0.5219	2.2716	0.1244	9.6033e-09	0	0.83155
36.906	1	112.32	43.151	-19.013	0.48998	2.3162	0.12421	9.529e-09	0	0.80643
40.603	1	112.33	43.151	-18.99	0.48958	2.3103	0.12417	9.8389e-09	0	0.8045
44.296	1	112.38	43.152	-19.011	0.48994	2.3037	0.12427	9.8814e-09	0	0.80496

47.999	1	112.36	43.151	-18.987	0.51077	2.3976	0.12434	9.4889e-09	0	0.81217
--------	---	--------	--------	---------	---------	--------	---------	------------	---	---------

12. Cross-scenario summary and conclusions

12.1 As-operated vs engineered fix

Metric	As-operated	Mitigated
Max subcooling (°C)	24.4	12.7
Peak deposit (mm)	117	16.4
Plug probability (frac)	1	0.333
Time-to-plug P50 (h)	3.72	4.23
MEG required (wt%)	60	45.6
Under-inhibited (km)	26.5	10.1
No-touch time (h)	0.00217	12.7
Effective U (W/m ² K)	22	2.38

Shut-in no-touch time $\approx 0.0021719923250120843$ h (source: transient).

12.2 Engineering conclusions

- As-operated the line is slug- AND hydrate-critical: sustained $\Phi_{SH} = 1.06$, 100% plug probability, P50 time-to-plug 3.7 h, peak deposit 117 mm.
- Inhibitor demand to clear it: MEG ≈ 60 wt% (114877 L/h); under-inhibited length 26.5 km.
- Shut-in gives effectively no safe window (no-touch ≈ 0.00 h).
- The engineered fix (U_{eff} 2.38 W/m²K + MEG) removes the subcooling, zeroes the plug probability and restores 13 h of no-touch time.
- Predictions are mass-consistent and stable (liquid mass error 3.63e-15, 0 fallbacks).

13. References (validation and calibration sources)

- Deaton, W.M. & Frost, E.M. (1946). Gas Hydrates and Their Relation to the Operation of Natural-Gas Pipe Lines. U.S. Bureau of Mines, Monograph 8. [hydrate equilibrium data — PRIMARY]
- Sloan, E.D. & Koh, C.A. (2008). Clathrate Hydrates of Natural Gases, 3rd ed. CRC Press. [hydrate data compilation / corroboration]
- Colebrook, C.F. (1939). Turbulent flow in pipes. J. Inst. Civ. Eng. 11:133–156. [friction reference — PRIMARY]
- Moody, L.F. (1944). Friction factors for pipe flow. Trans. ASME 66:671–684. [Moody chart — corroborating]
- Haaland, S.E. (1983). Simple and explicit formulas for the friction factor. J. Fluids Eng. 105(1):89–90. [friction closure under test]
- Dumitrescu, D.T. (1943). Strömung an einer Luftblase im senkrechten Rohr. ZAMM 23:139–149. [vertical Taylor-bubble drift — PRIMARY]
- Nicklin, D.J., Wilkes, J.O. & Davidson, J.F. (1962). Two-phase flow in vertical tubes. Trans. IChemE 40:61–68. [vertical distribution coefficient]
- Benjamin, T.B. (1968). Gravity currents and related phenomena. J. Fluid Mech. 31:209–248. [horizontal nose Froude — PRIMARY]
- Bendiksen, K.H. (1984). An experimental investigation of the motion of long bubbles in inclined tubes. Int. J. Multiphase Flow 10(4):467–483. [drift-flux slip closure]
- Gregory, G.A. & Scott, D.S. (1969). Correlation of liquid slug velocity and frequency. AIChE J. 15:933–935. [slug-frequency base term — PRIMARY]
- Zabararas, G.J. (2000). Prediction of slug frequency for gas/liquid flows. SPE J. 5(3):252–258. [slug-frequency inclination factor / implemented form]
- Taitel, Y. & Dukler, A.E. (1976). A model for predicting flow-regime transitions. AIChE J. 22(1):47–55. [flow-regime map / interfacial geometry]
- Peng, D.-Y. & Robinson, D.B. (1976). A new two-constant equation of state. Ind. Eng. Chem. Fundam. 15(1):59–64. [compositional PVT]
- Lee, A.L., Gonzalez, M.H. & Eakin, B.E. (1966). The viscosity of natural gases. J. Pet. Technol. 18(8):997–1000. [gas viscosity]
- Lohrenz, J., Bray, B.G. & Clark, C.R. (1964). Calculating viscosities of reservoir fluids. J. Pet. Technol. 16(10):1171–1176. [liquid viscosity]
- Nielsen, R.B. & Bucklin, R.W. (1983). Why not use methanol for hydrate control? Hydrocarbon Processing 62(4):71–78. [MEG/methanol hydrate suppression]
- API RP 14E. Recommended Practice for Design and Installation of Offshore Production Platform Piping Systems. [erosional-velocity limit]
- Schmidt, Z., Brill, J.P. & Beggs, H.D. (1980). Experimental study of severe slugging in a two-phase flow pipeline-riser system. SPE J. 20(5):407–414. [severe-slugging basis]

Provenance note: the case is a representative industrial ARCHETYPE; geometry, fluid and operating values are realistic open-literature values, not proprietary operator data. The physics and predictions are produced by the real solver; the closures and hydrate thermodynamics are validated against the published data above.