

## OBJECT RELATIONAL LAB (2)

**PLEASE NOTE THIS LAB ASSUMES YOU HAVE COMPLETED THE PREVIOUS Object Relational Lab**

**Make sure to read EACH section to the end before starting the exercises.**

### 2.1 Information about object types

We have seen already there are data dictionary views available to us. The following select statements can be used to list user types and their attributes.

```
SELECT * FROM USER_TYPES;  
SELECT * FROM USER_TYPE_METHODS;  
SELECT * FROM USER_TYPE_ATTRS;  
SELECT * FROM USER_OBJECTS;  
SELECT * FROM USER_SOURCE;
```

---

### 2.2 Subtypes

Subtypes can be created under an existing type using "UNDER". But subtypes can only be created under types that are not "FINAL", i.e. not at the bottom of the type hierarchy. For example, to create a subtype "O\_EMPLOYEE" under "person", the type "O\_PERSON" (from last week's exercises) must first be changed to "NOT FINAL". Because there is already an object table (person\_table) with objects attached to "person", the last word in the alter statement should be "CASCADE". That means that an alteration of "O\_PERSON" also applies to "person\_table" and its objects.

```
ALTER TYPE O_PERSON NOT FINAL CASCADE;
```

Next, a subtype "employee" can be generated under "person". This subtype can itself be either NOT FINAL or FINAL. A subtype inherits all columns from its supertype but can also have additional columns, which are declared within the brackets.

```
CREATE TYPE O_employee UNDER O_PERSON (  
    empno  INTEGER,  
    ppsn   VARCHAR2(10)  
) NOT FINAL ;
```

```
CREATE TABLE EMPLOYEE_TABLE OF O_PERSON
```

Row objects or indeed column objects can be created which can store person objects and any of its subtypes. This is called substitutability. However, this can be turned off by using the clause NOT SUBSTITUTABLE AT ALL LEVELS for the object table of column object definition.

The "IS OF" clause can be used to check the type of objects. The following statement selects all contacts who are also a person, i.e., it selects all rows in employee\_table. It assumes the EMPLOYEE\_TABLE was created using the person object type.

```
SELECT e.pname.lastname FROM employee_table e WHERE value(e) IS OF (O_PERSON);
```

### Exercise

1. Firstly, examine and create the objects below ( **note:** you should have these already created from the last lab),
2. Now, create a type "O\_EMPLOYEE" under "O\_PERSON" that has an additional attributes "emp\_ID", a "PPSN" and emp\_status which is a string . Create it as NOT FINAL. First you need to alter your individual type to allow inheritance:
3. Create a corresponding CONTACTS\_TABLE **object table** based on super type O\_PERSON
4. Insert 4 rows (2 of which are employees and 2 of which are persons).
5. Write a query that returns firstname, lastname of contacts that are employees ONLY (See Example above with IS OF). Extend the query to provide the number of employees in the table

### FOR REFERENCE PURPOSES

**NOTE YOU CREATED THESE OBJECT TYPES IN THE LAST LAB**

```
CREATE OR REPLACE TYPE O_STREET AS OBJECT (  
    SNAME VARCHAR2(30),  
    SNUMBER NUMBER,  
    FLATNUMBER VARCHAR2(5));
```

```
CREATE or REPLACE TYPE O_ADDRESS AS OBJECT (  
    STREET_AND_NUMBER O_STREET,  
    CITY VARCHAR2(30),  
    POSTAL_CODE VARCHAR2(8)  
);
```

```
CREATE OR REPLACE TYPE O_PHONE AS OBJECT (  
    HOMEPHONE          VARCHAR(15),  
    BUSINESSPHONE      VARCHAR2(15),  
    MOBILEPHONE         VARCHAR2(15));
```

```
CREATE OR REPLACE TYPE O_NAME AS OBJECT (
    FIRSTNAME          VARCHAR2(15),
    MIDDLE_INITIAL     VARCHAR2(2),
    LASTNAME           VARCHAR2(15));
```

```
CREATE OR REPLACE TYPE O_PERSON AS OBJECT (
    PNAME              O_NAME,
    PPHONE             O_PHONE,
    PADDRESS           O_ADDRESS);
```

--WANT TO START AFRESH

--Use these definitions. Please note all objects now start with OT\_

```
CREATE OR REPLACE TYPE OT_STREET AS OBJECT (
    SNAME VARCHAR2(30),
    SNUMBER NUMBER,
    FLATNUMBER VARCHAR2(5));
```

```
CREATE or REPLACE TYPE OT_ADDRESS AS OBJECT (
    STREET_AND_NUMBER OT_STREET,
    CITY VARCHAR2(30),
    POSTAL_CODE VARCHAR2(8)
);
```

```
CREATE OR REPLACE TYPE OT_PHONE AS OBJECT (
    HOMEPHONE          VARCHAR(15),
    BUSINESSPHONE      VARCHAR2(15),
    MOBILEPHONE        VARCHAR2(15));
```

```
CREATE OR REPLACE TYPE OT_NAME AS OBJECT (
    FIRSTNAME          VARCHAR2(15),
    MIDDLE_INITIAL     VARCHAR2(2),
    LASTNAME           VARCHAR2(15));
```

```
CREATE OR REPLACE TYPE OT_PERSON AS OBJECT (
    PNAME              OT_NAME,
    PPHONE             OT_PHONE,
    PADDRESS           OT_ADDRESS);
```

Sols

-----

```
ALTER TYPE O_PERSON NOT FINAL CASCADE;
```

```
CREATE TYPE O_EMPLOYEE UNDER O_PERSON
    (emp_id INTEGER,
    ppsn VARCHAR2(10),
    emp_status VARCHAR2(10)
    ) NOT FINAL;
```

Exercise 2: (

```

create table CONTACTS_table of O_PERSON;

INSERT INTO CONTACTS_TABLE VALUES (
  O_PERSON( O_NAME('JOHN', 'R', 'SMITH'),
    O_PHONE('123-4567', NULL, '73746-56'),
    O_ADDRESS(O_STREET('MARY ST', 3, '11A'),
      'DUBLIN',
      '1',
      'LEINSTER',
      'IRELAND')
    )
);

INSERT INTO CONTACTS_TABLE VALUES (
  O_PERSON( O_NAME('MARY', NULL, 'MILLER'),
    O_PHONE('354-5643', '453-5746', '73346-56'),
    O_ADDRESS(O_STREET('GRAFTON ST.', 212, NULL),
      'DUBLIN',
      '2',
      'LEINSTER',
      'IRELAND')
    )
);

INSERT INTO CONTACTS_TABLE VALUES (
  O_EMPLOYEE( O_NAME('MARY', 'S', 'MILLER'),
    O_PHONE('322-8484', NULL, '645-2929'),
    O_ADDRESS(O_STREET('OXFORD STREET', 443, NULL),
      'LONDON',
      'W10'
    ),
    1,
    '3533533M',
    'temporary'
  )
);

INSERT INTO CONTACTS_TABLE VALUES (
  O_EMPLOYEE( O_NAME('MATTHEW', 'P', 'HAYES'),
    O_PHONE('322-8484', NULL, '645-2929'),
    O_ADDRESS(O_STREET('OXFORD STREET', 443, NULL),
      'LONDON',
      'W10',
    ),
    2,
    '6767633N',
    'permanent'
  )
);

COMMIT;

```

### Exercise 3:

```

SELECT c.pname.firstname, c.pname.lastname FROM CONTACTS_table c WHERE
value(c) IS OF (O_EMPLOYEE);

```

```

SELECT COUNT(c.pname.lastname) FROM CONTACTS_table c WHERE value(c) IS OF
(O_EMPLOYEE);

```

### Exercise

6. Create a student supertype object type called Student\_T with the following attributes: ID, Name, phone, course ( choose appropriate DataTypes)
7. Create the following subtypes (allow for future inheritance from these subtypes)
  - i) PostGrad\_T that has 2 attributes ResearchGrantAmount\_T and researchArea
  - ii) Undergrad that has two attributes academic year e.g. year of study 1,2,3 and status e.g. FT or PT
8. Create an object table called CollegeStudents base on Student\_T
9. Insert 2 postgrad and 2 undergrad students into the table
10. Write a query that returns name of students that are postgrads Extend the query to provide the number of students in the table

Sols

6.

```
CREATE TYPE student_t as Object
(ID          INTEGER,
Name         VARCHAR2(30),
Phone        VARCHAR2(10),
course       VARCHAR2(30))
NOT FINAL;
```

7.

```
CREATE OR REPLACE TYPE postgrad UNDER student_t
(researchGrantAmount  NUMBER(7,2),
researchArea          VARCHAR2(50)
) NOT FINAL;
```

```
CREATE TYPE undergrad UNDER student_t
(academicYear INTEGER,
status        CHAR(2)
) NOT FINAL;
```

8.

```
CREATE TABLE CollegeStudents OF student_t;
```

9.

```
INSERT INTO CollegeStudents VALUES
(
    postgrad( 1001,
              'James',
              '087-123456',
              'Computing',
              12000.00,
              'Deep Learning'
            )
);
```

```
INSERT INTO CollegeStudents VALUES
(
    postgrad( 1002,
```

```

        'Jack',
        '089-16756',
        'Business',
        12000.00,
        'Macro Econom'
    )
);

INSERT INTO CollegeStudents VALUES
(
    undergrad( 1003,
        'Jane',
        '086-16756',
        'Arts',
        1,
        'FT'
    )
);

INSERT INTO CollegeStudents VALUES
(
    undergrad( 1003,
        'June',
        '088-89896',
        'Engineering',
        2,
        'FT'
    )
);

```

```

10.
SELECT c.name FROM CollegeStudents c WHERE value(c) IS OF (postgrad);

SELECT COUNT(*) FROM CollegeStudents c WHERE value(c) IS OF (student_t);

```

## 2.3 Primary Keys and Constraints

Even though an object-relational database maintains object IDs for all objects (i.e., for types, row objects, column objects), it is still a good idea to use primary keys for some tables. The following statement shows the object IDs. Obviously they are too long and would be too difficult to remember to be used directly by users. You can view OIDs using script below but do not try accessing them beyond this!

```
SELECT SYS_NC_OID$ FROM CONTACTS_TABLE;
```

Object tables can be altered so that they have primary keys. Let us assume `job_table` is an object table and it contains a attribute `job_ID`

```
ALTER TABLE job_table
ADD (CONSTRAINT jobIDPK PRIMARY KEY (job_ID));
```

In this case "jobIDPK" is the name of the constraint whereas `job_ID` is the name of an actual column in `job_table`. If `job_ID` contains duplicates, then the alter statement produces an error.

## Exercises

11. Alter the `contacts_table` (created above) that it has a primary key. The first `name`, `middle_initial` and `last_name` (i.e. an object type you created last week – check your definition! ) is the composite primary key for the `contacts_table`. Here is the ALTER command to add the Primary Key. Explain why the `.` notation is used.

```
ALTER TABLE contacts_table
ADD CONSTRAINT contactsPK PRIMARY KEY (PNAME.FIRSTNAME,
PNAME.MIDDLE_INITIAL, PNAME.LASTNAME);
```

12. Now alter the `job_table` (from last week's lab exercise) so that it `job_id` is primary key.
13. Please also add NOT NULL constraints for "jobtitle" column in the `job_table`. Use ALTER TABLE commands to achieve this

[ For Reference purposes. Created from last lab:

```
CREATE TYPE O_JOB AS OBJECT (
JOBTITLE VARCHAR(20),
JOB_ID INTEGER,
SALARY_AMOUNT INTEGER,
YEARS_OF_EXPERIENCE INTEGER );
```

```
CREATE TABLE JOB_TABLE OF O_JOB;
]
```

14. Design 2 object types
- a. **TeamType** – whose attributes are `team_name`, `year_established`, `league_name`, and the `home_stadium`
  - b. **PlayerType**– whose attributes are `player_name`, `age`, `nationality`, and `sign_on_fee`, `playing_position`
15. Create 1 **object** table called **Team** based on the **TeamType** object type you have just created. **Note** also `team_name` is the primary key of the **Team** table and the remaining attributes are mandatory.
16. Create a Relational Table called **UEFAPlayer** that has columns `UEFA_ID` (integer) `UEFAPlayerStatus`(varchar), `playerDetails`(`playerType`). Note: `UEFA_ID` (primary key,) `player_name`, `age`, `nationality`, and `playing_position` are all mandatory)
17. Insert 2 rows into each table.
18. Write a query that displays the `team_name`, `year_established` from **Team** for a particular team.
19. Write a query that displays `UEFA_ID`, `player_name`, `age` and `playing_position` from **UEFAPlayer** for a particular named player.

11.

```
ALTER TABLE contacts_table
  ADD CONSTRAINT contactSPK PRIMARY KEY (PNAME.FIRSTNAME,
PNAME.MIDDLE_INITIAL, PNAME.LASTNAME);
```

12.

```
ALTER TABLE job_table
  ADD (CONSTRAINT jobIDPK PRIMARY KEY (job_ID));
```

13.

```
ALTER TABLE job_table
  MODIFY(jobtitle NOT NULL);
```

--Or

```
ALTER TABLE job_table ADD CONSTRAINT job_table_cons1
  CHECK(jobtitle IS NOT NULL);
```

14.

```
CREATE OR REPLACE TYPE teamtype AS OBJECT
(teamname VARCHAR2(20),
year_est CHAR(4),
league_name VARCHAR2(40),
stadium VARCHAR2(40));
```

```
CREATE OR REPLACE TYPE playertype AS OBJECT (
playername VARCHAR2(20),
age INTEGER,
fee NUMBER(10,2),
nationality VARCHAR2(30),
playing_position VARCHAR2(40));
```

15.

```
CREATE TABLE team OF teamtype (
teamname PRIMARY KEY,
year_est NOT NULL,
league_name NOT NULL,
stadium NOT NULL );
```



```

16.
CREATE TABLE UEFAplayer(
UEFA_ID          INTEGER PRIMARY KEY,
UEFAPlayerStatus VARCHAR2(30) NULL,
playerDetails    playerType,
CONSTRAINT playernameCons CHECK(playerDetails.playername IS NOT
NULL),
CONSTRAINT ageCons CHECK (playerDetails.age IS NOT NULL),
CONSTRAINT ppositionCons CHECK (playerDetails.playing_position IS
NOT NULL) );

```

```

16.
INSERT INTO team VALUES(teamtype('Tottenham Hotspur', '1892', 'The
Premier League', 'White Hart Lane'));

```

```

INSERT INTO team VALUES(teamtype('Real Madrid', '1902', 'La Liga',
'Santiago Bernabéu Stadium'));

```

```

INSERT INTO UEFAplayer VALUES (
                                1,
                                'current',
                                playerType('connolly',
                                             21,
                                             200000,
                                             'ireland',
                                             'forward'
                                             )
                                );

```

```

INSERT INTO UEFAplayer VALUES (
                                2,
                                'current',
                                playerType('maguire',
                                             26,
                                             2000000,
                                             'england',
                                             'defender'
                                             )
                                );

```

18.

```

SELECT t.teamname,t.year_est
FROM team t
WHERE t.teamname='Real Madrid';

```

19.

```

SELECT UEFA_ID, u.playerDetails.playername, u.playerDetails.age,
u.playerDetails.nationality
FROM UEFAplayer u
WHERE u.playerDetails.playername='maguire';

```