

Do not use the STL `<list>` or Templates in your code. Do not change the specification or member functions interfaces or add extra member variables or you could get zero marks. Also do not use Structs, only use Classes.

Part A

1. Go back to your `ListOfInts` class files from Lab 5A and add an **overloaded stream insertion operator** `<<` which can be used for output of the List. If the List is empty this should output an "Empty List" message.
2. Now add a **copy constructor** for your list classes (Node and List).

Part B

3. Now make a Phone `Contacts` Class. A Contact has only two attributes, name (string) and number (integer), and corresponding accessor and mutator member functions.
4. Make a `NodeofContacts` class. A Node of Contacts only has two private member variables: `Contact theContact`, and `NodeofContacts* next`, and a constructor that sets values for the Contact's name and number, and the `next` pointer to `nullptr`.
5. Now make a singly Linked List of Contacts class called `ListofContacts`, which should have the following members functions:
 - a constructor `ListofContacts()` and a destructor `~ListofContacts()` methods
 - `bool insertFront(Contact)` which will be passed a contact object to insert at the front of the list
 - an overloaded stream insertion operator `<<` which will print out the name and number of all the contacts in the list
 - `Contact deleteFront()` which returns the contact at the head of the list, and deletes it from the list.
6. Implement a main function (in a separate source.cpp file) to test your `ListofBooks` class functionality.

Note: In Part B you should have 7 separate files. `Contacts.h`, `NodeofContacts.h`, `ListofContacts.h`, and corresponding `.cpp` files, `ListofContacts.cpp`, `NodeofContacts.cpp`, `Contacts.cpp` and `source.cpp`