UNIVERSITÀ
DI TRENTO

A system for estimating crowd density based on Wi-Fi probe request frames

Department of Information Engineering and Computer Science

Supervisors

Fabrizio Granelli
Daniele Miorandi

Student

Samuel Bortolin

Academic year 2019/2020

About this Project

External internship at U-Hopper:

Big Data Analytics

Business Intelligence

Chatbot

IoT solutions

Artificial Intelligence solutions

Problem Statement

Badly handled demand in company that provides services to physical customers can lead to overcrowding and inefficiency of the services

→ Inefficient and bad organized service leads to higher costs

→ It is important to avoid generating crowds to reduce the risk of COVID-19 spreading during this global pandemic period

State of the Art

→ Analysis of different methods for estimating crowd density

Infrared sensors, LSE, treadle switch-based systems, Video methods,

Audio methods, Wi-Fi, Bluetooth, BLE, LTE, Radar, RFID approaches

→ Many fields of application and several implementations

Why Wi-Fi Solution?

High diffusion of Wi-Fi devices

Low-cost implementation

Real-time data transmission

Customer privacy ensured

Standard 802.11 → Management frames → Probe request frames

Research Statement

Is it possible to continuously estimate the density of the crowd

in a place of interest based on the Wi-Fi probe request frames?

Achievements

Designed and developed a system for this problem that could work in several context

Tested the system in a Cafe and collected 4 weeks of data and manually-annotated ground truth

System Architecture



Scalable Architecture



Data Collector Logic









Back-End Logic









Presence of Devices



Presence of Devices



Presence of Devices



Feasibility Test at Home

Tests at home before validation

3 days of data collection

65928 probe request frames captured

12 home devices revealed

2 main range of RSSI -71 ÷ -91 not in the kitchen, -35 ÷ -69 in the kitchen

→ Feasibility of the method for detecting devices in the area

System Validation

→ Raspberry Pi in a Cafe where I annotate manually the ground truth

→ Eclipse Mosquitto Broker MQTT of U-Hopper on their server

→ MQTT receiver and MongoDB on U-Hopper server

→ Analyzer and Estimator on my pc to use on the data + collected ground truth to test accuracy and reliability of the proposed system

Ground Truth Collection





Ground Truth Collection





Ground Truth Collection





Test Results at Cafe

→ 4 weeks of data collection (24 days)

→ 1270 manual annotation of ground truth

→ 861979 probe request frames captured (~ 560MB)

→ 38771 MAC addresses revealed

Test Results at Cafe





Error Distribution

Mean Absolute Error = 1.731



Mean Squared Error = 5.710



Scatter Plot of the Error

High number of people, lower predictions



No systematic error



Low number of people, higher predictions

Summary

→ It is possible to continuously estimate the density of the crowd in a place of interest based on the Wi-Fi probe request frames

→ Designed and developed a reliable system to do that

→ Tested the system in a Cafe and collected 4 weeks of data and manually-annotated ground truth with an overall MAE of 1.731

Future Works

→ Real-time execution

→ Test of the system in different contexts

→ Extension to multiple data collectors

→ Improvement of the Machine Learning model

UNIVERSITÀ
DI TRENTO

A system for estimating crowd density based on Wi-Fi probe request frames

Thank you for your attention

Samuel Bortolin