

A forecasting system for electricity production and customer demand

Department of Information Engineering and Computer Science
Master's Degree in Artificial Intelligence Systems

Supervisors Student

Elisa Ricci Samuel Bortolin

Daniele Miorandi

Academic year 2021/2022



Problem Statement

- Global energy crisis caused an **increased volatility** in the electricity market
- Crucial for electricity suppliers to optimize the purchase of the necessary electricity
- Avoid to resort solely to the instantaneous electricity market
- Plan energy procurement strategies avoiding cost fluctuations and unbalanced fees
- Offer customers the necessary electricity and supply it at a competitive price



Problem Statement

- Vital to forecast customers' electricity demand
- Crucial to forecast production from own electricity generation facilities
- Understand the consumption habits of individual customers by establishing a reference consumption baseline
- Personalized energy solutions (dynamic pricing scheme, energy storage systems, ...)



Minergín Datasets

- Aggregated consumption data over all their customers, from 2 to 4 thousand (19 months)
- Production data from **8 photovoltaic plants** (from 2 to 10 months)
- Individual consumption data from **3 customers** (from 9 to 15 months)
- Weather data from Murcia airport, including solar energy data, as additional features



Research Questions


- Can the customers' electricity demand be forecasted based on past aggregated
 consumption data over the customers and historical weather data?
- Can the photovoltaic plants' production be forecasted based on past aggregated **production** data over the photovoltaic plants and historical weather data, including solar energy data?
- Can a consumption baseline of individual customers be established based on past consumption data of individual customers and historical weather data?




Achievements

- Designed a **novel forecasting system** for addressing the research questions
- Implemented a **prototype** of the system with a focus on key components
- Comprehensively evaluated the performance of a set of **developed models** for :
 - Electricity demand forecasting
 - Electricity production forecasting
 - Consumption baseline forecasting


























Samuel Bortolin












Implemented Prototype





Models

- Baselines: combination of previous days or weeks
- Statistical: ARIMA/SARIMA
- ML: SVR, Hist gradient boosting regressor, XGBoost regressor, and Prophet
- DL: LSTM, GRU, CNN, and TFT
- AutoML
- Combinations of Baselines, Prophet, and DL models



Performance Evaluation

MAPE and MAE as error metrics



Samuel Bortolin 16/28




Hourly Results

k = 12Split size = 30 days

Model	Blocked k-fold cross-validation MAPE	Test on the last split MAPE
TFT	15.0 ± 4.3	14.8
Best combination: GRU + One Week Baseline	/	14.8
GRU	30.8 ± 14.5	16.8
AutoML	/	17.0
CNN	34.6 ± 15.8	17.5
One Week Baseline	12.9 ± 4.3	17.6
SARIMA	15.4 ± 4.6	18.5
One Day Baseline	22.9 ± 7.1	20.5
LSTM	34.1 ± 11.9	23.2
Hist gradient boosting regressor	14.5 ± 5.5	29.3
SVR	61.8 ± 22.6	29.5
Prophet	28.7 ± 7.1	31.6
XGBoost regressor	16.9 ± 8.9	37.8



TFT Forecasts






Daily Results

k = 12Split size = 30 days

Model	Blocked k-fold cross-validation MAPE	Test on the last split MAPE
CNN	50.6 ± 36.8	7.5
XGBoost regressor	13.0 ± 4.4	7.7
Hist gradient boosting regressor	13.0 ± 5.5	9.8
Best combination: CNN + One Week Baseline	/	12.3
LSTM	29.6 ± 13.8	14.5
TFT	13.7 ± 5.1	14.9
One Week Baseline	11.5 ± 4.8	18.4
SARIMA	11.9 ± 7.0	19.6
GRU	28.8 ± 29.3	20.5
AutoML	/	21.0
One Day Baseline	22.8 ± 8.2	21.5
Prophet	19.1 ± 10.8	26.3
SVR	53.6 ± 22.4	39.8



CNN Forecasts






Hourly Results

k = 12Split size = 7 days

Model	Blocked k-fold cross-validation MAE normalized on PV plants' nominal power	Test on the last split MAE normalized on PV plants' nominal power
GRU	5.7 ± 1.8	2.8
Hist gradient boosting regressor	4.2 ± 1.0	3.0
SVR	5.2 ± 1.1	3.1
CNN	6.0 ± 1.5	3.3
Best combination: LSTM + One Day Baseline	/	3.4
XGBoost regressor	4.6 ± 1.0	3.4
LSTM	5.2 ± 1.5	3.5
TFT	4.7 ± 1.4	3.6
ARIMA	5.1 ± 1.4	3.6
Prophet	7.9 ± 1.6	4.4
One Day Baseline	6.8 ± 3.1	4.6
AutoML	/	5.9



GRU Forecasts





Hourly Results


k = 12Split size = 7 days

Model	Blocked k-fold cross-validation MAPE — MAE [kWh]	Test on the last split MAPE — MAE [kWh]
TFT	$47.3 \pm 5.6 - 0.29 \pm 0.03$	44.2 — 0.23
Hist gradient boosting regressor	$54.0 \pm 7.0 - 0.26 \pm 0.02$	50.4 — 0.23
SVR	$60.3 \pm 6.8 - 0.28 \pm 0.03$	60.4 — 0.24
SARIMA	$74.2 \pm 10.0 - 0.27 \pm 0.02$	78.0 — 0.24
XGBoost regressor	$73.7 \pm 9.5 - 0.28 \pm 0.02$	68.1 — 0.25
Prophet	$83.8 \pm 10.2 - 0.28 \pm 0.02$	81.9 — 0.25
GRU	58.9 ± 19.6 — 0.31 ± 0.04	42.6 — 0.26
LSTM	111.9 ± 212.1 — 0.46 ± 0.52	44.2 — 0.27
4 Week Baseline	74.1 ± 12.5 — 0.28 ± 0.03	79.1 — 0.27
12 Week Baseline	$74.3 \pm 13.7 - 0.27 \pm 0.02$	89.2 — 0.28
One Week Baseline	$82.7 \pm 12.8 - 0.33 \pm 0.03$	70.5 — 0.28
One Day Baseline	$75.8 \pm 14.0 - 0.32 \pm 0.04$	71.3 — 0.29
CNN	148.2 ± 30.1 — 0.51 ± 0.11	70.2 — 0.32
AutoML	/	61.6 — 0.34

MAE



TFT Forecasts





Daily Results


k = 12Split size = 7 days

Model	Blocked k-fold cross-validation MAPE — MAE [kWh]	Test on the last split MAPE — MAE [kWh]
4 Week Baseline	16.2 ± 4.9 — 1.9 ± 0.6	14.4 — 1.3
One Week Baseline	$19.6 \pm 7.5 - 2.3 \pm 0.9$	14.5 — 1.6
CNN	28.5 ± 17.5 — 3.3 ± 1.9	13.5 — 1.8
SARIMA	$16.4 \pm 4.8 - 1.9 \pm 0.5$	17.1 — 1.8
TFT	$16.7 \pm 6.3 - 2.0 \pm 0.6$	14.6 — 1.8
Hist gradient boosting regressor	$15.4 \pm 3.7 - 1.9 \pm 0.4$	16.8 — 1.9
12 Week Baseline	$15.6 \pm 4.4 - 1.9 \pm 0.5$	20.0 — 2.0
XGBoost regressor	$17.6 \pm 4.9 - 2.1 \pm 0.6$	21.4 — 2.1
AutoML	/	19.9 — 2.2
GRU	$18.7 \pm 3.4 - 2.5 \pm 0.5$	17.9 — 2.4
LSTM	$19.0 \pm 3.5 - 2.5 \pm 0.6$	18.4 — 2.4
One Day Baseline	$20.4 \pm 3.9 - 2.7 \pm 0.6$	19.0 — 2.4
Prophet	17.4 ± 5.2 — 1.9 ± 0.4	25.5 — 2.5
SVR	18.1 ± 3.2 — 2.4 ± 0.6	23.4 — 2.7

MAE



Baseline average 4 weeks Forecasts





Conclusions

- Global energy crisis caused an **increased volatility** in the electricity market
- Designed a **novel forecasting system** and implemented a **prototype** of the system
- Electricity production and customer demand can be accurately forecasted
- Consumption baseline cannot be accurately forecasted considering the high variability of the data of the provided customers and the limited amount of historical data
- AutoML struggled to achieve competitive results and model combinations resulted in an improvement to DL models only in a limited number of cases




Future Directions

- Ensemble learning techniques
- Additional features (socio-demographic, household, ...)
- Consumption disaggregation
- Full-fledged SaaS solution implementation




Model Training






Forecasting






Task Scheduler






One week baseline combined with GRU Forecasts






HistGradientBoostingRegressor Forecasts






HistGradientBoostingRegressor Forecasts






HistGradientBoostingRegressor Forecasts






GRU Forecasts





Baseline one week Forecasts





CNN Forecasts

