

1662 - Run-Length Encoding-Decoding

Description

Encoding is the process of transforming information from one format into another. There exist several different types of encoding scheme. In this problem we will talk about a very simple encoding technique; Run-Length Encoding.

Run-length encoding is a very simple and easy form of data compression in which consecutive occurrences of the same characters are replaced by a single character followed by its frequency. As an example, the string "AABBBBDAA" would be encoded to "A2B4D1A2", quotes for clarity. In this problem, we are interested in decoding strings that were encoded using the above procedure.

Input specification

The first line of input is an integer T ($T < 50$) that indicates the number of test cases. Each case is a line consisting of an encoded string. The string will contain only digits [0-9] and letters [A-Z]. Every inputted string will be valid. That is, every letter will be followed by 1 or more digits, with no leading zeros.

Output specification

For each case, output the case number followed by the decoded string. Adhere to the sample for exact format. You may assume the decoded string won't have a length greater than 200 and it will only consist of upper case alphabets.

Sample input

```
3
A2B4D1A2
A12
A1B1C1D1
```

Sample output

```
Case 1: AABBBBDAA
Case 2: AAAAAAAAAAA
```

Case 3: ABCD

Hint(s)

Source	Dairon Freddy Calderio Hechavarria
Added by	ymondelo20
Addition date	2011-12-07
Time limit (ms)	500
Test limit (ms)	500
Memory limit (kb)	130000
Output limit (mb)	64
Size limit (bytes)	30000
Enabled languages	C C# C++ Java Pascal Perl PHP Python Ruby Text