

# **Deploying a Service on EDITO Datalab**

Learn how to turn your script into a containerized web service and launch it on the EDITO platform.

By Samuel Fooks

Flanders Marine Institute (VLIZ)







# **What You'll Learn**

- ✓ Dockerize a script (R or Python)
- ✓ Push the image to a public Docker registry
- ✓ Configure a Helm chart
- Deploy the service on the EDITO playground
- ✓ Publish to production via Merge Request









### view\_parquet\_service

#### view\_parquet.Rmd

The view\_parquet.Rmd script provides an interactive tool to load, filter, and visualize Parquet datasets. It includes:

- Interactive Table: View and filter data using a searchable, paginated table.
- Map Visualization: Display geospatial data (e.g., points, polygons) on an interactive map using leaflet.
- **Download Filtered Data**: Export selected data as a CSV file.
- Metadata Schema: Display the schema of the loaded Parquet dataset.

Is not instructional (Tutorial), and doesn't only perform a specific calculation/rungenodel (Process).

### **Dockerfile Example**

```
FROM rocker/shiny:4.5.0
RUN apt-get update && apt-get install -y \
    libcurl4-openssl-dev \
    libssl-dev \
    libxml2-dev \
    libudunits2-dev \
    libgdal-dev \
    libgeos-dev \
    libproi-dev \
    libfontconfig1-dev \
    libharfbuzz-dev \
    libfribidi-dev \
    libfreetype6-dev \
    libpng-dev \
    libtiff5-dev \
    && rm -rf /var/lib/apt/lists/*
RUN R -e "install.packages(c('shiny', 'arrow', 'leaflet', 'DT', 'dplyr', 'sf', 'leaflet.extras', 'shinythemes'))"
COPY view_parquet.Rmd /srv/shiny-server/view_parquet.Rmd
EXPOSE 3838
CMD ["R", "-e", "rmarkdown::run('/srv/shiny-server/view_parquet.Rmd', shiny_args = list(host = '0.0.0.0', port = 3838))"]
```







# Make a container registry token

Working with container registry

You need your container registry token









# **Build and Push Docker Image**

Build and version your container using semantic versioning docs Not technically required, but if your new version fails, roll back easily.

```
docker build -t ghcr.io/yourusername/view_parquet:1.0.0 .
export CR_PAT = mycontainerregistrytoken
echo $CR_PAT | docker login ghcr.io -u yourusername --password-stdin
docker push ghcr.io/yourusername/view_parquet:1.0.1
```







# Test your public image

docker run -p 3838:3838 ghcr.io/yourusername/view\_parquet:1.0.1

Open your browser and navigate to:

http://localhost:3838

Your working app version is now usable by anyone, anywhere with Docker and an internet connection







### Clone the service playground, and add your service

How to add your service, README.md

```
#clone the repo
git clone https://gitlab.mercator-ocean.fr/pub/edito-infra/service-playground.git
cd service-playground
# make your own branch
git checkout -b parquet_viewer_r
git push origin parquet_viewer_r
## Here we use the terria-map-viewer as a basis for our service
## instead of making from scratch
cp -r terria-map-viewer parquet_viewer_r
```







# **Chart.yaml**

Basic outline for deployment

Edit Chart.yaml:

```
name: view-parquet
description: An interactive Parquet viewer on EDITO
home: https://github.com/yourusername/view_parquet
icon: https://your.icon.url/icon.png
keywords: [shiny, r, parquet, viewer]
version: 1.0.0
appVersion: "1.0.0"
dependencies:
  - name: library-chart
    version: 1.5.16
    repository: https://inseefrlab.github.io/helm-charts-interactive-services
```







# **# Update Chart Values**

### values.yaml

```
service:
  image:
    version: "ghcr.io/yourusername/view-parquet:1.0.1"
networking:
  service:
    port: 3838
```







# **Update values.schema.json**

Choose which version(s) of your package/app that users should be able to select in the User interface

#### values.schema.json

```
"listEnum": [
    "ghcr.io/yourusername/view-parquet:1.0.1",
    "ghcr.io/yourusername/view-parquet:1.0.0"
],
"default": "ghcr.io/yourusername/view-parquet:1.0.1"
```







# **Update templates/NOTES.txt**

Can show the link where the service is deployed, link to sample dataset, etc.

This will be displayed in the pop-up to the user while the service is being deployed.

#### templates/NOTES.txt

```
Your Parquet Viewer in R is being deployed!

It will be available on this [link](http{{ if $.Values.ingress.tls }}s{{ end }}://{{ .Values.ingress.hostname }}).
```







# **Enable Ingress (Optional)**

In values.schema.json, allow user-defined ingress:

```
"x-onyxia": {
   "overwriteDefaultWith": "{{project.id}}-{{k8s.randomSubdomain}}-0.{{k8s.domain}}"
}
// Remove "hidden": true line
```









# Add S3 or Marine Service Secrets (Optional)

Add to values.schema.json:

```
"s3": {
 "x-onyxia": { "overwriteSchemaWith": "ide/s3.json" }
```

#### Enable secret in templates:

```
envFrom:
- secretRef:
    name: {{ include "library-chart.secretNameS3" . }}
```







## **Commit your changes**

First install pre-commit

Run 'make check-format' and it will make sure the formatting is ok

make check-format

#### Commit your changes

```
# Stage all changes
git add .
# Commit the changes with a descriptive message
git commit -m "Added my awesome service"
# Push the changes to your branch
git push origin parquet_viewer_r
```







# Launch in Playground

- Check your commit in the [pipelines] (https://gitlab.mercator-ocean.fr/pub/edito-infra/service-playground/-/pipelines)
- If successful, Wait for 5–10 min
- If it fails, check the pipeline logs
- Launch from EDITO Datalab and open the 'link' to your awesome App!





# **✓** Production Release, out of the playground

#### Once tested and matured:

- Add yourself to Chart.yaml as maintainer
- Submit a Merge Request
- Ping @pub/edito-infra/codeowners











- Your service is live on EDITO!
- **You now know how to go from script**  $\rightarrow$  **container**  $\rightarrow$  **Helm**  $\rightarrow$  **Datalab.**

#### Questions?

edito-infra-dev@mercator-ocean.eu

#### Docs

- Service Playground README.md
- EDITO docs





