

Deploying a Service on EDITO Datalab

Learn how to turn your script into a containerized web service and launch it on the EDITO platform.

By Samuel Fooks

Flanders Marine Institute (VLIZ)







What You'll Learn

- ✓ Dockerize a script (R or Python)
- ✓ Push the image to a public Docker registry
- ✓ Configure a Helm chart
- ✓ Deploy the service on the EDITO playground
- ✓ Publish to production via Merge Request









Application/Service

view_parquet_service

The view_parquet_service/app:

- ui.R
- server.R
- global.R

These files collectively provide an interactive tool to load, filter, and visualize Parquet datasets

Is not instructional (Tutorial), and doesn't only perform a specific calculation/run a model (Process).

We should add it as a service







Dockerfile Example

```
FROM rocker/shiny:4.5.0
RUN apt-get update && apt-get install -y \
    libcurl4-openssl-dev \
    libssl-dev \
    libxml2-dev \
    libudunits2-dev \
    libqdal-dev \
    libgeos-dev \
    libproj-dev \
    libfontconfig1-dev \
    libharfbuzz-dev \
    libfribidi-dev \
    libfreetype6-dev \
    libpng-dev \
    libtiff5-dev \
   && rm -rf /var/lib/apt/lists/*
# Install required R packages
RUN R -e "install.packages(c('shiny', 'arrow', 'leaflet', 'DT', 'dplyr', 'sf', 'leaflet.extras', 'shinythemes'))"
# Create app folder and copy files
RUN mkdir -p /srv/shiny-server
COPY ui.R server.R global.R /srv/shiny-server/
# Copy the startup script
COPY start.sh /start.sh
RUN chmod +x /start.sh
# Expose port
EXPOSE 3838
# Start Shiny server
CMD ["/start.sh"]
```

Make a container registry token

Working with container registry

You need your container registry token









Build and Push Docker Image

Build and version your container using semantic versioning docs Not technically required, but if your new version fails, roll back easily.

```
docker build -t ghcr.io/yourusername/view_parquet:1.0.1 .
export CR_PAT = mycontainerregistrytoken
echo $CR_PAT | docker login ghcr.io -u yourusername --password-stdin
docker push ghcr.io/yourusername/view_parquet:1.0.1
```







Test your public image

Test the public image before adding it as a service

```
docker run -p 3838:3838 ghcr.io/samuelfooks/view_parquet:1.0.4
```

Open your browser and navigate to:

```
http://localhost:3838/
```

Your working app version is now usable by anyone, anywhere with Docker and an internet connection







Clone the service playground, and add your service

How to add your service, README.md

```
#clone the repo
git clone https://gitlab.mercator-ocean.fr/pub/edito-infra/service-playground.git
cd service-playground
# make your own branch
git checkout -b parquet_viewer_r
git push origin parquet_viewer_r
## Here we use the terria-map-viewer as a basis for our service
## instead of making from scratch
cp -r terria-map-viewer parquet_viewer_r
```







Helm and Kubernetes Overview

Kubernetes

- Pods: Smallest deployable units in Kubernetes, running one or more containers.
- Cluster: A group of nodes (machines) managed by Kubernetes.
- Service: Exposes your application to the network, enabling communication. (Not to be confused with the predefined datalab deployment services)

Helm

- Helm Charts: Pre-configured Kubernetes resources packaged together.
- Templates: YAML files with placeholders for dynamic values.
- Values: Configuration file (values.yaml) to customize deployments.







Basic Helm Template Example

Chart.yaml

```
name: my-service
version: 1.0.0
description: A sample Helm chart
```

values.yaml

```
image:
    repository: my-docker-repo/my-service
    tag: "1.0.0"
service:
    type: ClusterIP
    port: 3838
```







Let's edit our Chart.yaml

Edit Chart.yaml:

```
name: view-parquet
description: An interactive Parquet viewer on EDITO
home: https://github.com/yourusername/view_parquet
icon: https://your.icon.url/icon.png
keywords: [shiny, r, parquet, viewer]
version: 1.0.0
appVersion: "1.0.3"
dependencies:
  - name: library-chart
    version: 1.5.16
    repository: https://inseefrlab.github.io/helm-charts-interactive-services
```







K Let's update values.yaml

values.yaml

```
service:
  image:
    version: "ghcr.io/yourusername/view-parquet:1.0.3"
networking:
  service:
    port: 3838
```







The additional values.schema.json

Inputs from the user interface go into here, and this goes with the Helm chart deployment into the cluster.

- app version
- resources

Ex. Let users select different versions of your app

values.schema.json

```
"listEnum": [
    "ghcr.io/yourusername/view-parquet:1.0.3",
    "ghcr.io/yourusername/view-parquet:1.0.1"
],
"default": "ghcr.io/yourusername/view-parquet:1.0.3"
```







Update templates/NOTES.txt

Can show the link where the service is deployed, link to sample dataset, etc.

This will be displayed in the pop-up to the user while the service is being deployed.

templates/NOTES.txt

```
Your Parquet Viewer in R is being deployed!

It will be available on this [link](http{{ if $.Values.ingress.tls }}s{{ end }}://{{ .Values.ingress.hostname }}).
```







Enable Ingress (Optional)

In values.schema.json, allow user-defined ingress:

```
"x-onyxia": {
  "overwriteDefaultWith": "{{project.id}}-{{k8s.randomSubdomain}}-0.{{k8s.domain}}"
  Remove "hidden": true line
```

For more details, refer to the Kubernetes Ingress documentation.







Add S3 or Marine Service Secrets (Optional)

Add to values.schema.json:

```
"s3": {
   "x-onyxia": { "overwriteSchemaWith": "ide/s3.json" }
}
```

Enable secret in templates:

```
envFrom:
    secretRef:
    name: {{ include "library-chart.secretNameS3" . }}
```

For more details, refer to the Kubernetes Secrets documentation.







Commit your changes

First install pre-commit

Run 'make check-format' and it will make sure the formatting is ok

```
make check-format
```

Commit your changes

```
# Stage all changes
git add .
# Commit the changes with a descriptive message
git commit -m "Added my awesome service"
# Push the changes to your branch
git push origin parquet_viewer_r
```







Launch in Playground

- Check your commit in the [pipelines] (https://gitlab.mercator-ocean.fr/pub/edito-infra/service-playground/-/pipelines)
- If successful, Wait for 5–10 min
- If it fails, check the pipeline logs
- Launch from EDITO Datalab and open the 'link' to your awesome App!





✓ Production Release, out of the playground

Once tested and matured:

- Add yourself to Chart.yaml as maintainer
- Submit a Merge Request
- Ping @pub/edito-infra/codeowners







Done!

- Your service is live on EDITO!
- **?** You now know how to go from script \rightarrow container \rightarrow Helm \rightarrow Datalab.

Questions?

edito-infra-dev@mercator-ocean.eu

Docs

- Service Playground README.md
- EDITO docs





