



Conditional Access Block Legacy Authentication

Generated at — July 20, 2026, 1:52 p.m.

Proceed with caution as there are multiple opportunities for mistakes that will result in all users, including Global Admin accounts, to be locked out.

1 Prerequisite before continuing ☐

This registration step is imperative to review and confirm for all Global Admin accounts. Do NOT continue until this has been verified.

[Require phishing-resistant multifactor authentication for Microsoft Entra administrator roles - Microsoft Entra ID | Microsoft Learn](#)

2 Untitled Step ☐

FYI: ****After Security Defaults are enabled within your tenant, all authentication requests made by an older protocol will be blocked!**** ([reference](#))

- Login to the [Azure Portal > Conditional Access > Policies](#)
- Look for a policy named "CA003: Block legacy authentication"
- Review the conditions to ensure legacy authentication clients are blocked, for example:

Home > Conditional Access | Policies >

CA003: Block legacy authentication

Conditional Access policy

Delete View policy information

Control access based on Conditional Access policy to bring signals together, to make decisions, and enforce organizational policies. [Learn more](#)

Name *

CA003: Block legacy authentication

Assignments

Users

All users included and specific users excluded

Target resources

All cloud apps

Conditions

1 condition selected

Access controls

Grant

Block access

Control access based on signals from conditions like risk, device platform, location, client apps, or device state. [Learn more](#)

Device platforms

Not configured

Locations

Not configured

Client apps

2 included

Filter for devices

Not configured

Client apps

Control user access to target specific client applications not using modern authentication. [Learn more](#)

Configure

Yes No

Select the client apps this policy will apply to

Modern authentication clients

☐ Browser

☐ Mobile apps and desktop clients

Legacy authentication clients

☒ Exchange ActiveSync clients

☒ Other clients

- Check the users that the policy is targetting as well as any excluded users/groups, for example:

Control access based on Conditional Access policy to bring signals together, to make decisions, and enforce organizational policies.
[Learn more](#)

Control access based on who the policy will apply to, such as users and groups, workload identities, directory roles, or external guests.
[Learn more](#)

Name *

CA003: Block legacy authentication

Include Exclude

- ☐ None
- ☒ All users
- ☐ Select users and groups

Assignments

Users ⓘ

1

All users included and specific users excluded

[Home](#) > [Conditional Access | Policies](#) >

CA003: Block legacy authentication

Conditional Access policy



Delete



View policy information

Control access based on Conditional Access policy to bring signals together, to make decisions, and enforce organizational policies.
[Learn more](#)

Control access based on who the policy will apply to, such as users and groups, workload identities, directory roles, or external guests.
[Learn more](#)

Name *

CA003: Block legacy authentication

Include Exclude 2

Select the users and groups to exempt from the policy

- ☐ Guest or external users ⓘ
- ☐ Directory roles ⓘ
- ☒ Users and groups

Assignments

Users ⓘ

1

All users included and specific users excluded

Target resources ⓘ

All cloud apps

Conditions ⓘ

1 condition selected

Select excluded users and groups

2 users

Access controls

Grant ⓘ

Block access

3



Admin o365
o365@



4



...

