

SEM2220: iOS Word Pairs Assignment

Samuel Jackson
University Of Aberystwyth
slj11@aber.ac.uk

April 11, 2016

word pairs/tags but loads the data for the selected item into the view so that it can be edited by the user.

These two tabs both also implement the additional feature of a search bar. I was initially concerned that this interface was going to become too busy and offer too many operations at this point. However I eventually decided that adding another section for searching or editing would be lead to too many layers for the user to dive into. Encompassing all of this functionality into one view keeps the interface from becoming too deep.

The word pairs section of the application has an additional option on the add button that lets the user choose between create a new word pair from scratch and importing them from a remote URL. This is a very simple interface which allows the user to directly input a URL. If the URL fails to import for some reason then the user will be performed. The actual loading of the JSON data is performed on a separate thread to avoid interface locking. A loading animation is displayed to the user during this time to inform them that the application is doing something.

The third and final section of the interface is used to test the user via a revision exercise. This provides two different ways to generate an revision exercise. A user can choose to generate a test based on the most recent words (based on the time a word pair was added). The second way is to generate a test exercise based on words associated with a particular tag. Tags with no associated words are not shown. Tests are carried out by simply requiring the user to enter the correct word in the other language. At the end of an exercise the user is shown how many they got correct and is given an option to retry the test.

I found that this part of the application required a little bit of extra work. Swift does have an array shuffling function by default. I chose to use some code from a stack overflow question (referenced in the code) which would add this feature. Secondly, I found I required several pieces of data to be passed between the three views. I chose to simplify this by using a class to group data.

Generally speaking I found that one of the most difficult aspects of implementing this project was realising how various segues work, as well as how to send and manage them both automatically and manually. Implementing the project became easier as I better understood how these worked. Another issue I found with this project that I would try to tackle better if I were to do this project again is the reuse of interfaces. There are several parts of the application that share similar functionality. Ideally I would have liked to have refactored my code to manage this better. A better understanding of iOS views and swift in general would help me here.

3 Data Model

In my implementation the core data model sticks very closely to the one provided in the assignment brief. There are two slight modifications that I have made to the original model which I will justify here. The first change modifies the names of the word pairs in the code from “English” and “Welsh” to “Native” and “Foreign” respectively. I made this change because I feel it’s more extensible. It lends itself to storing alternative languages with the application. It is also potentially open to modification later to add support for multiple sets of word pairs.

The second change is the addition of a “timeAdded” member to the *WordPhrasePair* entity in the core data model. This is to make it possible to provide a revision exercise based on the most recent word pairs added to the system. This is implemented as an NSDate object. When a new word pair is created by a user then current time is added to the record that is stored in core data. This is never updated even if the user edits the pair at a later date. The case where word pairs are imported from a remote URL is more complex. If JSON data imported from a remote URL includes an element called *timeAdded* and is a string in the format “HH:mm” then this will be used as the value for for the timeAdded property in core data. If this element is omitted in the JSON file then the current date and time at the point of local creation will be used instead.

I found core data relatively easy to work this. The only real issue that I encountered with this is when the model becomes out of sync with the code base. I found I had to learn how to migrate the core data model to a new version. Another issue I had with core data is that it has some “magic” functions to set many to many relationship between tag and word pair entities. As a newcomer to the platform this wasn’t entirely obvious and did lead to a loss of development time.

4 Self Evaluation

I feel that I have made a good attempt at this project. I have no prior experience with the swift language or iOS development and I do not even experience using the iOS platform. I feel that I have produced a passible application that fulfils all of the functional requirements of the brief. I feel that I have made a reasonable attempt to conform the the familiar way in which iOS applications work and have not deviated too far from how other applications are laid out. Based on these conclusions I would award myself an A grade with room for improvement.

If I had more time on this project I have several suggestions for what could be improved. The testing section could be expanded to use several different types of testing. For example the native and foreign word input could be flipped randomly so that the user is given a foreign word and must enter the native equivalent. Another idea would be to use a collection view (or similar) which shows multiple pairs of words that the user must “tap to match” similar to functionality offer in mobile applications such as Duolingo [1]. Another improvement I would like to make would be to add functionality to have multiple collections of word pairs. For example one collection for English and Welsh word pairs and one for English and German word pairs. This would be an easy extension to the core data model and could be implemented as an additional tab on the main interface or a side menu which allows the user to choose the collection to use.

5 Test Table

#	Functional Requirement	Test Description	Expected Outcome	Pass/Fail	Actual Outcome	Solution
1	FR1	Add new word pair	A new word is added and is shown in the main word pairs view.	Fail	High level exception thrown when setting the data.	The model had recently just been updated through refactoring. Incrementing the version solved this issue.
2	FR1	Add new word pair with no type	A new word is added without type and is shown in the main word pairs view.	Pass	As Expected	N/a
3	FR1	Add new word pair with a note	A new word pair is added and a note is shown when clicking on it and viewing it.	Pass	As Expected	N/a
4	FR1	Edit a word pair and change the content	Word pair is edited and the details are saved the viewed after editing	Pass	As Expected	N/a
5	FR1	Delete a word pair	Deleting a word pair should remove it from the table view and remove it from core data. Closing a reopening the app should show the entry is still removed.	Pass	As Expected	N/a
6	FR2	Create a new tag	A new tag is created	Pass	As Expected	N/a
7	FR2	Assign a tag to an existing word pair	Viewing the word pair should show that a tag is associated with it	Pass	As Expected	N/a
8	FR2	View a list of words for tag	Clicking on a tag should show a list of word pairs that are associated with this tag	Pass	As Expected	N/a

#	Functional Requirement	Test Description	Expected Outcome	Pass/Fail	Actual Outcome	Solution
9	FR2	Cannot view words for a tag that has zero references	Clicking on the tag should do nothing. The row should also have the chevron (>) removed from the interface to indicate this.	Pass	As Expected	N/a
10	FR2	Editing a tag	Editing a tag should change update tag. The tag should not lose its references to word pairs. Word pairs should show as being associated with the edited name of the tag	Pass	As Expected	N/a
11	FR2	Delete a tag	Deleting a tag should remove it from the table view. All word pairs that were associated with the tag should no longer have the tag associated with them	Pass	As Expected	N/a
12	FR2	Assign multiple word pairs a tag	All of the tags should be shown in the when viewing the word pair	Pass	As Expected	N/a
13	FR2	Remove all tags associated with a word pair	An association with a tag is optional, so the it should be possible to remove all tags associated with a word pair.	Fail	Tags are not removed.	The NSSet holding the tags was not being cleared before adding new tags. This meant that the set was only ever updated with new tags, but removing a tag had not effect. This is now resolved by clearing before updating.
14	FR3	Search for a word pair by foreign/native word	Searching by a word pair should filter all of the pairs that match either the foreign or the native word	Pass	As Expected	N/a

#	Functional Requirement	Test Description	Expected Outcome	Pass/Fail	Actual Outcome	Solution
15	FR3	Search for a word pair by tag	Searching by tag should return all words that are associated with that particular tag	Pass	As Expected	N/a
16	FR3	Search for a word pair by type	Searching by type should return all words that are associated with that particular type	Pass	As Expected	N/a
17	FR3	Editing a word pair while a search filter is active	Editing a word pair while a search filter is active should edit the correct word. When the filter is removed the edited version of the word pair should be present and correct in the table view	Pass	As Expected	N/a
18	FR3	Removing a word pair while a search filter is active	Removing a word pair while a search filter is active should remove the correct word. When the filter is removed the word pair should no longer be present and correct in the table view	Pass	As Expected	N/a
19	FR3	Searching for a tag by name	Searching by name for a tag should return all of the tags which match the filter value	Pass	As Expected	N/a
20	FR4	Starting a test set with the most recent words	A new test set should be generated that only consists of the 10 most recent words added to the application. This collection of words should be randomised.	Pass	As Expected	N/a

#	Functional Requirement	Test Description	Expected Outcome	Pass/Fail	Actual Outcome	Solution
21	FR4	Starting a test set using a tag	All of the word pairs associated with a tag should be added to used in the test and the word pairs should be randomised.	Pass	As Expected	N/a
22	FR4	Entering a correct guess for a word	Entering a correct guess should show confirmation that it was correct and display the foreign word.	Pass	As Expected	N/a
23	FR4	Entering an incorrect guess for a word	Entering an incorrect guess should inform the user that they were wrong and display the correct foreign word.	Pass	As Expected	N/a
24	FR4	Cancelling a revision exercise	At any point during the test the user should be able to click the cross icon to return the the home screen.	Pass	As Expected	N/a
25	FR4	Review a revision exercise	The total number of correct guesses and the total number of words in the exercise should be displayed. The user should be able to navigate back to the home screen	Pass	As Expected	N/a
26	FR4	Retake a revision exercise	On the revision page, clicking the try again button restart the test. Entries should be randomised again, but the same words should be reused.	Pass	As Expected	N/a

#	Functional Requirement	Test Description	Expected Outcome	Pass/Fail	Actual Outcome	Solution
27	FR5	Importing data from a URL	New word pairs should be added on the main screen. A loading spinner should be shown while loading. A message should be shown when the operation successfully completes. Dismissing the message should return the user to the home screen.	Pass	As Expected	N/a
28	FR5	Importing data from an invalid URL	The operation should fail and a message should be displayed to the user informing them that it was unsuccessful. They should not be segued back to the main screen.	Pass	As Expected	N/a

References

- [1] Duolingo website. <https://www.duolingo.com>. Accessed: 2016-04-11.