

# CSCI4333 Database Design & Implement

## SQL 4

Instructor: Dr. Yifeng Gao

## Sailors

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

## Reserves

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/04
22	102	10/10/04
22	103	10/08/04
22	104	10/07/04
31	102	11/10/04
31	103	11/06/04
31	104	11/12/04
64	101	09/05/04
64	102	09/08/04
74	103	09/08/04

## Boats

<i>bid</i>	<i>bname</i>	<i>Color</i>
101	Interlake	blue
102	Interlake	red
103	Clipper	green
104	Marine	red

# Correlated Nested Queries...1

*Find names of sailors who have reserved boat 103*

```
SELECT S.sname
FROM Sailors S
WHERE EXISTS (SELECT *
               FROM Reserves R
               WHERE R.bid=103 AND R.sid=S.sid);
```



Plug in **Table S** row and tests whether the set is nonempty. If it is, then return TRUE.

(For finding sailors who have **not** reserved boat 103, we would use **NOT EXISTS**)

# Correlated Nested Queries...1

*Find names of sailors who have reserved boat 103*

```
SELECT S.sname  
FROM Sailors S  
WHERE EXISTS
```

```
(SELECT *  
FROM Reserves R  
WHERE R.bid=103 AND R.sid=S.sid);
```

For **each sailor**, check  
the reserve table if  
he/she reserved boat  
103

(For finding sailors who have **not** reserved boat 103, we  
would use **NOT EXISTS**)

## Sailors

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

## Reserves

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/04
22	102	10/10/04
22	103	10/08/04
22	104	10/07/04
31	102	11/10/04
31	103	11/06/04
31	104	11/12/04
64	101	09/05/04
64	102	09/08/04
74	103	09/08/04

SELECT \* FROM Reserves R WHERE R.bid=103  
AND R.sid=22;


## Sailors

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

## Reserves

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/04
22	102	10/10/04
22	103	10/08/04
22	104	10/07/04
31	102	11/10/04
31	103	11/06/04
31	104	11/12/04
64	101	09/05/04
64	102	09/08/04
74	103	09/08/04

non-empty



True

SELECT \* FROM Reserves R WHERE R.bid=103  
AND R.sid=22;


## Sailors

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

## Reserves

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/04
22	102	10/10/04
22	103	10/08/04
22	104	10/07/04
31	102	11/10/04
31	103	11/06/04
31	104	11/12/04
64	101	09/05/04
64	102	09/08/04
74	103	09/08/04

non-empty



True

SELECT \* FROM Reserves R WHERE R.bid=103  
AND R.sid=22;

## Sailors

## Reserves

empty

True

False

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/04
22	102	10/10/04
22	103	10/08/04
22	104	10/07/04
31	102	11/10/04
31	103	11/06/04
31	104	11/12/04
64	101	09/05/04
64	102	09/08/04
74	103	09/08/04

SELECT \* FROM Reserves R WHERE R.bid=103  
AND R.sid=29;



## Sailors

## Reserves

True

False

True

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/04
22	102	10/10/04
22	103	10/08/04
22	104	10/07/04
31	102	11/10/04
31	103	11/06/04
31	104	11/12/04
64	101	09/05/04
64	102	09/08/04
74	103	09/08/04

Non-empty

SELECT \* FROM Reserves R WHERE R.bid=103  
AND R.sid=31;

## Sailors

## Reserves

**True**

**False**

**True**

**False**

**False**

**False**

**False**

**True**

**False**


**False**

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/04
22	102	10/10/04
22	103	10/08/04
22	104	10/07/04
31	102	11/10/04
31	103	11/06/04
31	104	11/12/04
64	101	09/05/04
64	102	09/08/04
74	103	09/08/04

## Sailors

	<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
<b>True</b>	22	Dustin	7	45.0
<b>False</b>	29	Brutus	4	33.0
<b>True</b>	31	Lubber	8	55.5
<b>False</b>	32	Andy	8	25.5
<b>False</b>	58	Rusty	10	35.0
<b>True</b>	64	Horatio	7	35.0
<b>False</b>	71	Zorba	10	16.0
<b>True</b>	74	Horatio	9	35.0
<b>False</b>	85	Art	3	25.5
<b>False</b>	95	Bob	3	63.5



<i>sname</i>
Dustin
Lubber
Horatio

```

SELECT S.sname
FROM Sailors S
WHERE EXISTS (SELECT *
               FROM Reserves R
               WHERE R.bid=103 AND R.sid=S.sid);
    
```

# Correlated Nested Queries...2

*Find the sid of the sailor who never reserve a red boat?*

*Hint: Using NOT EXISTS*

# Correlated Nested Queries...2

*Find the sid of the sailor who never reserve a red boat?*

```
SELECT R.sid FROM Reserve R
WHERE NOT EXISTS (
  SELECT * FROM Boat B WHERE B.color = 'red'
  AND B.bid = R.bid
)
```

# Correlated Nested Queries...3

*Find the sid of the sailor who previously reserve a red boat and blue boat?*

# Correlated Nested Queries...3

*Find the sid of the sailor who previously reserve a red boat and blue boat?*

```
SELECT R.sid FROM Reserve R
WHERE
EXISTS (SELECT * FROM Boat B WHERE B.color = 'red' AND
        B.bid = R.bid)
AND
EXISTS (SELECT * FROM Boat B WHERE B.color = 'blue' AND
        B.bid = R.bid)
```

# Correlated Nested Query 4

*Find the names of sailors who have reserved ALL boats*

```
SELECT S.sname
FROM Sailors S
WHERE NOT EXISTS ((SELECT B.bid
                    FROM Boats B)
                  EXCEPT
                  (SELECT R.bid
                   FROM Reserves R
                   WHERE R.sid = S.sid));
```

(For each sailor S, we check to see that the set of boats reserved by S includes every boat)



# Correlated Nested Query 4

Alternatively,

*Find the names of sailors who have reserved ALL boats*

```
SELECT S.sname
FROM Sailors S
WHERE NOT EXISTS (SELECT B.bid
                  FROM Boats B
                  WHERE NOT EXISTS (SELECT R.bid
                                    FROM Reserves R
                                    WHERE R.bid = B.bid AND
                                           R.sid = S.sid ));
```

# ANY and ALL operators

*Find sailors whose rating is better than some sailor named Horatio*

```
SELECT S.sid  
FROM Sailors S  
WHERE S.rating > ANY (SELECT S2.rating  
                       FROM Sailors S2  
                       WHERE S2.sname= 'Horatio' );
```

(Can you find the probable bug in this SQL query??)  
Hint: what if there are several sailors named Horatio?

# Using ALL operator

*Find sailors whose rating is better than **every** sailor named Horatio*

```
SELECT S.sid  
FROM Sailors S  
WHERE S.rating > ALL(SELECT S2.rating  
                        FROM Sailors S2  
                        WHERE S2.sname= 'Horatio' );
```