

STAINLESS STEEL PRESSURE REGULATOR

APPLICATIONS

Chemical and Petrochemical Industry
High pressure system
Testing lab



SPECIFICATIONS		MATERIALS OF CONSTRUCTION	
Max. Inlet Pressure	3.625 psi (250 bar)	Body	Stainless steel
Outlet Ranges	Up to 3.000 psi (206 bar)	Bonnet	Stainless steel
		Seat	PCTFE
Working Temperature	-30 ... +70 °C	Piston	Stainless Steel
Pressure gauge	On pilot regulator only	Filter	Use filter model 991.350.3N.3N - 10u
Seat	Qualitec ballanced seat system	Seals	NBR

PART NUMBER	OUTLET RANGE	INLET CONNECTION	OUTLET CONNECTION	PILOT REGULATOR
591.250.040.3N.4N-N	0 ... 600 psi (41.3 bar)	3/4" NPT(F)	1" NPT(F)	NOT INCLUDED
591.250.200.3N.4N-N	0 ... 3.000 psi (206 bar)	3/4" NPT(F)	1" NPT(F)	NOT INCLUDED
591.250.040.3N.4N-P	0 ... 600 psi (41.3 bar)	3/4" NPT(F)	1" NPT(F)	INCLUDED
591.250.200.3N.4N-P	0 ... 3.000 psi (206 bar)	3/4" NPT(F)	1" NPT(F)	INCLUDED

FLOW CHART

		Inlet pressure (bar)						
		10	30	50	150	150	200	250
Working pressure (bar)	5	165	165	165	165	165	165	165
	15	-	465	465	465	465	465	465
	30	-	-	745	745	745	745	745
	60	-	-		1480	1480	1480	1480
	100	-	-			2130	2130	2130
	150	-	-				2605	2605
	200	-	-					3000

Performance in Mm³/h Air with an outlet gas speed of 30 m/s.