Utilisation de MySQL pour le CRUD

Modification de show-article.php

Nous utilisons PDO et notre base de données MySQL:

```
<?php
$pdo = require once 'database.php';
$statement = $pdo->prepare('SELECT * FROM article WHERE id = :id');
$ GET = filter input array(INPUT GET,
FILTER SANITIZE FULL SPECIAL CHARS);
$id = $ GET['id'] ?? '';
if (!$id) {
  header('Location: /');
} else {
  $statement->bindValue(':id', $id);
  $statement->execute();
  $article = $statement->fetch();
}
?>
<!DOCTYPE html>
<html lang="fr">
<head>
  <?php require_once 'includes/head.php' ?>
  <link rel="stylesheet" href="/public/css/show-article.css">
  <title>Article</title>
</head>
<body>
  <div class="container">
    <?php require_once 'includes/header.php' ?>
    <div class="content">
      <div class="article-container">
        <a class="article-back" href="/">Retour à la liste des
articles</a>
```

```
<div class="article-cover-img" style="background-image:url(<?=</pre>
$article['image'] ?>)"></div>
       <h1 class="article-title"><?= $article['title'] ?></h1>
       <div class="separator"></div>
       <?= $article['content'] ?>
       <div class="action">
         <a class="btn btn-secondary" href="/delete-article.php?id=<?=</pre>
$article['id'] ?>">Supprimer</a>
         <a class="btn btn-primary" href="/form-article.php?id=<?=</pre>
$article['id'] ?>">Editer l'article</a>
       </div>
      </div>
   </div>
   <?php require_once 'includes/footer.php' ?>
 </div>
</body>
</html>
```

Modification de form-article.php

Nous utilisons PDO et notre base de données MySQL:

```
<?php
$pdo = require_once 'database.php';
$statementReadOne = $pdo->prepare('SELECT * FROM article WHERE id =
:id');
$statementCreateOne = $pdo->prepare('
  INSERT INTO article (
    title,
    category,
    content,
    image
  ) VALUES (
    :title,
    :category,
    :content,
    :image
  )
```

```
');
$statementUpdateOne = $pdo->prepare('
  UPDATE article
  SET
    title=:title,
    category=:category,
    content=:content,
    image=:image
 WHERE id=:id;
');
const ERROR REQUIRED = 'Veuillez renseigner ce champ';
const ERROR TITLE TOO SHORT = 'Le titre est trop court';
const ERROR CONTENT TOO SHORT = 'L\'article est trop court';
const ERROR IMAGE URL = 'L\'image doit être une url valide';
$filename = DIR . '/data/articles.json';
$errors = [
  'title' => '',
  'image' => '',
  'category' => '',
  'content' => ''
1;
$category = '';
$ GET = filter input array(INPUT GET,
FILTER SANITIZE FULL SPECIAL CHARS);
$id = $_GET['id'] ?? '';
if ($id) {
  $statementReadOne->bindValue(':id', $id);
  $statementReadOne->execute();
  $article = $statementReadOne->fetch();
  $title = $article['title'];
  $image = $article['image'];
  $category = $article['category'];
  $content = $article['content'];
}
if ($ SERVER['REQUEST METHOD'] === 'POST') {
  $ POST = filter input array(INPUT POST, [
    'title' => FILTER SANITIZE FULL SPECIAL CHARS,
    'image' => FILTER SANITIZE URL,
```

```
'category' => FILTER SANITIZE FULL SPECIAL CHARS,
  'content' => [
    'filter' => FILTER SANITIZE FULL SPECIAL CHARS,
    'flags' => FILTER FLAG NO ENCODE QUOTES
  1
1);
$title = $ POST['title'] ?? '';
$image = $ POST['image'] ?? '';
$category = $ POST['category'] ?? '';
$content = $ POST['content'] ?? '';
if (!$title) {
  $errors['title'] = ERROR REQUIRED;
} elseif (mb strlen($title) < 5) {</pre>
  $errors['title'] = ERROR TITLE TOO SHORT;
}
if (!$image) {
  $errors['image'] = ERROR REQUIRED;
} elseif (!filter var($image, FILTER VALIDATE URL)) {
  $errors['image'] = ERROR IMAGE URL;
}
if (!$category) {
  $errors['category'] = ERROR_REQUIRED;
}
if (!$content) {
  $errors['content'] = ERROR_REQUIRED;
} elseif (mb_strlen($content) < 50) {</pre>
  $errors['content'] = ERROR_CONTENT_TOO_SHORT;
}
if (empty(array filter($errors, fn ($e) => $e !== ''))) {
  if ($id) {
    $statementUpdateOne->bindValue(':title', $title);
    $statementUpdateOne->bindValue(':image', $image);
    $statementUpdateOne->bindValue(':category', $category);
    $statementUpdateOne->bindValue(':content', $content);
    $statementUpdateOne->bindValue(':id', $id);
```

```
$statementUpdateOne->execute();
    } else {
      $statementCreateOne->bindValue(':title', $title);
      $statementCreateOne->bindValue(':image', $image);
      $statementCreateOne->bindValue(':category', $category);
      $statementCreateOne->bindValue(':content', $content);
      $statementCreateOne->execute();
    }
    header('Location: /');
  }
}
?>
<!DOCTYPE html>
<html lang="fr">
<head>
  <?php require once 'includes/head.php' ?>
  <link rel="stylesheet" href="/public/css/form-article.css">
  <title><?= $id ? 'Modifier' : 'Créer' ?> un article</title>
</head>
<body>
  <div class="container">
    <?php require_once 'includes/header.php' ?>
    <div class="content">
      <div class="block p-20 form-container">
        <h1><?= $id ? 'Modifier' : 'Écrire' ?> un article</h1>
        <form action="/form-article.php<?= $id ? "?id=$id" : '' ?>" ,
method="POST">
          <div class="form-control">
            <label for="title">Titre</label>
            <input type="text" name="title" id="title" value="<?= $title</pre>
?? '' ?>">
            <?php if ($errors['title']) : ?>
              <?= $errors['title'] ?>
            <?php endif; ?>
          </div>
          <div class="form-control">
```

```
<label for="image">Image</label>
           <input type="text" name="image" id="image" value="<?= $image</pre>
?? '' ?>">
           <?php if ($errors['image']) : ?>
             <?= $errors['image'] ?>
           <?php endif; ?>
         </div>
         <div class="form-control">
           <label for="category">Catégorie</label>
           <select name="category" id="category">
             <option <?= !$category || $category === 'technologie' ?</pre>
'selected' : '' ?> value="technologie">Technologie</option>
             <option <?= $category === 'nature' ? 'selected' : '' ?>
value="nature">Nature</option>
             <option <?= $category === 'politique' ? 'selected' : '' ?>
value="politique">Politique</option>
           </select>
           <?php if ($errors['category']) : ?>
             <?= $errors['category'] ?>
           <?php endif; ?>
         </div>
         <div class="form-control">
           <label for="content">Content</label>
           <textarea name="content" id="content"><?= $content ?? '' ?>
</textarea>
           <?php if ($errors['content']) : ?>
             <?= $errors['content'] ?>
           <?php endif; ?>
         </div>
         <div class="form-actions">
           <a href="/" class="btn btn-secondary"</pre>
type="button">Annuler</a>
           <button class="btn btn-primary" type="submit"><?= $id ?</pre>
'Modifier' : 'Sauvegarder' ?></button>
         </div>
       </form>
     </div>
   </div>
   <?php require_once 'includes/footer.php' ?>
 </div>
```

```
</body>
```

Modification de show-article.css

Nous en profitons pour modifier une classe :

```
.article-container {
  width: 100%;
  padding-bottom: 10rem;
}
```

Modification de delete-article.php

Nous utilisons PDO et notre base de données MySQL:

```
$pdo = require_once 'database.php';

$statement = $pdo->prepare('DELETE FROM article WHERE id=:id');

$_GET = filter_input_array(INPUT_GET,

FILTER_SANITIZE_FULL_SPECIAL_CHARS);

$id = $_GET['id'] ?? '';

if ($id) {

    $statement->bindValue(':id', $id);

    $statement->execute();
}

header('Location: /');
```