

Lab 4 - Vibe Coding: Complete LLM Chat History

Name: Samvith Vaddiparthi | SRN: PES1UG24AM468 | Section H | Scenario 19 - Battleship vs AI
LLM used: Claude (Claude Code desktop app, model Claude Opus 5.5). Long tool outputs are truncated for readability.

Student (Samvith)

https://github.com/RuthuHK/software-engineering-lab-material_sec_h/blob/main/Sec_H_Scenarios_assigned.xlsx

this is the github link, my scenario is 64, finish the lab

u have to record some videos of some before and after, is it mentioned anywhere in the instructions in the github? Imk before u finish the full thing, also use name: Samvith Vaddiparthi , SRN: PES1UG24AM468

Tool call: Bash

```
# Clone lab repo and list its files
ls -la && git clone --depth 1 https://github.com/RuthuHK/software-engineering-lab-material_sec_h.git 2>&1 | tail -2 && find software-engineering-lab-material_sec_h -not -path '*/.git*' | head -100
```

▼ Tool output

```
total 17408
drwxr-xr-x 23 samvithvaddiparthi staff 736 Oct 6 21:08 .
drwxr-x---+ 79 samvithvaddiparthi staff 2528 Oct 7 11:44 ..
-rw-r--r--@ 1 samvithvaddiparthi staff 6148 Sep 27 16:46 .DS_Store
-rw-r--r--@ 1 samvithvaddiparthi staff 1079119 Sep 3 20:24 PES1UG24AM448_LAB2.docx
-rw-r--r--@ 1 samvithvaddiparthi staff 1081713 Sep 3 20:21 PES1UG24AM448_LAB2.pdf
-rw-r--r--@ 1 samvithvaddiparthi staff 315425 Sep 13 16:51 PES1UG24AM448_LAB3.docx
-rw-r--r--@ 1 samvithvaddiparthi staff 290754 Sep 13 16:51 PES1UG24AM448_LAB3.pdf
-rw-r--r--@ 1 samvithvaddiparthi staff 52197 Sep 13 16:51
PES1UG24AM448_LAB3_ComponentDiagram.pdf
-rw-r--r--@ 1 samvithvaddiparthi staff 299939 Sep 13 16:51
PES1UG24AM448_LAB3_ComponentDiagram.png
-rw-r--r--@ 1 samvithvaddiparthi staff 1347043 Sep 2 23:03 PES1UG24AM468_LAB2.docx
-rw-r--r--@ 1 samvithvaddiparthi staff 1307127 Sep 5 12:42 PES1UG24AM468_LAB2.pdf
-rw-r--r--@ 1 samvithvaddiparthi staff 319469 Sep 11 19:46 PES1UG24AM468_LAB3.docx
-rw-r--r--@ 1 samvithvaddiparthi staff 292540 Sep 11 19:46 PES1UG24AM468_LAB3.pdf
-rw-r--r--@ 1 samvithvaddiparthi staff 50162 Sep 10 10:34
PES1UG24AM468_LAB3_ComponentDiagram.pdf
-rw-r--r--@ 1 samvithvaddiparthi staff 305906 Sep 10 10:34
PES1UG24AM468_LAB3_ComponentDiagram.png
-rw-r--r--@ 1 samvithvaddiparthi staff 38486 Sep 10 10:34
PES1UG24AM468_LAB3_Justification.docx
-rw-r--r--@ 1 samvithvaddiparthi staff 59304 Sep 10 10:34 PES1UG24AM468_LA
... [8573 more characters truncated]
```

Tool call: Bash

```
# Read README, recent commits, and Lab 4 handout
cd /Users/samvithvaddiparthi/SE_Lab/software-engineering-lab-material_sec_h && cat README.md;
git log -5 --format='%ad %s' --date=short; echo ----; pdftotext -layout
lab4/Lab_4_VibeCoding_Student_handout.pdf - 2>/dev/null || python3 -c "import
pypdf;r=pypdf.PdfReader('lab4/Lab_4_VibeCoding_Student_handout.pdf');print('\n'.join(p.extract_t
ext() for p in r.pages))"
```

Tool call: Bash

```
# Find scenario 64 and user's row in spreadsheets
cd /Users/samvithvaddiparthi/SE_Lab/software-engineering-lab-material_sec_h && python3 -c "
import openpyxl
for f in ['Sec_H_Scenarios_assigned.xlsx','lab4/Section_H_Vibe_Coding_Assignments.xlsx']:
```

```

wb=openpyxl.load_workbook(f)
for ws in wb:
    print('==',f,ws.title,ws.max_row,ws.max_column)
    for r in ws.iter_rows(values_only=True):
        s=' | '.join(str(c) for c in r if c is not None)
        if s and ('64' in s or 'AM468' in s or r==next(ws.iter_rows(values_only=True))):
            print(s)

```

▼ Tool output

```

**Name:** Ruthu H Kumar
**Email:** [peslug23am246@pesu.pes.edu](mailto:peslug23am246@pesu.pes.edu)

```

Contact

For any queries or communication regarding the SE lab classes, please contact me via my PES University email.

2026-10-06 Rename Section_H_Vibe_Coding_Assignments.xlsx to
lab4/Section_H_Vibe_Coding_Assignments.xlsx

Lab 4: VibeCoding

Objective

Use Vibe Coding tools to fix the broken code and add features to the same. Learn how to prompt to get the job done in under three to four attempts. Clone a repo assigned to you, make changes and push to your repo in your personal account.

THIS IS AN INDIVIDUAL ASSIGNMENT. WORK INDIVIDUALLY!!

Duration

60 minutes

Software Requirements

- Access to Vibe Coding tool. (ChatGPT, Gemini, Claude etc)

Instructions:

1. Go to the repo assigned to you
2. Go through the ReadMe file to understand the deliverables
3. Clone or Fork the repo
4. Run the Python based code (A game/ A Puzzle)
5. Record 10 seconds of video before making any changes.
6. Write prompts and fix the broken code
7. Write prompts to add all the features listed in the ReadMe file of the repo one by one.
8. Record another 10 seconds of video again after making all the changes.
9. Push the code to your repo.
10. Have Separate Commits for each task
11. Do not raise PR to the main repo (SETAPESU26)

Deliverables:

Upload the following to your Lab repo under Lab-4 folder,

- a. Videos (before and after)

... [69 more characters truncated]

▼ Tool output

Exit code 1

Traceback (most recent call last):

```

File "<string>", line 2, in <module>
ModuleNotFoundError: No module named 'openpyxl'

```

Tool call: Bash

```
# Install openpyxl and find user's rows
pip3 install -q openpyxl 2>&1 | tail -1; python3 -c "
import openpyxl
for f in ['Sec_H_Scenarios_assigned.xlsx','lab4/Section_H_Vibe_Coding_Assignments.xlsx']:
    wb=openpyxl.load_workbook(f)
    for ws in wb:
        print('==',f,ws.title,ws.max_row,ws.max_column)
        rows=list(ws.iter_rows(values_only=True))
        print(rows[0])
        for r in rows:
            s=' | '.join(str(c) for c in r if c is not None)
            if 'AM468' in s or 'Samvith' in s or any(str(c).strip()=='64' for c in r if c is not
None): print(s)
"
```

▼ Tool output

```
[notice] To update, run: pip3 install --upgrade pip
== Sec_H_Scenarios_assigned.xlsx 5-H 61 5
('#', 'SRN', 'Name', 'Problem Statement', None)
46 | PES1UG24AM468 | VADDIPARTHI SAMVITH | 64_SE_Lab1_SE_Problem_Statements
== lab4/Section_H_Vibe_Coding_Assignments.xlsx 5-H 63 5
('PES UNIVERSITY, Bangalore', None, None, None, None)
1 | PES1UG24AM420 | ADITYA SINGHAL | 64 | https://github.com/SETAPESU26/64_fruit_catcher
46 | PES1UG24AM468 | VADDIPARTHI SAMVITH | 19 | https://github.com/SETAPESU26/19_battleship
```

Tool call: Bash

```
# Clone both candidate Lab 4 repos and check GitHub auth
cd /Users/samvithvaddiparthi/SE_Lab && for r in 19_battleship 64_fruit_catcher; do git clone -q
--depth 1 https://github.com/SETAPESU26/$r.git lab4_$r 2>&1; echo "=== $r"; find lab4_$r -not -
path '*/.git*' -type f; cat lab4_$r/README.md; done; gh auth status 2>&1 | head -3; gh repo list
--limit 30 2>&1
```

▼ Tool output

```
Exit code 127
=== 19_battleship
lab4_19_battleship/board.py
lab4_19_battleship/requirements.txt
lab4_19_battleship/game.py
lab4_19_battleship/ai.py
lab4_19_battleship/README.md
lab4_19_battleship/main.py
# Scenario 19 – Battleship vs AI
```

A terminal Battleship game with separate board and AI modules.

Provided files

- `main.py` – entry point.
- `game.py` – turn flow and setup.
- `board.py` – ship and shot state.
- `ai.py` – computer targeting.
- `requirements.txt` – dependency declaration.

Setup

```
```bash
python main.py
```
```

Before changing the code

Inspect how coordinates are represented in every module. Fire at known ship cells and known empty cells. Then trace an AI shot from selection to hit detection.

Task 1 – Consistent coordinate handling

Make coordinate representation consistent across input, ship placement, player shots, and AI shots so occupied cells are recognised correctly.

****Done when:**** every real ship coordinate is treated as a hit and every known empty coordinate is treated as a miss.

Task 2 – Complete fleet and win logic

Support multiple ships, track individual ship damage, identify sunk ships, prevent repeated shots, and end the game when the fleet is sunk.

Task 3 – Improve the AI

After a hit, make the AI preferentially consider nearby untried cells. It must never shoot the same coordinate twice and must handle a board with no remaining choices.

Task 4 – Shot-level feedback

Ensure hit/miss/sunk feedback occurs exactly once for
... [5445 more characters truncated]

Tool call: Bash

```
# Check for existing lab repo and available tools
cd /Users/samvithvaddiparthi/SE_Lab && ls lab3_build; git -C lab3_build remote -v 2>&1 | head;
which ffmpeg asciinema vhs python3; python3 --version; python3 -c "import pygame" 2>&1
```

▼ Tool output

```
Exit code 1
coffee_kiosk_version
diagram.pdf
diagram.png
diagram.svg
justification.docx
make_report.py
s63
fatal: not a git repository (or any of the parent directories): .git
ffmpeg not found
asciinema not found
vhs not found
/Library/Frameworks/Python.framework/Versions/3.12/bin/python3
Python 3.12.4
Traceback (most recent call last):
  File "<string>", line 1, in <module>
ModuleNotFoundError: No module named 'pygame'
```

Claude

I've read the lab instructions but haven't changed any code yet. Before I start, there's a problem with which scenario to do.

Your Lab 4 repo is 19 (Battleship), not 64. In lab4/Section_H_Vibe_Coding_Assignments.xlsx the row for PES1UG24AM468 (VADDIPARTHI SAMVITH) gives **19** → https://github.com/SETAPESU26/19_battleship. Scenario 64 (64_fruit_catcher) is assigned to ADITYA SINGHAL (PES1UG24AM420). Your "64" comes from Sec_H_Scenarios_assigned.xlsx, which is the Lab 1–3 problem statement your ATM SRS was based on. I've downloaded both repos so I can do either one.

Yes, videos are required. Both the Lab 4 handout and the repo README say so: - Step 5: record a **10-second video before** making any changes, showing the bug. - Step 8: record a **10-second video after** all the changes, showing the fix and the new features working.

Everything else you need to hand in, from the handout: - Upload to your own Lab repo, inside a Lab-4 folder: (a) the before and after videos, (b) the updated code, (c) your chat history exported as a doc or PDF. - Make a **separate commit for each task**, and push to your personal repo. **Don't raise**

a PR to SETAPESU26. - The Battleship README lists 4 tasks: (1) use the same coordinate format everywhere, so real ship cells count as hits; (2) multiple ships, sunk ships, no repeat shots, and a win condition; (3) the AI aims at cells next to a hit, never fires twice at the same cell, and copes when no cells are left; (4) hit/miss/sunk messages print exactly once per real shot. It also lists required tests.

Before I finish it, I need two things from you: 1. **Battleship (19) or Fruit Catcher (64)?** I'd go with 19 because that's what the sheet assigns you, unless your instructor told you otherwise. 2. **Your Lab repo URL.** The GitHub CLI (gh) isn't installed here and I can't find a local copy of your lab repo. If you don't have one yet, I can set up the Lab-4 folder locally with one commit per task, and you push it.

About the videos: Battleship runs in the terminal, so the easiest way is to record your screen yourself with Cmd+Shift+5 (about 10 seconds each). I'll give you the exact inputs that show the bug before the fix and the features after it. I can't record them with what's installed: there's no ffmpeg and no terminal recorder. If you'd rather I generate them, I'd need to install ffmpeg with Homebrew.

I'll also use **Samvith Vaddiparthi / PES1UG24AM468** for the commit author and file names.

Student (Samvith)

yes i will push it, use 19, do it properly, no mistakes

Tool call: Bash

```
# Read all Battleship source files
cd /Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship && for f in main.py game.py board.py
ai.py requirements.txt; do echo "==== $f"; cat -n $f; done; git log --oneline
```

▼ Tool output

```
==== main.py
1  from game import Battleship
2
3  if __name__ == "__main__":
4      Battleship().run()
==== game.py
1  from board import Board
2  from ai import AI
3
4
5  class Battleship:
6      def __init__(self):
7          self.player = Board()
8          self.enemy = Board()
9          self.ai = AI()
10         self._setup()
11
12     def _setup(self):
13         self.player.place_ship({(1, 1), (1, 2), (1, 3)})
14         self.enemy.place_ship({(2, 2), (2, 3), (2, 4)})
15
16     def show(self):
17         print("\nYour shots are coordinates like 2,3.")
18         print("Ship cells remaining:", len(self.enemy.ships - self.player.shots))
19
20     def run(self):
21         print("Battleship")
22         while True:
23             self.show()
24             raw = input("> ").strip().lower()
25             if raw == "q":
26                 return
27             try:
28                 r, c = map(int, raw.split(","))
29                 pos = (r - 1, c - 1)
30             except ValueError:
31                 print("Use row,col.")
```

```

32         continue
33     if not (0 <= pos[0] < Board.SIZE and 0 <= pos[1] < Board.SIZE):
34         print("Outside board.")
35         continue
36     if pos in self.player.shots:
37         print("Already fired there.")
38
... [1921 more characters truncated]

```

Student (Samvith)

do 19 battleship, set it up locally and i'll push, and yes install the recording things required cuz u only record it as well

Tool call: Bash

```

# Check Homebrew and git identity
which brew && brew --version | head -1; git config --global user.name; git config --global user.email

```

▼ Tool output

```

/opt/homebrew/bin/brew
Homebrew 6.0.21
samvithvaddiparthi-ship-it
samvith.vaddiparthi@gmail.com

```

Tool call: Bash

```

# Install VHS terminal recorder and ffmpeg
brew install vhs ffmpeg 2>&1 | tail -15

```

▼ Tool output

Command running in background with ID: b3h9zxtvk. Output is being written to: /private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/tasks/b3h9zxtvk.output. You will be notified when it completes. To check interim output, use Read on that file path.

Claude

Installing the recorder in the background. Meanwhile, reproducing the original bugs:

Tool call: Bash

```

# Reproduce original defects with scripted input
git remote rename origin upstream && git config user.name "Samvith Vaddiparthi" && git config user.email "samvith.vaddiparthi@gmail.com" && printf '1,1\n3,3\n3,3\n3,4\n3,5\n' | python3 main.py; echo; python3 -c "
import random
from game import Battleship
from ai import AI
a=AI(); s=a.choose(); print('AI.choose() returns', repr(s), type(s).__name__)
# trace: AI picks internal (0,0) -> string '1,1' -> game parses to (1,1) which is a player ship cell
g=Battleship(); print('player ships', sorted(g.player.ships))
for internal in [(0,0),(1,1)]:
    s=f'{internal[0]+1},{internal[1]+1}'; parsed=tuple(map(int,s.split(',')))
    print('AI actual cell',internal,'-> string',s,'-> parsed',parsed,'-> game says hit?',parsed in g.player.ships,'| truly a ship?',internal in g.player.ships)
"

```

▼ Tool output

Battleship

Your shots are coordinates like 2,3.

```

Ship cells remaining: 3
> MISS!
AI fired at 4,5

Your shots are coordinates like 2,3.
Ship cells remaining: 3
> HIT!
AI fired at 3,3

Your shots are coordinates like 2,3.
Ship cells remaining: 3
> HIT!
AI fired at 2,5

Your shots are coordinates like 2,3.
Ship cells remaining: 3
> HIT!
You sank the fleet.

AI.choose() returns '6,4' str
player ships [(1, 1), (1, 2), (1, 3)]
AI actual cell (0, 0) -> string 1,1 -> parsed (1, 1) -> game says hit? True | truly a ship?
False
AI actual cell (1, 1) -> string 2,2 -> parsed (2, 2) -> game says hit? False | truly a ship?
True

```

Tool call: Write

/Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/coords.py

```

"""Single source of truth for coordinates.

```

```

Inside the game every coordinate is a 0-based ``(row, col)`` tuple: ship
placement, the shots stored on a board, player shots and AI shots all use
it. The 1-based ``"row,col"`` text the player types and reads is converted
only at the edges with :func:`parse_coord` and :func:`format_coord`.
"""

```

```

SIZE = 6

```

```

def in_bounds(pos, size=SIZE):
    row, col = pos
    return 0 <= row < size and 0 <= col < size

```

```

def parse_coord(raw, size=SIZE):
    """Convert player text such as ``"2,3"`` into the internal ``(1, 2)``.

    Raises ValueError with a message that can be shown to the player.
    """
    parts = raw.split(",")
    if len(parts) != 2:
        raise ValueError("Use row,col (for example 2,3).")
    try:
        row, col = (int(part) for part in parts)
    except ValueError:
        raise ValueError("Use row,col (for example 2,3).") from None
    pos = (row - 1, col - 1)
    if not in_bounds(pos, size):
        raise ValueError(f"Outside board. Rows and columns go from 1 to {size}.")
    return pos

```

```
def format_coord(pos):
    """Convert an internal ``(row, col)`` tuple into the text the player sees."""
    return f"{pos[0] + 1},{pos[1] + 1}"
```

Tool call: Write

/Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/board.py

```
from coords import SIZE, in_bounds

class Board:
    SIZE = SIZE

    def __init__(self, size=SIZE):
        self.size = size
        self.ships = set() # occupied cells, 0-based (row, col)
        self.shots = set() # cells fired at on this board, 0-based (row, col)

    def place_ship(self, cells):
        cells = set(cells)
        if not all(in_bounds(cell, self.size) for cell in cells):
            raise ValueError("Ship placed outside the board.")
        self.ships.update(cells)

    def fire(self, pos):
        self.shots.add(pos)
        return pos in self.ships

    def remaining(self):
        return len(self.ships - self.shots)

    def all_sunk(self):
        return self.ships <= self.shots
```

Tool call: Write

/Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/ai.py

```
import random

from coords import SIZE

class AI:
    def __init__(self, size=SIZE):
        self.size = size
        self.tried = set()

    def choose(self):
        """Return an untried cell as a 0-based (row, col) tuple."""
        options = [(r, c) for r in range(self.size) for c in range(self.size)
                    if (r, c) not in self.tried]
        pos = random.choice(options)
        self.tried.add(pos)
        return pos
```

Tool call: Write

/Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/game.py

```
from board import Board
from ai import AI
from coords import parse_coord, format_coord

class Battleship:
    def __init__(self):
        self.player = Board()
```

```

self.enemy = Board()
self.ai = AI()
self._setup()

def _setup(self):
    # Internal coordinates are 0-based: (1, 1) is shown to the player as 2,2.
    self.player.place_ship({(1, 1), (1, 2), (1, 3)})
    self.enemy.place_ship({(2, 2), (2, 3), (2, 4)})

def show(self):
    print("\nYour shots are coordinates like 2,3.")
    print("Ship cells remaining:", self.enemy.remaining())

def run(self):
    print("Battleship")
    while True:
        self.show()
        raw = input("> ").strip().lower()
        if raw == "q":
            return
        try:
            pos = parse_coord(raw)
        except ValueError as err:
            print(err)
            continue
        if pos in self.enemy.shots:
            print("Already fired there.")
            continue
        print("HIT!" if self.enemy.fire(pos) else "MISS!")
        if self.enemy.all_sunk():
            print("You sank the fleet.")
            return

        # The AI hands back the same (row, col) tuple used everywhere
        # else, and its shot is resolved against the player's board.
        ai_pos = self.ai.choose()
        print("AI fired at", format_coord(ai_pos))
        print("AI scored a hit." if self.player.fire(ai_pos) else "AI missed.")

```

▼ Tool output

File created successfully at: /Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/coords.py
(file state is current in your context – no need to Read it back)

▼ Tool output

The file /Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/board.py has been updated successfully. (file state is current in your context – no need to Read it back)

▼ Tool output

The file /Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/ai.py has been updated successfully. (file state is current in your context – no need to Read it back)

▼ Tool output

The file /Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/game.py has been updated successfully. (file state is current in your context – no need to Read it back)

Tool call: Bash

```

# Add Task 1 tests, run them, and replay the bug scenario
mkdir -p tests && cat > tests/test_coordinates.py <<'EOF'
"""Task 1: one coordinate representation across input, placement and shots."""
import unittest

from ai import AI
from board import Board
from coords import format_coord, parse_coord

```

```

from game import Battleship

class CoordinateTests(unittest.TestCase):
    def test_parse_is_one_based_text_to_zero_based_tuple(self):
        self.assertEqual(parse_coord("1,1"), (0, 0))
        self.assertEqual(parse_coord("2,3"), (1, 2))
        self.assertEqual(parse_coord(" 6 , 6 "), (5, 5))

    def test_format_round_trips(self):
        for r in range(Board.SIZE):
            for c in range(Board.SIZE):
                self.assertEqual(parse_coord(format_coord((r, c))), (r, c))

    def test_invalid_coordinates_rejected(self):
        for raw in [ "", "2", "2,", ",3", "a,b", "1,2,3", "0,1", "1,0", "7,1", "1,7", "-1,2",
"2.5,1" ]:
            with self.subTest(row=raw):
                with self.assertRaises(ValueError):
                    parse_coord(raw)

    def test_ai_returns_internal_tuple(self):
        pos = AI().choose()
        self.assertIsInstance(pos, tuple)
        self.assertTrue(0 <= pos[0] < Board.SIZE and 0 <= pos[1] < Board.SIZE)

    def test_every_ship_cell_hits_and_every_empty_cell_misses(self):
        # Both boards, every cell, exactly as the game sets them up.
        game = Battleship()
        for board in (game.player, game.enemy):
            ships = set(board.ships)
            for r in range(Board.SIZE):
                for c in range(Board.SIZE):
                    self.assertEqual(board.fire((r, c)), (r, c) in ships)

    def test_player_text_hits_the_cell_it_names(self):
        game = Battleship()
        self.assertTrue(game.enemy.fire(parse_coord("3,3"))) # enemy ship at (2, 2)
        self.assertFalse(game.enemy.fire(parse_coord("1,1"))) # known empty cell

    def test_ai_shot_is_resolved_on_the_cell_it_chose(self):
        # Previously the AI's 1-based text was compared with 0-based cells,
        # so AI cell (0, 0) was reported as a hit on the ship at (1, 1).
        game = Battleship()
        self.assertFalse(game.player.fire((0, 0)))
        self.assertTrue(game.player.fire((1, 1)))
        self.assertEqual(game.player.shots, {(0, 0), (1, 1)})

if __name__ == "__main__":
    unittest.main()
EOF
python3 -m unittest discover -s tests -v 2>&1 | tail -15; printf '1,1\n3,3\n3,3\n3,4\n3,5\n' |
python3 main.py

```

▼ Tool output

```

test_ai_returns_internal_tuple (test_coordinates.CoordinateTests.test_ai_returns_internal_tuple)
... ok
test_ai_shot_is_resolved_on_the_cell_it_chose
(test_coordinates.CoordinateTests.test_ai_shot_is_resolved_on_the_cell_it_chose) ... ok
test_every_ship_cell_hits_and_every_empty_cell_misses
(test_coordinates.CoordinateTests.test_every_ship_cell_hits_and_every_empty_cell_misses) ... ok
test_format_round_trips (test_coordinates.CoordinateTests.test_format_round_trips) ... ok
test_invalid_coordinates_rejected
(test_coordinates.CoordinateTests.test_invalid_coordinates_rejected) ... ok
test_parse_is_one_based_text_to_zero_based_tuple
(test_coordinates.CoordinateTests.test_parse_is_one_based_text_to_zero_based_tuple) ... ok
test_player_text_hits_the_cell_it_names
(test_coordinates.CoordinateTests.test_player_text_hits_the_cell_it_names) ... ok

```

Ran 7 tests in 0.000s

OK

Battleship

Your shots are coordinates like 2,3.

Ship cells remaining: 3

> MISS!

AI fired at 3,1

AI missed.

Your shots are coordinates like 2,3.

Ship cells remaining: 3

> HIT!

AI fired at 5,4

AI missed.

Your shots are coordinates like 2,3.

Ship cells remaining: 2

> Already fired there.

Your shots are coordinates like 2,3.

Ship cells remaining: 2

> HIT!

AI fired at 6,6

AI missed.

Your shots are coordinates like 2,3.

Ship cells remaining: 1

> HIT!

You sank the fleet.

Claude

Task 1 tests pass, and the replay now behaves correctly. Committing Task 1:

Tool call: Bash

```
# Commit Task 1 and verify recorder install
printf '__pycache__/\n*.pyc\n' > .gitignore && git add -A && git commit -q -F - <<'EOF'
Task 1: Use one coordinate representation everywhere
```

All modules now use 0-based (row, col) tuples internally; 1-based "row,col" text is converted only at the input/output edge (new coords.py).

Fixes:

- AI.choose() returned 1-based text that game.py compared to 0-based ship cells, so AI cell (0,0) was reported as a hit and real ship cells as misses.
- AI shots were never recorded on the player's board.
- Repeat-shot check and "cells remaining" looked at the player's board instead of the enemy board, so the same cell could be hit repeatedly.
- Invalid input such as "1,2,3" or "a,b" is rejected with a clear message.

Adds tests/test_coordinates.py.

Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>

EOF

```
git log --oneline; tail -5 /private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/tasks/b3h9zxtvk.output; which vhs ffmpeg ttyd
```

▼ Tool output

9927faa Task 1: Use one coordinate representation everywhere

68e3f33 Updated scenario title

OpenSSL 3.6 is only supported until 2026-11-01 so the `openssl@3` formula will be downgraded to OpenSSL 3.5 (LTS) in a future update.

```
[exited with code 0]
/opt/homebrew/bin/vhs
/opt/homebrew/bin/ffmpeg
/opt/homebrew/bin/ttyd
```

Claude

Task 2: fleet, sinking, repeated shots, and win/lose logic.

Tool call: Write

/Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/board.py

```
from coords import SIZE, format_coord, in_bounds

class RepeatedShotError(ValueError):
    """Raised when a cell that was already fired at is fired at again."""

class Ship:
    def __init__(self, name, cells):
        self.name = name
        self.cells = frozenset(cells)
        self.hits = set()

    @property
    def sunk(self):
        return self.hits == self.cells

class ShotResult:
    """Outcome of one shot: whether it hit and which ship (if any) it sank."""

    def __init__(self, pos, hit, sunk_ship=None):
        self.pos = pos
        self.hit = hit
        self.sunk_ship = sunk_ship

class Board:
    SIZE = SIZE

    def __init__(self, size=SIZE):
        self.size = size
        self.fleet = []
        self.shots = set() # cells fired at on this board, 0-based (row, col)

    @property
    def ships(self):
        """Every occupied cell, 0-based (row, col)."""
        return {cell for ship in self.fleet for cell in ship.cells}

    def place_ship(self, name, cells):
        cells = set(cells)
        if not cells:
            raise ValueError("A ship needs at least one cell.")
        if not all(in_bounds(cell, self.size) for cell in cells):
            raise ValueError(f"{name} is outside the board.")
        if cells & self.ships:
            raise ValueError(f"{name} overlaps another ship.")
        rows = {r for r, _ in cells}
        cols = {c for _, c in cells}
        straight = len(rows) == 1 or len(cols) == 1
```

```

        span = max(len(rows), len(cols))
        if not straight or span != len(cells):
            raise ValueError(f"{name} must be one straight, unbroken line.")
        ship = Ship(name, cells)
        self.fleet.append(ship)
        return ship

    def ship_at(self, pos):
        for ship in self.fleet:
            if pos in ship.cells:
                return ship
        return None

    def already_fired(self, pos):
        return pos in self.shots

    def fire(self, pos):
        if not in_bounds(pos, self.size):
            raise ValueError("Shot outside the board.")
        if pos in self.shots:
            raise RepeatedShotError(f"Already fired at {format_coord(pos)}.")
        self.shots.add(pos)
        ship = self.ship_at(pos)
        if ship is None:
            return ShotResult(pos, hit=False)
        ship.hits.add(pos)
        return ShotResult(pos, hit=True, sunk_ship=ship if ship.sunk else None)

    def remaining(self):
        return len
... [216 more characters truncated]

```

Tool call: Write

/Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/game.py

```

from board import Board
from ai import AI
from coords import parse_coord, format_coord

# Internal coordinates are 0-based: (1, 1) is shown to the player as 2,2.
PLAYER_FLEET = {
    "Cruiser": [(1, 1), (1, 2), (1, 3)],
    "Destroyer": [(3, 4), (4, 4)],
    "Patrol Boat": [(5, 0), (5, 1)],
}
ENEMY_FLEET = {
    "Cruiser": [(2, 2), (2, 3), (2, 4)],
    "Destroyer": [(4, 0), (5, 0)],
    "Patrol Boat": [(0, 4), (0, 5)],
}
QUIT_WORDS = {"q", "quit", "exit"}

class Battleship:
    def __init__(self, ai=None, input_func=input):
        self.player = Board()
        self.enemy = Board()
        self.ai = ai if ai is not None else AI()
        self.input = input_func
        self._setup()

    def _setup(self):
        for name, cells in PLAYER_FLEET.items():
            self.player.place_ship(name, cells)
        for name, cells in ENEMY_FLEET.items():
            self.enemy.place_ship(name, cells)

    def show(self):

```

```

        print("\nYour shots are coordinates like 2,3.")
        print(f"Enemy ships afloat: {len(self.enemy.ships_afloat())}/{len(self.enemy.fleet)}"
              f" | Your ships afloat: {len(self.player.ships_afloat())}/{len(self.player.fleet)}")

    def _read_player_shot(self):
        """Prompt until the player gives a new, valid cell. None means quit."""
        while True:
            try:
                raw = self.input("> ").strip().lower()
            except (EOFError, KeyboardInterrupt):
                print()
                return None
            if raw in QUIT_WORDS:
                return None
            try:
                pos = parse_coord(raw)
            except ValueError as err:
                print(err)
                continue
            if self.enemy.already_fired(pos):
                print(f"Already fired at {format_coord(pos)}. Pick another cell.")
                continue
            return pos

    def run(self):
        """Play until someone's fleet is sunk. Returns "player", "ai" or "quit"."""
        print("Battleship")
        while True:
            self.show()
            pos = self._read_player_shot()
            if pos is None:
                print("You quit the game.")
                return "quit"
            result = self.enemy.fire(pos)
            print("HIT!" if result.hit else "MISS!")
            if result.sunk_ship:
                print(f"You sank the enemy {result.sunk_ship.name}!")
            if self.enemy.all_sunk():

```

... [518 more characters truncated]

▼ Tool output

The file /Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/board.py has been updated successfully. (file state is current in your context – no need to Read it back)

▼ Tool output

The file /Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/game.py has been updated successfully. (file state is current in your context – no need to Read it back)

Tool call: Bash

```

# Update Task 1 tests, add Task 2 tests, run suite
sed -i 's/self.assertEqual(board.fire((r, c)), (r, c) in ships)/self.assertEqual(board.fire((r, c)).hit, (r, c) in ships)/;
s/self.assertEqual(game.enemy.fire(parse_coord("3,3"))/self.assertTrue(game.enemy.fire(parse_coord("3,3")).hit)/;
s/self.assertFalse(game.enemy.fire(parse_coord("1,1"))/self.assertFalse(game.enemy.fire(parse_coord("1,1")).hit)/; s/self.assertFalse(game.player.fire((0, 0))/self.assertFalse(game.player.fire((0, 0)).hit)/; s/self.assertTrue(game.player.fire((1, 1))/self.assertTrue(game.player.fire((1, 1)).hit)/' tests/test_coordinates.py && grep -n 'fire' tests/test_coordinates.py
cat > tests/helpers.py <<'EOF'
"""Shared test helpers: scripted input and a scripted AI."""
import contextlib
import io

```

```

class ScriptedAI:
    """Stands in for AI; fires at a fixed list of 0-based cells in order."""

    def __init__(self, shots):
        self.shots = list(shots)
        self.recorded = []

    def choose(self):
        return self.shots.pop(0) if self.shots else None

    def record(self, pos, result):
        self.recorded.append((pos, result))

def scripted_input(lines):
    """input() replacement that replays lines, then behaves like Ctrl+D."""
    lines = list(lines)

    def fake_input(prompt=""):
        if not lines:
            raise EOFError
        return lines.pop(0)
    return fake_input

def play(game):
    """Run a game, returning (outcome, printed output)."""
    out = io.StringIO()
    with contextlib.redirect_stdout(out):
        outcome = game.run()
    return outcome, out.getvalue()

EOF
cat > tests/test_fleet.py <<'EOF'
"""Task 2: multiple ships, per-ship damage, sinking, repeat shots, win/lose."""
import unittest

from board import Board, RepeatedShotError
from coords import format_coord
from game import ENEMY_FLEET, PLAYER_FLEET, Battleship
from tests.helpers import ScriptedAI, play, scripted_input

ENEMY_CELLS = [cell for cells in ENEMY_FLEET.values() for cell in cells]
PLAYER_CELLS = [cell for cells in PLAYER_FLEET.values() for cell in cells]
# Cells with no ship on either board, used as harmless "misses".
EMPTY = [(r, c) for r in range(Board.SIZE) for c in range(Board.SIZE)
          if (r, c) not in ENEMY_CELLS and (r, c) not in PLAYER_CELLS]

def text(cells):
    return [format_coord(cell) for cell in cells]

class BoardTests(unittest.TestCase):
    def setUp(self):
        self.board = Board()
        self.cruiser = self.board.place_ship("Cruiser", [(0, 0),
... [4698 more characters truncated]

```

▼ Tool output

```

39:             self.assertEqual(board.fire((r, c)).hit, (r, c) in ships)
43:             self.assertTrue(game.enemy.fire(parse_coord("3,3")).hit) # enemy ship at (2, 2)
44:             self.assertFalse(game.enemy.fire(parse_coord("1,1")).hit) # known empty cell
50:             self.assertFalse(game.player.fire((0, 0)).hit)
51:             self.assertTrue(game.player.fire((1, 1)).hit)
test_player_text_hits_the_cell_it_names
(tests.test_coordinates.CoordinateTests.test_player_text_hits_the_cell_it_names) ... ok
test_damage_is_tracked_per_ship (tests.test_fleet.BoardTests.test_damage_is_tracked_per_ship)
... ok

```

```

test_empty_board_is_not_sunk (tests.test_fleet.BoardTests.test_empty_board_is_not_sunk) ... ok
test_hit_and_miss (tests.test_fleet.BoardTests.test_hit_and_miss) ... ok
test_invalid_placements_rejected (tests.test_fleet.BoardTests.test_invalid_placements_rejected)
...
test_invalid_placements_rejected
(tests.test_fleet.BoardTests.test_invalid_placements_rejected) (name='Gap') ... FAIL
test_repeated_shot_rejected_and_not_counted
(tests.test_fleet.BoardTests.test_repeated_shot_rejected_and_not_counted) ... ok
test_shot_outside_board_rejected (tests.test_fleet.BoardTests.test_shot_outside_board_rejected)
... ok
test_sinking_all_ships (tests.test_fleet.BoardTests.test_sinking_all_ships) ... ok
test_sinking_one_ship (tests.test_fleet.BoardTests.test_sinking_one_ship) ... ok
test_ai_wins_when_player_fleet_sunk
(tests.test_fleet.GameFlowTests.test_ai_wins_when_player_fleet_sunk) ... ok

... [1319 more characters truncated]

```

Tool call: Bash

```

# Fix contiguity check, rerun tests and a full game
python3 - <<'EOF'
import re
p='board.py'; s=open(p).read()
old=''
    rows = {r for r, _ in cells}
    cols = {c for _, c in cells}
    straight = len(rows) == 1 or len(cols) == 1
    span = max(len(rows), len(cols))
    if not straight or span != len(cells):
...
new=''
    rows = {r for r, _ in cells}
    cols = {c for _, c in cells}
    straight = len(rows) == 1 or len(cols) == 1
    line = cols if len(rows) == 1 else rows
    unbroken = max(line) - min(line) + 1 == len(cells)
    if not (straight and unbroken):
...
assert old in s; open(p,'w').write(s.replace(old,new))
p='tests/test_fleet.py'; s=open(p).read()
old=''
    with self.assertRaises(RepeatedShotError):
        self.board.fire((5, 5)) if self.board.fire((5, 5)) else None
...
new=''
    self.board.fire((5, 5))
    with self.assertRaises(RepeatedShotError):
        self.board.fire((5, 5))
...
assert old in s; open(p,'w').write(s.replace(old,new))
EOF
python3 -m unittest discover -s tests -t . 2>&1 | tail -3; printf
'1,1\n3,3\n3,3\n3,4\n3,5\n5,1\n6,1\n1,5\n1,6\n' | python3 main.py | tail -22

```

▼ Tool output

Ran 22 tests in 0.001s

OK

> HIT!

AI fired at 2,1

AI missed.

Your shots are coordinates like 2,3.

Enemy ships afloat: 2/3 | Your ships afloat: 3/3

> HIT!

You sank the enemy Destroyer!

AI fired at 5,2

AI missed.

Your shots are coordinates like 2,3.

Enemy ships afloat: 1/3 | Your ships afloat: 3/3

> HIT!

AI fired at 1,1
AI missed.

Your shots are coordinates like 2,3.
Enemy ships afloat: 1/3 | Your ships afloat: 3/3
> HIT!
You sank the enemy Patrol Boat!
You sank the fleet. You win!

Tool call: Bash

```
# Run all tests and commit Task 2
python3 -m unittest 2>&1 | tail -2 && git add -A && git commit -q -F - <<'EOF'
Task 2: Complete fleet, sinking, repeat-shot and win logic
```

- Ship class tracks its own cells and hits; Board keeps a fleet of ships.
- Each side now has three ships (Cruiser, Destroyer, Patrol Boat).
- Board.place_ship rejects overlapping, off-board, diagonal or broken ships.
- Board.fire returns a ShotResult (hit, sunk ship) and raises RepeatedShotError for a cell that was already fired at.
- Repeated or invalid player shots are rejected without using a turn.
- Sunk ships are announced; the game ends when either fleet is sunk (player win or AI win), on q/quit/exit, or on Ctrl+D/Ctrl+C.

Adds tests/test_fleet.py and shared test helpers.

Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>
EOF
git log --online

▼ Tool output

OK
110f7ba Task 2: Complete fleet, sinking, repeat-shot and win logic
9927faa Task 1: Use one coordinate representation everywhere
68e3f33 Updated scenario title

Claude

Task 3: smarter AI targeting.

Tool call: Write

```
/Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/ai.py
```

```
import random

from coords import SIZE, in_bounds

DIRECTIONS = ((0, 1), (1, 0), (0, -1), (-1, 0))

class AI:
    """Hunt/target AI.

    Hunt: with no unsunk hits, fire at a random untried cell.
    Target: after a hit, fire at untried cells next to it. Once two hits
    line up, keep extending that line before trying other neighbours.
    Cells are 0-based (row, col) tuples and every cell is tried at most once.
    """

    def __init__(self, size=SIZE, rng=None):
        self.size = size
        self.rng = rng if rng is not None else random.Random()
        self.tried = set()
        self.open_hits = set() # hits on ships that are not sunk yet
```

```

def choose(self):
    """Return an untried cell, or None if every cell has been tried."""
    options = self._line_targets() or self._neighbour_targets() or self._untried()
    if not options:
        return None
    pos = self.rng.choice(sorted(options))
    self.tried.add(pos)
    return pos

def record(self, pos, result):
    """Learn from the outcome of the shot the AI just took."""
    self.tried.add(pos)
    if result.hit:
        self.open_hits.add(pos)
    if result.sunk_ship:
        self.open_hits -= result.sunk_ship.cells

def _is_open(self, pos):
    return in_bounds(pos, self.size) and pos not in self.tried

def _untried(self):
    return {(r, c) for r in range(self.size) for c in range(self.size)
            if (r, c) not in self.tried}

def _neighbour_targets(self):
    return {(r + dr, c + dc) for r, c in self.open_hits for dr, dc in DIRECTIONS
            if self._is_open((r + dr, c + dc))}

def _line_targets(self):
    """Open cells at either end of a run of two or more adjacent hits."""
    targets = set()
    for r, c in self.open_hits:
        for dr, dc in ((0, 1), (1, 0)):
            if (r + dr, c + dc) not in self.open_hits:
                continue
            for step in (1, -1):
                end = (r, c)
                while end in self.open_hits:
                    end = (end[0] + dr * step, end[1] + dc * step)
                    if self._is_open(end):
                        targets.add(end)
    return targets

```

Tool call: Edit

/Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/game.py

```

--- old
    ai_pos = self.ai.choose()
    result = self.player.fire(ai_pos)
    print("AI fired at", format_coord(ai_pos))

+++ new
    ai_pos = self.ai.choose()
    if ai_pos is None:
        print("The AI has no cells left to fire at.")
        continue
    result = self.player.fire(ai_pos)
    self.ai.record(ai_pos, result)
    print("AI fired at", format_coord(ai_pos))

```

▼ Tool output

The file /Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/ai.py has been updated successfully. (file state is current in your context – no need to Read it back)

▼ Tool output

The file /Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship/game.py has been updated successfully. (file state is current in your context – no need to Read it back)

Tool call: Bash

```
# Add Task 3 AI tests and compare AI vs random
cat > tests/test_ai.py <<'EOF'
"""Task 3: AI targets nearby cells after a hit and never repeats a shot."""
import random
import unittest

from ai import AI
from board import Board
from game import ENEMY_FLEET, Battleship
from coords import format_coord
from tests.helpers import play, scripted_input

def neighbours(pos):
    r, c = pos
    return {(r + 1, c), (r - 1, c), (r, c + 1), (r, c - 1)}

def take_shot(ai, board):
    pos = ai.choose()
    result = board.fire(pos)
    ai.record(pos, result)
    return pos, result

class AITests(unittest.TestCase):
    def test_never_repeats_and_covers_whole_board(self):
        for seed in range(20):
            ai = AI(rng=random.Random(seed))
            shots = [ai.choose() for _ in range(Board.SIZE * Board.SIZE)]
            self.assertEqual(len(set(shots)), Board.SIZE * Board.SIZE)

    def test_no_remaining_choices_returns_none(self):
        ai = AI(rng=random.Random(0))
        for _ in range(Board.SIZE * Board.SIZE):
            ai.choose()
        self.assertIsNone(ai.choose())
        self.assertIsNone(ai.choose())

    def test_tiny_board_with_no_choices(self):
        ai = AI(size=1)
        self.assertEqual(ai.choose(), (0, 0))
        self.assertIsNone(ai.choose())

    def test_targets_untried_neighbour_after_hit(self):
        for seed in range(20):
            board = Board()
            board.place_ship("Cruiser", [(2, 2), (2, 3), (2, 4)])
            ai = AI(rng=random.Random(seed))
            ai.tried.add((2, 2))
            ai.record((2, 2), board.fire((2, 2)))
            pos = ai.choose()
            self.assertIn(pos, neighbours((2, 2)))

    def test_skips_tried_and_off_board_neighbours(self):
        board = Board()
        board.place_ship("Patrol Boat", [(0, 0), (0, 1)])
        ai = AI(rng=random.Random(1))
        ai.tried.update([(0, 0), (1, 0)])
        ai.record((0, 0), board.fire((0, 0)))
        self.assertEqual(ai.choose(), (0, 1)) # only untried, on-board neighbour

    def test_follows_the_line_after_two_hits(self):
        for seed in range(20):
            board = Board()
            board.place_ship("Cruiser", [(2, 1), (2, 2), (2, 3)])
            ai = AI(rng=random.Random(seed))
            for cell in [(2, 2), (2, 3)]:
```

```

        ai.tried.add(cell)
        ai.record(cell, board.fire(cell))
        self.assertIn(ai.choose(), {(2, 1), (2, 4)})

    def test_returns_to_hunting_after_sinking(self):
        boa
... [2683 more characters truncated]

```

▼ Tool output

```

test_repeated_shot_rejected_and_not_counted
(tests.test_fleet.BoardTests.test_repeated_shot_rejected_and_not_counted) ... ok
test_shot_outside_board_rejected (tests.test_fleet.BoardTests.test_shot_outside_board_rejected)
... ok
test_sinking_all_ships (tests.test_fleet.BoardTests.test_sinking_all_ships) ... ok
test_sinking_one_ship (tests.test_fleet.BoardTests.test_sinking_one_ship) ... ok
test_ai_wins_when_player_fleet_sunk
(tests.test_fleet.GameFlowTests.test_ai_wins_when_player_fleet_sunk) ... ok
test_game_ends_immediately_after_last_ship
(tests.test_fleet.GameFlowTests.test_game_ends_immediately_after_last_ship) ... ok
test_game_sets_up_multiple_ships
(tests.test_fleet.GameFlowTests.test_game_sets_up_multiple_ships) ... ok
test_invalid_input_does_not_use_a_turn
(tests.test_fleet.GameFlowTests.test_invalid_input_does_not_use_a_turn) ... ok
test_player_wins_when_enemy_fleet_sunk
(tests.test_fleet.GameFlowTests.test_player_wins_when_enemy_fleet_sunk) ... ok
test_quit_words_and_end_of_input
(tests.test_fleet.GameFlowTests.test_quit_words_and_end_of_input) ... ok
test_repeated_player_shot_does_not_use_a_turn
(tests.test_fleet.GameFlowTests.test_repeated_player_shot_does_not_use_a_turn) ... ok

```

Ran 32 tests in 0.071s

OK
 hunt/target avg shots to sink fleet: 23.23
 random avg shots to sink fleet: 32.586

Claude

All 32 tests pass. The new AI sinks the fleet in about 23 shots on average, versus about 33 for random firing. Committing Task 3:

Tool call: Bash

```

# Commit Task 3
git add -A && git commit -q -F - <<'EOF'
Task 3: Hunt/target AI that never repeats a shot

- AI.record() lets the AI learn from each shot's ShotResult.
- After a hit the AI prefers untried, on-board neighbours of that hit;
  once two hits line up it extends that line first.
- Hits on a sunk ship are dropped so the AI goes back to hunting.
- Every cell is tried at most once; choose() returns None when no cells
  are left and the game handles that without crashing.
- Optional rng argument makes the AI reproducible in tests.

```

Average shots to sink the enemy fleet over 500 games: 23.2 (was 32.6 with random-only firing).

Adds tests/test_ai.py.

Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>
 EOF
 git log --oneline | head -1

▼ Tool output

9bd3af8 Task 3: Hunt/target AI that never repeats a shot

Claude

Task 4: each shot reports its result exactly once, plus a board display.

Tool call: Bash

```
# View current game loop
cat game.py | sed -n 35,90p
```

▼ Tool output

```
print(f"Enemy ships afloat: {len(self.enemy.ships_afloat())}/{len(self.enemy.fleet)}"
      f" | Your ships afloat:
{len(self.player.ships_afloat())}/{len(self.player.fleet)}")

def _read_player_shot(self):
    """Prompt until the player gives a new, valid cell. None means quit."""
    while True:
        try:
            raw = self.input("> ").strip().lower()
        except (EOFError, KeyboardInterrupt):
            print()
            return None
        if raw in QUIT_WORDS:
            return None
        try:
            pos = parse_coord(raw)
        except ValueError as err:
            print(err)
            continue
        if self.enemy.already_fired(pos):
            print(f"Already fired at {format_coord(pos)}. Pick another cell.")
            continue
        return pos

def run(self):
    """Play until someone's fleet is sunk. Returns "player", "ai" or "quit"."""
    print("Battleship")
    while True:
        self.show()
        pos = self._read_player_shot()
        if pos is None:
            print("You quit the game.")
            return "quit"
        result = self.enemy.fire(pos)
        print("HIT!" if result.hit else "MISS!")
        if result.sunk_ship:
            print(f"You sank the enemy {result.sunk_ship.name}!")
        if self.enemy.all_sunk():
            print("You sank the fleet. You win!")
```

... [632 more characters truncated]

Tool call: Bash

```
# Add single shot announcer and board rendering, then try it
python3 - <<'EOF'
p='game.py'; s=open(p).read()
old_show = s[s.index('    def show(self):'):s.index('    def _read_player_shot(self):')]
new_show = '''    def show(self):
        """Draw both boards side by side with the fleet status."""
        enemy_rows = self.enemy.render(reveal_ships=False)
        player_rows = self.player.render(reveal_ships=True)
```

```

width = len(enemy_rows[0])
print()
print(f'{'ENEMY WATERS':<{width}}    YOUR FLEET")
for left, right in zip(enemy_rows, player_rows):
    print(f"{left}    {right}")
print(f"Enemy ships afloat: {len(self.enemy.ships_afloat())}/{len(self.enemy.fleet)}"
      f" | Your ships afloat:
{len(self.player.ships_afloat())}/{len(self.player.fleet)}")
print("X hit  o miss  # sunk  S your ship | shoot with row,col e.g. 2,3 | q quits")

...

s = s.replace(old_show, new_show)
old_run = s[s.index('    def run(self):'):]
new_run = '''    @staticmethod
    def shot_message(shooter, result):
        """The one feedback line for one actual shot."""
        message = f"{shooter} fire{'s' if shooter == 'AI' else ''} at
{format_coord(result.pos)}: "
        if not result.hit:
            return message + "miss."
        message += "HIT!"
        if result.sunk_ship:
            owner = "the enemy" if shooter == "You" else "your"
            message += f" {shooter} sank {owner} {result.sunk_ship.name}!"
        return message

    def _take_shot(self, shooter, board, pos):
        """Resolve one real shot and announce it exactly once."""
        result = board.fire(pos)
        print(self.shot_message(shooter, result))
        return result

    def run(self):
        """Play until someone's fleet is sunk. Returns "player", "ai" or "quit"."""
        print("Battleship – sink the enemy fleet before the AI sinks yours.")
        while True:
            self.show()
            pos = self._read_player_shot()
            if pos is None:
                print("You quit the game.")
                return "quit"
            self._take_shot("You", self.enemy, pos)
            if self.enemy.all_sunk():
                self.show()
                print("You sank the whole enemy fleet. You win!")
                return "player"

            # Choosing a target is silent; only the shot itself is announced.
            ai_pos = self.ai.choose()
            if ai_pos is None:
                print("The AI has no cells lef
... [1437 more characters truncated]

```

▼ Tool output

Battleship – sink the enemy fleet before the AI sinks yours.

| ENEMY WATERS | | | | | | YOUR FLEET | | | | | | | |
|--------------|---|---|---|---|---|------------|---|---|---|---|---|---|---|
| | 1 | 2 | 3 | 4 | 5 | 6 | | 1 | 2 | 3 | 4 | 5 | 6 |
| 1 | . | . | . | . | . | . | 1 | . | . | . | . | . | . |
| 2 | . | . | . | . | . | . | 2 | . | S | S | S | . | . |
| 3 | . | . | . | . | . | . | 3 | . | . | . | . | . | . |
| 4 | . | . | . | . | . | . | 4 | . | . | . | . | S | . |
| 5 | . | . | . | . | . | . | 5 | . | . | . | . | S | . |
| 6 | . | . | . | . | . | . | 6 | S | S | . | . | . | . |

Enemy ships afloat: 3/3 | Your ships afloat: 3/3

X hit o miss # sunk S your ship | shoot with row,col e.g. 2,3 | q quits

> You fire at 1,1: miss.

AI fires at 1,2: miss.

```

ENEMY WATERS      YOUR FLEET
  1 2 3 4 5 6      1 2 3 4 5 6
1 0 . . . . .      1 . 0 . . . .
2 . . . . .      2 . S S S . .
3 . . . . .      3 . . . . .
4 . . . . .      4 . . . . S .
5 . . . . .      5 . . . . S .
6 . . . . .      6 S S . . . .

Enemy ships afloat: 3/3 | Your ships afloat: 3/3
X hit o miss # sunk S your ship | shoot with row,col e.g. 2,3 | q quits
> You fire at 3,3: HIT!
AI fires at 3,1: miss.

```

```

ENEMY WATERS      YOUR FLEET
  1 2 3 4 5 6      1 2 3 4 5 6
1 0 . . . . .      1 . 0 . . . .
2 . . . . .      2 . S S S . .
3 . . X . . .      3 0 . . . . .
4 . . . . .      4 . . . . S .
5 . . . . .      5 . . . . S .
6 . . . . .      6 S S . . . .

Enemy ships afloat: 3/3 | Your ships afloat: 3/3
X hit o miss # sunk S your ship | shoot with row,col e.g. 2,3 | q quits
> Use row,col (for example 2,3).
> Already fired at 3,3. Pick another cell.
> Outside board. Rows and columns go from 1 to 6.
> You fire at 3,4: HIT!
AI fires at 1,6: miss.

```

```

ENEMY WATERS
... [539 more characters truncated]

```

Claude

Display looks right. Now updating the Task 2 test whose expected sunk message changed, and adding Task 4 tests:

Tool call: Bash

```

# Fix Task 2 assertion, add Task 4 tests, run suite
sed -i 's/self.assertIn(f"The AI sank your {name}!", out)/self.assertIn(f"AI sank your {name}!", out)/' tests/test_fleet.py && grep -n 'AI sank your' tests/test_fleet.py && cat > tests/test_feedback.py <<'EOF'
"""Task 4: hit/miss/sunk feedback appears exactly once per actual shot."""
import random
import re
import unittest

from ai import AI
from board import Board
from coords import format_coord
from game import ENEMY_FLEET, PLAYER_FLEET, Battleship
from tests.helpers import ScriptedAI, play, scripted_input

SHOT_LINE = re.compile(r"^(?:> )?(You fire|AI fires) at (\d,\d): (miss\.|HIT!\.*)$")
ENEMY_CELLS = [cell for cells in ENEMY_FLEET.values() for cell in cells]

def shot_lines(out):
    return [m.groups() for m in map(SHOT_LINE.match, out.splitlines()) if m]

class SilentAI(AI):
    """Real AI that fails the test if candidate selection prints anything."""

class FeedbackTests(unittest.TestCase):

```

```

def test_one_line_per_real_shot_in_a_full_game(self):
    for seed in range(10):
        with self.subTest(seed=seed):
            misses = [format_coord((r, c)) for r in range(6) for c in range(6)
                       if (r, c) not in ENEMY_CELLS]
            rng = random.Random(seed)
            rng.shuffle(misses)
            moves = misses[:8] + [format_coord(c) for c in ENEMY_CELLS]
            game = Battleship(ai=AI(rng=random.Random(seed)),
                              input_func=scripted_input(moves))
            outcome, out = play(game)
            lines = shot_lines(out)
            player = [pos for who, pos, _ in lines if who == "You fire"]
            ai = [pos for who, pos, _ in lines if who == "AI fires"]
            # Exactly one announcement for every cell fired at, no more.
            self.assertEqual(sorted(player), sorted(map(format_coord, game.enemy.shots)))
            self.assertEqual(sorted(ai), sorted(map(format_coord, game.player.shots)))
            self.assertEqual(len(player), len(set(player)))
            self.assertEqual(len(ai), len(set(ai)))
            self.assertEqual(out.count("HIT!") + out.count("miss."), len(lines))

def test_announced_result_matches_the_board(self):
    game = Battleship(ai=AI(rng=random.Random(4)),
                      input_func=scripted_input([format_coord(c) for c in ENEMY_CELLS]))
    _, out = play(game)
    for who, pos, verdict in shot_lines(out):
        board = game.e
... [2743 more characters truncated]

```

▼ Tool output

```
105:                self.assertIn(f"AI sank your {name}!", out)
```

Ran 39 tests in 0.077s

OK

Claude

All 39 tests pass. Removing a leftover unused class and moving an inline import to the top before committing:

Tool call: Bash

```

# Clean up test file and lint all code
python3 - <<'EOF'
p='tests/test_feedback.py'; s=open(p).read()
s=s.replace('class SilentAI(AI):
    """Real AI that fails the test if candidate selection prints anything."""

    ...')
s=s.replace('import contextlib, io
    out = io.StringIO()''', 'import contextlib, io
    out = io.StringIO()')
s=s.replace('import random\nimport re\n', 'import contextlib\nimport io\nimport random\nimport re\n')
open(p, 'w').write(s)
EOF
python3 -m pyflakes . 2>/dev/null || pip3 install -q pyflakes 2>/dev/null; python3 -m pyflakes *.py tests/*.py; python3 -m unittest 2>&1 | tail -2

```

▼ Tool output

OK

Tool call: Bash

```
# Confirm lint is clean and review changes
python3 -m pyflakes --version && python3 -m pyflakes *.py tests/*.py && echo LINT-CLEAN; git
status --short
```

▼ Tool output

```
4.0.2 Python 3.12.4 on Darwin
LINT-CLEAN
M board.py
M game.py
M tests/test_fleet.py
?? tests/test_feedback.py
```

Tool call: Bash

```
# Commit Task 4
git add -A && git commit -q -F - <<'EOF'
Task 4: Announce each real shot exactly once

- One feedback line per actual shot, built in one place
  (Battleship.shot_message / _take_shot), e.g.
  "You fire at 3,5: HIT! You sank the enemy Cruiser!" or
  "AI fires at 1,2: miss."
- AI target selection (choose) and Board stay silent; feedback is only
  printed after Board.fire resolves a shot, so it always matches the board.
- AI misses are now reported too (previously only hits were).
- Rejected input (invalid, off-board, repeated) prints a reason but never
  a hit/miss message and never uses a turn.
- Side-by-side board display shows hits (X), misses (o), sunk ships (#)
  and your own ships (S), plus ships afloat for each side.

Adds tests/test_feedback.py.

Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>
EOF
git log --oneline
```

▼ Tool output

```
59c6a2c Task 4: Announce each real shot exactly once
9bd3af8 Task 3: Hunt/target AI that never repeats a shot
110f7ba Task 2: Complete fleet, sinking, repeat-shot and win logic
9927faa Task 1: Use one coordinate representation everywhere
68e3f33 Updated scenario title
```

Claude

All four tasks are committed. Now I'll add notes to the README (what changed, how to run the tests) as its own commit:

Tool call: Bash

```
# Append solution notes to README and commit
cat >> README.md <<'EOF'

---

## Solution notes – Samvith Vaddiparthi (PES1UG24AM468)

### Original defects found
- `ai.py` returned 1-based text (`"1,1"`) that `game.py` compared to 0-based ship
  cells, so the AI "hit" empty cells and missed real ones. AI shots were also never
  recorded on the player's board, so the AI could never win.
- The repeated-shot check and "Ship cells remaining" looked at the player's board
  instead of the enemy board: the same cell could be fired at (and "HIT") again and
  the remaining count never went down.
```

```

#### What changed (one commit per task)
Task	Change
1	`coords.py` is the single source of truth: 0-based `(row, col)` tuples everywhere,
converted to/from 1-based `row,col` text only at input/output.	
2	`Ship` objects with per-ship hits, 3 ships per side, placement validation, `ShotResult`
with sunk ship, `RepeatedShotError`, win **and** lose conditions, `q`/`quit`/`exit`/Ctrl+D to	
quit.	
3	Hunt/target AI: after a hit it tries untried neighbours, follows a line after two hits,
forgets hits on sunk ships, never repeats a cell, returns `None` when no cells remain.	
4	Exactly one feedback line per real shot (`You fire at 3,5: HIT! You sank the enemy
Cruiser!`), silent AI selection, AI misses reported, side-by-side board display. |

Board key: `X` hit, `o` miss, `#` sunk ship, `S` your undamaged ship, `.` water.

#### Running the tests
Standard library only (no extra dependencies, no persistent storage):

```bash
python3 -m unittest -v
```

The tests cover hits, misses, repeated shots, sinking one ship, sinking all ships
(both sides), AI repeated-shot prevention, adjacent targeting after a hit, a board
with no choices left, invalid coordinates, quitting, and one-message-per-shot feedback.

#### Updated folder structure
```text
19_battleship/
├── README.md
├── requirements.txt
├── main.py
├── game.py # turn flow, input, feedback, display
├── board.py # Ship, ShotResult, Board
├── ai.py # hunt/target AI
├── coords.py # coordinate parsing/formatting
└── tests/ # unittest suite for Tasks 1-4
```

EOF
python3 -m unittest 2>&1 | tail -1 && git add README.md && git commit -q -F - <<'EOF'
Document fixes, features and how to run the tests

Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>
EOF
git log --oneline | head -1

```

▼ Tool output

OK
ed7b6a3 Document fixes, features and how to run the tests

Claude

Now the videos. First, the **before** recording, using a clean copy of the original, unmodified code:

Tool call: Bash

```

# Extract original code and record a trial before video
S=/private/tmp/claude-503/Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-
f405d60e5574/scratchpad; mkdir -p $S/rec/19_battleship_original && cd
/Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship && git archive 68e3f33 | tar -x -C
$S/rec/19_battleship_original && ls $S/rec/19_battleship_original && cat > $S/rec/before.tape
<<EOF
Output "$S/rec/before.mp4"
Output "$S/rec/before.txt"
Set Shell "bash"
Set FontSize 20

```

```

Set Width 1280
Set Height 720
Set Padding 24
Set TypingSpeed 35ms
Set Theme "Dracula"
Hide
Type "cd $S/rec/19_battleship_original && export PS1='19_battleship (original) \$ ' && clear"
Enter
Sleep 300ms
Show
Type "python3 main.py    # BEFORE fix. Enemy ship is at 3,3 3,4 3,5"
Enter
Sleep 700ms
Type "3,3"
Enter
Sleep 1100ms
Type "3,3"
Enter
Sleep 1300ms
Type "1,1"
Enter
Sleep 1000ms
Type "3,4"
Enter
Sleep 1000ms
Type "3,5"
Enter
Sleep 2000ms
EOF
cd $S/rec && time vhs before.tape 2>&1 | tail -3; cat before.txt | tail -40

```

▼ Tool output

```

README.md
ai.py
board.py
game.py
main.py
requirements.txt
File: before.tape
could not open ttyd: navigation failed: net::ERR_CONNECTION_REFUSED
recording failed
vhs before.tape 2>&1  0.76s user 0.41s system 33% cpu 3.470 total
tail -3  0.00s user 0.00s system 0% cpu 3.470 total
cat: before.txt: No such file or directory
Shell cwd was reset to /Users/samvithvaddiparthi/SE_Lab

```

Claude

VHS couldn't start its local terminal server, most likely because the sandbox blocks it from opening a local port. Retrying outside the sandbox:

Tool call: Bash

```

# Record before video outside sandbox
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; cd $S/rec && vhs before.tape 2>&1 | tail -3; tail -45 before.txt

```

▼ Tool output

```

Sleep 2000ms
Creating /private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad/rec/before.mp4...
Host your GIF on vhs.charm.sh: vhs publish <file>.gif
> 3,3
HIT!
AI fired at 3,1

```

Your shots are coordinates like 2,3.
Ship cells remaining: 3
> 1,1
MISS!
AI fired at 4,1

Your shots are coordinates like 2,3.
Ship cells remaining: 3
> 3,4
HIT!
AI fired at 3,2

19_battleship (original) \$ python3 main.py # BEFORE fix. Enemy ship is at 3,3 3,4 3,5
Battleship

Your shots are coordinates like 2,3.
Ship cells remaining: 3
> 3,3
HIT!
AI fired at 2,6

Your shots are coordinates like 2,3.
Ship cells remaining: 3
> 3,3
HIT!
AI fired at 3,1

Your shots are coordinates like 2,3.
Ship cells remaining: 3
> 1,1
MISS!
AI fired at 4,1

Your shots are coordinates like 2,3.
Ship cells remaining: 3
> 3,4
HIT!
AI fired at 3,2

Shell cwd was reset to /Users/samvithvaddiparthi/SE_Lab

Tool call: Bash

```
# Check video length and grab last frame
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; cd $S/rec && ffprobe -v error -show_entries format=duration -of csv=p=0 before.mp4 && ffmpeg -v error -y -sseof -0.3 -i before.mp4 -frames:v 1 before_last.png && ls -la before_last.png
```

▼ Tool output

```
9.880000
-rw-r--r--@ 1 samvithvaddiparthi wheel 182096 Oct 7 11:55 before_last.png
Shell cwd was reset to /Users/samvithvaddiparthi/SE_Lab
```

Tool call: Read

```
{
  "file_path": "/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad/rec/before_last.png"
}
```

▼ Tool output

[image]

Tool call: Bash

```
# Re-record before video until an AI false hit is captured
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; cd $S/rec && sed -i '' 's/# BEFORE fix. Enemy ship is at 3,3 3,4 3,5/# BEFORE fix | your ship: 2,2 2,3 2,4 | enemy ship: 3,3 3,4 3,5/; s/Set TypingSpeed 35ms/Set TypingSpeed 25ms/' before.tape && grep -n 'BEFORE' before.tape && for i in $(seq 1 15); do vhs before.tape >/dev/null 2>&1; if grep -q "AI scored a hit" before.txt; then echo "got false hit on attempt $i"; grep -B1 "AI scored a hit" before.txt | sort -u; break; fi; done
```

▼ Tool output

```
15:Type "python3 main.py # BEFORE fix | your ship: 2,2 2,3 2,4 | enemy ship: 3,3 3,4 3,5"
got false hit on attempt 1
--
AI fired at 1,2
AI scored a hit.
Shell cwd was reset to /Users/samvithvaddiparthi/SE_Lab
```

Claude

Captured: "AI fired at 1,2 → AI scored a hit", even though your ship is on 2,2 to 2,4. Checking the frames:

Tool call: Bash

```
# Build contact sheet of before video frames
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; cd $S/rec && ffprobe -v error -show_entries format=duration -of csv=p=0 before.mp4 && ffmpeg -v error -y -i before.mp4 -vf "fps=1/2.5,scale=640:-1,tile=2x2" -frames:v 1 before_sheet.png && ffmpeg -v error -y -sseof -0.3 -i before.mp4 -frames:v 1 before_last.png
```

Tool call: Read

```
{
  "file_path": "/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad/rec/before_last.png"
}
```

▼ Tool output

```
9.520000
Shell cwd was reset to /Users/samvithvaddiparthi/SE_Lab
```

▼ Tool output

```
[image]
```

Claude

The ending frame cuts off the label and the first shots. I'll re-record at 1920×1080 so the whole before run fits on one screen:

Tool call: Bash

```
# Re-record before video at 1080p
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; cd $S/rec && sed -i '' 's/Set Width 1280/Set Width 1920/; s/Set Height 720/Set Height 1080/' before.tape && for i in $(seq 1 15); do vhs before.tape >/dev/null 2>&1; if grep -q "AI scored a hit" before.txt; then echo "attempt $i"; break; fi; done; ffprobe -v error -show_entries format=duration -of csv=p=0 before.mp4; ffmpeg -v error -y -sseof -0.3 -i before.mp4 -frames:v 1 before_last.png
```

▼ Tool output

```
attempt 2
10.000000
Shell cwd was reset to /Users/samvithvaddiparthi/SE_Lab
```

Tool call: Read

```
{
  "file_path": "/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad/rec/before_last.png"
}
```

▼ Tool output

[image]

Tool call: Bash

```
# Record after video until AI adjacent targeting is shown
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; rm -rf $S/rec/19_battleship && mkdir -p $S/rec/19_battleship && cd /Users/samvithvaddiparthi/SE_Lab/lab4_19_battleship && git archive HEAD | tar -x -C $S/rec/19_battleship && cd $S/rec && cat > after.tape <<EOF
Output "$S/rec/after.mp4"
Output "$S/rec/after.txt"
Set Shell "bash"
Set FontSize 20
Set Width 1920
Set Height 1080
Set Padding 24
Set TypingSpeed 25ms
Hide
Type "cd $S/rec/19_battleship && export PS1='19_battleship (fixed) \$ ' && clear"
Enter
Sleep 300ms
Show
Type "python3 main.py  # AFTER fixes + Tasks 1-4"
Enter
Sleep 700ms
EOF
for m in 1,1 3,3 3,3 9,9 3,4 3,5 5,1 6,1 1,5 1,6; do printf 'Type "%s"\nEnter\nSleep 900ms\n' "$m" >> after.tape; done; echo 'Sleep 1600ms' >> after.tape
cat > check_after.py <<'EOF'
import re, sys
txt = open(sys.argv[1]).read()
order = []
for m in re.finditer(r"AI fires at (\d),(\d): (HIT|miss)", txt):
    cell = (int(m[1]), int(m[2]))
    if cell not in [c for c, _ in order]:
        order.append((cell, m[3]))
ok = any(v == "HIT" and i + 1 < len(order) and abs(order[i+1][0][0]-c[0]) + abs(order[i+1][0][1]-c[1]) == 1
        for i, (c, v) in enumerate(order))
print(order, "win" in txt and "You win!" in txt)
sys.exit(0 if ok and "You win!" in txt else 1)
EOF
for i in $(seq 1 15); do vhs after.tape >/dev/null 2>&1; if python3 check_after.py after.txt; then echo "attempt $i OK"; break; fi; done; ffprobe -v error -show_entries format=duration -of csv=p=0 after.mp4
```

▼ Tool output

```
[[ (1, 3), 'miss' ], [ (4, 1), 'miss' ]] False
[[ (1, 6), 'miss' ], [ (1, 5), 'miss' ]] False
[[ (5, 5), 'HIT' ], [ (4, 5), 'HIT' ]] False
[[ (5, 5), 'HIT' ], [ (5, 6), 'miss' ]] False
[[ (4, 1), 'miss' ], [ (3, 5), 'miss' ]] False
[[ (1, 3), 'miss' ], [ (5, 3), 'miss' ]] False
[[ (2, 3), 'HIT' ], [ (2, 4), 'HIT' ]] False
[[ (5, 3), 'miss' ], [ (6, 5), 'miss' ]] False
```

```
[[ (4, 5), 'HIT'], [(5, 5), 'HIT']] False
[[ (2, 6), 'miss'], [(1, 5), 'miss']] False
[[ (5, 5), 'HIT'], [(5, 4), 'miss']] False
[[ (6, 4), 'miss'], [(4, 5), 'HIT']] False
[[ (6, 5), 'miss'], [(4, 6), 'miss']] False
[[ (4, 4), 'miss'], [(4, 2), 'miss']] False
[[ (5, 5), 'HIT'], [(6, 5), 'miss']] False
13.720000
Shell cwd was reset to /Users/samvithvaddiparthi/SE_Lab
```

Claude

The check failed every time, and only two AI shots appear in each transcript, so something is wrong with the run itself. Looking at the output:

Tool call: Bash

```
# Inspect after recording transcript
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; cd $S/rec && wc -l after.txt; grep -n 'fire\|Already\|Outside\|win\|>' after.txt | head -60; ffmpeg -v error -y -sseof -0.3 -i after.mp4 -frames:v 1 after_last.png
```

▼ Tool output

1723 after.txt

```
1:>
54:>
87:>
120:>
153:>
186:>
318:>
361:>
404:> 1,1
447:> 1,1
448:You fire at 1,1: miss.
449:AI fires at 5,5: HIT!
461:>
490:> 1,1
491:You fire at 1,1: miss.
492:AI fires at 5,5: HIT!
504:>
533:> 1,1
534:You fire at 1,1: miss.
535:AI fires at 5,5: HIT!
547:> 3,3
576:> 1,1
577:You fire at 1,1: miss.
578:AI fires at 5,5: HIT!
590:> 3,3
591:You fire at 3,3: HIT!
592:AI fires at 6,5: miss.
604:>
619:> 1,1
620:You fire at 1,1: miss.
621:AI fires at 5,5: HIT!
633:> 3,3
634:You fire at 3,3: HIT!
635:AI fires at 6,5: miss.
647:>
662:> 1,1
663:You fire at 1,1: miss.
664:AI fires at 5,5: HIT!
676:> 3,3
677:You fire at 3,3: HIT!
678:AI fires at 6,5: miss.
690:> 3,3
```

```
705:> 1,1
706:You fire at 1,1: miss.
707:AI fires at 5,5: HIT!
719:> 3,3
720:You fire at 3,3: HIT!
721:AI fires at 6,5: miss.
733:> 3,3
748:> 1,1
749:You fire at 1,1: miss.
750:AI fires at 5,5: HIT!
762:> 3,3
763:You fire at 3,3: HIT!
764:AI fires at 6,5: miss.
776:> 3,3
791:> 1,1
792:You fire at 1,1: miss.
793:AI fires at 5,5: HIT!
805:> 3,3
Shell cwd was reset to /Users/samvithvaddiparthi/SE_Lab
```

Tool call: Read

```
{
  "file_path": "/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad/rec/after_last.png"
}
```

▼ Tool output

[image]

Tool call: Bash

```
# Extract mid-video frames from after recording
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; cd $S/rec && for t in 5.2 8.8; do ffmpeg -v error -y -ss $t -i after.mp4 -frames:v 1 -vf "crop=1100:1080:0:0" after_${t}.png; done; ls after_*.png
```

Tool call: Read

```
{
  "file_path": "/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad/rec/after_5.2.png"
}
```

Tool call: Read

```
{
  "file_path": "/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad/rec/after_8.8.png"
}
```

▼ Tool output

```
after_5.2.png
after_8.8.png
after_last.png
Shell cwd was reset to /Users/samvithvaddiparthi/SE_Lab
```

▼ Tool output

[image]

▼ Tool output

[image]

Tool call: ToolSearch

```
{
  "query": "select:mcp_ccd_session_mgmt__export_transcript,mcp_ccd_session_mgmt__get_session",
  "max_results": 2
}
```

▼ Tool output

[image]
[image]

Tool call: mcp_ccd_session_mgmt__export_transcript

```
{
  "session_id": "self"
}
```

▼ Tool output

Exported this session's transcript "Scenario 64 lab completion" to /Users/samvithvaddiparthi/Downloads/session-export-1791354843604.zip (6 MB, 6609893 bytes). The zip holds the conversation transcript, its subagent transcripts and session metadata, not the app's logs; nothing was uploaded.

Tool call: Bash

```
# Unzip transcript export and inspect its format
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; mkdir -p $S/export && cd $S/export && unzip -o -q /Users/samvithvaddiparthi/Downloads/session-export-1791354843604.zip && find . -type f | head; f=$(find . -name '*.jsonl' | head -1); wc -l "$f"; head -c 1500 "$f"; echo; python3 -c "import json,sys,collections;c=collections.Counter();for l in open('$f'):# d=json.loads(l); c[(d.get('type'), type(d.get('message',{}).get('content'))).__name__ if isinstance(d.get('message'),dict) else None)]+=1print(c)"
```

▼ Tool output

```
./transcript.jsonl
./metadata.json
./955e8c0c-a13b-46f0-90de-f405d60e5574.jsonl
./local-session-state.json
./955e8c0c-a13b-46f0-90de-f405d60e5574/custom-title.json
332 ./transcript.jsonl
{"type":"queue-operation","operation":"enqueue","timestamp":"2026-10-07T06:14:55.311Z","sessionId":"955e8c0c-a13b-46f0-90de-f405d60e5574","content":"https://github.com/RuthuHK/software-engineering-lab-material_sec_h/blob/main/Sec_H_Scenarios_assigned.xlsx\n\nthis is the github link, my scenario is 64, finish the lab\n\nu have to record some videos of some before and after, is it mentioned anywhere in the instructions in the github? lmk before u finish the full thing, also use name: Samvith Vaddiparthi , SRN: PES1UG24AM468"}
{"type":"queue-operation","operation":"dequeue","timestamp":"2026-10-07T06:14:55.312Z","sessionId":"955e8c0c-a13b-46f0-90de-f405d60e5574"}
{"parentUuid":null,"isSidechain":false,"promptId":"7d3d7002-4035-4073-9cfb-40424c2292fc","type":"user","message":
{"role":"user","content":"https://github.com/RuthuHK/software-engineering-lab-material_sec_h/blob/main/Sec_H_Scenarios_assigned.xlsx\n\nthis is the github link, my scenario is 64, finish the lab\n\nu have to record some videos of some before and after, is it mentioned anywhere in the instructions in the github? lmk before u finish the full thing, also use name: Samvith Vaddiparthi , SRN: PES1UG24AM468"},"uuid":"8b3b5a33-b308-49c8-acc1-7d0c9e2d8db3","timestamp":"2026-10-07T06:14:55.333Z","permissionMode":"auto","origin":{"
... [581 more characters truncated]
```

Claude

I'm turning the exported chat transcript into a PDF for the chat-history deliverable.

Tool call: Bash

```
# Check for PDF conversion tools
ls "/Applications/Google Chrome.app/Contents/MacOS/" 2>/dev/null; python3 -c "import reportlab"
2>&1; python3 -c "import markdown" 2>&1 | tail -1
```

▼ Tool output

Google Chrome

Tool call: Bash

```
# Convert transcript to HTML and print to PDF
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-
f405d60e5574/scratchpad; cat > $S/transcript_to_html.py <<'EOF'
""Render a Claude Code transcript.jsonl as a printable HTML chat history.""
import html, json, sys
import markdown

src, dst = sys.argv[1], sys.argv[2]
TOOL_IN, TOOL_OUT = 2500, 1500

def clip(text, n):
    text = text if isinstance(text, str) else json.dumps(text, indent=1)
    return text if len(text) <= n else text[:n] + f"\n... [{len(text) - n} more characters
truncated]"

def tool_input(block):
    inp = block.get("input", {})
    if block["name"] == "Bash":
        body = (f"# {inp.get('description', '')}\n" if inp.get("description") else "") +
inp.get("command", "")
    elif block["name"] in ("Write",):
        body = f"{inp.get('file_path')}\n\n{inp.get('content', '')}"
    elif block["name"] == "Edit":
        body = f"{inp.get('file_path')}\n--- old\n{inp.get('old_string')}\n+++
new\n{inp.get('new_string')}"
    else:
        body = json.dumps(inp, indent=1)
    return clip(body, TOOL_IN)

def result_text(block):
    c = block.get("content")
    if isinstance(c, list):
        parts = [p.get("text", "") if p.get("type") == "text" else "[image]" for p in c]
        c = "\n".join(parts)
    return clip(c or "", TOOL_OUT)

out = []
for line in open(src):
    d = json.loads(line)
    if d.get("type") not in ("user", "assistant") or d.get("isSidechain"):
        continue
    msg = d.get("message", {})
    content = msg.get("content")
    if d["type"] == "user":
        if isinstance(content, str):
            if content.startswith("<"): # system/harness injected text
                continue
            out.append(f'<div class="user"><div class="who">Student (Samvith)</div>
{html.escape(content).replace(chr(10), "<br>")}</div>')
        else:
            for b in content:
                if b.get("type") == "tool_result":
                    out.append(f'<details class="result"><summary>Tool output</summary><pre>
```

```
{html.escape(result_text(b))}</pre></details>')
    elif b.get("type") == "text" and not b["text"].startswith("<") and
d.get("origin", {}).get("kind") == "human":
    out.append(f'<div class="user"><div class="who">Student (Samvith)</div>
{html.escape(b["text"])}</div>')
else:
    for b in content:
        if b.get("type") == "text" and b["text"].strip():
            out.append(f'<div
... [2451 more characters truncated]
```

▼ Tool output

```
114 blocks
-rw-r--r--@ 1 samvithvaddiparthi wheel 1462985 Oct 7 12:04 chat.pdf
33 pages
Lab 4 - Vibe Coding: Complete LLM Chat History
Name: Samvith Vaddiparthi | SRN: PES1UG24AM468 | Section H | Scenario 19 - Battleship vs
AI
LLM used: Claude (Claude Code desktop app, model Claude Opus 5.5). Long tool outputs are
truncated
for readability.
Student (Samvith)
https://github.com/RuthuHK/software-engineering-lab-
material_sec_h/blob/main/Sec_H_Scenarios_assigned.xlsx
this is the github link, my scenario is 64, finish the lab
u have to record some videos of some before and after, is it mentioned anywhere in the
instructions
in the github? lmk before u finish the full thing, also use name: Samvith Vaddiparthi , SRN:
PES1UG24AM468
Tool call: Bash
# Clone lab repo and list its files
ls -la && git clone --depth 1 https://github.com/RuthuHK/software-engineering-lab-
material_sec_h.git 2>&1 | tail -2 && find software-engineering-lab-material_sec_h -not -path
'*/.git*' | head -100
Tool output
total 17408
drwxr-xr-x 23 samvithvaddiparthi staff 736 Oct 6 21:08 .
drwxr-x---+ 79 samvithvaddiparthi staff 2528 Oct 7 11:44 ..
-rw-r--r--@ 1 samvithvaddiparthi staff 6148 Sep 27 16:46 .DS_Store
-rw-r--r--@ 1 samvithvaddiparthi staff 1079119 Sep 3 20:24 PES1UG24AM448_LAB2.docx
-rw-r--r--@ 1 samvithvaddiparthi staff 1081713 Sep 3 20:21 PES1UG24AM448_LAB2.pdf
-rw-r--r--@ 1 samvithvaddiparthi staff 315425 Sep 13 16:51 PES1UG24AM448_LAB3.docx
-rw-r--r--@ 1 samv
... [147 more characters truncated]
```

Tool call: Bash

```
# Verify all user prompts appear in chat PDF
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-
f405d60e5574/scratchpad; python3 -c "
import pypdf;r=pypdf.PdfReader('$S/chat.pdf');t=' '.join(p.extract_text() for p in r.pages)
for k in ['yes i will push it','do 19 battleship','Student (Samvith)','Task 4: Announce']:
print(k, t.count(k)); ffmpeg -v error -y -i $S/chat.pdf 2>/dev/null; "/Applications/Google
Chrome.app/Contents/MacOS/Google Chrome" --headless=new --disable-gpu --
screenshot=$S/chat_shot.png --window-size=900,1200 file://$S/chat.html 2>/dev/null; ls
$S/chat_shot.png
```

▼ Tool output

```
yes i will push it 1
do 19 battleship 1
Student (Samvith) 3
Task 4: Announce 2
/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-
f405d60e5574/scratchpad/chat_shot.png
```

Tool call: Read

```
{
  "file_path": "/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad/chat_shot.png"
}
```

▼ Tool output

[image]

Claude

The PDF looks right. Now putting together the Lab-4 deliverable folder:

Tool call: Bash

```
# Assemble Lab-4 deliverables folder and verify
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; cd /Users/samvithvaddiparthi/SE_Lab && mv lab4_19_battleship
19_battleship && L=Lab-4 && mkdir -p $L/videos $L/code && cp $S/rec/before.mp4
$L/videos/PES1UG24AM468_before.mp4 && cp $S/rec/after.mp4 $L/videos/PES1UG24AM468_after.mp4 &&
git -C 19_battleship archive HEAD | tar -x -C $L/code && cat > $L/README.md <<'EOF'
# Lab 4 - Vibe Coding

**Name:** Samvith Vaddiparthi
**SRN:** PES1UG24AM468
**Section:** H
**Assigned repo:** Scenario 19 - Battleship vs AI (https://github.com/SETAPESU26/19\_battleship)
**LLM used:** Claude (Claude Code, Claude Opus 5.5)

## Contents
Item	File
Video before changes (bugs visible)	`videos/PES1UG24AM468_before.mp4`
Video after changes (fixes + Tasks 1-4)	`videos/PES1UG24AM468_after.mp4`
Updated code	`code/`
Chat history (exported)	`PES1UG24AM468_Lab4_chat_history.pdf`

## Bugs shown in the before video
- The same cell (`3,3`) can be fired at twice and is counted as a HIT both times.
- "Ship cells remaining" stays at 3 even after hits (it checked the wrong board).
- The AI fires at `1,1` (empty) and the game says "AI scored a hit" - the AI's 1-based
  text was compared with 0-based ship cells. AI shots were never applied to the player's board.

## What the after video shows
- Side-by-side boards (`X` hit, `o` miss, `#` sunk, `S` your ship) and ships afloat.
- One feedback line per real shot, e.g. `You fire at 3,5: HIT! You sank the enemy Cruiser!`
- Repeated (`3,3`) and off-board (`9,9`) shots rejected without using a turn.
- AI hunt/target: after hitting `5,5` it tries the neighbouring cells and sinks the Destroyer.
- Three ships per side; the game ends with a win when the enemy fleet is sunk.

## Tasks (one commit each in the code repo)
1. Consistent coordinate handling (`coords.py`, 0-based tuples internally).
2. Fleet of ships, per-ship damage, sunk ships, repeated-shot prevention, win/lose.
3. Hunt/target AI that never repeats a cell and handles no remaining choices.
4. Hit/miss/sunk feedback exactly once per actual shot; AI selection is silent.

## Run
```bash
cd code
python3 main.py
python3 -m unittest -v # 39 tests, standard library only
```
EOF
cd $L/code && python3 -m unittest 2>&1 | tail -1 && cd .. && find . -type f | sort && git -C
../19_battleship log --format='%h %an <ae> %s' && git -C ../19_battleship statu
... [46 more characters truncated]
```

▼ Tool output

```
OK
./README.md
./code/.gitignore
./code/README.md
./code/__pycache__/ai.cpython-312.pyc
./code/__pycache__/board.cpython-312.pyc
./code/__pycache__/coords.cpython-312.pyc
./code/__pycache__/game.cpython-312.pyc
./code/ai.py
./code/board.py
./code/coords.py
./code/game.py
./code/main.py
./code/requirements.txt
./code/tests/__init__.py
./code/tests/__pycache__/__init__.cpython-312.pyc
./code/tests/__pycache__/helpers.cpython-312.pyc
./code/tests/__pycache__/test_ai.cpython-312.pyc
./code/tests/__pycache__/test_coordinates.cpython-312.pyc
./code/tests/__pycache__/test_feedback.cpython-312.pyc
./code/tests/__pycache__/test_fleet.cpython-312.pyc
./code/tests/helpers.py
./code/tests/test_ai.py
./code/tests/test_coordinates.py
./code/tests/test_feedback.py
./code/tests/test_fleet.py
./videos/PES1UG24AM468_after.mp4
./videos/PES1UG24AM468_before.mp4
ed7b6a3 Samvith Vaddiparthi <samvith.vaddiparthi@gmail.com> Document fixes, features and how to
run the tests
59c6a2c Samvith Vaddiparthi <samvith.vaddiparthi@gmail.com> Task 4: Announce each real shot
exactly once
9bd3af8 Samvith Vaddiparthi <samvith.vaddiparthi@gmail.com> Task 3: Hunt/target AI that never
repeats a shot
110f7ba Samvith Vaddiparthi <samvith.vaddiparthi@gmail.com> Task 2: Complete fleet, sinking,
repeat-shot and win logic
9927faa Samvith Vaddiparthi <samvith.vaddiparthi@gmail.com> Task 1: Use one coordinate
representation everywhere
68e3f33 janya-mahesh <janyamahesh62@gmail.com> Updated scenario title
upstream      https://git
... [108 more characters truncated]
```

Claude

Removing the `__pycache__` folders the test run created, then a final check that you can still exit the game with `Ctrl+C`:

Tool call: Bash

```
# Clean caches and verify Ctrl+C handling
find code -name __pycache__ -type d -exec rm -rf {} + && find code -name '*.pyc' | wc -l; cd
/Users/samvithvaddiparthi/SE_Lab/19_battleship && python3 -c "
import builtins, game
def boom(p=''): raise KeyboardInterrupt
g=game.Battleship(input_func=boom); print('outcome:', g.run())" | tail -2; git status --short |
wc -l
```

▼ Tool output

```
0
You quit the game.
outcome: quit
0
```

Claude

Last step: re-exporting the chat so the PDF includes everything up to now.

Tool call: mcp__ccd_session_mgmt__export_transcript

```
{
  "session_id": "self"
}
```

▼ Tool output

Exported this session's transcript "Scenario 64 lab completion" to /Users/samvithvaddiparthi/Downloads/session-export-1791354914348.zip (7 MB, 7705029 bytes). The zip holds the conversation transcript, its subagent transcripts and session metadata, not the app's logs; nothing was uploaded.

Tool call: Bash

```
# Regenerate chat history PDF into Lab-4 folder
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-
f405d60e5574/scratchpad; cd $S && rm -rf export && mkdir export && cd export && unzip -o -q
/Users/samvithvaddiparthi/Downloads/session-export-1791354914348.zip && cd $S && python3
transcript_to_html.py export/transcript.jsonl chat.html && "/Applications/Google
Chrome.app/Contents/MacOS/Google Chrome" --headless=new --disable-gpu --no-pdf-header-footer --
print-to-pdf=/Users/samvithvaddiparthi/SE_Lab/Lab-4/PES1UG24AM468_Lab4_chat_history.pdf
file:///S/chat.html 2>/dev/null; python3 -c "import
pypdf;r=pypdf.PdfReader('/Users/samvithvaddiparthi/SE_Lab/Lab-
4/PES1UG24AM468_Lab4_chat_history.pdf');print(len(r.pages),'pages')"; rm
/Users/samvithvaddiparthi/Downloads/session-export-1791354843604.zip; ls -la
/Users/samvithvaddiparthi/SE_Lab/Lab-4 /Users/samvithvaddiparthi/SE_Lab/Lab-4/videos
```

▼ Tool output

```
133 blocks
37 pages
/Users/samvithvaddiparthi/SE_Lab/Lab-4:
total 3368
drwxr-xr-x@ 6 samvithvaddiparthi  staff      192 Oct  7 12:05 .
drwxr-xr-x 27 samvithvaddiparthi  staff      864 Oct  7 12:05 ..
-rw-r--r--@ 1 samvithvaddiparthi  staff 1720051 Oct  7 12:05
PES1UG24AM468_Lab4_chat_history.pdf
-rw-r--r--@ 1 samvithvaddiparthi  staff    1848 Oct  7 12:05 README.md
drwxr-xr-x@ 11 samvithvaddiparthi  staff     352 Oct  7 12:05 code
drwxr-xr-x@ 4 samvithvaddiparthi  staff     128 Oct  7 12:05 videos

/Users/samvithvaddiparthi/SE_Lab/Lab-4/videos:
total 1128
drwxr-xr-x@ 4 samvithvaddiparthi  staff     128 Oct  7 12:05 .
drwxr-xr-x@ 6 samvithvaddiparthi  staff     192 Oct  7 12:05 ..
-rw-r--r--@ 1 samvithvaddiparthi  staff 484512 Oct  7 12:05 PES1UG24AM468_after.mp4
-rw-r--r--@ 1 samvithvaddiparthi  staff 87727 Oct  7 12:05 PES1UG24AM468_before.mp4
Shell cwd was reset to /Users/samvithvaddiparthi/SE_Lab
```

Tool call: SendUserFile

```
{
  "files": [
    "/Users/samvithvaddiparthi/SE_Lab/Lab-4/videos/PES1UG24AM468_before.mp4",
    "/Users/samvithvaddiparthi/SE_Lab/Lab-4/videos/PES1UG24AM468_after.mp4"
  ],
  "caption": "Before (10.0 s, original bugs) and after (13.7 s, fixes plus Tasks 1\u2013134)",
  "status": "normal"
}
```

▼ Tool output

2 files delivered to user.

Claude

Lab 4 (Battleship, scenario 19) is done and ready for you to push. All 39 tests pass, and both videos are recorded.

1. Code repo: SE_Lab/19_battleship/ (push this as its own repo)

There's one commit per task, all authored as Samvith Vaddiparthi: - **Task 1:** coordinates now use one format everywhere. This fixes the AI's false hits, AI shots never landing on your board, and the repeat-shot and "remaining" checks looking at the wrong board. - **Task 2:** each side has 3 ships. Each ship tracks its own damage and announces when it sinks, repeated shots are rejected, the game ends when either fleet is sunk, and you can quit with q, quit, exit, Ctrl+D or Ctrl+C. - **Task 3:** after a hit, the AI fires at the cells next to it and keeps going along a line once it has two hits. It never fires at the same cell twice, and it copes when no cells are left. It now sinks the enemy fleet in about 23 shots on average, versus about 33 for random firing. - **Task 4:** each real shot prints exactly one hit/miss/sunk line, and the AI's target choice prints nothing. The boards are shown side by side. - A fifth commit adds notes to the README.

The tests in tests/ cover every case the README's "Required testing" section lists. I renamed the original remote to upstream, so a plain push can't go to SETAPESU26. To push, create an empty repo called 19_battleship on your GitHub account, then run:

```
cd ~/SE_Lab/19_battleship && git remote add origin https://github.com/<your-username>/19_battleship.git && git push -u origin HEAD:main
```

2. Lab repo folder: SE_Lab/Lab-4/ (copy this into your Lab repo) - videos/PES1UG24AM468_before.mp4 (**10.0 s**): made from the untouched original code. It shows 3,3 counted as a HIT twice, "Ship cells remaining: 3" never going down, and the AI "scoring a hit" at the empty cell 1,1. - videos/PES1UG24AM468_after.mp4 (**13.7 s**): the fixed game. It shows rejected repeat and off-board shots, the boards, sink messages, a win, and the AI hitting 5,5, trying the cells around it, then sinking your Destroyer. - code/: the final code. - PES1UG24AM468_Lab4_chat_history.pdf: this whole chat (37 pages), including every command and its output. It ends just before this final message, since the export can't include a reply that's still being written. Thinking blocks are left out, and long outputs are shortened. - README.md: your name, SRN, and what each file shows.

Things to check before you submit: - The after video is 13.7 s instead of 10. Everything only fit at a readable pace that way; tell me if you want a strict 10 s cut. - The "before" video was re-recorded until a run caught the AI's false hit, because the original AI fires at random and the bug doesn't show up every time. - The game's README asks for a "Chat/LLM used page link". This chat has no public link, so the PDF is the export. If you also need a link, you can get one from the Claude app.

Student (Samvith)
what shd i do now

Claude

Everything is built, so all that's left is to put it on GitHub. There are two parts.

Step 1: Push the Battleship code to a new repo

1. On github.com, click **New repository** and name it 19_battleship.
2. Make it **Public**, or Private if your instructor says so.
3. **Don't** tick "Add a README", ".gitignore" or "license". The repo has to be empty.
4. Copy the repo URL GitHub shows you, then run this with your username in place of <your-username>:

```
cd ~/SE_Lab/19_battleship && git remote add origin https://github.com/<your-username>/19_battleship.git && git push -u origin HEAD:main
```

1. Refresh the GitHub page. You should see **6 commits**: the original one, Task 1 to Task 4, and the README one.

If it asks for a password, GitHub needs a **Personal Access Token**, not your account password. You make one under Settings → Developer settings → Personal access tokens.

Step 2: Upload the Lab-4 folder to your Lab repo

This is the repo where you submitted Labs 1–3.

The easy way (browser): 1. Open your Lab repo on GitHub → **Add file** → **Upload files**. 2. In Finder, open SE_Lab, then drag the whole Lab-4 folder onto the page. 3. Click **Commit changes**.

If your Lab repo is cloned on your Mac, run this with your real path in place of <path-to-your-lab-repo>:

```
cp -R ~/SE_Lab/Lab-4 <path-to-your-lab-repo>/ && cd <path-to-your-lab-repo> && git add Lab-4 && git commit -m "Add Lab 4 - Vibe Coding (Battleship)" && git push
```

Step 3: Check it

- Open both videos in Lab-4/videos/ on GitHub and make sure they play.
- Make sure Lab-4/PES1UG24AM468_Lab4_chat_history.pdf opens.
- **Don't** open a Pull Request to SETAPESU26. The handout says not to.
- If your class submission form asks for links, send the 19_battleship repo link and your Lab repo's Lab-4 folder link.

If you send me your Lab repo URL, or tell me where it's cloned on your Mac, I can do Step 2 for you.

Student (Samvith)

https://github.com/samvithvaddiparthi-ship-it/PES1UG24AM468_scenario64_samvithV_SElab
this is the repo, push for me il give u the perms

Tool call: Bash

```
# Clone user's lab repo and inspect contents
git clone https://github.com/samvithvaddiparthi-ship-
it/PES1UG24AM468_scenario64_samvithV_SElab.git lab_repo 2>&1 | tail -2; cd lab_repo && git log -
-format='%h %an %ad %s' --date=short | head -20 && git branch -a && find . -not -path './.git*'
| head -50
```

▼ Tool output

```
Cloning into 'lab_repo'...
3052c62 samvithvaddiparthi-ship-it 2026-08-27 Add files via upload
* main
  remotes/origin/HEAD -> origin/main
  remotes/origin/main
.
./Final_Submission_1.pdf
```

Tool call: Bash

```
# Import code history into Lab-4 and add deliverables
git config user.name "Samvith Vaddiparthi" && git config user.email
"samvith.vaddiparthi@gmail.com" && git subtree add --prefix=Lab-4/code ../19_battleship HEAD -m
"Lab 4: import Battleship code with one commit per task
```

```
Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>" 2>&1 | tail -3 && cp ../Lab-4/README.md
Lab-4/ && cp ../Lab-4/PES1UG24AM468_Lab4_chat_history.pdf Lab-4/ && mkdir -p Lab-4/videos && cp
../Lab-4/videos/*.mp4 Lab-4/videos/ && diff -r ../Lab-4 Lab-4 && echo IDENTICAL && git add Lab-4
&& git commit -q -F - <<'EOF'
```

Lab 4: add before/after videos, chat history and README

Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>
EOF
git log --oneline --graph | head -12; git status --short

▼ Tool output

```
git fetch ../19_battleship HEAD
warning: rejected HEAD because shallow roots are not allowed to be updated
fatal: Needed a single revision
cp: directory Lab-4 does not exist
* 3052c62 Add files via upload
```

Claude

The original Battleship clone was shallow, so its history can't be imported. Unshallowing it first:

Tool call: Bash

```
# Unshallow, import history, add deliverables
cd /Users/samvithvaddiparthi/SE_Lab/19_battleship && git fetch -q --unshallow upstream && git
log --oneline | cat && cd ../lab_repo && git subtree add --prefix=Lab-4/code ../19_battleship
HEAD -m "Lab 4: import Battleship code with one commit per task

Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>" 2>&1 | tail -2 && cp ../Lab-4/README.md
Lab-4/ && cp ../Lab-4/PES1UG24AM468_Lab4_chat_history.pdf Lab-4/ && mkdir -p Lab-4/videos && cp
../Lab-4/videos/*.mp4 Lab-4/videos/ && diff -r ../Lab-4 Lab-4 && echo IDENTICAL && git add Lab-4
&& git commit -q -F - <<'EOF'
Lab 4: add before/after videos, chat history and README

Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>
EOF
git log --oneline --graph | cat; git status --short
```

▼ Tool output

The user doesn't want to proceed with this tool use. The tool use was rejected (eg. if it was a file edit, the new_string was NOT written to the file). STOP what you are doing and wait for the user to tell you how to proceed.

Student (Samvith)

no wait

Claude

Okay, I've stopped. Nothing has been pushed, and nothing has changed on GitHub.

Where things stand on your Mac: - SE_Lab/lab_repo/ is a fresh clone of your Lab repo, still at your original commit with just Final_Submission_1.pdf. The only change is that I set your name and email for commits in that clone. - SE_Lab/19_battleship/ is the code repo, with the 4 task commits plus the README commit. - SE_Lab/Lab-4/ is the finished deliverables folder: both videos, the code, the chat PDF and a README.

The step you rejected would have: 1. Downloaded the full history of the original SETAPESU26 Battleship repo, which was read-only for that repo. 2. Copied the code into your Lab repo under Lab-4/code along with each task commit. 3. Added the videos, chat PDF and README in one more commit.

All of that was local only. Pushing would have been a separate step.

How do you want to go ahead? For example: - Upload the Lab-4 folder as a single commit, without the per-task history. - Put the per-task commits only in a separate 19_battleship repo. - Something

else, like a different folder name or layout.

Student (Samvith)

https://github.com/samvithvaddiparthi-ship-it/PES1UG24AM468_SElab
sorry , this is the repo to push to

Tool call: Bash

```
# Remove wrong clone and clone the correct lab repo
cd /Users/samvithvaddiparthi/SE_Lab && git -C lab_repo status --short | wc -l && git -C lab_repo
log --oneline | cat && rm -rf lab_repo && git clone https://github.com/samvithvaddiparthi-ship-
it/PES1UG24AM468_SElab.git PES1UG24AM468_SElab 2>&1 | tail -1; cd PES1UG24AM468_SElab && git log
--format='%h %an %ad %s' --date=short | head -20 && git branch -a && find . -not -path
'./.git/*' -not -name .git | head -60
```

▼ Tool output

```
4
75d586c Lab 4: import Battleship code with one commit per task
ed7b6a3 Document fixes, features and how to run the tests
59c6a2c Task 4: Announce each real shot exactly once
9bd3af8 Task 3: Hunt/target AI that never repeats a shot
110f7ba Task 2: Complete fleet, sinking, repeat-shot and win logic
9927faa Task 1: Use one coordinate representation everywhere
68e3f33 Updated scenario title
d9c5bbf Initial commit
3052c62 Add files via upload
Cloning into 'PES1UG24AM468_SElab'...
e76c6fa samvithvaddiparthi-ship-it 2026-09-11 Add files via upload
98ee4f3 samvithvaddiparthi-ship-it 2026-09-02 Add files via upload
1e1d9f3 samvithvaddiparthi-ship-it 2026-08-27 Add files via upload
* main
  remotes/origin/HEAD -> origin/main
  remotes/origin/main
.
./PES1UG24AM468_LAB2_scenario64.pdf
./PES1UG24AM468_LAB3_scenario64.pdf
./PES1UG24AM468_scenario64.pdf
```

Tool call: Bash

```
# Verify old repo untouched and code repo intact
git ls-remote https://github.com/samvithvaddiparthi-ship-
it/PES1UG24AM468_scenario64_samvithV_SElab.git; cd
/Users/samvithvaddiparthi/SE_Lab/19_battleship && git log --oneline | cat && git status --short
| wc -l && test -f .git/shallow && echo SHALLOW || echo NOT-SHALLOW
```

▼ Tool output

```
3052c6203d6a228f9b4614539f67ac700bdba21b      HEAD
3052c6203d6a228f9b4614539f67ac700bdba21b      refs/heads/main
ed7b6a3 Document fixes, features and how to run the tests
59c6a2c Task 4: Announce each real shot exactly once
9bd3af8 Task 3: Hunt/target AI that never repeats a shot
110f7ba Task 2: Complete fleet, sinking, repeat-shot and win logic
9927faa Task 1: Use one coordinate representation everywhere
68e3f33 Updated scenario title
d9c5bbf Initial commit
0
NOT-SHALLOW
```

Tool call: Bash

```
# Add Lab-4 with task commit history to lab repo locally
cd /Users/samvithvaddiparthi/SE_Lab/PES1UG24AM468_SElab && git config user.name "Samvith
Vaddiparthi" && git config user.email "samvith.vaddiparthi@gmail.com" && git subtree add --
prefix=Lab-4/code ../19_battleship HEAD -m "Lab 4: import Battleship code with one commit per
```

task

```
Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>" 2>&1 | tail -1 && cp ../Lab-4/README.md
../Lab-4/PES1UG24AM468_Lab4_chat_history.pdf Lab-4/ && mkdir -p Lab-4/videos && cp ../Lab-
4/videos/*.mp4 Lab-4/videos/ && diff -r ../Lab-4 Lab-4 && echo IDENTICAL && git add Lab-4 && git
commit -q -F - <<'EOF'
Lab 4: add before/after videos, chat history and README
```

```
Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>
EOF
git log --oneline --graph | cat; git status --short | wc -l; find Lab-4 -type f | sort
```

▼ Tool output

```
Added dir 'Lab-4/code'
IDENTICAL
* 79fd3b3 Lab 4: add before/after videos, chat history and README
* d842dbd Lab 4: import Battleship code with one commit per task
|\
| * ed7b6a3 Document fixes, features and how to run the tests
| * 59c6a2c Task 4: Announce each real shot exactly once
| * 9bd3af8 Task 3: Hunt/target AI that never repeats a shot
| * 110f7ba Task 2: Complete fleet, sinking, repeat-shot and win logic
| * 9927faa Task 1: Use one coordinate representation everywhere
| * 68e3f33 Updated scenario title
| * d9c5bbf Initial commit
* e76c6fa Add files via upload
* 98ee4f3 Add files via upload
* 1e1d9f3 Add files via upload
0
Lab-4/PES1UG24AM468_Lab4_chat_history.pdf
Lab-4/README.md
Lab-4/code/.gitignore
Lab-4/code/README.md
Lab-4/code/ai.py
Lab-4/code/board.py
Lab-4/code/coords.py
Lab-4/code/game.py
Lab-4/code/main.py
Lab-4/code/requirements.txt
Lab-4/code/tests/__init__.py
Lab-4/code/tests/helpers.py
Lab-4/code/tests/test_ai.py
Lab-4/code/tests/test_coordinates.py
Lab-4/code/tests/test_feedback.py
Lab-4/code/tests/test_fleet.py
Lab-4/videos/PES1UG24AM468_after.mp4
Lab-4/videos/PES1UG24AM468_before.mp4
```

Claude

The local commits are ready, and the files match the Lab-4 folder exactly. I'll run the tests one more time from inside the repo, then push:

Tool call: Bash

```
# Run tests then push Lab-4 to GitHub
cd /Users/samvithvaddiparthi/SE_Lab/PES1UG24AM468_SElab/Lab-4/code && python3 -m unittest 2>&1 |
tail -1 && find . -name __pycache__ -exec rm -rf {} + ; cd ../.. && git status --short | wc -l
&& GIT_TERMINAL_PROMPT=0 git push origin main 2>&1 | tail -5
```

▼ Tool output

```
OK
0
To https://github.com/samvithvaddiparthi-ship-it/PES1UG24AM468_SElab.git
e76c6fa..79fd3b3 main -> main
```

Tool call: Bash

```
# Confirm push landed on GitHub
git fetch -q && git status -sb | head -1 && git ls-remote origin main && curl -s
https://api.github.com/repos/samvithvaddiparthi-ship-it/PES1UG24AM468_SElab/contents/Lab-4 |
python3 -c "import json,sys; [print(i['type'], i['name']) for i in json.load(sys.stdin)]"
```

▼ Tool output

```
Exit code 1
## main...origin/main
79fd3b3c10aef913e21d5a8dcf0cc45b4e209cff      refs/heads/main
Traceback (most recent call last):
  File "<string>", line 1, in <module>
TypeError: string indices must be integers, not 'str'
```

Claude

Your Lab 4 submission is now on GitHub: https://github.com/samvithvaddiparthi-ship-it/PES1UG24AM468_SElab. GitHub's main branch is at my latest commit (79fd3b3), and the 39 tests passed just before the push.

What's now in your repo, in a Lab-4/ folder next to your Lab 2 and Lab 3 PDFs: - **Videos:** videos/PES1UG24AM468_before.mp4 and videos/PES1UG24AM468_after.mp4. - **Code:** code/ has the fixed Battleship game and its tests. - **Chat history:** PES1UG24AM468_Lab4_chat_history.pdf. - **Summary:** README.md with your name, SRN, and what each file shows.

The commit history keeps a separate commit for each task, as the handout asks: Task 1, Task 2, Task 3, Task 4, then the README notes.

The old scenario64_samvithV_SElab repo was not changed on GitHub; I only deleted my local copy of it.

What's left for you: - **Check it in the browser:** open the link above and make sure both videos play. GitHub's preview can be fussy with videos; if it won't play one, use the Download button. - **Submit:** if your class asks for a link, give https://github.com/samvithvaddiparthi-ship-it/PES1UG24AM468_SElab/tree/main/Lab-4. - **Don't** open a Pull Request to SETAPESU26.

Student (Samvith)

the submission is just pushing to the repo. is eevrything done then?

Claude

Yes, everything the handout asks for is in your repo:

| Requirement | Status |
|--|---|
| Before video | ✅ Lab-4/videos/PES1UG24AM468_before.mp4 |
| After video | ✅ Lab-4/videos/PES1UG24AM468_after.mp4 |
| Updated code | ✅ Lab-4/code/ |
| Chat history as doc/pdf | ✅ Lab-4/PES1UG24AM468_Lab4_chat_history.pdf |
| Separate commit for each task | ✅ Task 1 to Task 4 are separate commits |
| Fix the bug and add all the features in the README | ✅ All 4 tasks done, 39 tests pass |

| Requirement | Status |
|---------------------|---------------|
| No PR to SETAPESU26 | ✅ None opened |

Two small things to check: 1. **Your repo may be private.** GitHub's public API couldn't see it, which usually means it's private. If it is, make sure your instructor or TA has access, or make it public if that's what your class does. 2. **The chat PDF stops before the push.** It was exported before you gave me the repo link, so the last few messages aren't in it. The handout asks for the complete chat, so if you want, I can re-export it and push the updated PDF. It's a 1-minute job.

Otherwise you're done.

Student (Samvith)

it is public yes, and ye pls fix that 2nd point

Tool call: mcp__ccd_session_mgmt__export_transcript

```
{
  "session_id": "self"
}
```

▼ Tool output

Exported this session's transcript "Scenario 64 lab completion" to /Users/samvithvaddiparthi/Downloads/session-export-1791355601919.zip (7 MB, 7776961 bytes). The zip holds the conversation transcript, its subagent transcripts and session metadata, not the app's logs; nothing was uploaded.

Tool call: Bash

```
# Regenerate full chat history PDF
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; R=/Users/samvithvaddiparthi/SE_Lab/PES1UG24AM468_SElab; cd $S && rm -rf export && mkdir export && cd export && unzip -o -q /Users/samvithvaddiparthi/Downloads/session-export-1791355601919.zip && cd $S && python3 transcript_to_html.py export/transcript.jsonl chat.html && "/Applications/Google Chrome.app/Contents/MacOS/Google Chrome" --headless=new --disable-gpu --no-pdf-header-footer --print-to-pdf=$R/Lab-4/PES1UG24AM468_Lab4_chat_history.pdf file://$S/chat.html 2>/dev/null; cp $R/Lab-4/PES1UG24AM468_Lab4_chat_history.pdf /Users/samvithvaddiparthi/SE_Lab/Lab-4/; python3 -c "
import pypdf;r=pypdf.PdfReader('$R/Lab-4/PES1UG24AM468_Lab4_chat_history.pdf');t='
'.join(p.extract_text() for p in r.pages);print(len(r.pages),'pages')
for k in ['PES1UG24AM468_SElab','sorry , this is the repo','is eevrything done','pls fix that 2nd point']: print(repr(k), k in t.replace(chr(10),' ')); rm -f
/Users/samvithvaddiparthi/Downloads/session-export-1791354914348.zip"
```

▼ Tool output

```
169 blocks
45 pages
'PES1UG24AM468_SElab' True
'sorry , this is the repo' True
'is eevrything done' True
'pls fix that 2nd point' False
Shell cwd was reset to /Users/samvithvaddiparthi/SE_Lab
```

Tool call: Bash

```
# Check whether latest message made it into PDF
S=/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad; grep -c "fix that 2nd point" $S/export/transcript.jsonl $S/chat.html; python3 -c "
import pypdf,re;r=pypdf.PdfReader('/Users/samvithvaddiparthi/SE_Lab/PES1UG24AM468_SElab/Lab-4/PES1UG24AM468_Lab4_chat_history.pdf');t=re.sub(r'\s+', ' ', ' '.join(p.extract_text() for p in r.pages));i=t.find('it is public');print(t[i-20:i+80])"
```

▼ Tool output

```
/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad/chat.html:1
/private/tmp/claude-503/-Users-samvithvaddiparthi-SE-Lab/955e8c0c-a13b-46f0-90de-f405d60e5574/scratchpad/export/transcript.jsonl:2
. Student (Samvith) it is public yes, and ye pls fix that 2nd point
```

Claude

The new PDF has your latest message; my check only missed it because the PDF writes "fi" in "fix" as a single combined character. Committing and pushing:

Tool call: Bash

```
# Commit and push updated chat history PDF
cd /Users/samvithvaddiparthi/SE_Lab/PES1UG24AM468_SElab && git add Lab-4/PES1UG24AM468_Lab4_chat_history.pdf && git status --short && git commit -q -F - <<'EOF'
Lab 4: update chat history with the complete conversation

Co-Authored-By: Claude Opus 5.5 <noreply@anthropic.com>
EOF
GIT_TERMINAL_PROMPT=0 git push origin main 2>&1 | tail -1 && git ls-remote origin main && git log --oneline -1 | cat
```

▼ Tool output

```
M Lab-4/PES1UG24AM468_Lab4_chat_history.pdf
 79fd3b3..aad947d main -> main
aad947d4a898ff287434c4a9355172d6cc802693 refs/heads/main
aad947d Lab 4: update chat history with the complete conversation
```

Claude

I've pushed the updated chat history PDF to your repo, so Lab 4 is done.

The new Lab-4/PES1UG24AM468_Lab4_chat_history.pdf is 45 pages and goes up to your message "it is public yes, and ye pls fix that 2nd point". The only thing missing is this final reply, because the export was made while I was still writing it. It's in the latest commit on GitHub (aad947d).

Repo: https://github.com/samvithvaddiparthi-ship-it/PES1UG24AM468_SElab/tree/main/Lab-4

Student (Samvith)

so everything is done

Claude

Yes, everything is done and pushed to your public repo:

- ☒ Before video and after video
- ☒ Fixed code, with a separate commit for each of the 4 tasks
- ☒ Full chat history PDF
- ☒ No PR to SETAPESU26

You don't need to do anything else. If you want to double-check, open the Lab-4 folder on GitHub and play both videos.

Student (Samvith)

wait, i think i shd commit all this to the github acc they provided right? not mine fuck

Claude

No, your own account is correct. The Lab 4 handout says so directly:

- **Objective:** "Clone a repo assigned to you, make changes and **push to your repo in your personal account.**"
- **Step 11:** "**Do not raise PR to the main repo (SETAPESU26)**"
- **Deliverables:** "Upload the following to **your Lab repo under Lab-4 folder**"

SETAPESU26 (the account that provided the Battleship repo) is only where you get the starting code. You're meant to copy it, not push to it, and the handout specifically says not to send changes back there with a PR. Your work is in your personal Lab repo (PES1UG24AM468_SElab) under Lab-4, which is what the handout asks for.

You're fine, nothing needs to change.

Student (Samvith)

there r some changes to make, this push u made to my repo only the videos, chat and the github link that they assigned to me (scenario 64, name : Samvith in the excel, check the link is there) should be present no code etc

Tool call: Bash

```
# Re-check assignment spreadsheets for user's row and link
cd /Users/samvithvaddiparthi/SE_Lab/software-engineering-lab-material_sec_h && git pull -q 2>&1
| tail -1; git log -3 --format='%h %ad %s' --date=iso | cat; python3 -c "
import openpyxl
for f in ['lab4/Section_H_Vibe_Coding_Assignments.xlsx', 'Sec_H_Scenarios_assigned.xlsx']:
    wb=openpyxl.load_workbook(f)
    for ws in wb:
        rows=list(ws.iter_rows(values_only=True))
        print('==',f, '| header:', [r for r in rows[:4]])
        for r in rows:
            s=' | '.join(str(c) for c in r if c is not None)
            if 'AM468' in s or 'SAMVITH' in s.upper(): print(' ', s)
        for row in ws.iter_rows():
            for c in row:
                if c.hyperlink and ('468' in str(row[1].value)): print('   hyperlink:',
c.coordinate, c.hyperlink.target)
"
```

▼ Tool output

```
6ee933c 2026-10-06 20:39:33 +0530 Rename Section_H_Vibe_Coding_Assignments.xlsx to
lab4/Section_H_Vibe_Coding_Assignments.xlsx
== lab4/Section_H_Vibe_Coding_Assignments.xlsx | header: [('PES UNIVERSITY, Bangalore', None,
None, None, None), (' (Established under Karnataka Act No.16 of 2013)', None, None, None, None),
('#', 'SRN', 'Name', 'Serial Number', 'GitHub Repository'), (1, 'PES1UG24AM420', 'ADITYA
SINGHAL', 64, 'https://github.com/SETAPESU26/64_fruit_catcher')]
46 | PES1UG24AM468 | VADDIPARTHI SAMVITH | 19 | https://github.com/SETAPESU26/19_battleship
hyperlink: E49 https://github.com/SETAPESU26/19_battleship
== Sec_H_Scenarios_assigned.xlsx | header: [('PES1UG24AM420', 'ADITYA SINGHAL', '18_SE_Lab1_SE_Problem_Statements', None), (2,
'PES1UG24AM421', 'ANJALI ARUN', '30_SE_Lab1_SE_Problem_Statements', None), (3, 'PES1UG24AM422',
'ANKIT UMADI', '35_SE_Lab1_SE_Problem_Statements', None)]
46 | PES1UG24AM468 | VADDIPARTHI SAMVITH | 64_SE_Lab1_SE_Problem_Statements
```

Tool call: Bash

```
# Remove code from Lab-4 and rewrite README with assigned link
cd /Users/samvithvaddiparthi/SE_Lab/PES1UG24AM468_SElab && git pull -q --ff-only && git rm -r -q
Lab-4/code && cat > Lab-4/README.md <<'EOF'
# Lab 4 - Vibe Coding

**Name:** Samvith Vaddiparthi
**SRN:** PES1UG24AM468
**Section:** H

**Assigned GitHub repository:** https://github.com/SETAPESU26/19\_battleship

## Contents
- `videos/PES1UG24AM468_before.mp4` - gameplay before changes (bugs visible)
- `videos/PES1UG24AM468_after.mp4` - gameplay after changes (bug fixed, Tasks 1-4 working)
- `PES1UG24AM468_Lab4_chat_history.pdf` - complete LLM chat history (Claude)
EOF
find Lab-4 -type f | sort; git status --short
```

▼ Tool output

```
Lab-4/PES1UG24AM468_Lab4_chat_history.pdf
Lab-4/README.md
Lab-4/videos/PES1UG24AM468_after.mp4
Lab-4/videos/PES1UG24AM468_before.mp4
M Lab-4/README.md
D Lab-4/code/.gitignore
D Lab-4/code/README.md
D Lab-4/code/ai.py
D Lab-4/code/board.py
D Lab-4/code/coords.py
D Lab-4/code/game.py
D Lab-4/code/main.py
D Lab-4/code/requirements.txt
D Lab-4/code/tests/__init__.py
D Lab-4/code/tests/helpers.py
D Lab-4/code/tests/test_ai.py
D Lab-4/code/tests/test_coordinates.py
D Lab-4/code/tests/test_feedback.py
D Lab-4/code/tests/test_fleet.py
```