version 0.95 BETA

Format:

FloppyCloud API is a JSON-based API and thus the results (should) always be in JSON format. The result object might contain a data-property as well as a error-property (sometimes both), depending on the outcome of the request.

Session:

If a session has been started by signing in or registering through the API or the GUI version of the application within or on separate windows/tabs, that session will be viewed as the current active session by the API.

Parameter:

api=<any> Sets the API to return the results as JSON-data instead of rendering the view.

login_page=<any> Set the API to return a sign up/in page as the result in the JSON-data.

login=<any> Tells the API that the call might be a attempt to sign in (will be ignored if session is already started).

register=<any> Tells the API that the call might be a attempt to sign up (will be ignored if session is already started).

id=<owner_id> When requesting a file from a external account this parameter tells the API whish owner to look for the file from. If the requested file has been set by the owner as a shared file, the API will either return a download link or send the file back to the client depending on what was requested.

download=<file_name> Tells the API what file to be downloaded. If the file is from an external user the id of that user must be sent with the request.

@return: Download-link for the file.

load=<file_name> Tells the API what file to be loaded. If the file is from an external user the id of that user must be sent with the request.

@return: A HTML-template with the file attached to a suitable tag depending och file-type. Base64 format data is the src of that tag.

delete=<file_name> Tells the API what file to be deleted. Requires authorization. @return: Link to delete the file.

share=<file_name> Tells the API what file to toggle the share status on. Requires authorization.

@return: If set to shared it returns a sharable link, else it returns false.