


## Tutorials on List structures, Tuple

### Indexing:


Let's take a simple example:

```
colors = ['red', 'green', 'blue', 'yellow', 'white', 'black']
```


**Python uses zero-based indexing.** That means, the first element(value 'red') has an index 0, the second(value 'green') has index 1, and so on.



To address this requirement there is negative indexing. So, instead of using indexes from zero and above, we can use indexes from -1 and below.



In negative indexing system -1 corresponds to the last element of the list(value 'black'), -2 to the penultimate (value 'white'), and so on.

**Slicing:****[start : stop : steps]**

which means that slicing will start from index **start**  
will go up to **stop** in **step** of steps.  
Default value of **start** is 0, **stop** is last index of list  
and for **step** it is 1


## append() and extend() in Python

Last Updated: 01-04-2020

**Append:** Adds its argument as a single element to the end of a list. The length of the list increases by one.

**syntax:**

```
# Adds an object (a number, a string or a  
# another list) at the end of my_list  
my_list.append(object)
```




```
my_list = ['geeks', 'for']  
my_list.append('geeks')  
print my_list
```

Output:

```
['geeks', 'for', 'geeks']
```

**NOTE:** A list is an object. If you append another list onto a list, the parameter list will be a single object at the end of the list.



```
my_list = ['geeks', 'for', 'geeks']  
another_list = [6, 0, 4, 1]  
my_list.append(another_list)  
print my_list
```

Output:

```
['geeks', 'for', 'geeks', [6, 0, 4, 1]]
```

## Tuple

Tuples are used to store multiple items in a single variable.

Tuple is one of 4 built-in data types in Python used to store collections of data, the other 3 are List, Set, and Dictionary, all with different qualities and usage.

A tuple is a collection which is ordered and **unchangeable**.

Tuples are written with round brackets.

### Example

Create a Tuple:

```
thistuple = ("apple", "banana", "cherry")  
print(thistuple)
```

## Tutorials on List structures, Tuple

---

1. Printing a empty list:

```
a=list()
print(a)
Output: []
```

2. Check index:

```
a=[10, 20, 30, 40]
c=a[1:2]
print(c)
Output: 20
```

3. Reverse a string

```
L = [1,2,3]
print(list(reversed(L)))
Output: [3,2,1]
```

4. Check any number

```
L = [1,2,3]
print(5 in L)
Output: False
```

5. Sort the list

```
L=[1,3,5,2,7,8]
print(sorted(L))
Output: [1,2,3,5,7,8]
```

6. Value at a index:

```
L=[1,3,5,2,7,8]
print(L.index(5))
Output: 2
```

7. Pop the value

```
L=[1,2,3]
L.pop()
Print(L)
```

## Tutorials on List structures, Tuple

---

**Output: [1,2]**

8. Copy the list:

```
a= [10,20,30,40]
```

```
c=a
```

```
print(c)
```

**Output: [10,20,30,40]**

9. Pick the last index:

```
L= [1,2,3]
```

```
print(L[-1])
```

**Output: 3**

10. l= (10,20,30)

```
print(l)
```

```
print(l[1:2])
```

```
print(l.index(20))
```

```
del()
```

**Output:**

**(10, 20, 30)**

**(20,)**

**1**

11. List = [['Python ', 'is' ], ['Easy']]

```
print("\nValue in Multi-Dimensional List: ")
```

```
print(List[0][0], List[1][0][0])
```

```
List = [1, 2, 'Python', 4, 'is', 6, 'Easy']
```

```
print("\nList with the use of Mixed Values: ")
```

```
print(List[1], List[2][2])
```

**Output:**

**Value in Multi-Dimensional List:**

**Python E**

**List with the use of Mixed Values:****2 t****12. Predict the output: (difference between append, insert and extend)**

```
List = [1,2,3,4]

List.append(12)

print(List)

List.insert(3, 12)

print(List)

List.extend(['Bennett', 'University'])

print(List)
```

**Output:****[1, 2, 3, 4, 12]****[1, 2, 3, 12, 4, 12]****[1, 2, 3, 12, 4, 12, 'Bennett', 'University']****13. Predict the output**

```
List = [1, 2, 3, 9, 5, 6, 4, 7, 8, 7, 10, 11, 12]

List.remove(7)

print(List)

for i in range(3, 5):

    List.remove(i)

print(List)

List = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12]

List.remove(7)

print(List)
```

## Tutorials on List structures, Tuple

---

```
List.pop(7)
```

```
print(List)
```

**Output:**

```
[1, 2, 3, 9, 5, 6, 4, 8, 7, 10, 11, 12]
```

```
[1, 2, 9, 5, 6, 8, 7, 10, 11, 12]
```

```
[1, 2, 3, 4, 5, 6, 8, 9, 10, 11, 12]
```

```
[1, 2, 3, 4, 5, 6, 8, 10, 11, 12]
```

### 14. Predict the output:

```
round1 = ['chuck norris', 'bruce lee', 'sonny chiba']
```

```
round2 = round1.copy()
```

```
round1.remove('sonny chiba')
```

```
print(round1)
```

```
print(round2)
```

**Output:**

```
['chuck norris', 'bruce lee']
```

```
['chuck norris', 'bruce lee', 'sonny chiba']
```

### 15. Predict the output:

```
lst = ['python', 'is', 'cool', 'language']
```

```
for i in range(len(lst)):
```

```
    print(lst[i])
```

**Output:**

```
python
```

```
is
```

```
cool
```

```
language
```

### 16. Create a matrix and display the elements of it, using python program.

**Solution:**

```
r=int(input("Enter row size"))
```

## Tutorials on List structures, Tuple

---

```
c=int(input("Enter column size"))

m=[]

for i in range(r):

    n=[]

    print("Enter elements in row")

    for j in range(c):

        l=int(input())

        k=[l]

        n.extend(k)

    m.append(n)

    print("Matrix is" ,m)
```

**17. A list a provided to you, print a sub-list of a given range using python Program:**

```
r=int(input("Enter list size"))
m=[]
for i in range(r):
    print("Enter elements in list")
    l=input()
    k=[l]
    m.extend(k)
print("The input list" ,m)
s_i=int(input("enter start index"))
e_i=int(input("enter start index"))
if((s_i>0 and e_i<=r)):
    sub=m[s_i-1:e_i-1]
print("Sublist is:",sub)
```

**18. Write a program to pack and unpack a tuple.**

```
x=(10,20,30,40) #Tuple packing
print("Type of x:",type(x))
print("Values of x:", x)
(v1,v2,v3,v4)=x #Tuple unpacking
print("Value1:",v1)
print("Value2:",v2)
```



## Tutorials on List structures, Tuple

---

```
print("Value3:",v3)  
print("Value4:",v4)
```