

Open Biomedical Knowledge Graphs at Scale: Construction, Federation, and AI Agent Access with Samyama Graph Database

Madhulatha Mandarapu* Sandeep Kunkunuru†

VaidhyaMegha Private Limited, India

<https://samyama.ai/>

March 2026

Abstract

Biomedical knowledge is fragmented across siloed databases—Reactome for pathways, STRING for protein interactions, Gene Ontology for functional annotations, ClinicalTrials.gov for study registries, and dozens more. Researchers routinely download flat files from each source and write bespoke scripts to cross-reference them, a process that is slow, error-prone, and not reproducible. We present two open-source biomedical knowledge graphs—**Pathways KG** (118,686 nodes, 834,785 edges from 5 sources) and **Clinical Trials KG** (7,774,446 nodes, 26,973,997 edges from 5 sources)—built on Samyama, a high-performance graph database written in Rust.

Our contributions are threefold. First, we describe a **reproducible ETL pattern** for constructing large-scale KGs from heterogeneous public data sources, with cross-source deduplication, batch Cypher loading, and portable snapshot export. Second, we demonstrate **cross-KG federation**: loading both snapshots into a single graph tenant enables property-based joins across datasets, answering questions like “Which biological pathways are disrupted by drugs currently in Phase 3 trials for breast cancer?”—a query that neither KG can answer alone. Third, we introduce **schema-driven MCP server generation**: each KG automatically exposes typed tools for LLM agents via the Model Context Protocol, enabling natural-language access to graph queries without manual tool authoring.

All data sources are open-license (CC BY 4.0, CC0, OBO). Snapshots, ETL code, and MCP configurations are publicly available. The combined federated graph (7.89M nodes, 27.8M edges) loads in 76 seconds on commodity hardware (Mac Mini M4, 16GB RAM), and the signature cross-KG query—“which pathways are disrupted by drugs in Phase 3 breast cancer trials?”—returns validated results in 2.1 seconds.

Keywords: Knowledge Graphs, Biomedical Data Integration, Graph Databases, Cross-KG Federation, Model Context Protocol, Clinical Trials, Biological Pathways, OpenCypher.

1 Introduction

Biological and clinical knowledge is distributed across dozens of public databases, each with its own schema, identifiers, and access patterns. A researcher investigating how a cancer drug affects cellular signaling must consult ClinicalTrials.gov for trial metadata, DrugBank for drug–target interactions,

*madhulatha@samyama.ai, ORCID: <https://orcid.org/0009-0005-2837-6725>

†sandeep@samyama.ai, ORCID: <https://orcid.org/0000-0002-8886-1846>

Reactome for pathway membership, STRING for protein–protein interactions, and Gene Ontology for functional annotations. These databases are maintained by independent communities, updated on different schedules, and stored in incompatible formats (TSV, XML, JSON, OBO, GAF).

Knowledge graphs (KGs) offer a natural integration point [Hogan et al., 2021]: entities from different sources become nodes, and relationships between them become edges. A single Cypher query can traverse from a clinical trial to the biological pathways disrupted by its drug candidate—a query that would require joining across five separate databases in the flat-file paradigm.

However, constructing biomedical KGs at scale remains challenging. Prior efforts such as Bio2RDF [Callahan et al., 2013], Hetionet [Himmelstein et al., 2017], and the Clinical Knowledge Graph [Santos et al., 2022] have made significant progress, but each faces limitations: Bio2RDF requires a dedicated SPARQL endpoint infrastructure, Hetionet is a static dataset without an update pipeline, and the Clinical Knowledge Graph targets a single data source.

We address these limitations with three contributions:

1. **Reproducible KG construction.** We present ETL pipelines for two large-scale biomedical KGs—Pathways KG (5 sources, 119K nodes) and Clinical Trials KG (5 sources, 7.7M nodes)—built on Samyama Graph Database using a common pattern: download, parse, deduplicate, batch-load via Cypher, and export as portable `.sgsnap` snapshots.
2. **Cross-KG federation.** We show that loading multiple snapshots into a single graph tenant enables property-based federation—joining on shared identifiers (UniProt accessions, DrugBank IDs, NCBI Gene IDs) without ETL-time merging. We demonstrate five cross-KG query patterns spanning translational medicine.
3. **Schema-driven AI agent access.** Each KG ships with a Model Context Protocol (MCP) [Anthropic, 2024] server configuration that auto-generates typed tools from the graph schema. LLM agents can query the KG via natural language without hand-coded tool definitions.

All code, snapshots, and MCP configurations are open-source¹.

2 Background and Related Work

2.1 Biomedical Knowledge Graphs

Hetionet [Himmelstein et al., 2017] integrates 29 public resources into a single heterogeneous network (47K nodes, 2.25M edges, 24 edge types) for drug repurposing. While influential, it is a static dataset from 2017 with no update pipeline.

Bio2RDF [Callahan et al., 2013] converts life science databases to RDF and serves them via SPARQL endpoints. The RDF approach offers semantic interoperability but introduces complexity (OWL reasoning, blank nodes) and performance overhead for traversal-heavy queries.

Clinical Knowledge Graph (CKG) [Santos et al., 2022] builds a comprehensive biomedical graph from 25+ databases using Neo4j. CKG is the closest prior work to ours; we differ in three ways: (1) we use a Rust-native engine rather than Neo4j, achieving higher ingestion throughput; (2) we introduce portable snapshots for instant deployment; and (3) we provide schema-driven MCP servers for LLM agent integration.

PrimeKG [Chandak et al., 2023] constructs a precision medicine KG (129K nodes, 8M edges) from 20 sources. PrimeKG targets drug–disease prediction via graph neural networks; our focus is on interactive querying and AI agent access.

¹Pathways KG: <https://github.com/samyama-ai/pathways-kg>; Clinical Trials KG: <https://github.com/samyama-ai/clinicaltrials-kg>; Snapshots: <https://github.com/samyama-ai/samyama-graph/releases>

2.2 Graph Database Systems

Neo4j [Neo4j, Inc., 2024] is the dominant property graph database. Amazon Neptune, TigerGraph, and MemGraph offer alternatives with varying trade-offs. Samyama [Mandarapu and Kunkumuru, 2026] is a Rust-native graph database combining property graph storage, vector search, 22 metaheuristic solvers, and OpenCypher support in a single binary.

2.3 Model Context Protocol (MCP)

MCP [Anthropic, 2024] is an open standard for connecting LLM agents to external data sources via typed tools. An MCP server exposes a set of tools (functions with typed parameters and return values) that an LLM can invoke during a conversation. Schema-driven MCP generation—automatically creating tools from a KG schema—eliminates the manual tool authoring bottleneck.

3 Data Sources

Both KGs draw exclusively from open-license public databases. Table 1 summarizes the sources.

Table 1: Data sources for the two biomedical KGs. All are open-license and human-specific (organism 9606 where applicable).

KG	Source	Content	License	Size
Pathways	Reactome	Pathways, reactions, complexes	CC BY 4.0	172 MB
	STRING v12.0	Protein–protein interactions	CC BY 4.0	900 MB
	Gene Ontology	GO terms & annotations	OBO	265 MB
	WikiPathways	Community-curated pathways	CC0	336 KB
	UniProt	Protein metadata, gene/disease/drug links	CC BY 4.0	20 MB
Clinical	ClinicalTrials.gov	Trial registry (575K studies)	Public domain	API
	MeSH (NLM)	Disease hierarchy	Free	API
	RxNorm (NLM)	Drug normalization & ATC codes	Free	API
	OpenFDA	Adverse event reports (FAERS)	Public domain	API
	PubMed (NLM)	Trial-linked publications	Free	API

4 Knowledge Graph Construction

4.1 ETL Pattern

Both KGs follow a common five-phase pattern:

1. **Download.** A data downloader with resume support fetches all source files. Compressed files are decompressed automatically.
2. **Parse & Filter.** Source-specific parsers extract entities and relationships. Human-only filters are applied where applicable (organism ID 9606).
3. **Deduplicate.** A shared *Registry* tracks seen entities across phases (e.g., a protein loaded from Reactome is not re-created when encountered in STRING).
4. **Batch Load.** Nodes and edges are loaded via batched Cypher **CREATE** statements (50–100 entities per batch) through Samyama’s HTTP API.

5. **Snapshot Export.** The loaded graph is exported as a portable `.sgsnap` file (gzip JSON-lines), enabling instant restoration on any Samyama instance.

4.2 Pathways KG

The Pathways KG integrates molecular biology data into a graph with 5 node labels and 9 edge types (Table 2).

Table 2: Pathways KG schema.

			Edge Type	Count
Node Label	Key Property	Count	ANNOTATED_WITH	265,492
GOTerm	go_id	51,897	INTERACTS_WITH	227,818
Protein	uniprot_id	37,990	PARTICIPATES_IN	140,153
Complex	reactome_id	15,963	CATALYZES	121,365
Reaction	reactome_id	9,988	IS_A	58,799
Pathway	reactome_id	2,848	COMPONENT_OF	8,186
Total nodes		118,686	PART_OF	7,122
			REGULATES	2,986
			CHILD_OF	2,864
			Total edges	834,785

The five ETL phases execute in order: (1) **Reactome Core**—pathways, reactions, complexes, and protein participants from Reactome’s flat files; (2) **STRING Interactions**—high-confidence ($\geq 700/999$) protein–protein interactions with ENSP→UniProt ID mapping; (3) **Gene Ontology**—47K GO terms with IS_A/PART_OF/REGULATES hierarchy and 265K protein annotations; (4) **WikiPathways**—community-curated pathways deduplicated against Reactome; (5) **UniProt Enrichment**—gene mappings, disease associations, and drug targets.

4.3 Clinical Trials KG

The Clinical Trials KG models the translational medicine domain with 15 node labels and 25 edge types (Table 3).

Table 3: Clinical Trials KG schema (abbreviated; 15 labels, 25 edge types).

Node Label	Key Property	Est. Count
ClinicalTrial	nct_id	575,000+
Condition	name, mesh_id	varies
Intervention	name, type	varies
Drug	rxnorm_cui, drugbank_id	varies
Protein	uniprot_id	varies
Gene	gene_id, symbol	varies
MeSHDescriptor	descriptor_id	varies
Sponsor	name, class	varies
Site	facility, country	varies
Publication	pmid, doi	varies
AdverseEvent	term, is_serious	varies
ArmGroup	label, type	varies
Outcome	measure, type	varies
DrugClass	atc_code, level	varies
LabTest	loinc_code	varies
Total nodes		7,774,446
Total edges		26,973,997

The ETL pipeline queries the ClinicalTrials.gov API v2 for study metadata, enriches conditions with MeSH hierarchy, normalizes drug names via RxNorm, links adverse events from OpenFDA’s FAERS database, and associates publications from PubMed E-utilities.

5 Cross-KG Federation

5.1 Motivation

The Pathways KG knows molecular biology—which proteins interact, what pathways they participate in. The Clinical Trials KG knows translational medicine—which drugs are in trials, what conditions they treat. Neither alone can answer:

“Which biological pathways are disrupted by drugs currently in Phase 3 trials for breast cancer?”

This query requires traversing: **ClinicalTrial** $\xrightarrow{\text{STUDIES}}$ **Condition** (breast cancer) $\leftarrow$ **ClinicalTrial** $\xrightarrow{\text{TESTS}}$ **Intervention** $\xrightarrow{\text{CODED_AS_DRUG}}$ **Drug** $\xrightarrow{\text{TARGETS}}$ **Protein** $\xrightarrow{\text{PARTICIPATES_IN}}$ **Pathway**. The first three hops are in the Clinical Trials KG; the last two are in the Pathways KG. The **Drug**→**Protein** edge is the bridge.

5.2 Join Points

Three entity types appear in both KGs with matching identifiers:

Table 4: Cross-KG join points.

Entity	Pathways Property	Clinical Trials Property	Identifier
Protein	Protein.uniprot_id	Protein.uniprot_id	UniProt accession
Drug	Drug.drugbank_id	Drug.drugbank_id	DrugBank ID
Gene	Gene.gene_id	Gene.gene_id	NCBI Gene ID

5.3 Federation Mechanism

Samyama supports loading multiple snapshots into a single tenant. Each snapshot import appends nodes and edges to the existing graph. Since imports create new node IDs, entities from different snapshots with the same identifier (e.g., UniProt P04637 for TP53) exist as separate graph nodes. Cross-KG queries use **property-based joins**:

```
-- Pathways disrupted by Phase 3 breast cancer drugs
MATCH (ct:ClinicalTrial)-[:STUDIES]->(cond:Condition)
WHERE ct.phase = 'Phase_3' AND cond.name CONTAINS 'Breast'
WITH ct
MATCH (ct)-[:TESTS]->(int:Intervention)
      -[:CODED_AS_DRUG]->(drug:Drug)
WITH DISTINCT drug
MATCH (drug)-[:TARGETS]->(prot1:Protein)
MATCH (prot2:Protein)-[:PARTICIPATES_IN]->(pw:Pathway)
WHERE prot1.uniprot_id = prot2.uniprot_id
RETURN pw.name AS pathway,
       count(DISTINCT drug.name) AS drugs_targeting
ORDER BY drugs_targeting DESC LIMIT 15
```

The WHERE `prot1.uniprot_id = prot2.uniprot_id` clause is the cross-KG bridge—it joins a Protein node from the Clinical Trials snapshot with a Protein node from the Pathways snapshot.

5.4 Federation Query Patterns

We identify five cross-KG query patterns of increasing complexity:

Table 5: Cross-KG federation query patterns.

Pattern	Clinical Trials →	→ Pathways
Drug → Pathway	Trial → Drug (via intervention)	Drug target → Protein → Pathway
Drug → GO Process	Trial → Drug	Drug target → Protein → GOTerm
Drug → PPI Network	Trial → Drug → Protein target	Target → INTER-ACTS_WITH neighbors
Disease → Pathway	Gene → Disease association	Gene → Protein → Pathway
Adverse Event → Pathway	Trial → AdverseEvent → Drug	Drug → Protein → Pathway

6 Schema-Driven MCP Server Generation

Each KG ships with a YAML configuration that defines domain-specific MCP tools. At startup, the MCP server:

1. **Discovers schema** from the running Samyama instance (GET /api/schema).
2. **Auto-generates tools** for each node label (search, get, count) and each edge type (find connections).
3. **Registers domain tools** from the YAML configuration—each tool is a parameterized Cypher template with typed inputs (e.g., `protein_name: string, confidence_threshold: int`).

The Pathways KG MCP server exposes 12 domain-specific tools (Table 6).

Table 6: Pathways KG MCP tools (subset).

Tool	Description
<code>pathway_members</code>	List proteins in a pathway (search by name)
<code>interaction_partners</code>	PPI neighbors above confidence threshold
<code>shared_pathways</code>	Pathways shared between two proteins
<code>upstream_regulators</code>	Multi-hop PPI traversal up to N steps
<code>drug_pathway_impact</code>	Pathways affected by a drug via protein targets
<code>disease_pathways</code>	Pathways associated with a disease through gene links
<code>go_enrichment</code>	GO terms enriched in pathway proteins
<code>protein_function_summary</code>	Pathways, GO processes, disease associations for a protein

An LLM agent connected to this MCP server can answer “What pathways does TP53 participate in?” without writing Cypher. The agent calls `pathway_members(protein_name="TP53")` and receives structured results.

7 Evaluation

We evaluate construction time, query performance, and federation correctness on a Mac Mini M4 (Apple M4, 10 cores, 16GB RAM).

7.1 Construction Performance

Table 7: KG construction performance.

KG	Nodes	Edges	Snapshot Size	Import Time
Pathways KG	118,686	834,785	9 MB	1 s
Clinical Trials KG	7,774,446	26,973,997	711 MB	72 s
Drug enrichment (32 drugs)	+33	+235	—	3 s
Combined	7,893,165	27,809,017	720 MB	76 s

Snapshot import uses gzip-compressed JSON-lines format. The Pathways KG loads in 1 second; the Clinical Trials KG, with its 7.8M nodes, loads in 72 seconds. A targeted drug enrichment step adds 32 breast cancer drug nodes with 36 TARGETS edges and 199 CODED_AS_DRUG edges in 3 seconds. The full pipeline—from empty tenant to federated graph—completes in 76 seconds.

7.2 Query Performance

We benchmark representative queries from each KG and the federated graph:

Table 8: Query latency on Mac Mini M4.

Query	KG	Results	Latency
Label distribution (15 labels)	Combined	15 rows	7.8 s
Proteins with uniprot_id	Combined	1 row	0.5 s
Top pathways by protein count	Pathways	10 rows	85 ms
PPI hub proteins (TP53: 739)	Pathways	5 rows	1.4 s
Breast cancer trial count	Clinical	5 rows	1.2 s
Drug → Pathway (6-hop)	Combined	10 rows	2.1 s

The signature federated query—“pathways disrupted by breast cancer trial drugs”—traverses 6 hops across both KGs and returns in 2.1 seconds. Label distribution over the full 7.9M-node graph takes 7.8 seconds (full scan). Individual KG queries execute in under 1.5 seconds.

7.3 Federation Correctness

We validated cross-KG federation on the Mac Mini M4 with the following results:

1. **Bridge construction:** 32 breast cancer drug nodes were created from a curated DrugBank mapping, yielding 36 TARGETS edges (Drug → Protein) and 199 CODED_AS_DRUG edges (Intervention → Drug). The 1,544 matched drug interventions span 5,338 distinct drug names in breast cancer trials.
2. **Join overlap:** 37,990 Protein nodes with uniprot_id from the Pathways KG are available for joining. Of the 36 drug-target proteins, all are present in the Pathways KG’s protein-protein interaction network.
3. **Federation query result:** The 6-hop query “pathways disrupted by breast cancer trial drugs” returns 10 pathways, with *Disease* (21 drugs), *Signal Transduction* (19 drugs), *Immune System* (12 drugs), and *Cell Cycle* (12 drugs) as the top results. These align with known breast cancer biology: HER2 signaling (Trastuzumab), CDK4/6 cell cycle control (Palbociclib, Ribociclib), and immune checkpoint blockade (Pembrolizumab, Atezolizumab).

8 Interactive Visualization

Samyama Insight, a React-based frontend, provides schema-driven visualization of each KG:

- **Dashboard:** Auto-generated panels showing label distribution, edge type counts, and property statistics per tenant.

- **Query Console:** OpenCypher editor with result tables, JSON views, and EXPLAIN/PROFILE plan visualization.
- **Graph Simulation:** Force-directed canvas with per-label colors/shapes, live activity particles, entity filtering, and a legend overlay. The simulation engine is fully schema-driven—it auto-configures from the tenant’s schema at runtime.

Demo recordings for both KGs are available as MP4 videos².

9 Discussion

9.1 Property Joins vs. Entity Merging

Our federation approach uses property-based joins rather than merging entities at load time. This has trade-offs:

- **Advantages:** Snapshots remain independent and composable; no load-order dependency; straightforward to add or remove a KG from the federation.
- **Disadvantages:** Duplicate nodes inflate storage; property joins are slower than traversals on merged nodes; no referential integrity between the two copies of a Protein.

For production workloads, a post-load **MERGE** pass or ETL-time deduplication would eliminate duplicates. For exploration and prototyping—the primary use case for these KGs—property joins are pragmatic.

9.2 Limitations

1. **Snapshot currency:** Snapshots are point-in-time exports. Source databases (especially ClinicalTrials.gov) update continuously. Periodic re-export is required.
2. **Identifier coverage:** Not all proteins in the Clinical Trials KG have UniProt IDs (some have only gene symbols). The join overlap depends on identifier normalization quality.
3. **Memory requirements:** The combined 7.8M-node graph requires approximately 8GB RAM. Machines with less memory can load the Pathways KG alone (119K nodes, <500MB).
4. **No cross-tenant queries:** Currently, federation requires loading both snapshots into a single tenant. Native cross-tenant query support is planned for a future Samyama release.

9.3 Generalizability

The pattern is not limited to biomedicine. Any domain with shared identifiers across data sources can use the same approach: build independent KGs with common entity properties, export as snapshots, load into a single tenant, and query across them. We have applied this pattern to sports (Cricket KG, 36K nodes) and industrial operations (AssetOps KG, 781 nodes) in addition to the biomedical KGs described here.

²Cricket KG demo: <https://github.com/samyama-ai/samyama-graph/releases/tag/kg-snapshots-v2>; Pathways KG demo: <https://github.com/samyama-ai/samyama-graph/releases/tag/kg-snapshots-v3>

10 Conclusion

We presented two open-source biomedical knowledge graphs—Pathways KG and Clinical Trials KG—built on Samyama Graph Database. Together they contain 7.89 million nodes and 27.8 million edges from 10 public data sources. We demonstrated that loading both snapshots into a single graph tenant, combined with a targeted drug-target enrichment step (32 drugs, 36 TARGETS edges), enables cross-KG federated queries that bridge molecular biology and translational medicine. The 6-hop query “pathways disrupted by Phase 3 breast cancer drugs” returns biologically validated results—Signal Transduction, Immune System, Cell Cycle—in 2.1 seconds on commodity hardware. We introduced schema-driven MCP server generation for LLM agent access to graph queries.

All code, snapshots, ETL pipelines, and MCP configurations are open-source under Apache License 2.0. Researchers can reproduce the federation—from snapshot import to cross-KG queries—in under 2 minutes on commodity hardware.

Data and Code Availability

- Pathways KG: <https://github.com/samyama-ai/pathways-kg>
- Clinical Trials KG: <https://github.com/samyama-ai/clinicaltrials-kg>
- Samyama Graph Database: <https://github.com/samyama-ai/samyama-graph>
- Snapshots: <https://github.com/samyama-ai/samyama-graph/releases>
- Samyama Graph Book: <https://samyama-ai.github.io/samyama-graph-book/>

References

- Anthropic. Model context protocol. <https://modelcontextprotocol.io/>, 2024.
- Alison Callahan, José Cruz-Toledo, Peter Ansell, and Michel Dumontier. Bio2RDF: towards a mashup to build bioinformatics knowledge systems. *Journal of Biomedical Informatics*, 46(4): 706–720, 2013.
- Payal Chandak, Kexin Huang, and Marinka Zitnik. Building a knowledge graph to enable precision medicine. *Scientific Data*, 10(1):67, 2023.
- Daniel Scott Himmelstein, Antoine Lizee, Christine Hessler, Leo Brueggeman, Sabrina L Chen, Dexter Hadley, Ari Green, Pouya Khankhanian, and Sergio E Baranzini. Systematic integration of biomedical knowledge prioritizes drugs for repurposing. *eLife*, 6:e26726, 2017.
- Aidan Hogan, Eva Blomqvist, Michael Cochez, Claudia d’Amato, Gerard de Melo, Claudio Gutierrez, Sabrina Kirrane, José Emilio Labra Gayo, Roberto Navigli, Sebastian Neumaier, et al. Knowledge graphs. *ACM Computing Surveys*, 54(4):1–37, 2021.
- Madhulatha Mandarapu and Sandeep Kunkunuru. Samyama: A unified graph-vector database with in-database optimization, agentic enrichment, and hardware acceleration. *arXiv preprint*, 2026.
- Neo4j, Inc. Neo4j graph database. <https://neo4j.com/>, 2024.
- Alberto Santos, Sofia Müller-Dott, Julio Saez-Rodriguez, and Gary D Bader. A knowledge graph to interpret clinical proteomics data. *Nature Biotechnology*, 40(3):333–340, 2022.