

Knowledge Graphs as the Missing Data Layer for LLM-Based Industrial Asset Operations

Madhulatha Mandarapu* Sandeep Kunkunuru†

VaidhyaMegha Private Limited, India

<https://samyama.ai/>

March 2026

Abstract

LLM-based agents for industrial asset operations show promise but achieve limited accuracy when reasoning over flat document stores. The AssetOpsBench benchmark [Patel et al., 2025] establishes that GPT-4 agents achieve 65% success on 139 industrial maintenance scenarios backed by CouchDB, YAML, and CSV data sources. AssetOpsBench evaluates LLM agent autonomy; we ask a complementary question: *how much does the data model behind the tools affect agent performance?*

Building on the same benchmark data and scenarios, we introduce a knowledge graph layer (781 nodes, 955 edges, 16 relationship types) and evaluate three architectures of increasing LLM involvement: (1) deterministic graph handlers with no LLM, achieving 99% (137/139); (2) LLM-generated Cypher queries against the graph, achieving 83% (115/139); and (3) the original tool-augmented LLM baseline at 65% (91/139).

Our key finding is **inverted LLM usage**: instead of asking the LLM to reason over raw data (a broad, error-prone task), we ask it to generate structured queries from a typed schema—a narrow problem that plays to LLM strengths. The graph then executes deterministically. We additionally contribute 40 new graph-native evaluation scenarios covering multi-hop dependency analysis, vector similarity search, and PageRank-based criticality ranking, on which the knowledge graph scores 100% versus GPT-4o’s 85%. We further evaluate against the full expanded AssetOpsBench suite of 467 scenarios released on HuggingFace (ibm-research/AssetOpsBench), spanning 6 operational domains including monitoring rules, failure-mode-sensor recommendation, and prognostics. Using an expanded graph (1,360 nodes, 14 labels, 21 edge types), deterministic handlers achieve 100% (467/467) with an average score of 0.848—demonstrating that the knowledge graph approach scales to the complete benchmark without degradation.

These results suggest that for structured operational domains, the data model—not the LLM—is the primary bottleneck, and that knowledge graphs can serve as an integration layer between raw industrial data and LLM-based reasoning.

Keywords: Knowledge Graphs, Large Language Models, Industrial Asset Operations, Benchmark, OpenCypher, Vector Search, Graph Algorithms.

1 Introduction

Industrial asset management generates vast quantities of structured data: sensor telemetry, work orders, failure mode analyses, equipment hierarchies, and maintenance schedules. The rise of Large

*madhulatha@samyama.ai, ORCID: <https://orcid.org/0009-0005-2837-6725>

†sandeep@samyama.ai, ORCID: <https://orcid.org/0000-0002-8886-1846>

Language Models (LLMs) [OpenAI, 2023] has prompted efforts to build autonomous agents that can reason over this data—answering operational questions, predicting failures, and recommending maintenance actions.

AssetOpsBench [Patel et al., 2025] provides the first systematic evaluation of such agents, benchmarking GPT-4 across 139 industrial maintenance scenarios spanning five agent types: IoT telemetry, failure mode and symptom reasoning (FMSR), work order management, time-series foundation model queries, and multi-agent coordination. The benchmark architecture follows the now-standard tool-augmented LLM pattern [Schick et al., 2023, Yao et al., 2023]: the LLM parses user intent, selects the appropriate tool, formulates arguments, retrieves data from document stores (CouchDB [Anderson et al., 2010], YAML, CSV), and synthesizes an answer. GPT-4 achieves 65% on this benchmark.

AssetOpsBench was designed to evaluate LLM agent autonomy—a valuable research question. We ask a *complementary* question: how much does the data model behind the tools affect agent performance? Examining the benchmark’s failure cases, we observe that many are not failures of reasoning but failures of *data access*: hallucinated equipment identifiers, miscounted events across documents, inability to traverse equipment dependencies, and fabricated sensor readings. These are symptoms of asking an LLM to perform *data operations*—counting, joining, traversing—that structured query engines handle deterministically.

This observation motivates our central hypothesis: **for structured operational domains, the data model is the primary bottleneck.** Introducing a knowledge graph [Hogan et al., 2021] as the data layer should improve accuracy at every level of LLM involvement.

Contributions.

1. **Three-tier evaluation** of the same 139 AssetOpsBench scenarios under three architectures: deterministic graph handlers (99%), LLM-generated Cypher over the graph (83%), and the original tool-augmented LLM baseline (65%). This isolates the data model as the key variable (§5).
2. **Inverted LLM usage pattern**: we show that constraining the LLM to query generation from a typed schema—rather than free-form data reasoning—yields an 18 percentage point improvement over reasoning over raw documents (§4.2).
3. **Knowledge graph construction**: a complete ETL pipeline transforming the AssetOpsBench data sources into an 11-label, 16-edge-type graph with 384-dimensional failure mode embeddings and equipment dependency topology (§3).
4. **40 new graph-native scenarios** extending the benchmark with multi-hop dependency analysis, vector similarity search, PageRank criticality, cascade analysis, maintenance optimization, and temporal patterns—capabilities structurally impossible with flat document stores (§5.4).
5. **Expanded 467-scenario evaluation** against the full HuggingFace AssetOpsBench release (6 domains, 26 equipment types), achieving 100% pass rate with 0.848 average score using an extended knowledge graph (§5.5).
6. **Scalability analysis** comparing operational cost, latency, and capability at scale across the three architectures (§8).

Table 1: Expanded AssetOpsBench scenario distribution (HuggingFace release).

Config	Domain	Count
scenarios	IoT, FMSA, TSFM, WO, multi-agent (original)	152
rule_logic	Monitoring rules & anomaly detection	120
FMSR	Failure mode–sensor recommendation	88
PHM	Prognostics, RUL, fault classification	75
hydraulic_pump	Hydraulic pump condition detection	17
compressor	Compressor predictive maintenance	15
Total		467

2 Background: AssetOpsBench

AssetOpsBench [Patel et al., 2025] is a benchmark for evaluating LLM agent autonomy on industrial maintenance tasks. The evaluation measures whether an LLM can autonomously navigate a set of tools to answer operational questions. The benchmark comprises 467 scenarios across six operational domains (Table 1).

The benchmark architecture follows a ReAct-style [Yao et al., 2023] loop: the user poses a natural language question; the LLM parses intent, selects which agent to invoke, formulates tool arguments, retrieves data from CouchDB/YAML/CSV, interprets the results, and synthesizes an answer. The data sources are document-oriented: JSON documents in CouchDB, YAML configuration files for failure modes, and CSV exports for events and work orders. This is a natural design choice for the benchmark’s purpose of evaluating LLM autonomy—the flat data model places the full reasoning burden on the agent, which is precisely what AssetOpsBench aims to measure.

GPT-4 achieves approximately 65% (91/139) on these scenarios [Patel et al., 2025]. The failures cluster around tasks requiring counting across documents, correlating data from multiple sources, and traversing implicit equipment relationships—operations that are inherently difficult for LLMs to perform over unstructured document collections.

3 Knowledge Graph Construction

We transform the AssetOpsBench data sources into a typed knowledge graph using an 8-step ETL pipeline. The resulting graph contains 1,360 nodes across 14 labels, connected by approximately 2,500 edges across 21 relationship types (Table 2).

3.1 Data Sources and ETL

The ETL pipeline processes four AssetOpsBench data sources into graph structure:

1. **EAMLite** (Enterprise Asset Management): Provides the equipment hierarchy. We create 1 Site, 4 Locations (Mechanical, Electrical, HVAC, Utility), and 11 Equipment nodes (chillers with CWC04xxx identifiers), linked by CONTAINS_LOCATION and CONTAINS_EQUIPMENT edges. Equipment nodes carry ISA-95 [ISA, 2010] level classification and ISO 14224 [ISO, 2016] asset class properties.
2. **CouchDB JSON**: Contains sensor metadata. We create 110 Sensor nodes (10 per chiller) with type, unit, and range properties, linked to Equipment via HAS_SENSOR edges.

Table 2: Knowledge graph schema: 14 node labels, 21 edge types.

Node Labels	Site, Location, Equipment, Sensor, FailureMode, WorkOrder, SparePart, Supplier, SensorReading, Anomaly, Event, MonitoringRule, PHMScenario, HFS-scenario	
Edge Types	CONTAINS_LOCATION, CONTAINS_EQUIPMENT, HAS_SENSOR, MONITORS, EXPERIENCED, DEPENDS_ON, SHARES_SYSTEM_WITH, FOR_EQUIPMENT, ADDRESSES, USES_PART, SUPPLIED_BY, PRODUCED_READING, DETECTED_ANOMALY, TRIGGERED, FOLLOWS_PLAN, HAS_RULE, HAS_PHM_SCENARIO, TARGETS_EQUIPMENT, INVOLVES_FAILURE_MODE, TESTS_RULE	

3. **FMSR YAML**: Defines 12 failure modes (e.g., “Compressor Overheating”, “Refrigerant Leak”). Each becomes a FailureMode node with a 384-dimensional embedding generated by Sentence-BERT [Reimers and Gurevych, 2019], indexed in an HNSW [Malkov and Yashunin, 2020] vector index for similarity search. MONITORS edges connect sensors to the failure modes they detect.
4. **Event CSV**: Contains 6,256 unified events (work orders, alerts, anomalies) with ISO timestamps. We create Event nodes linked to Equipment via FOR_EQUIPMENT edges, enabling temporal queries and event counting.

3.2 Dependency Topology

Beyond the data directly present in the benchmark sources, we add an equipment dependency layer: DEPENDS_ON edges model thermal/electrical dependencies (e.g., AHU depends on Chiller for cooling), and SHARES_SYSTEM_WITH edges model shared infrastructure (e.g., chillers on the same cooling loop). This topology enables cascade analysis and criticality ranking—capabilities absent from the flat data model.

3.3 Implementation

The knowledge graph is built using Samyama, an embedded graph database with OpenCypher [Francis et al., 2018] query support, HNSW vector indexing, and graph algorithm libraries including PageRank [Page et al., 1999] and NSGA-II [Deb et al., 2002] multi-objective optimization. The Python SDK enables the graph to be created in-process with no external server dependencies.

4 Three Architectures for LLM-Assisted Industrial Operations

We evaluate three architectures that vary in LLM involvement, holding the underlying data constant.

4.1 Architecture A: Tool-Augmented LLM (AssetOpsBench Baseline)

Question → LLM parses intent → LLM selects tool → LLM formulates arguments → Tool queries document store → LLM interprets raw results → LLM synthesizes answer

The LLM handles five distinct subtasks: intent parsing, tool selection, argument crafting, data interpretation, and answer synthesis. The data sources are document stores with no typed schema or relationship structure. This is the baseline architecture established by AssetOpsBench; GPT-4 achieves 65%.

4.2 Architecture B: LLM Generates Queries (NLQ + Graph)

Question → LLM generates Cypher query (given schema) → Graph executes deterministically → LLM synthesizes answer from structured results

We **invert** the LLM’s role: instead of asking it to reason over raw data (a broad problem), we ask it to generate a structured query from a typed schema (a narrow problem). This is *code generation*—a task LLMs excel at. The graph engine then handles traversal, counting, aggregation, and relationship reasoning deterministically. The LLM does one thing well instead of five things poorly.

The NLQ pipeline provides the graph schema (node labels, edge types, property names with example values) and few-shot Cypher examples. If query execution fails, the error message is fed back for one retry. The LLM then synthesizes a natural language answer from the structured query results.

4.3 Architecture C: Deterministic Handlers (No LLM)

Question → Keyword routing → Cypher query on graph → Structured response

Pre-coded handlers match question patterns to Cypher queries. No LLM is involved. This is a software engineering solution: we wrote the answers. It demonstrates the ceiling achievable with the right data model for known query patterns.

4.4 The Inverted LLM Pattern

The key insight connecting Architectures A and B is what we term **inverted LLM usage**. Both use an LLM, but they pose fundamentally different problems:

- **Architecture A** asks: “LLM, answer this question from this data.” The LLM must count across documents, correlate fields from different sources, and traverse implicit relationships—tasks where LLMs consistently struggle.
- **Architecture B** asks: “LLM, given this schema, write me a Cypher query.” The LLM performs code generation from a structured specification—a task where LLMs consistently excel.

The same LLM, given a sharper problem scoped to its strengths, produces dramatically better results. This pattern generalizes beyond industrial operations: **schema-aware query generation outperforms free-form data reasoning** for any structured domain.

5 Evaluation

5.1 AssetOpsBench 139 Scenarios: Three-Tier Results

Table 3 presents the primary comparison across all three architectures on the original 139 AssetOpsBench scenarios.

Table 3: Three-tier performance on the 139 AssetOpsBench scenarios.

Architecture	LLM Role	Data Layer	Pass Rate	Avg Lat
A: Baseline	Does everything	Document stores (CouchDB/YAML/CSV)	91/139 (65%)	not rep
B: NLQ + graph	Generates Cypher	Knowledge graph	115/139 (83%)	5,8
C: Deterministic	None	Knowledge graph	137/139 (99%)	6

Table 4: Per-type breakdown: Deterministic handlers vs. NLQ (GPT-4o).

Type	Det. Pass	Det. Avg	NLQ Pass	NLQ Avg
IoT (20)	20/20 (100%)	0.988	17/20 (85%)	0.742
FMSR (40)	40/40 (100%)	0.907	37/40 (93%)	0.880
TSFM (23)	23/23 (100%)	0.920	21/23 (91%)	0.936
Multi (20)	20/20 (100%)	0.877	8/20 (40%)	0.605
WO (36)	34/36 (94%)	0.801	32/36 (89%)	0.723
Total (139)	137/139 (99%)	0.889	115/139 (83%)	0.789

Model caveat. The baseline used GPT-4; our NLQ benchmark used GPT-4o (a more capable model released later). The +18 percentage point gap between NLQ (83%) and the baseline (65%) is therefore an *upper bound* on the graph’s contribution—part of the improvement may stem from the stronger LLM. A GPT-4 NLQ run is in progress to isolate the graph’s effect.

5.2 Per-Type Breakdown

Table 4 shows performance by scenario type for both the deterministic and NLQ architectures.

NLQ failure analysis. Multi-agent scenarios remain at 40% for NLQ because 12 of 20 require TSFM pipeline execution (time-series forecasting, anomaly detection) that cannot be expressed as Cypher queries. This is a structural limitation: these scenarios require running ML inference, not querying stored data. The deterministic architecture handles them by routing to domain-knowledge handlers.

Deterministic failures. Only 2 of 139 scenarios fail: both are work order bundling edge cases (IDs 411, 424) where the benchmark’s expected answer groups work orders into specific bundle sizes. Our date-window clustering produces different groupings. These are response-format mismatches, not knowledge gaps.

5.3 NLQ Progression

The NLQ architecture improved across three iterations of prompt engineering (Table 5), demonstrating that the quality of the schema description provided to the LLM matters as much as the underlying data model.

A striking example: in v1, FMSR scenarios scored 30% because the schema introspection returned node metadata (`['id', 'labels', 'properties']`) instead of actual property names, causing the LLM to generate `fm.properties` instead of `fm.name`. Correcting the schema prompt alone raised FMSR to 93%. The LLM was capable; it was given the wrong specification.

Table 5: NLQ prompt engineering progression.

Version	Key Changes	Pass Rate	Avg Score
NLQ v1	Naive prompt, schema introspection	77/139 (55%)	0.583
NLQ v2	Few-shot examples, explicit property schema, retry on error	108/139 (78%)	0.755
NLQ v3	Actual property values, anomaly schema, Cypher-first constraint	115/139 (83%)	0.789

Table 6: 40 custom graph-native scenarios by category.

Category	Count	Example Query
Multi-hop dependency	8	“What equipment is affected if Chiller 6 fails?”
Cross-asset correlation	6	“Are AHU anomalies correlated with chiller temperature drops?”
Failure similarity	6	“Which pumps had failures similar to Motor 3?”
Criticality analysis	5	“Rank all equipment by operational criticality”
Maintenance optimization	5	“Schedule maintenance minimizing downtime + cost”
Root cause analysis	5	“Trace events leading to WO-2024-0042”
Temporal pattern	5	“What is MTBF for Chiller 6’s compressor?”

5.4 Custom 40 Scenarios: Graph-Native Capabilities

We designed 40 additional scenarios that extend the benchmark’s scope to queries requiring graph structure, vector search, or graph algorithms—capabilities structurally impossible with flat document stores (Table 6).

Table 7 shows the head-to-head comparison. We use an 8-dimensional scoring framework covering correctness, completeness, relevance, tool usage, efficiency, safety, graph utilization, and semantic precision, with category-specific weight overrides (e.g., semantic precision is weighted 0.25 for failure similarity scenarios).

The largest gains occur on **failure similarity** (+0.401) and **criticality analysis** (+0.372)—precisely where graph structure (dependency edges) and vector search (failure mode embeddings) provide capabilities that LLMs fundamentally cannot replicate from parametric knowledge alone.

GPT-4o’s 6 failures (scenarios requiring PageRank, BFS traversal, or vector similarity) demonstrate a hard capability boundary: no amount of prompt engineering enables an LLM to execute graph algorithms.

5.5 Expanded HuggingFace Benchmark: 467 Scenarios

Following the release of an expanded AssetOpsBench dataset on HuggingFace [Patel et al., 2025], we evaluate our knowledge graph approach against all 467 scenarios spanning six operational domains. This represents a $3.4\times$ expansion over the original 139-scenario benchmark, adding monitoring rule evaluation, failure-mode-sensor recommendation across 10 equipment types (electric motor, pump, compressor, turbine, etc.), and prognostics tasks including remaining useful life prediction and fault classification.

To support the expanded scenarios, we extend the knowledge graph with three new node types (MonitoringRule, PHMScenario, HFSScenario) and five new edge types, and add three new deterministic handlers: (1) a rule-logic handler that evaluates monitoring rules against sensor

Table 7: Custom 40 scenarios: Knowledge graph vs. GPT-4o baseline.

Metric	GPT-4o (no graph)	Samyama-KG
Pass rate	34/40 (85%)	40/40 (100%)
Avg score	0.602	0.927
Avg latency	11,259 ms	110 ms
Tokens/scenario	632	0

Table 8: Per-category breakdown on custom 40 scenarios.

Category	GPT-4o Avg	KG Avg	Δ
Failure similarity	0.501	0.902	+0.401
Criticality analysis	0.566	0.938	+0.372
Root cause analysis	0.580	0.934	+0.354
Multi-hop dependency	0.618	0.934	+0.316
Maintenance optimization	0.634	0.931	+0.297
Cross-asset correlation	0.638	0.929	+0.291
Temporal pattern	0.679	0.923	+0.244

readings, (2) an FMSR handler that maps failure modes to detectable sensors via graph traversal, and (3) a PHM handler that provides asset health profiles from failure history and maintenance records.

The rule-logic scenarios achieve the highest average score (0.949) because anomaly detection against threshold rules is a pure graph operation: the monitoring rules are stored as nodes with threshold properties, sensor readings are evaluated against these thresholds, and anomalies are detected deterministically. The PHM scenarios score lower (0.787) because prognostics tasks (RUL prediction, fault classification) require domain knowledge beyond what is stored in the graph—the graph provides asset context (failure history, MTBF, maintenance records) but the actual prediction requires analytical models.

Critically, the 100% pass rate on 467 scenarios demonstrates that the knowledge graph approach scales to the full benchmark without degradation. The expanded benchmark covers 26 equipment types across manufacturing, utilities, and transportation—a substantial increase over the original chiller-focused dataset.

6 Analysis

6.1 The Data Model Is the Bottleneck

The baseline agents do not fail because GPT-4 lacks reasoning ability. Rather, document stores make certain queries structurally hard or impossible for any LLM:

- **Counting across documents:** “How many events for CWC04009 in 2019?” requires the LLM to scan multiple JSON documents, parse dates, and aggregate—error-prone at scale. With a graph: `MATCH (e:Event) WHERE e.equipment_id = 'CWC04009' RETURN count(e)` executes deterministically.
- **Relationship traversal:** “Which sensors monitor overheating?” is one edge hop in the graph: `(s:Sensor)-[:MONITORS]->(fm:FailureMode)`. With document stores, the LLM must correlate

Table 9: Expanded AssetOpsBench: 467 scenarios across 6 domains.

Config	Scenarios	Pass Rate	Avg Score
scenarios (original)	152	152/152 (100%)	0.781
rule_logic	120	120/120 (100%)	0.949
FMSR	88	88/88 (100%)	0.868
compressor	15	15/15 (100%)	0.877
hydraulic_pump	17	17/17 (100%)	0.885
PHM	75	75/75 (100%)	0.787
Total	467	467/467 (100%)	0.848

YAML failure definitions with CouchDB sensor metadata—a cross-source join with no explicit link.

- **Structurally impossible operations:** Multi-hop cascade analysis, vector similarity search, PageRank criticality, and Pareto-optimal scheduling have no equivalent on document stores regardless of LLM capability.

6.2 Why Constraining the LLM Helps

The 18pp improvement from Architecture A (65%) to Architecture B (83%) illustrates a broader principle: **LLMs perform better on narrow, well-specified generation tasks than on broad, open-ended reasoning tasks.**

- Asking “answer this question from this data” requires the LLM to simultaneously handle intent parsing, tool selection, data traversal, numerical reasoning, and answer synthesis. Each step introduces error probability.
- Asking “given this schema, write a Cypher query” is a translation task from natural language to a structured query language—fundamentally *code generation*, where LLMs have demonstrated strong performance across benchmarks.

The graph absorbs the hard parts (traversal, counting, joining, algorithms), leaving the LLM with the easy part (structured query generation from a specification). This separation of concerns is why both Architecture B (+18pp) and Architecture C (+34pp) outperform Architecture A.

6.3 Honest Caveats

1. **Deterministic vs. autonomous:** Architecture C’s 99% result compares a pre-coded solution against an autonomous agent. We wrote the answers; AssetOpsBench measures whether GPT-4 can figure them out independently. These are fundamentally different tasks—the comparison illustrates the ceiling achievable with the right data model, not a claim of superior agent intelligence.
2. **Model mismatch:** The baseline used GPT-4; our NLQ runs used GPT-4o. The +18pp gap is an upper bound on the graph’s contribution. A same-model comparison is in progress.
3. **Clean data assumption:** AssetOpsBench provides clean, structured data. Real industrial environments involve noisy sensors, scanned PDFs, legacy Excel files, and inconsistent naming—challenges addressed in §7.2.

4. **Custom scenarios:** Our 40 new scenarios are designed to extend the benchmark with graph-native capabilities. They are complementary to, not replacements for, the original AssetOpsBench scenarios.
5. **Different research questions:** AssetOpsBench evaluates LLM agent autonomy—whether an LLM can independently navigate tools and data. We evaluate data model impact—whether a different data layer improves agent performance. Both are valid research questions; our results do not diminish the value of the original benchmark.

7 The Full Pipeline: Where LLMs Belong

The three-architecture comparison in §5 focuses on the *query layer*—the final stage of a multi-layer data pipeline. To place our results in context, we examine the full pipeline and identify where LLMs provide genuine value.

7.1 Three Layers of Industrial Data

1. **Data Ingestion** (software engineering): Raw sensor telemetry, CMMS exports, work order records, and equipment registries are loaded into the database via deterministic ETL pipelines. For structured data (90%+ of industrial data), this is pure software engineering: `pandas.read_csv()` → Cypher `CREATE` statements. The AssetOpsBench pipeline is similarly deterministic—`couchdb_setup.sh` bulk-inserts JSON documents; EAMLite uses an SQLAlchemy ORM. No LLM is needed for structured ingestion regardless of the target data model.
2. **Data Model** (architecture decision): The choice between flat documents and a graph is a one-time design decision with compounding returns at the query layer. Both require comparable ETL effort; the graph requires explicit relationship typing but enables traversal, algorithms, and vector indexing.
3. **Query** (LLM optional): This is where the three architectures diverge. The data model determines what is possible at this layer.

7.2 The Real-World Caveat: Unstructured Data

AssetOpsBench uses clean, structured data. Real industrial environments are messier. Maintenance logs contain free text (“Replaced compressor bearings, noticed oil leak on unit 6—same issue as last month”). Equipment manuals arrive as scanned PDFs. Legacy spreadsheets use inconsistent column names across decades of records. Sensor data includes drift, stuck-at-zero readings, and calibration shifts.

For this unstructured data, deterministic ETL reaches its limits. LLMs provide genuine value at the *data preparation* layer:

- **Entity extraction:** “Replaced compressor bearings on Chiller 6” → (Equipment:CH06, Part:compressor_bearings, Action:replaced)
- **Relationship detection:** “Same issue as last month” → SIMILAR_TO edge to previous failure event
- **Entity resolution:** “CH06” = “Chiller-6” = “Chiller #6” → canonical identifier

Table 10: Scalability comparison across architectures.

Dimension	Arch. A (LLM + docs)	Arch. B/C (graph ± LLM)
10K queries/day	\$300–500 (tokens)	\$0 (deterministic) or ~\$30 (NLQ)
Real-time streaming	Not supported (request-response)	Graph updates + continuous queries
Multi-hop at 10K assets	LLM reasons across 10K docs	BFS traversal, $O(E)$
New query patterns	Prompt engineering	Add handler or use NLQ
Latency per query	5–11 s	63 ms (det.) / ~6 s (NLQ)

- **Classification:** Free-text maintenance log $\rightarrow$ category (preventive, corrective, emergency)

This yields a complete architecture we term **LLMs at the edges, graph in the middle**:

- **Input edge:** LLM-assisted data preparation transforms messy, unstructured data into structured graph elements (entity extraction, resolution, classification)
- **Center:** The knowledge graph stores clean, typed, connected data
- **Output edge:** LLM-assisted query generation translates natural language into Cypher (or deterministic handlers serve known patterns)

In both cases, the LLM performs a *generation task* (structured output from unstructured input)—its strength—while the graph handles *data operations* (storage, traversal, algorithms)—its strength. Neither component is asked to do what it is bad at.

8 Scalability Comparison

Table 10 compares the three architectures on operational dimensions relevant to production deployment.

The cost asymmetry is particularly relevant for industrial operations: sensor networks may generate thousands of queries per day (anomaly checks, threshold alerts, status polls). At \$0.03–0.05 per LLM query, a fully LLM-driven architecture costs \$300–500/day for 10K queries. Deterministic graph queries cost nothing after the initial ETL.

9 Related Work

LLM agents for tool use. The ReAct framework [Yao et al., 2023] and Toolformer [Schick et al., 2023] established the pattern of LLMs selecting and invoking external tools. AssetOpsBench [Patel et al., 2025] makes an important contribution by applying this pattern to industrial asset operations via the Model Context Protocol [Anthropic, 2024], providing the first standardized benchmark in this domain. Our work builds on AssetOpsBench by investigating a complementary dimension: the effect of the data layer behind the tools on agent performance.

Knowledge graphs and LLMs. Pan et al. [2024] survey approaches to combining LLMs with knowledge graphs, identifying three paradigms: KG-enhanced LLMs, LLM-enhanced KGs, and synergized architectures. Our inverted LLM pattern aligns with their “synergized” category—the KG provides structured data access, the LLM provides natural language understanding, and each system handles what it does best.

Graph RAG. Retrieval-Augmented Generation [Lewis et al., 2020] typically retrieves text passages for LLM context. Graph RAG [Edge et al., 2024] extends this to graph-structured retrieval, combining vector search with graph traversal. Our NLQ architecture goes further: rather than retrieving context for the LLM to reason over, we ask the LLM to *generate queries* that the graph executes—eliminating the context-window bottleneck and enabling exact aggregation.

Industrial knowledge graphs. Knowledge graphs have been applied to manufacturing [Hogan et al., 2021], but prior work focuses on knowledge representation rather than benchmarking LLM agent performance. To our knowledge, this is the first study comparing LLM-over-flat-documents against LLM-over-graph on a standardized industrial benchmark.

10 Conclusion

Building on the AssetOpsBench benchmark, we have shown that introducing a knowledge graph as the data layer improves LLM-based industrial operations at every level of LLM involvement: from 65% (LLM over document stores) to 83% (LLM generates queries over graph) to 99% (deterministic graph handlers). For structured operational domains, the data model is the primary bottleneck. When evaluated against the expanded 467-scenario HuggingFace release spanning six operational domains, deterministic graph handlers achieve 100% (467/467) with an average score of 0.848, demonstrating scalability beyond the original chiller-focused dataset.

The inverted LLM pattern—asking the LLM to generate structured queries rather than reason over raw data—is generalizable beyond industrial operations. For any structured domain with a typed schema, **schema-aware query generation outperforms free-form data reasoning**. LLMs excel at code generation from specifications; graphs excel at data traversal, aggregation, and algorithms. Each system should do what it is good at.

Contributions. (1) A three-tier evaluation isolating the data model as the key variable on the 139-scenario AssetOpsBench benchmark. (2) The inverted LLM usage pattern, demonstrating +18pp improvement by constraining the LLM to query generation. (3) A complete ETL pipeline and knowledge graph schema for industrial asset operations. (4) 40 new graph-native scenarios extending the benchmark with multi-hop, vector, and algorithmic capabilities. (5) An honest analysis of limitations including the model mismatch caveat and clean-data assumption.

Future work. A same-model (GPT-4) NLQ comparison to isolate the graph’s contribution from the model improvement; evaluation on larger industrial environments (10K+ assets, multi-site); joint NeurIPS 2026 Datasets & Benchmarks track submission with IBM Research; integration of LLM-assisted data preparation for unstructured maintenance logs; and a hybrid architecture that uses deterministic handlers for known patterns and NLQ for novel queries.

Availability. The benchmark code, ETL pipeline, and evaluation framework are available at <https://github.com/samyama-ai/assetops-kg>. The Samyama graph database is at <https://github.com/samyama-ai/samyama-graph>. The 40 new scenarios have been submitted to the AssetOpsBench repository as a community contribution.

References

- J. Chris Anderson, Jan Lehnardt, and Noah Slater. *CouchDB: The Definitive Guide*. O'Reilly Media, 2010.
- Anthropic. Model context protocol (MCP). Open Standard, 2024. URL <https://modelcontextprotocol.io/>.
- Kalyanmoy Deb, Amrit Pratap, Sameer Agarwal, and T. Meyarivan. A fast and elitist multiobjective genetic algorithm: NSGA-II. *IEEE Transactions on Evolutionary Computation*, 6(2):182–197, 2002.
- Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, Dasha Metropolitansky, Robert Osazuwa Ness, and Jonathan Larson. From local to global: A graph RAG approach to query-focused summarization. In *arXiv preprint arXiv:2404.16130*, 2024.
- Nadime Francis, Alastair Green, Paolo Guagliardo, Leonid Libkin, Tobias Lindaaker, Victor Marsault, Stefan Plantikow, Mats Rydberg, Petra Selmer, and Andrés Taylor. Cypher: An evolving query language for property graphs. In *Proceedings of the ACM SIGMOD International Conference on Management of Data*, pages 1433–1445, 2018.
- Aidan Hogan, Eva Blomqvist, Michael Cochez, Claudia d’Amato, Gerard de Melo, Claudio Gutierrez, Sabrina Kirrane, José Emilio Labra Gayo, Roberto Navigli, Sebastian Neumaier, et al. Knowledge graphs. *ACM Computing Surveys*, 54(4):1–37, 2021.
- ISA. ISA-95: Enterprise-control system integration. International Standard, 2010.
- ISO. ISO 14224:2016 — petroleum, petrochemical and natural gas industries — collection and exchange of reliability and maintenance data for equipment. International Standard, 2016.
- Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pages 9459–9474, 2020.
- Yu. A. Malkov and D. A. Yashunin. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 42(4):824–836, 2020.
- OpenAI. GPT-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.
- Lawrence Page, Sergey Brin, Rajeev Motwani, and Terry Winograd. The PageRank citation ranking: Bringing order to the web. Technical report, Stanford InfoLab, 1999.
- Shirui Pan, Linhao Luo, Yufei Wang, Chen Chen, Jiapu Wang, and Xindong Wu. Unifying large language models and knowledge graphs: A roadmap. *IEEE Transactions on Knowledge and Data Engineering*, 36(7):3580–3599, 2024.

- Dhaval Patel, Shuxin Lin, James Rayfield, Nianjun Zhou, Roman Vaculin, Natalia Martinez, Fearghal O’Donncha, and Jayant Kalagnanam. AssetOpsBench: Benchmarking AI agents for task automation in industrial asset operations and maintenance. *arXiv preprint arXiv:2506.03828*, 2025. URL <https://github.com/IBM/AssetOpsBench>. Published at NeurIPS 2025 and AAAI 2026. Expanded 467-scenario dataset at <https://huggingface.co/datasets/ibm-research/AssetOpsBench>.
- Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence embeddings using siamese BERT-networks. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 3982–3992, 2019.
- Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 36, 2023.
- Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*, 2023.