

P1: Security architecture and requirements

Notional small UAS · PDR-style brief

A PX4 flight controller, a Linux companion computer, a ground control station and a MAVLink C2 link, secured from threat model to verification plan.

github.com/samyoon727ca/uas-sec-p1-architecture · every number here is generated from the repo's checked data

1. System, mission and scope

Mission: generic survey/ISR. The vehicle flies a pre-planned pattern, collects EO imagery, streams video and returns.


Component	Basis
Flight controller (FC)	PX4 v1.18 on a Pixhawk-standard FMU
Companion computer (CC)	ARM64 Linux; WireGuard endpoint, MAVLink router, command filter
Ground control station (GCS)	QGroundControl v5.1.5 on a Linux laptop
Maintenance and support station (MSS)	Builds, signs and loads software; provisions keys
IP data-link radios	Untrusted transport (A-05)

Adversaries (A-08): RF-proximate with an SDR · physical access · supply chain.

Constraint (A-11): a security fault must lead to a safe flight state.

Out of scope: airworthiness, waveform and EW, RC link.

2. Architecture and trust boundaries



Every C2 path runs GCS → CC → FC (DD-01). Red outline: holders of the signing key. 46 elements in all.

TB-01 air-ground RF · TB-02 flight-critical / mission computing · TB-03 air-vehicle physical · TB-04 GCS host · TB-05 supply chain · TB-06 GNSS RF

3. Headline finding: one shared signing key

- PX4 MAVLink signing uses **one 32-byte key** on the FC, CC, GCS and MSS, enforced on every link including USB.
- **Any key holder can forge any command**, so the C2 trust base is four nodes.
- **The CC is the most exposed**. It terminates the RF link, runs general-purpose Linux and stays connected throughout flight.
- **Signing first ships in PX4 v1.18**. It is absent from v1.17.0 (checked in the source), so the baseline is v1.18 (DD-06). PX4's own docs say its signing implementation is unaudited.


Inputs to the threat model: CC compromise · no per-node attribution · the key file on the FC's SD card · the first-key provisioning window · the four messages PX4 accepts unsigned · GCS-loss detection that relies on unsigned heartbeats.

4. Threat model: 65 threats, STRIDE per element

- **Coverage:** 40 elements, using Microsoft's STRIDE-per-element chart, which the validator enforces.
- **Framework mapping:** EMB3D v2.0.2 (43 threats) and ATT&CK for ICS v19.2 (52). IDs are checked against pinned catalogs, so revoked IDs fail.
- **Impact, consequence only:** 41 MI-1 · 16 MI-2 · 6 MI-3 · 2 MI-4. 62 mitigated, 3 accepted with rationale.

Priority threat	Impact	Mitigated by
THR-010 Code execution on the CC yields full vehicle C2	MI-1	SR-001, SR-005, SR-008, SR-009
THR-001 Spoofed GCS heartbeats suppress the data-link-loss failsafe	MI-1	SR-001 (tested in VE-01)
THR-026/027 Key file on the FC's SD card read, replaced or deleted	MI-1	SR-023, SR-025, SR-036
THR-057 Unauthorized peer installs the first signing key	MI-2	SR-011, SR-025, SR-037
THR-021/063 Malicious code in signed artifacts	MI-1	SR-031, SR-032, SR-033

5. Design: C2 protected in three layers



Decision	What it does
DD-02 WireGuard between GCS and CC	Confidentiality over the untrusted link. Not FIPS-approved , so a DoD deployment would likely use IPsec with a validated module
DD-03 MAVLink over UART only at the FC–CC boundary	uXRCE-DDS disabled, because MAVLink signing does not cover it
DD-04 CC allowlist	Defense in depth, not authentication. Drops the shell, MAVLink FTP, <code>SETUP_SIGNING</code> and spoofable unsigned messages
DD-05 <code>NAV_DLL_ACT</code> = Return	PX4's default is Disabled. Jamming, tunnel loss and CC failure all appear as link loss

6. Requirements: 44 derived "shall" statements

- **Allocation:** CC 15 · MSS 13 · FC 9 · GCS 7.
- **Method:** Test 23 · Inspection 13 · Demonstration 8.
- **Traceability:** every requirement traces to a threat, is allocated to one component and is verifiable. CI enforces all three.

Example	Requirement
SR-001	The CC shall discard all traffic on its radio interface except WireGuard traffic from the provisioned GCS peer
SR-020	The FC shall run with the GNSS spoofing and jamming checks enabled (<code>EKF2_GPS_CHECK</code> bits 9 and 11). PX4's default leaves jamming off
SR-037	The MSS shall provision the first signing key on the FC over USB at first power-up, before any other link is connected

Resiliency (NIST SP 800-160 Vol. 2): 11 of 14 techniques, through 16 of 50 approaches. **Gap: Path Diversity.** No C2 path bypasses the CC (OI-03).

7. Verification: every requirement has a planned event

16 verification events cover all 44 requirements. Each event's method and evidence repo match its requirements, and the validator enforces that.

Repo	Builds	Requirements	Events
P2	Verified boot (CC and FC)	3	VE-07, VE-08
P3	Keys, signing, SITL harness	13	VE-01 to VE-06
P4	Hardened CC image, MSS pipeline, supply chain	14	VE-09 to VE-11
P5	Hardware and debug-port assessment	2	VE-12, VE-13
P6	RMF-as-code: configuration and procedure evidence	12	VE-14 to VE-16

- **VE-01:** a SITL test injects spoofed GCS heartbeats with the tunnel down. Its control run bypasses the CC to show the test can detect the threat.
- **VE-02:** signed C2 with QGroundControl v5.1.5 and PX4 v1.18. **Until it passes, end-to-end signing is design intent only.**

8. Rigor: a machine-checked digital thread

- **Five CSVs are the single source of truth:** elements, threats, requirements, trace and verification.
- **The CI validator fails the build** on an orphaned ID, an unresolved threat, a misapplied STRIDE category, an unknown EMB3D, ATT&CK or SP 800-160 entry, or a requirement without a matching verification event.
- **Generated, drift-checked views:** the doc tables and the SysML v2 threats, requirements and verification cases.
- **SysML v2 model** (architecture hand-written, security content generated) validates on the **OMG SysML v2 Pilot Implementation** in CI, headless, against a SHA-256-pinned release: 0 errors, 0 warnings.
- **Supply chain:** every GitHub Action is pinned by commit SHA, toolchains by lockfile or hash, and the validator uses the standard library only.

9. Residual risk and open items

Residual risk:

- **Shared signing key.** Mitigations make a key-holder compromise less likely and more evident, but don't change its consequence.
- **RF jamming** cannot be prevented within scope. Its effect is bounded to a Return.
- **GNSS spoofing that the receiver does not report** goes undetected.
- **Physical tampering** is detected (seals), not prevented.
- **Hardware supply-chain insertion** before receipt.

Open item	Closed by
OI-01 QGroundControl v5.1.5 ↔ PX4 v1.18 signing interoperability	VE-02 (P3)
OI-02 Per-node authentication to the FC (PX4 signing has one key for all nodes)	Trade study (P3)
OI-03 No independent C2 path (Path Diversity)	Later P1 revision

10. Next: P2–P6 produce the evidence

Order	Repo	First deliverable
1	P2 Verified boot	Signed boot chain and TPM-sealed keys on a dev board (VE-07); PX4 Bootloader Secure Boot (VE-08)
2	P3 PKI and signing	SITL harness; VE-01 and VE-02 close THR-001 and OI-01
3	P4 Supply chain	Hardened CC image, command filter, SBOM and provenance pipeline (VE-09 to VE-11)
4	P5 Hardware test	Seal and debug-port assessment on an owned device (VE-12, VE-13)
5	P6 RMF-as-code	OSCAL SSP with configuration evidence (VE-14 to VE-16)

Each repo opens the same way: **threat** → **requirement** → **design** → **verification evidence**, traced back to P1.