

EXP 8- First Fit Contiguous Memory Allocation

[Back To Practice](#)

Completed

First Fit Contiguous Memory Allocation

Write a C program to implement the First Fit contiguous memory allocation technique. The program should take the sizes of various memory blocks and the sizes of processes as input. For each process, search through the memory blocks sequentially and allocate the first block that meets the size requirement. If no such block exists, indicate that the process cannot be allocated. Finally, display the allocation details and calculate internal fragmentation.

Input Format

1. The first line contains an integer m representing the number of memory blocks.
2. The next line contains m integers representing the sizes of each memory block.
3. The next line contains an integer n representing the number of processes.
4. The next line contains n integers representing the sizes of each process.

Output Format

- For each process, the program prints whether the process is

Select Language: C (GCC 9.2.0)

```
1 #include <stdio.h>
2
3 int main() {
4     int m, n;
5
6     printf("Enter number of memory blocks:\n");
7     scanf("%d", &m);
8
9     int blockSize[m], originalBlockSize[m];
10
11     printf("Enter size of each block:\n");
12     for(int i = 0; i < m; i++) {
13         scanf("%d", &blockSize[i]);
14         originalBlockSize[i] = blockSize[i]; // store original
15     }
16
17     printf("Enter number of processes:\n");
18     scanf("%d", &n);
19
20     int processSize[n];
21
22     printf("Enter size of each process:\n");
23     for(int i = 0; i < n; i++) {
24         scanf("%d", &processSize[i]);
```

[Test Cases](#) [Run Sample Cases](#) [Run All Cases](#)

Select Language: C (GCC 9.2.0)

```
25 }
26
27 // First Fit with splitting
28 for(int i = 0; i < n; i++) {
29     int allocated = 0;
30
31     for(int j = 0; j < m; j++) {
32         if(blockSize[j] >= processSize[i]) {
33
34             int fragment = blockSize[j] - processSize[i];
35
36             printf("Process %d of size %d is allocated to Block %d of size %d with Fragment %d\n",
37                 i + 1, processSize[i], j + 1, originalBlockSize[j], fragment);
38
39             // Update remaining size
40             blockSize[j] = fragment;
41
42             allocated = 1;
43             break;
44         }
45     }
46
47     if(allocated == 0) {
48         printf("Process %d of size %d is not allocated\n",
49             i + 1, processSize[i]);
```

Select Language: C (GCC 9.2.0)

```
31     for(int j = 0; j < m; j++) {
32         if(blockSize[j] >= processSize[i]) {
33
34             int fragment = blockSize[j] - processSize[i];
35
36             printf("Process %d of size %d is allocated to Block %d of size %d with Fragment %d\n",
37                 i + 1, processSize[i], j + 1, originalBlockSize[j], fragment);
38
39             // Update remaining size
40             blockSize[j] = fragment;
41
42             allocated = 1;
43             break;
44         }
45     }
46
47     if(allocated == 0) {
48         printf("Process %d of size %d is not allocated\n",
49             i + 1, processSize[i]);
50     }
51 }
52
53 return 0;
54 }
```

```
5
100 500 200 300 600
4
212 417 112 426
```

```
Enter number of memory blocks:
Enter size of each block:
Enter number of processes:
Enter size of each process:
Process 1 of size 212 is allocated to Block 2 of size 500
with Fragment 288
Process 2 of size 417 is allocated to Block 5 of size 600
with Fragment 183
Process 3 of size 112 is allocated to Block 2 of size 500
with Fragment 176
Process 4 of size 426 is not allocated
```

Output:

```
Enter number of memory blocks:
Enter size of each block:
Enter number of processes:
Enter size of each process:
Process 1 of size 212 is allocated to Block 2 of size 500 with Fragment 288
Process 2 of size 417 is allocated to Block 5 of size 600 with Fragment 183
Process 3 of size 112 is allocated to Block 2 of size 500 with Fragment 176
Process 4 of size 426 is not allocated
```