

Question 1

Correct

Marked out of 3.00

Flag question

Objective

This is a simple challenge to help you practice printing to stdout.

We're starting out by printing the most famous computing phrase of all time! In the editor below, use either `printf` or `cout` to print the string *Hello, World!* to stdout.

Input Format

You do not need to read any input in this challenge.

Output Format

Print *Hello, World!* to stdout.

Sample Output

Hello, World!

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     printf("Hello, World!");
5     return 0;
6 }
7 }
```

Expected	Got
✓ Hello, World!	Hello, World! ✓

Passed all tests! ✓

Question 2

Correct

Marked out of 5.00

Flag question

Objective

This challenge will help you to learn how to take a character, a string and a sentence as input in C.

To take a single character `ch` as input, you can use `scanf("%c", &ch);` and `printf("%c", ch)` writes a character specified by the argument `char` to stdout.

Char `ch`:

```
scanf("%c", &ch);
printf("%c", ch);
```

This piece of code prints the character `ch`.

Task

You have to print the character, `ch`.

Input Format

Take a character, `ch` as input.

Output Format

Print the character, `ch`.

Answer: (Penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     char ch;
5     scanf("%c", &ch);
6     printf("%c", ch);
7     return 0;
8 }
```

	Input	Expected	Got	
✓	c	c	c	✓

Passed all tests! ✓

Sample Input

10 4
4.0 2.0

Sample Output

14 6
6.0 2.0

Explanation

When we sum the integers **10** and **4**, we get the integer **14**. When we subtract the second number **4** from the first number **10** we get **6** as their difference.
When we sum the floating-point numbers **4.0** and **2.0**, we get **6.0**. When we subtract the second number **2.0** from the first number **4.0**, we get **2.0** as their difference.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,d;
5     float e,f,g,h;
6     scanf("%d %d",&a,&b);
7     scanf("%f %f",&e,&f);
8     c=a+b;
9     d=a-b;
10    g=e+f;
11    h=e-f;
12    printf("%d %d",c,d);
13    printf("\n\n");
14    printf("%f %f",g,h);
15 }
```

	Input	Expected	Got	
✓	10 4 4.0 2.0	14 6 6.0 2.0	14 6 6.0 2.0	✓
✓	20 8	28 12	28 12	✓

Sample Input 1:

A
3 4 6

Sample Output 1:

A
4

Sample Input 2:

T
7 3 8

Sample Output 2:

T
6

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int a,b,c,e;
5     char d;
6     scanf("%c",&d);
7     scanf("%d %d %d",&a,&b,&c);
8     e=(a+b+c)/3;
9     printf("%c",d);
10    printf("\n%d",e);
11    return 0;
12 }
13
```

	Input	Expected	Got	
✓	A 3 4 6	A 4	A 4	✓
✓	T 7 3 8	T 6	T 6	✓
✓	A 8 200 99	A 60	A 60	✓

```
printf("format_specifier", val)
```

For example, to print a character followed by a double:

```
char ch = 'd';  
double d = 234.432;  
printf("%c %lf", ch, d);
```

Note: You can also use *cin* and *cout* instead of *scanf* and *printf*, however, if you are taking a million numbers as input and printing a million lines, it is faster to use *scanf* and *printf*.

Input Format

Input consists of the following space-separated values: *int*, *long*, *char*, *float*, and *double*, respectively.

Output Format

Print each element on a new line in the same order it was received as input. Note that the floating point value should be correct up to 3 decimal places and the double to 9 decimal places.

Sample Input

3 12345678912345 a 334.23 14049.30493

Sample Output

3
12345678912345
a
334.230
14049.304930000

Explanation

Print *int* 3,
followed by *long* 12345678912345,
followed by *char* a,
followed by *float* 334.23,
followed by *double* 14049.30493.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>  
2 int main()  
3 {  
4     int a;  
5     long b;  
6     char c;  
7     float d;  
8     double e;  
9     scanf("%d %ld %c %f %lf",&a,&b,&c,&d,&e);  
10    printf("%d\n%ld\n%c\n%.3f\n%.9lf",a,b,c,d,e);  
11    return 0;  
12 }
```

printf format specifier

For example, to print a character followed by a double:

char ch = 'd';

double d = 234.432;

printf("%c %lf", ch, d);

Note: You can also use cin and cout instead of scanf and printf, however, if you are taking a million numbers as input and printing a million lines, it is faster to use scanf and printf.

Input Format

Input consists of the following space-separated values: int, long, char, float, and double, respectively.

Output Format

Print each element on a new line in the same order it was received as input. Note that the floating point value should be correct up to 3 decimal places and the double to 9 decimal places.

Sample Input

3 12345678912345 a 334.23 14049.30493

Sample Output

3

12345678912345

a

334.230

14049.304930000

Explanation

Print int 3,

followed by long 12345678912345,

followed by char a,

followed by float 334.23,

followed by double 14049.30493.

	Input	Expected	Got	
✓	3 12345678912345 a 334.23 14049.30493	3 12345678912345 a 334.230 14049.304930000	3 12345678912345 a 334.230 14049.304930000	✓

Passed all tests! ✓

Sc

Au

Write a program to print the ASCII value and the two adjacent characters of the given character.

Input

E

Output

69

D F

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     char a,b,c;
5     scanf("%c",&a);
6     b=a-1;
7     c=a+1;
8     printf("%d",a);
9     printf("\n%c %c",b,c);
10    return 0;
11 }
```

	Input	Expected	Got	
✓	E	69 D F	69 D F	✓

Passed all tests! ✓

The program must accept a positive integer N and print the digit in the tenth position.

Input Format:

The first line denotes the value of N.

Output Format:

The first line contains the value of N.

Boundary Conditions:

10 <= N <= 9999999

Example Input/Output 1:

Input:

20

Output:

2

Example Input/Output 2:

Input:

37843

Output:

4

Answer: (penalty regime: 0 %)

```
1. #include<stdio.h>
2. int main()
3. {
4.     int x,d,a;
5.     scanf("%d",&x);
6.     a=x/10;
7.     d=a%10;
8.     printf("%d",d);
9.     return 0;
10 }
```

	Input	Expected	Got	
✓	20	2	2	✓
✓	37843	4	4	✓

Passed all tests! ✓

Write a C Program to calculates the area (floating point number with two decimal places) of a Circle given it's radius (integer value). The value of Pi is 3.14.

Sample Test Cases

Test Case 1

Input

7

Output

Area of a circle = 153.86

Test Case 2

Input

50

Output

Area of a circle = 7850.00

Test Case 3

Input

42

Output

Area of a circle = 5538.96

For example:

Input	Result
7	Area of a circle - 153.86
50	Area of a circle - 7850.00

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int r;
5     float a;
6     scanf("%d",&r);
7     a=3.14*r*r;
8     printf("Area of a circle = %.2f",a);
9     return 0;
10 }
11
12
```

	Input	Expected	Got	
✓	7	Area of a circle = 153.86	Area of a circle = 153.86	✓

Question 1

Content

Marked out of 100

Flag question

Develop a 'C' program to swap two numbers (using three variables).

Input

10 20

Output

Before swapping :

a = 10 b = 20

After swapping :

a = 20 b = 10

For example:

Input	Result
10 20	Before swapping : a = 10 b = 20 After swapping : a = 20 b = 10

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,d;
5     scanf("%d %d",&a,&b);
6     printf("Before swapping : a = %d b = %d",a,b);
7     c=a;
8     a=b;
9     b=c;
10    printf("\nAfter swapping : a = %d b = %d",a,b);
11    return 0;
12 }
```

	Input	Expected	Got	
✓	10 20	Before swapping : a = 10 b = 20 After swapping : a = 20 b = 10	Before swapping : a = 10 b = 20 After swapping : a = 20 b = 10	✓

Passed all tests! ✓

Question 1

Correct

Marked out of 1.00

Flag question

Write a program to print the ASCII value of the given character.

Input:

A

Output:

The ASCII value of the given character A is : 65

For example:

Input	Result
A	The ASCII value of the given character A is : 65

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     char a;
5     scanf("%c",&a);
6     printf("The ASCII value of the given character A is : %d",a);
7     return 0;
8 }
```

	Input	Expected	Got	
✓	A	The ASCII value of the given character A is : 65	The ASCII value of the given character A is : 65	✓

Passed all tests! ✓