

```
1  #include<stdio.h>
2  int findPivotIndex(int arr[],int n)
3  {
4      int totalSum=0,leftSum=0;
5      for(int i=0;i<n;i++)
6      {
7          totalSum+=arr[i];
8      }
9      for(int i=0;i<n;i++)
10     {
11         int rightSum=totalSum-leftSum-arr[i];
12         if (leftSum==rightSum)
13         {
14             return i;
15         }
16         leftSum+=arr[i];
17     }
18     return -1;
19 }
20 int main()
21 {
22     int n;
23     scanf("%d",&n);
24     int arr[n];
25     for(int i=0;i<n;i++)
26     {
27         scanf("%d",&arr[i]);
28     }
29     int pivotIndex=findPivotIndex(arr,n);
30     if(pivotIndex!=-1)
31     {
32         printf("%d ",pivotIndex);
33     } else
34         printf("-1");
35     return 0;
36
37 }
```

```
1  ▾ /*
2    * Complete the 'arraySum' function below.
3    *
4    * The function is expected to return an INTEGER.
5    * The function accepts INTEGER_ARRAY numbers as parameter.
6    */
7
8  int arraySum(int numbers_count, int *numbers)
9  ▾ {
10     int s=0;
11     for(int i=0;i<numbers_count;i++)
12         s+=numbers[i];
13     return s;
14
15 }
16
```