

```

1  #include <stdio.h>
2  int main()
3  {
4      int i = 0, n;
5      scanf("%d",&n ); //Fill the missing code in scanf() function
6      while ( i<n )
7      { // complete the condition here
8          printf("Ganga \n"); // Write the text to be printed here
9          i++ ; // Complete the statement
10     }
11     return 0;
12 }
13

```

	Input	Expected	Got	
✓	3	Ganga Ganga Ganga	Ganga Ganga Ganga	✓

```

1 #include <stdio.h>
2
3 int main()
4 {
5     int a,b,c=0;
6     scanf("%d %d",&a,&b);
7     while(a<=b)
8     {
9         if(a%2==0)
10        {
11            c=c+a;
12        }
13        a++;
14    }
15    printf("The sum of even integers between the given limits = %d",c);
16    return 0;
17 }

```

	Input	Expected	Got	
✓	3 6	The sum of even integers between the given limits = 10	The sum of even integers between the given limits = 10	✓

```

1 #include <stdio.h>
2
3 int main()
4 {
5     int n, r ;
6     scanf("%d", &n);
7     printf("The reverse number of a given number = ");
8     while (n!=0)
9     {
10         r=n%10;
11         printf("%d",r);
12         n=n/10;
13     }
14
15     return 0;
16 }
17

```

	Input	Expected	Got	
✓	1234	The reverse number of a given number = 4321	The reverse number of a given number = 4321	✓
✓	765	The reverse number of a given number = 567	The reverse number of a given number = 567	✓

```

1  #include <stdio.h>
2
3  int main()
4  {
5      int i, n, factorial = 1;
6      scanf("%d", &n);
7      i = 2;
8      while (i<=n )
9      { // Write the condition
10     factorial =factorial*i; ; // Fill the correct code
11     i++;
12     }
13     printf("Factorial of given number %d = %d\n", n, factorial);
14     return 0;
15 }

```

	Input	Expected	Got	
✓	2	Factorial of given number 2 = 2	Factorial of given number 2 = 2	✓
✓	4	Factorial of given number 4 = 24	Factorial of given number 4 = 24	✓

```

1 #include <stdio.h>
2
3 int main()
4 {
5     int n, i =2 , count =0 ; // initialize i and count with appropriate values
6     scanf("%d", &n);
7     while ( i<=n)
8     { // complete the condition to iterate the loop
9         if (n%i==0)
10        { // complete the condition to check the remainder is 0 or not
11            count++;
12        }
13        i++;
14    }
15    if (count ==1 )
16    { // complete the condition to check the count
17        printf("The given number %d is a prime number\n", n);
18    }
19    else
20    {
21        printf("The given number %d is not a prime number\n", n);
22    }
23    return 0;
24 }

```

	Input	Expected	Got	
✓	7	The given number 7 is a prime number	The given number 7 is a prime number	✓
✓	119	The given number 119 is not a prime number	The given number 119 is not a prime number	✓

```

1 #include<stdio.h>
2 int main()
3 {
4     int i=1,n;
5     scanf("%d",&n);
6     printf("The natural numbers from 1 - %d : ",n);
7     while(i<=n)
8     {
9         printf("%d ",i);
10        i++;
11    }
12    return 0;
13 }
14 }

```

	Input	Expected	Got	
✓	3	The natural numbers from 1 - 3 : 1 2 3	The natural numbers from 1 - 3 : 1 2 3	✓
✓	9	The natural numbers from 1 - 9 : 1 2 3 4 5 6 7 8 9	The natural numbers from 1 - 9 : 1 2 3 4 5 6 7 8 9	✓

Passed all tests! ✓

```

1  #include <stdio.h>
2
3  int main()
4  {
5      int a,b,c=0;
6      scanf("%d %d",&a,&b);
7      while(a<=b)
8      {
9          if(a%2==0)
10         {
11             c=c+a;
12         }
13         a++;
14     }
15     printf("The sum of even integers between the given limits = %d",c);
16     return 0;
17 }

```

	Input	Expected	Got	
✓	3 6	The sum of even integers between the given limits = 10	The sum of even integers between the given limits = 10	✓

Passed all tests! ✓

```

1 #include <stdio.h>
2
3 int main()
4 {
5     int n, r ;
6     scanf("%d", &n);
7     printf("The reverse number of a given number = ");
8     while (n!=0)
9     {
10         r=n%10;
11         printf("%d",r);
12         n=n/10;
13     }
14
15     return 0;
16 }
17

```

	Input	Expected	Got	
✓	1234	The reverse number of a given number = 4321	The reverse number of a given number = 4321	✓
✓	765	The reverse number of a given number = 567	The reverse number of a given number = 567	✓

Question 1

Correct

Marked out of 3.00

Flag question

Many people think about their height in feet and inches, even in some countries that primarily use the metric system. Write a program that reads a number of feet from the user, followed by a number of inches. Once these values are read, your program should compute and display the equivalent number of centimeters.

Hint:

One foot is 12 inches.

One inch is 2.54 centimeters.

Input Format:

First line, read the number of feet.

Second line, read the number of inches.

Output Format:

In one line print the height in centimeters.

Note: All of the values should be displayed using two decimal places.

Sample Input 1

5 6

Sample Output 1

107.04

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int f, i;
5     float c;
6     scanf("%d %d", &f, &i);
7     c=(f*30.48)+(i*2.54);
8     printf("%.2f", c);
9     return 0;
10 }
```

	Input	Expected	Got	
✓	3 367.04	367.04	367.04	✓
	5			

Passed all tests! ✓

Question 2

Correct

Marked out of 5.00

Report question

Create a program that reads two integers, a and b, from the user. Your program should compute and display: • The sum of a and b • The difference when b is subtracted from a • The product of a and b • The quotient when a is divided by b • The remainder when a is divided by b

Input Format:

First line, read the first number.

Second line, read the second number.

Output Format:

First line, print the sum of a and b

Second line, print the difference when b is subtracted from a

Third line, print the product of a and b

Fourth line, print the quotient when a is divided by b

Fifth line, print the remainder when a is divided by b

Sample

Input: 1 100 0

Sample Output:

101 99 000 100 0

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int a,b,c,d,e,f,g;
5     scanf("%d %d",&a,&b);
6     c=a+b;
7     d=a-b;
8     e=a*b;
9     f=a/b;
10    g=a%b;
11    printf("%d %d %d %d %d",c,d,e,f,g);
12    return 0;
13 }
```

	Input	Expected	Got	
✓	100	100	100	✓
	0	04	04	
		000	000	
		10	10	
		4	4	

Passed all tests! ✓