

Write a program to read two Integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 708 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,d;
5     scanf("%d",&a);
6     scanf("%d",&b);
7     c=a%10;
8     d=b%10;
9     if(c==d)
10    printf("true");
11    else
12    printf("false");
13    return 0;
14 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Sample Input 1

24

Sample Output: 1

Not Weird

Explanation

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print *Weird*.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print *Not Weird*.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     scanf("%d",&a);
6     if(a%2!=0)
7         printf("Weird");
8     else if((a%2==0)&&(2<a)&&(a%5))
9         printf("Not Weird");
10    else if((a%2==0)&&(6<a)&&(20<a))
11        printf("Weird");
12    else if((a%2==0)&&(a>20))
13        printf("Not Weird");
14    else
15        printf("Weird");
16    return 0;
17 }
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print 'yes', otherwise, print 'no'. Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d %d",&a,&b,&c);
6     if((a*a)+(b*b)==(c*c))
7         printf("yes");
8     else if((b*b)+(c*c)==(a*a))
9         printf("yes");
10    else if((c*c)+(a*a)==(b*b))
11        printf("yes");
12    else
13        printf("no");
14    return 0;
15 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

Sample Input 2

7

Sample Output 2

Heptagon

Sample Input 3

11

Sample Output 3

The number of sides is not supported.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     scanf("%d",&a);
6     switch(a)
7     {
8         case 3:
9             printf("Triangle");
10            break;
11            case 4:
12                printf("Quadrilateral");
13                break;
14                case 5:
15                    printf("Pentagon");
16                    break;
17                    case 6:
18                        printf("Hexagon");
19                        break;
20                        case 7:
21                            printf("Heptagon");
22                            break;
23                            case 8:
24                                printf("Octagon");
25                                break;
26                                case 9:
27                                    printf("Nonagon");
28                                    break;
29                                    case 10:
30                                        printf("Decagon");
31                                        break;
32                                        default:
33                                            printf("The number of sides is not supported.");
34                                            }
35    }
36    return 0;
37 }
```

	Input	Expected	Got	
✓	3	Triangle	Triangle	✓
✓	7	Heptagon	Heptagon	✓
✓	11	The number of sides is not supported	The number of sides is not supported	✓

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d",&a);
6     b=a/100;
7     c=b/12;
8     switch(c)
9     {
10         case 0:
11             printf("Dragon");
12             break;
13         case 1:
14             printf("Snake");
15             break;
16         case 2:
17             printf("Horse");
18             break;
19         case 3:
20             printf("Sheep");
21         case 4:
22             printf("Monkey");
23             break;
24         case 5:
25             printf("Rooster");
26             break;
27         case 6:
28             printf("Dog");
29             break;
30         case 7:
31             printf("Pig");
32             break;
33         case 8:
34             printf("Rat");
35             break;
36         case 9:
37             printf("Ox");
38             break;
39         case 10:
40             printf("Tiger");
41             break;
42         case 11:
43             printf("Hare");
44             break;
45     }
46     return 0;
47 }
```

	Input	Expected	Got	
✓	2004	Monkey	Monkey	✓
✓	2010	Tiger	Tiger	✓

Passed all tests! ✓

Sample Input 1

a 1

Sample Output 1

The square is black.

Sample Input 2

d 5

Sample Output 2

The square is white.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b;
5     char c;
6     scanf("%i %d", &c, &a);
7     b=a-c;
8     if(b%2==0)
9         printf("The square is black.");
10    else
11        printf("The square is white.");
12    return 0;
13 }
```

	Input	Expected	Got	
✓	a 1	The square is black.	The square is black.	✓
✓	d 5	The square is white.	The square is white.	✓

Passed all tests! ✓

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,feb,no;
5     scanf("%d %d %d",&a,&b,&c);
6     if(c!=0)
7     {
8         feb=20;
9         feb=28;
10        switch(b)
11        {
12            case 1:
13                printf("%d",a);
14                break;
15            case 2:
16                no=31-a;
17                printf("%d",no);
18                break;
19            case 3:
20                no=31-feb+a;
21                printf("%d",no);
22                break;
23            case 4:
24                no=31*2+feb+a;
25                printf("%d",no);
26                break;
27            case 5:
28                no=31*2+feb+30+a;
29                printf("%d",no);
30                break;
31            case 6:
32                no=31*3+feb+30+a;
33                printf("%d",no);
34                break;
35            case 7:
36                no=31*3+feb+30*2+a;
37                printf("%d",no);
38                break;
39            case 8:
40                no=31*4+feb+30*2+a;
41                printf("%d",no);
42                break;
43            case 9:
44                no=31*5+feb+30*2+a;
45                printf("%d",no);
46                break;
47            case 10:
48                no=31*5+feb+30*3+a;
49                printf("%d",no);
50                break;
51            case 11:
52                no=31*6+feb+30*3+a;
```

	Input	Expected	Got	
✓	18 6 2020	170	170	✓

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,s,t,r;
5     char d;
6     scanf("%d %d %d %d %d",&a,&b,&s,&t,&r);
7     t=a*b;
8     s=0.5*a*b;
9     r=a*b;
10    switch(d)
11    {
12        case('S'):
13            printf("%d",s);
14            break;
15        case('R'):
16            printf("%d",r);
17            break;
18        case('T'):
19            printf("%d",t);
20            break;
21        default:
22            printf("0");
23    }
24    return 0;
25 }
```

	Input	Expected	Got	
✓	1 10 10	100	100	✓
✓	5 10 40	600	600	✓
✓	8 2 11	0	0	✓
✓	8 10 10	300	300	✓
✓	5 40 10	1000	1000	✓

Passed all tests! ✓

main.c: getting input & output

```
1 #include <stdio.h>
2 int main()
3 {
4     int n,a,b;
5     scanf("%d",&a);
6     b=2020;
7     n=2020;
8     switch(a)
9     {
10
11         case 0:
12             printf("Sunday");
13             break;
14         case 1:
15             printf("Monday");
16             break;
17         case 2:
18             printf("Tuesday");
19             break;
20         case 3:
21             printf("Wednesday");
22             break;
23         case 4:
24             printf("Thursday");
25             break;
26         case 5:
27             printf("Friday");
28             break;
29         case 6:
30             printf("Saturday");
31             break;
32         case 7:
33             printf("Cryptonday");
34             break;
35         case 8:
36             printf("Coluday");
37             break;
38         case 9:
39             printf("Daxanday");
40             break;
41     }
42     return 0;
43 }
```

	Input	Expected	Got	
✓	7	xryptonday	xryptonday	✓
✓	1	Monday	Ponday	✓

Passed all tests! ✓