

Input

3
1
6
7

Output

Yes
Yes
No

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int t,n;
5     scanf("%d",&t);
6     while(t-->0)
7     {
8         scanf("%d",&n);
9         if(n%8==2 || n%8==5 || n%8==7 || n%8==0)
10        {
11            printf("No\n");
12        }
13        else
14        {
15            printf("Yes\n");
16        }
17    }
18    return 0;
19 }
```

	Input	Expected	Got	
✓	3	Yes	Yes	✓
	1	Yes	Yes	
	6	No	No	
	7			

Passed all tests! ✓

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,sum;
5     sum = 0;
6     scanf("%d",&n);
7     while(n>0)
8     {
9         int r = n%10;
10        switch(r)
11        {
12            case 0:
13            case 4:
14            case 6:
15            case 9:
16                sum+=1;
17                break;
18            case 8:
19                sum +=2;
20                break;
21        }
22        n=n/10;
23    }
24    printf("%d",sum);
25    return 0;
26 }
```

	Input	Expected	Got	
✓	638	2	2	✓
✓	1288	4	4	✓

Passed all tests! ✓

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c=1;
5     scanf("%d",&a);
6     while(c<=a)
7     {
8         b++;
9         c=c*2;
10    }
11    printf("%d",b);
12    return 0;
13 }
```

	Input	Expected	Got	
✓	10	4	4	✓
✓	5	3	3	✓
✓	20	5	5	✓
✓	500	9	9	✓
✓	1000	10	10	✓

Passed all tests! ✓

Input:

5 10 15 20 25 30 35 40 45 50

Output:

5

Explanation:

The numbers meeting the criteria are 5, 15, 25, 35, 45.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int num,numodd = 0;
5     while(scanf("%d",&num)>0)
6     {
7         if(num%2==1)
8             numodd++;
9         printf("%d",numodd);
10    }
```

	Input	Expected	Got	
✓	5 10 15 20 25 30 35 40 45 50	5	5	✓

Passed all tests! ✓

Example 2:
89 -> 68
Input: 89
Output: true
Explanation:
We get 68 after rotating 89, 86 is a valid number and 86!=89.

Example 3:
11 -> 11
Input: 11
Output: false
Explanation:
We get 11 after rotating 11, 11 is a valid number but the value remains the same, thus 11 is not a confusing number.

- Note:**
- 0 <= N <= 10^9
 - After the rotation we can ignore leading zeros for example if after rotation we have 0008 then this number is considered as just 8.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a ,rem,flag=0,c=9,s=6,b;
5     scanf("%d",&a);
6     b=a;
7     while(a)
8     {
9         rem = a%10;
10        if(rem==1||rem==6||rem==8||rem==9||rem==0)
11            flag++;
12        s=s*10+rem;
13        a=a/10;
14        c++;
15    }
16    if(flag==c)
17    {
18        if(s!=b||c==1)
19        {
20            printf("true");
21        }
22    }
23    else
24    {
25        printf("false");
26    }
27    return 0;
28 }
29
30
```

	Input	Expected	Got	
✓	6	true	true	✓
✓	89	true	true	✓
✓	34	false	false	✓

Sample Input 2

3
3

Sample Output 2

5

Explanation 2

2 + 3 = 5 is the best case for maximum nutrients.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     long long n,t,sum;
5     scanf("%lld %lld",&n,&k);
6     sum=0;
7     for(long long i=1;i<=n;i++)
8     {
9         sum+=i;
10        if(sum==k)
11        {
12            sum-=i;
13        }
14    }
15    printf("%lld",sum%1000000007);
16    return 0;
17 }
```

	Input	Expected	Got	
✓	2 2	3	3	✓
✓	3 1	3	3	✓
✓	3 5	5	5	✓