

Answer: (penalty regime: 0.5)

```
1 #include <stdio.h>
2 int main()
3 {
4     int o,t,d,i=0,11,12;
5     char c;
6     scanf("%d",&t);
7     while(i<t)
8     {
9         scanf("%d",&d);
10        11=0;
11        while(11<d)
12        {
13            o+=1;
14            12=0;
15            if(11%2==0)
16            {
17                o-=8;
18            }
19            while(12<d)
20            {
21                c='0';
22                if(12%2==0)
23                {
24                    c='a';
25                }
26                printf("%c",c);
27                12++;
28            }
29            11+=1;
30            printf("\n");
31        }
32        i+=1;
33    }return 0;
34 }
```

	Input	Expected	Got	
✓	1	000	000	✓
	3	000	000	
	5	000	000	
		00000	00000	
		00000	00000	
		00000	00000	
		00000	00000	

Input:

2
2 W
3 B

Output:

WB
BW
BWB
WBW
BWB

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int T,d,1,i1,i2,o,z;
5     char c,s;
6     scanf("%d",&T);
7     for(1=0;1<T;1++)
8     {
9         scanf("%d %c",&d,&s);
10        for(i1=0;i1<d;i1++)
11        {
12            z=(s=='W')?0:1;
13            o=(i1%2==2)?0:1;
14            for(i2=0;i2<d;i2++)
15            {
16                c=(i2%2==0)?'W':'B';
17                printf("%c",c);
18            }
19            printf("\n");
20        }
21    }
22    return 0;
23 }
```

	Input	Expected	Got	
✓	2	WB	WB	✓
	2 W	BW	BW	
	3 B	BWB	BWB	

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int a,v,p3,c,in,i,l1,l2,t,t1;
5     scanf("%d",&t);
6     for(tl=0;tl<t;tl++){
7         v=0;
8         scanf("%d",&n);
9         printf("Case %d\n",tl+1);
10        for(i=0;i<n;i++){
11            {
12                c=0;
13                if(i==0){
14                    for(jl=0;jl<i;jl++){
15                        printf("%d",j);
16                    }
17                    for(jl=i;jl<n;jl++){
18                        if(jl==0)
19                            c++;
20                        printf("%d",++v);
21                    }
22                    if(i==0){
23                        p3=v*(v-1)+1;
24                        in=p3;
25                    }
26                    in=in-c;
27                    p3=in;
28                    for(jl=i;jl<n;jl++){
29                        printf("%d",p3--);
30                        if(jl==n-1) printf("8");
31                    }
32                    printf("\n");
33                }
34            }
35        }
36    }
```

	Input	Expected	Got	
✓	3	Case #1	Case #1	✓
	3	10203010011012	10203010011012	
	4	**4050009	**4050009	
	5	***607	***607	
		Case #2	Case #2	
		102030017010010030	102030017010010030	
		**0007014015016	**0007014015016	
		***00012013	***00012013	
		*****10011	*****10011	
		Case #3	Case #3	
		1020304010010027020020030	1020304010010027020020030	
		**070009022023024025	**070009022023024025	
		***1001012010020021	***1001012010020021	
		*****13014017018	*****13014017018	
		*****15016	*****15016	

Passed all tests! ✓

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<math.h>
3 int countDigits(int num){
4     int count=0;
5     while(num!=0){
6         num/=10;
7         count++;
8     }
9     return count;
10 }
11 int isArmstrong(int num){
12     int originalNum=num;
13     int sum=0;
14     int digits=countDigits(num);
15     while(num!=0){
16         int digit=num%10;
17         sum+=pow(digit,digits);
18         num/=10;
19     }
20     return sum==originalNum;
21 }
22 int main(){
23     int num;
24     scanf("%d",&num);
25     if(isArmstrong(num))
26     {
27         printf("true");
28     }
29     else
30     {
31         printf("false");
32     }
33     return 0;
34 }
```

	Input	Expected	Got	
✓	153	true	true	✓
✓	123	false	false	✓

Passed all tests! ✓

Take a number, reverse it and add it to the original number until the obtained number is a palindrome. Constraints: $1 \leq \text{num} \leq 99999999$ Sample Input 1: 32 Sample Output: 1 55 Sample Input 2: 789 Sample Output: 2 00000

Answer: (panaly/runtime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int rn,rt,nt=0,i=0;
5     scanf("%d",&n);
6     do{
7         nt=n;
8         rn=0;
9         while(nt>0)
10         {
11             rn=rn*10+nt%10;
12             nt=nt/10;
13         }
14         n=nt+rn;
15         i++;
16     }
17     while(rn!=nt||i==1);
18     printf("%d",rn);
19     return 0;
20 }
21 }
```

	Input	Expected	Got	
✓	32	55	55	✓
✓	789	66066	66066	✓

Passed all tests! ✓

Answer: (sanity ragina: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n=1,i=0,nt,co=0,e;
5     scanf("%d",&n);
6     while(i<=n)
7     {
8         nt=n;
9         while(nt!=0)
10         {
11             co=0;if(nt%10!=3&&nt%10!=4)
12             {
13                 co=1;
14                 break;
15             }
16             nt=nt/10;
17         }
18         if(co==0)
19         {
20             i++;
21         }
22         n++;
23     }
24     printf("%d",--n);
25     return 0;
26 }
```

	Input	Expected	Got	
✓	24	33544	33344	✓

Passed all tests! ✓