

# INTRODUCTION TO FORENSIC SCIENCES

Final Project Report

---

## AI-Powered Fake Signature Detection

*Using Pressure, Writing Speed and Stroke Pattern Analysis*

### **Submitted By:**

Sana Ashfaq - 2503539

Afshan Nawaz - 2503544

Dua Masood - 2503525

Faaiza Mir - 2503500

**Department:** Cyber Security

**Program:** Cyber Forensics and Security

**Instructor:** Mam Zunaira Jalil

**Submission Date:** 3/6/2026

---

# **Abstract**

---

Signature forgery constitutes a critical threat across banking, legal, healthcare, and governmental sectors, causing massive annual losses globally. Traditional forensic examination methods are increasingly inadequate in the face of sophisticated digital forgeries and high-volume transaction environments. This project delivers an AI-powered signature forgery detection system that analyzes real-time behavioral biometric dimensions—specifically localized pen pressure, writing velocity, and stroke-point trajectories—to distinguish genuine signatures from skilled forgeries.

Unlike traditional static image analysis, the proposed system employs an advanced unsupervised hybrid machine learning architecture combining an Isolation Forest and a One-Class Support Vector Machine (SVM) to establish user-specific behavioral baselines. Dynamic signatures are captured live via a web-based client interface, extracting a 12-dimensional feature vector encompassing metrics such as total stroke duration, path length, average and maximum velocities, pressure variance, and geometric aspect ratios. The system evaluates authenticity through a calibrated Weighted Probability Fusion model to eliminate false acceptances while providing transparent, human-interpretable forensic metrics. Results demonstrate that this integrated behavioral-biometric approach significantly outperforms visual-only methods, providing explainable, court-admissible forensic evidence.

## **1. Introduction**

---

### **1.1 The Problem of Signature Forgery**

A handwritten signature is one of the oldest and most universally accepted forms of personal identification. For centuries, signatures have served as legally binding proof of consent, authorization, and identity across banking, legal contracts, government documents, healthcare, and corporate affairs. However, this very trust makes them a prime target for fraud. Signature forgery—the act of imitating or copying another person's signature without authorization is the foundation of a wide range of financial frauds, identity thefts, and legal disputes.

A handwritten signature is one of the oldest and most universally accepted forms of personal identification. For centuries, signatures have served as legally binding proof of consent, authorization, and identity across banking, legal contracts, government documents, healthcare, and corporate affairs. However, this very trust placed in signatures makes them a prime target for fraud.

Signature forgery the act of imitating or copying another person's signature without authorization is not a minor crime. It is the foundation of a wide range of financial frauds, identity thefts, and legal disputes. According to the Association of Certified Fraud Examiners (ACFE), companies worldwide lose an estimated 5% of their revenues to fraud annually, with signature forgery contributing significantly to these losses. The FBI has reported that signature forgery in check fraud alone results in losses exceeding \$15 billion annually in the United States. At a global scale, check fraud losses reached \$26.6 billion in 2023, with the Americas accounting for 80% of these losses. Perhaps most alarmingly, digital document forgeries rose by 244% annually in 2025, indicating that the problem is accelerating rather than diminishing in the digital age.

At a global scale, check and identity document fraud account for billions in annual losses, and digital document forgeries rose by 244% annually in 2025, indicating that the problem is accelerating rapidly in the digital age.

## 1.2 Real-World Impact of Signature Fraud

To understand the significance of automated signature forensics, it is essential to analyze how widely signature forgery impacts society across multiple sectors:

| Domain                   | Impact of Signature Forgery                                                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Banking & Finance        | Forged checks, withdrawal slips, and loan agreements cause billions in annual losses. Stolen identities are used to open fraudulent accounts. |
| Legal / Judiciary        | Forged signatures on wills, contracts, and power of attorney documents lead to inheritance fraud and prolonged litigation.                    |
| Real Estate              | Forged signatures on deed transfers and lease agreements enable fraudulent property sales, frequently targeting vulnerable populations.       |
| Healthcare               | Fraudulent medical claims and forged signatures on insurance policies or prescriptions introduce high operational liabilities.                |
| Government / Immigration | Forged signatures on identity papers and visa applications undermine national security and tracking infrastructures.                          |

## 1.3 Limitations of Traditional Detection Methods

For decades, the detection of forged signatures has relied on human forensic document examiners who physically inspect paper or scanned documents under magnification. While these experts are highly skilled, this approach has serious limitations:

- **Speed:** Manual examination of a single document can take hours or days, making it impractical for high-volume banking environments.
- **Subjectivity:** Expert opinion can vary between examiners, and conclusions are not always reproducible or mathematically standardized.
- **Scalability:** As the volume of digital transactions grows exponentially, manual human review cannot keep pace.
- **Digital Trace Forgeries:** Modern image editing tools and high-resolution copies can create forgeries that are visually indistinguishable from genuine signatures when subjected to purely static, visual inspection.

## 1.4 Proposed Approach and Objectives

This project proposes an automated solution that goes beyond visual appearance by analyzing the behavioral and biometric characteristics that are virtually impossible to forge: pen pressure, writing speed, and stroke-point timing patterns. The force applied, the speed of each stroke, and the rhythm of hand movements are deeply personal and neurologically rooted habits. A forger may visually replicate a signature's final geometric appearance, but reproducing its dynamic execution characteristics is exponentially harder.

---

Given this context, the primary objectives of this project are:

- To develop an AI-powered system that analyzes pen pressure, writing speed, and stroke patterns to detect forged signatures.
- To leverage unsupervised machine learning techniques (Isolation Forest and One-Class SVM) that can map complex behavioral features automatically from small enrollment sets.
- To produce an explainable system capable of presenting quantitative forensic metrics—pressure values, velocity profiles, and model confidence percentages—suitable for investigative and legal contexts.
- To evaluate operational system performance using standard biometric verification metrics: False Acceptance Rate (FAR) and False Rejection Rate (FRR).

### 1.5 Scope:

This project is designed with the following application contexts in mind:

- **Banking sector:** Automated cheque and loan document verification.
- **Legal sector:** Document authentication for contracts, wills, and affidavits.
- **Government agencies:** Identity document verification and immigration processing.

**Cyber forensics labs:** Evidence-grade signature analysis in fraud investigations

## 2. Literature Review

---

This literature review examines the existing landscape of signature verification solutions across two core dimensions: academic research and commercial products. Together, they highlight what has been achieved and precisely where this unsupervised dynamic project fits within the field.

### 2.1 Academic Research Summary

Early academic work heavily favored static image analysis. Hafemann et al. (2017) established benchmarks for offline signatures using deep Convolutional Neural Networks (CNNs) to extract structural features from image grids, achieving a 7% error rate but requiring large global training datasets. Similarly, Gowri et al. (2022) and Das et al. (2022) explored real-time classification and multi-stream networks to handle visual textures and skilled variations. Recent advancements, such as the 2025 Springer study on Residual Attention Mechanisms, have driven offline visual recognition accuracy up to 98.76% on isolated test corpora.

However, forensic science has increasingly recognized the need for temporal, behavioral features. The 2025 European Network of Forensic Science Institutes (ENFSI) empirical study on handwriting stability across touch devices confirmed that intra-writer dynamic characteristics—such as pressure distribution and speed rhythms—maintain low internal variance, validating them as highly reliable biometric discriminators. Stergiou et al. (2025) further validated hybrid architectures, proving that combining machine learning classifiers yields the balance of high classification accuracy and clear interpretability required for court-admissible evidence.

#### Paper 1: Hafemann, Sabourin & Oliveira (2017) Deep CNN for Offline Signature Verification

One of the most foundational and widely cited papers in this field, published in Pattern Recognition (2017), addressed verifying offline static image-based signatures in the presence of skilled forgeries. The authors proposed a CNN trained in writer-independent format on the GPDS-960 corpus (960 writers), achieving verification error

---

rates of approximately 7% establishing deep CNN feature learning as the benchmark for offline signature verification and forming the methodological foundation for the CNN component of our project.

[Paper 2: Gowri et al. \(2022\) Real-Time Forgery Detection \(IEEE ICAECT\)](#)

Published at IEEE ICAECT 2022, this paper proposes an automated preprocessing pipeline for signature images followed by machine learning classification, directly addressing the same real-time detection challenge our project solves. The research uses a CNN trained on genuine and forged signatures, emphasizing the need for automated systems capable of replacing or supporting human examination in real-time scenarios.

[Paper 3: Chokshi et al. \(2023\) SigScatNet: Siamese + Scattering Wavelets](#)

Introduced at MoSICom 2023, SigScatNet combines a Siamese deep learning network with Scattering wavelets, addressing a key limitation of binary-threshold CNN systems. Their approach computes a comprehensive similarity index, providing a graduated similarity score rather than simple binary classification more useful in forensic contexts where degrees of similarity matter, and more robust to natural intra-writer variability.

[Paper 4: Das, Bhaumik & Nath \(2022\) Multistream CNN for Skilled Forgeries](#)

This IEEE VLSI DCS 2022 paper addresses detecting skilled forgeries by proposing image transformation techniques to generate multiple views of the same signature, fed into a multistream CNN architecture. Each stream captures different aspects overall shape, local texture, edge structure and outputs are fused for final decision. This ensemble-style approach proved particularly effective against skilled forgers, directly informing our multi-feature integration approach.

[Paper 5: Malallah \(2022\) PCA & Boruta Feature Selection](#)

Presented at IEEE ICOASE 2022, this paper applies Principal Component Analysis (PCA) for dimensionality reduction and the Boruta feature selection algorithm to identify the most relevant features for distinguishing genuine from forged signatures. It provides a highly interpretable model an important consideration in forensic applications where examiners must explain why a signature was flagged as forged. Features related to stroke curvature and aspect ratio were identified as the most discriminating, consistent with our stroke pattern analysis module.

[Paper 6: Harris & Anitha \(2023\) Improved Forgery Detection via Modified CNN Siamese Network](#)

Presented at IEEE ICEEICT 2023, this paper proposes a modified CNN with adjusted convolutional filter sizes and attention mechanisms embedded within a Siamese network framework. The attention mechanism forces the network to focus on regions most likely to reveal forgery beginning and ending strokes, loop closures, and pen lift positions. Improved performance was particularly noted in detecting partially forged signatures, highly relevant to legal document fraud scenarios.

[Paper 7: Stergiou et al. \(2025\) Hybrid Deep Learning + Traditional ML](#)

Published in SAGE Journals in 2025, this paper proposes combining pre-trained deep learning models (VGG, DenseNet, MobileNet) with traditional ML classifiers (SVM, Random Forest). The hybrid approach outperforms both pure deep learning and pure traditional ML models, achieving high accuracy while maintaining the explainability needed for forensic applications strongly validating our own hybrid CNN + SVM architecture.

[Paper 8: Reyes et al. \(2022\) Computer Vision-Based Forgery Detection as Supervised Learning](#)

Published at IEEE CONECCT 2022, this paper frames signature forgery detection as a supervised computer vision classification problem. The systematic comparison of CNN and LSTM architectures confirmed CNN superiority for spatial feature analysis, while validating sequential models for online dynamic data. This finding reinforces our choice of CNN as the primary classifier for offline signature analysis.

[Paper 9: ENFSI Study on Handwriting Stability Across Devices \(2025\)](#)

Published in a peer-reviewed journal in 2025 and referenced by the European Network of Forensic Science Institutes (ENFSI), this study examined the stability of handwriting captured across different devices (Samsung Galaxy Tab, Apple iPad Pro, Apple iPad Mini). Findings confirmed that intra-writer variability was significantly lower than inter-writer variability, validating that pressure and velocity features are reliable biometric discriminators and directly supporting the scientific validity of our feature selection approach.

---

#### Paper 10: Residual Attention Mechanisms for Signature Forgery Detection (Springer, 2025)

This Springer 2025 paper incorporates Residual Attention Mechanisms into a deep learning architecture, allowing the network to dynamically focus on the most discriminative signature regions beginning and ending strokes, sharp directional changes, and loop structures. Using residual connections inspired by ResNet, the model achieved 98.76% accuracy on the CEDAR dataset, representing the current frontier of the field and demonstrating that attention mechanisms are the next evolutionary step beyond standard CNN approaches.

## **2.2 Commercial Products Overview**

- Signotec (eSig-Analyze): Evaluates up to 42 dynamic parameters. While forensically validated, it relies on expensive, proprietary hardware pads and closed enterprise licenses.
- DocuSign / Adobe Acrobat Sign: Industry leaders in digital identity verification and PKI-based document workflow security. However, these platforms focus on identity tracking or document encryption rather than the biometric mechanics of how a physical handwritten signature is executed.
- SIGNificant (XYZMO): Captures complete handwritten biometrics including air strokes. It remains a closed, highly expensive proprietary commercial server inaccessible for open integration or custom forensic tuning.

## **2.3 Gap Analysis — Where This Project Fits**

- The Research Gap: Most academic models address offline visual arrays or online sensor parameters in complete isolation. This project bridges the gap by extracting combined spatial, temporal, and force metrics from standard hardware.
- The Commercial Gap: Advanced biometric software engines are closed and expensive. This system implements complex biometric anomaly detection using open-source web APIs and standard computing platforms, making it accessible and extensible.
- The Forensic Gap: Existing commercial platforms output basic binary outcomes. This system calculates clear, feature-level forensic data, outputting explainable metrics that document exactly which physical deviations caused an execution to be flagged.

# **3. Proposed Methodology and System Architecture**

---

## **3.1 Problem statement:**

Traditional signature verification methodologies rely exclusively on the visual and morphological appearance of signatures comparing ink distribution, line width, spatial proportions, and shape contours. This static, appearance-centric approach is fundamentally vulnerable to skilled forgeries: an attacker with access to a genuine signature and adequate practice can replicate its visual characteristics with sufficient fidelity to deceive both human examiners and basic automated systems.

The core limitation of visual-only analysis is that it ignores the behavioral and biometric dimensions of how a signature is produced the kinematic and temporal characteristics that are neurologically determined and inherently unique to each individual. These dimensions include pen pressure distribution across the signature trajectory,

---

writing speed and acceleration patterns at each stroke segment, pause duration and frequency between strokes, inter-stroke distances and directional changes, and pressure variance and rhythmic timing signatures.

No special hardware infrastructure should be required to capture these behavioral parameters; modern smartphone touchscreens provide sufficient sensor data to record dynamic signature characteristics with forensically meaningful precision. Yet no open, AI-driven system exists that integrates these multi-dimensional behavioral features into a unified, explainable, and court-admissible forensic analysis pipeline.

This project therefore addresses the following core problem: How can an AI-powered system reliably detect forged signatures by analyzing their dynamic behavioral and biometric characteristics pen pressure, writing speed, and stroke patterns captured via standard touchscreen hardware, and produce explainable forensic evidence suitable for both real-time fraud prevention and retrospective forensic investigation?

The proposed platform shifts the paradigm from visual pixel matching to continuous biometric stream profiling. The application splits functionality into two distinct backend modes to ensure robust evaluation and real-world deployment:

- Evaluation Mode (Dataset Benchmark Analysis): Reads historical, pre-existing raw signature time-series records—such as the SVC2004 benchmark—to execute wide batch-processing, calculate global operational metrics, and prove baseline model reliability.
- Enrollment Mode (Biometric Management and Live Detection): Builds an in-memory profile envelope for a specific user based on 5 genuine live canvas inputs. Suspect incoming signatures are evaluated instantly against this personalized reference matrix.

### **3.2 proposed methodology:**

The proposed system employs a multi-stage pipeline integrating touchscreen-based data collection, behavioral feature engineering, user-specific profile construction, machine learning-based anomaly detection, and pressure heatmap visualization. The architecture is designed to be modular, allowing individual components to be validated, improved, or replaced independently.

### **3.3 Data Capture Pipeline**

Dynamic trajectory data streams directly from an active HTML5 Touch Events API web interface or a Python Tkinter touchscreen canvas. For every active cursor or stylus event, the application records variables at millisecond-level resolution:

- Cartesian coordinates (x, y) tracking the pen tip path.
- Instantaneous normalized pressure values (p).
- Precise timestamps (t) in epoch milliseconds.
- Discrete pen-lift events to compute pause boundaries.

### **3.4 12-Dimensional Forensic Feature Extraction**

The raw sensor arrays are transformed using NumPy and Pandas into a uniform 12-dimensional numerical feature vector for machine learning inference. The following metrics constitute the feature vector:

- Total Duration (T): The complete execution span of the signature event in seconds.

$$T = (t_{end} - t_{origin}) / 1000$$



- Path Length (L): The total scalar pixel distance traversed by the continuous stroke trajectory.

$$L = \sum \sqrt{(x_{i+1} - x_i)^2 + (y_{i+1} - y_i)^2}$$

- Average Velocity (V\_avg): The overall kinematic speed of execution.

$$V_{avg} = L / T$$

- Maximum Velocity (V\_max): The peak instantaneous velocity recorded between adjacent coordinate timestamps.
- Average Pressure (P\_avg): The mean downforce value exerted across all active stream points.
- Peak Pressure (P\_max): The absolute maximum downforce value recorded during the signature session.
- Minimum Pressure (P\_min): The minimum non-zero downforce boundary captured before point release.
- Pressure Variance ( $\sigma^2_p$ ): The statistical variance of the pressure array, capturing the signer's natural muscle rhythm.

$$\sigma^2_p = (1/n) \times \sum (p_i - P_{avg})^2$$

- Box Width (W): The horizontal spatial footprint bounding box (x\_max - x\_min).
- Box Height (H): The vertical spatial footprint bounding box (y\_max - y\_min).
- Aspect Ratio (R\_aspect): The geometric layout ratio of the signing window: W / H.
- Total Sample Points (N): The absolute coordinate density captured by the event polling loop.

## 4 implementation:

**Batch Training (Evaluation Mode):** The feature extraction engine reads raw input coordinates and outputs computed spatial-temporal vectors directly to features.csv. A hybrid pipeline utilizes these saved features to optimize classification boundaries, allowing auditors to measure exact overall accuracy and plot global ROC curves.

- **Per-User Verification (Enrollment Mode):** For live client deployment, the system bypasses the global dataset and builds an isolated reference metric from the user's initial enrollment. Suspect signatures are evaluated directly against this user-specific envelope, checking for deviations in handwriting kinematics to flag real-time forgery attempts.

### Feature Engineering Pipeline

The feature engineering pipeline processes raw sensor data through a series of transformations implemented in NumPy and Pandas. Stroke segmentation is performed by detecting pen-lift events (consecutive timestamps with zero pressure or exceeding a gap threshold of 150ms). For each identified stroke segment, kinematic features are computed via finite difference approximation of velocity and acceleration from the coordinate time series. Pressure gradient analysis computes the first and second derivatives of the pressure signal within each stroke, identifying characteristic pressure escalation patterns at stroke initiation and deceleration patterns at stroke termination. These signatures are neurologically determined and represent a highly discriminative biometric feature.

### CNN + SVM Hybrid Architecture



---

offline signature analysis component implements a CNN-based feature extractor applied to rasterized grayscale images of the signature trajectory. The CNN architecture follows the pattern established by Hafemann et al. (2017), adapted for our dataset scale: four convolutional blocks (32, 64, 128, 256 filters) with ReLU activation, batch normalization, and max-pooling, followed by two fully connected layers producing a 512-dimensional feature embedding. This CNN feature embedding is concatenated with the behavioral feature vector (extracted in the feature engineering pipeline) to form a combined 512+N dimensional feature representation. A trained SVM with RBF kernel then performs the final classification, leveraging both the deep visual features and the explicit behavioral biometric features in a unified decision boundary.

#### Anomaly Detection Training

For each enrolled user, the Isolation Forest model is trained on their genuine signature feature vectors using  $n\_estimators=100$  and  $contamination=0.05$ , reflecting the expected proportion of anomalies in a deployment setting. The One-Class SVM is trained with an RBF kernel ( $nu=0.05$ ,  $gamma='auto'$ ) on the same feature vectors. Both models are serialized using joblib for persistence and loaded during real-time inference.

#### Output and Reporting

The system produces structured forensic output for each analyzed signature, including the binary classification (Authentic / Suspicious), a confidence score (0.0–1.0), the feature vector comparison against the user's behavioral profile, an annotated pressure heatmap image, and a summary of the specific features that most significantly deviated from the expected profile providing interpretable, quantitative forensic evidence suitable for investigative and legal contexts.

---

## 4. machine Learning Framework and Mathematical Modeling

Instead of resource-heavy deep learning configurations that struggle with sparse personal training data, the backend instantiates parallel unsupervised anomaly detection models for each enrolled user profile.

### 4.1 Isolation Forest (IF) Model

The Isolation Forest isolates behavioral anomalies by randomly partitioning the 12-dimensional feature space. Because authentic signatures conform to a tight cluster, they require a deep path length to isolate within the ensemble of decision trees. Conversely, structural forgeries isolate rapidly near the root nodes. The mathematical anomaly score  $s(x, n)$  is derived as:

$$s(x, n) = 2^{(-E(h(x)) / c(n))}$$

Where  $E(h(x))$  represents the average path length across the forest, and  $c(n)$  is the average path length of an unisolated binary search node given sample size  $n$ .

### 4.2 One-Class Support Vector Machine (SVM) Model

The One-Class SVM maps the user's feature profile vectors into a high-dimensional space via a non-linear Radial Basis Function (RBF) kernel:

$$K(x, x') = \exp(-\gamma ||x - x'||^2)$$

The model optimizes a separating hyperplane boundary that isolates the genuine training cluster from the coordinate origin, utilizing a margin parameter ( $\nu = 0.05$ ) to safely accommodate natural, minor intra-writer variance.

### 4.3 Weighted Probability Fusion Engine

To prevent binary classification disagreements between the two core models from breaking user experience, the application extracts continuous real-number decision function scores and applies sigmoid mapping functions to generate clean probability distributions ( $0.0 \rightarrow 1.0$ ):

$$P_{if} = 1 / (1 + \exp(-(score_{if} + 0.05) \times 25))$$

$$P_{svm} = 1 / (1 + \exp(-score_{svm} \times 12))$$

The final probability is calculated using a weighted fusion model, assigning a 60% priority bias to the Isolation Forest's partitioning capabilities:

$$P_{final} = (P_{if} \times 0.6) + (P_{svm} \times 0.4)$$

$$Confidence\ Percentage = \lfloor P_{final} \times 100 \rfloor$$

### 4.4 Calibration Decision Matrix

| Confidence Range | Verdict          | Interpretation                                                                                            |
|------------------|------------------|-----------------------------------------------------------------------------------------------------------|
| $\geq 62\%$      | <b>GENUINE</b>   | The test signature aligns with the user's authentic kinetic cadence.                                      |
| 43% – 61%        | <b>UNCERTAIN</b> | Minor execution variations detected; flags a warning for secondary forensic review.                       |
| $\leq 42\%$      | <b>FORGERY</b>   | The feature distribution deviates significantly from the user's profile, signaling intentional imitation. |

## 5. Experimental Results and Discussion

The integrated backend was cross-verified using the task-specific benchmarks from the SVC2004 dataset alongside live-drawn user tests.

### 5.1 System Performance Metrics

The classification framework achieved strong diagnostic metrics when evaluated across the testing clusters:

| Performance Metric | Value |
|--------------------|-------|
|--------------------|-------|

|                              |        |
|------------------------------|--------|
| Overall System Test Accuracy | 84.4%  |
| Area Under Curve (AUC) Score | 0.997  |
| False Acceptance Rate (FAR)  | 0.300% |
| False Rejection Rate (FRR)   | 0.013% |

## 5.2 Forensic Feature Importance Analysis

Feature importance tracking confirmed that pressure variance ( $\sigma^2_p$ ) and average velocity ( $V_{avg}$ ) serve as the primary behavioral discriminators. Testing demonstrated that while a skilled human copycat can match spatial dimensions such as bounding box width and height, their conscious hesitation causes their writing speed to drop significantly below the natural 180 px/s execution threshold. This behavior creates sharp inconsistencies in their pressure profile, allowing the fusion models to reliably detect the forgery in real time.

# 6. Conclusion and Future Work

This project successfully demonstrates a deployable cyber-forensic signature verification system. By shifting the focus from static geometric shapes to real-time behavioral biometrics—velocity, pen pressure, and stroke cadence—the application circumvents the security vulnerabilities that limit traditional visual document inspection. The unsupervised Isolation Forest and One-Class SVM pipeline eliminates the need for large training datasets, enabling rapid personal profile enrollment from just 5 genuine baseline samples.

The system's near-zero False Rejection Rate (0.013%) ensures that legitimate users face minimal friction, while the low False Acceptance Rate (0.300%) provides meaningful resistance against skilled forgery attempts. The Weighted Probability Fusion mechanism prevents binary model disagreements from degrading user experience, and the explainable forensic output makes the system viable for both operational security and legal investigation contexts.

Future work will focus on integrating adaptive min-max normalization filters into the feature extraction layer. This enhancement will automatically adjust detection thresholds based on device surface friction, further optimizing verification accuracy across non-standardized client hardware. Additionally, extending enrollment to mobile-native Android touch APIs will broaden the system's accessibility and real-world deployment potential.

## References

- [1] L. G. Hafemann, R. Sabourin, and L. S. Oliveira, "Learning features for offline handwritten signature verification using deep convolutional neural networks," *Pattern Recognition*, vol. 70, pp. 163–176, 2017.
- [2] P. Gowri, G. Sivapriya, N. Kamaleshwar, and N. Kesavaraj, "Real time signature forgery detection using machine learning," in *Proc. IEEE Int. Conf. on Advances in Electrical, Computing, Communication and Sustainable Technologies (ICAECT)*, 2022.

- 
- [3] K. Stergiou, S. Ougiaroglou, and A. Sidiropoulos, "Signature forgery detection using deep and machine learning," *Int. Journal of Advanced Robotic Systems*, SAGE Journals, 2025.
  - [4] European Network of Forensic Science Institutes (ENFSI), "Research on the handwriting stability in different devices and conditions," NCBI/PMC, 2025.
  - [5] A. Chokshi, V. Jain, R. Bhope, and S. Dhage, "SigScatNet: A Siamese + scattering based deep learning approach for signature forgery detection," *arXiv:2311.05579*, 2023.
  - [6] Association of Certified Fraud Examiners (ACFE), *Report to the Nations on Occupational Fraud and Abuse*. ACFE Publications.